



FCC TEST REPORT

REPORT NO.: RF941115L16

MODEL NO.: WRV200

RECEIVED: Dec. 23, 2005

TESTED: Dec. 23, 2005 ~ Jan. 24, 2006

ISSUED: Feb. 06, 2006

APPLICANT : Cisco-Linksys LLC

ADDRESS : 121 Theory Drive Irvine, CA 92617 (USA)

ISSUED BY : Advance Data Technology Corporation

LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION : No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 72 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.





Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY.....	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	9
3.4	DESCRIPTION OF SUPPORT UNITS	10
4	TEST TYPES AND RESULTS.....	11
4.1	CONDUCTED EMISSION MEASUREMENT	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	11
4.1.2	TEST INSTRUMENTS.....	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	14
4.1.7	TEST RESULTS	15
4.2	RADIATED EMISSION MEASUREMENT.....	27
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	27
4.2.2	TEST INSTRUMENTS.....	28
4.2.3	TEST PROCEDURES	29
4.2.4	DEVIATION FROM TEST STANDARD	29
4.2.5	TEST SETUP	30
4.2.6	EUT OPERATING CONDITIONS	30
4.2.7	TEST RESULTS	31
4.3	6dB BANDWIDTH MEASUREMENT	39
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	39
4.3.2	TEST INSTRUMENTS.....	39
4.3.3	TEST PROCEDURE.....	39
4.3.4	DEVIATION FROM TEST STANDARD	39
4.3.5	TEST SETUP	40
4.3.6	EUT OPERATING CONDITIONS	40
4.3.7	TEST RESULTS	41
4.4	MAXIMUM PEAK OUTPUT POWER.....	47
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47
4.4.2	TEST INSTRUMENTS.....	47
4.4.3	TEST PROCEDURES	48
4.4.4	DEVIATION FROM TEST STANDARD	48
4.4.5	TEST SETUP	48
4.4.6	EUT OPERATING CONDITIONS	48



4.4.7 TEST RESULTS	49
4.5 POWER SPECTRAL DENSITY MEASUREMENT.....	50
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	50
4.5.2 TEST INSTRUMENTS.....	50
4.5.3 TEST PROCEDURE.....	50
4.5.4 DEVIATION FROM TEST STANDARD.....	50
4.5.5 TEST SETUP	50
4.5.6 EUT OPERATING CONDITIONS	50
4.5.7 TEST RESULTS	51
4.6 BAND EDGES MEASUREMENT.....	57
4.6.1 LIMITS OF BAND EDGES MEASUREMENT	57
4.6.2 TEST INSTRUMENTS.....	57
4.6.3 TEST PROCEDURE.....	57
4.6.4 DEVIATION FROM TEST STANDARD	57
4.6.5 EUT OPERATING CONDITION.....	57
4.6.6 TEST RESULTS	58
4.7 ANTENNA REQUIREMENT	66
4.7.1 STANDARD APPLICABLE.....	66
4.7.2 ANTENNA CONNECTED CONSTRUCTION.....	66
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	67
6 INFORMATION ON THE TESTING LABORATORIES	71
APPENDIX-A	A-1



1 CERTIFICATION

PRODUCT: Wireless-G VPN Router with RangeBooster

MODEL: WRV200

BRAND: Linksys

APPLICANT: Cisco-Linksys LLC

TESTED: Dec. 23, 2005 ~ Jan. 24, 2006

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rennie Wang, **DATE:** Feb. 06, 2006
Rennie Wang

**TECHNICAL
ACCEPTANCE** : Long Chen, **DATE:** Feb. 06, 2006
Responsible for RF
Long Chen

APPROVED BY : Gary Chang, **DATE:** Feb. 06, 2006
Gary Chang / Supervisor



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -8.84dB at 8.273MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.54dB at 2489.00MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz ~ 30MHz	2.44 dB
	30MHz ~ 200MHz	3.63 dB
	200MHz ~ 1000MHz	3.65 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-G VPN Router with RangeBooster
MODEL NO.	WRV200
FCC ID	Q87-WRV200
POWER SUPPLY	12Vdc from AC adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
MAXIMUM OUTPUT POWER	31.989mW
ANTENNA TYPE	Dipole antenna with 2.2dBi gain
DATA CABLE	NA
I/O PORTS	RJ45

NOTE:

1. The EUT was tested with following adapters:

BRAND:	Linksys
MODEL:	RH48-1201000DU
INPUT:	120Vac, 60Hz, 30W
OUTPUT:	12Vdc, 1000mA
POWER LINE:	DC 1.8m non-shielded cable without core

BRAND:	Linksys
MODEL:	MT12-4120100-A1
INPUT:	120Vac, 60Hz, 0.4A
OUTPUT:	12Vdc, 1.0A
POWER LINE:	DC 1.8m non-shielded cable without core


2. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
3. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

11 channels are provided to this EUT.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT Configure Mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	-	-	Adapter model: RH48-1201000DU
B	√	√	√	√	Adapter model: MT12-4120100-A1

Where PLC: Power Line Conducted Emission
 RE<1G: Radiated Emission below 1GHz
 RE≥1G: Radiated Emission above 1GHz
 APCM: Antenna Port Conducted Measurement

NOTE: “-“ means no effect.

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	11	OFDM	BPSK	6
B	802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

**Bandedge Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
B	802.11b	1 to 11	1, 11	DSSS	DBPSK	1
B	802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414
4	NOTEBOOK COMPUTER	DELL	PP05L	20838027664	E2K24CLNS

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m shielded cable
3	1.8m shielded cable
4	NA

NOTE1: All power cords of the above support units are non shielded (1.8m).

2: Item 4 acted as a communication partner to transfer data.



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
0.15 ~ 0.5 0.5 ~ 5 5 ~ 30	Quasi-peak	Average
	66 to 56	56 to 46
	56	46
	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 11, 2006
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 06, 2007
LISN SCHWARZBECK	NNBL 8226-2	8226-142	May 02, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 15, 2006
Software ADT	ADT_Cond_V3	NA	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Prepared another notebook system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency via an RJ45 cable.
- d. The communication partner sent data to EUT by command "PING".
- e. The notebook system sent "H" messages to its screen.
- f. The notebook system sent "H" messages to modem.
- g. The notebook system sent "H" messages to printer, and the printer printed them on paper.
- h. Steps e ~ g were repeated.

4.1.7 TEST RESULTS

Conducted Worst-Case Data


(Adapter model: RH48-1201000DU)

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 1			PHASE
MODULATION TYPE		BPSK			6dB BANDWIDTH
TRANSFER RATE		6Mbps			9 kHz
TESTED BY		Jay Hsu			ENVIRONMENTAL CONDITIONS
					25deg. C, 65%RH, 991hPa
TEST MODE		INPUT POWER (SYSTEM)			120Vac, 60 Hz
					A

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	Q.P.	AV.	Q.P.	AV.
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.201	0.11	46.43	-	46.54	-	63.58	53.58	-17.04	-
2	0.312	0.11	42.29	-	42.40	-	59.90	49.90	-17.50	-
3	0.466	0.12	38.01	-	38.13	-	56.58	46.58	-18.44	-
4	0.931	0.23	20.36	-	20.59	-	56.00	46.00	-35.41	-
5	8.289	0.50	42.38	-	42.88	-	60.00	50.00	-17.12	-
6	16.414	0.69	32.55	-	33.24	-	60.00	50.00	-26.76	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 1		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		A			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.228	0.11	46.28	-	46.39	-	62.52	52.52	-16.13	-
2	0.369	0.11	43.08	-	43.19	-	58.53	48.53	-15.34	-
3	0.533	0.14	40.00	-	40.14	-	56.00	46.00	-15.86	-
4	0.986	0.24	25.34	-	25.58	-	56.00	46.00	-30.42	-
5	8.289	0.43	39.44	-	39.87	-	60.00	50.00	-20.13	-
6	16.727	0.55	26.81	-	27.36	-	60.00	50.00	-32.64	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		PHASE	Line 1
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		A			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.205	0.11	46.45	-	46.56	-	63.42	53.42	-16.86	-
2	0.314	0.11	42.52	-	42.63	-	59.86	49.86	-17.23	-
3	0.392	0.11	40.07	-	40.18	-	58.02	48.02	-17.84	-
4	0.935	0.23	20.71	-	20.94	-	56.00	46.00	-35.06	-
5	8.441	0.50	39.42	-	39.92	-	60.00	50.00	-20.08	-
6	17.047	0.75	32.89	-	33.64	-	60.00	50.00	-26.36	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		A			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.213	0.11	46.89	-	47.00	-	63.11	53.11	-16.11	-
2	0.310	0.11	44.35	-	44.46	-	59.96	49.96	-15.50	-
3	0.560	0.14	38.95	-	39.09	-	56.00	46.00	-16.91	-
4	1.188	0.24	19.64	-	19.88	-	56.00	46.00	-36.12	-
5	7.977	0.42	40.51	-	40.93	-	60.00	50.00	-19.07	-
6	16.891	0.56	30.21	-	30.77	-	60.00	50.00	-29.23	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE	A		

No	Freq. Factor	Reading Value		Emission Level		Limit		Margin	
		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.11	48.45	-	48.56	-	65.57	55.57	-17.02
2	0.224	0.11	45.76	-	45.87	-	62.66	52.66	-16.79
3	0.365	0.11	40.84	-	40.95	-	58.62	48.62	-17.67
4	1.035	0.24	18.16	-	18.40	-	56.00	46.00	-37.60
5	8.273	0.50	44.75	-	45.25	-	60.00	50.00	-14.75
6	17.020	0.74	36.55	-	37.29	-	60.00	50.00	-22.71

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 11		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		A			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.11	48.71	-	48.82	-	64.43	54.43	-15.61	-
2	0.311	0.11	44.46	-	44.57	-	59.93	49.93	-15.36	-
3	0.469	0.12	42.24	-	42.36	-	56.54	46.54	-14.17	-
4	1.093	0.24	22.27	-	22.51	-	56.00	46.00	-33.49	-
5	8.266	0.43	41.77	-	42.20	-	60.00	50.00	-17.80	-
6	16.859	0.55	32.12	-	32.67	-	60.00	50.00	-27.33	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




(Adapter model: MT12-4120100-A1)

EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL	Channel 1		PHASE	Line 1	
MODULATION TYPE	BPSK		6dB BANDWIDTH	9 kHz	
TRANSFER RATE	6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	
TESTED BY	Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz	
TEST MODE	B				

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.533	0.14	43.09	-	43.23	-	56.00	46.00	-12.77	-
2	0.748	0.19	45.28	-	45.47	-	56.00	46.00	-10.53	-
3	1.016	0.24	44.36	-	44.60	-	56.00	46.00	-11.40	-
4	1.230	0.24	43.31	-	43.55	-	56.00	46.00	-12.45	-
5	2.293	0.28	38.02	-	38.30	-	56.00	46.00	-17.70	-
6	8.273	0.50	50.66	24.94	51.16	25.44	60.00	50.00	-8.84	-24.56

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 1		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		B			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.474	0.13	42.07	-	42.20	-	56.44	46.44	-14.24	-
2	0.646	0.16	38.59	-	38.75	-	56.00	46.00	-17.25	-
3	0.982	0.24	39.32	-	39.56	-	56.00	46.00	-16.44	-
4	1.191	0.24	36.06	-	36.30	-	56.00	46.00	-19.70	-
5	2.568	0.30	37.97	-	38.27	-	56.00	46.00	-17.73	-
6	8.137	0.42	49.38	-	49.80	-	60.00	50.00	-10.20	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		PHASE	Line 1
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		B			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.588	0.15	44.62	-	44.77	-	56.00	46.00	-11.23	-
2	0.748	0.19	45.09	-	45.28	-	56.00	46.00	-10.72	-
3	1.012	0.24	44.67	-	44.91	-	56.00	46.00	-11.09	-
4	1.277	0.25	42.58	-	42.83	-	56.00	46.00	-13.17	-
5	2.582	0.30	36.74	-	37.04	-	56.00	46.00	-18.96	-
6	7.836	0.49	44.76	-	45.25	-	60.00	50.00	-14.75	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 6		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		B			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.509	0.13	37.14	-	37.27	-	56.00	46.00	-18.73	-
2	0.642	0.16	38.05	-	38.21	-	56.00	46.00	-17.79	-
3	0.990	0.24	38.69	-	38.93	-	56.00	46.00	-17.07	-
4	2.617	0.30	39.07	-	39.37	-	56.00	46.00	-16.63	-
5	4.348	0.39	35.36	-	35.75	-	56.00	46.00	-20.25	-
6	8.051	0.42	49.65	21.49	50.07	21.91	60.00	50.00	-9.93	-28.09

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 11		PHASE	Line 1
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		B			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.588	0.15	44.56	-	44.71	-	56.00	46.00	-11.29	-
2	0.744	0.18	45.03	-	45.21	-	56.00	46.00	-10.79	-
3	0.959	0.23	44.50	-	44.73	-	56.00	46.00	-11.27	-
4	1.117	0.24	43.62	-	43.86	-	56.00	46.00	-12.14	-
5	1.734	0.25	38.90	-	39.15	-	56.00	46.00	-16.85	-
6	8.206	0.50	50.04	21.64	50.54	22.14	60.00	50.00	-9.46	-27.86

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION			MEASUREMENT DETAIL		
CHANNEL		Channel 11		PHASE	Line 2
MODULATION TYPE		BPSK		6dB BANDWIDTH	9 kHz
TRANSFER RATE		6Mbps		ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TESTED BY		Jay Hsu		INPUT POWER (SYSTEM)	120Vac, 60 Hz
TEST MODE		B			

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.420	0.11	42.81	-	42.92	-	57.46	47.46	-14.53	-
2	0.568	0.15	41.20	-	41.35	-	56.00	46.00	-14.65	-
3	0.740	0.18	37.14	-	37.32	-	56.00	46.00	-18.68	-
4	0.990	0.24	38.13	-	38.37	-	56.00	46.00	-17.63	-
5	1.734	0.25	38.90	-	39.15	-	56.00	46.00	-16.85	-
6	8.070	0.42	49.98	20.25	50.40	20.67	60.00	50.00	-9.60	-29.33

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 01, 2007
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Dec. 04, 2006
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 15, 2007
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 01, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 19, 2007
Preamplifier Agilent	8449B	3008A01960	Nov. 09, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219268/4	Dec. 20, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	230129/4	Dec. 20, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-4.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.



4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

(Adapter model: RH48-1201000DU)

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		FREQUENCY RANGE		Below 1000MHz
MODULATION TYPE		DETECTOR FUNCTION		Quasi-Peak
TRANSFER RATE		ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH, 991hPa
TESTED BY		INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	249.66	38.26 QP	46.00	-7.74	1.00 H	232	25.92	12.34
2	278.82	39.80 QP	46.00	-6.20	1.00 H	241	25.32	14.48
3	457.66	36.54 QP	46.00	-9.46	2.00 H	235	17.58	18.96
4	488.76	39.80 QP	46.00	-6.20	1.50 H	229	19.97	19.83
5	558.74	40.85 QP	46.00	-5.15	1.50 H	262	19.32	21.53
6	807.00	44.19 QP	46.00	-1.81	1.00 H	0	18.38	25.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	249.66	38.26 QP	46.00	-7.74	1.00 H	232	25.92	12.34
2	278.82	39.80 QP	46.00	-6.20	1.00 H	241	25.32	14.48
3	457.66	36.54 QP	46.00	-9.46	2.00 H	235	17.58	18.96
4	488.76	39.80 QP	46.00	-6.20	1.50 H	229	19.97	19.83
5	558.74	40.85 QP	46.00	-5.15	1.50 H	262	19.32	21.53
6	807.00	44.19 QP	46.00	-1.81	1.00 H	0	18.38	25.81

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



(Adapter model: MT12-4120100-A1)

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 11	FREQUENCY RANGE		Below 1000MHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION		Quasi-Peak
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH, 991hPa
TESTED BY	Brad Wu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	206.89	39.82 QP	43.50	-3.68	1.00 H	91	29.04	10.78
2	278.82	37.01 QP	46.00	-8.99	1.00 H	232	22.54	14.48
3	348.80	36.62 QP	46.00	-9.38	1.00 H	205	20.51	16.11
4	486.81	39.53 QP	46.00	-6.47	1.50 H	232	19.76	19.77
5	809.50	41.79 QP	46.00	-4.21	1.00 H	109	15.91	25.88
6	840.60	39.25 QP	46.00	-6.75	1.50 H	301	12.47	26.77

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	47.49	36.77 QP	40.00	-3.23	1.00 V	253	23.09	13.69
2	70.82	36.59 QP	40.00	-3.41	1.00 V	37	24.93	11.66
3	216.00	31.44 QP	43.50	-12.06	1.00 V	28	20.33	11.11
4	280.76	34.29 QP	46.00	-11.71	1.50 V	187	19.73	14.56
5	560.68	35.07 QP	46.00	-10.93	1.00 V	112	13.49	21.58
6	807.56	38.39 QP	46.00	-7.61	2.00 V	25	12.56	25.82

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



802.11b DSSS modulation

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.36 PK	74.00	-20.64	1.05 H	251	22.58	30.78
2	2390.00	44.21 AV	54.00	-9.79	1.05 H	251	13.43	30.78
3	*2412.00	94.93 PK			1.05 H	251	64.06	30.87
4	*2412.00	91.38 AV			1.05 H	251	60.51	30.87
5	2492.00	57.49 PK	74.00	-16.51	1.01 H	254	26.32	31.17
6	2492.00	48.12 AV	54.00	-5.88	1.01 H	254	16.95	31.17
7	4824.00	45.17 PK	74.00	-28.83	1.00 H	23	8.83	36.34
8	4824.00	32.47 AV	54.00	-21.53	1.00 H	23	-3.87	36.34

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.06 PK	74.00	-14.94	1.03 V	218	28.28	30.78
2	2390.00	51.94 AV	54.00	-2.06	1.03 V	218	21.16	30.78
3	*2412.00	103.50 PK			1.03 V	218	72.63	30.87
4	*2412.00	100.54 AV			1.03 V	218	69.67	30.87
5	2489.00	61.88 PK	74.00	-12.12	1.00 V	210	30.72	31.16
6	2489.00	52.46 AV	54.00	-1.54	1.00 V	210	21.30	31.16
7	4824.00	45.85 PK	74.00	-28.15	1.02 V	90	9.51	36.34
8	4824.00	34.31 AV	54.00	-19.69	1.02 V	90	-2.03	36.34

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 6	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	94.38 PK			1.42 H	273	63.42	30.96
2	*2437.00	91.12 AV			1.42 H	273	60.16	30.96
3	2514.00	40.65 PK	74.38	-33.73	1.42 H	273	9.41	31.24
4	2514.00	37.39 AV	71.12	-33.73	1.42 H	273	6.15	31.24
5	4874.00	46.23 PK	74.00	-27.77	1.29 H	126	9.75	36.48
6	4874.00	35.73 AV	54.00	-18.27	1.29 H	126	-0.75	36.48

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	103.19 PK			1.41 V	269	72.23	30.96
2	*2437.00	100.45 AV			1.41 V	269	69.49	30.96
3	2514.00	46.46 PK	83.19	-36.73	1.40 V	260	15.22	31.24
4	2514.00	42.72 AV	80.45	-37.73	1.40 V	260	11.48	31.24
5	4874.00	49.95 PK	74.00	-24.05	1.43 V	42	13.47	36.48
6	4874.00	45.04 AV	54.00	-8.96	1.43 V	42	8.56	36.48

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 11	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	DBPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	1Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	94.85 PK			1.35 H	273	63.79	31.06
2	*2462.00	91.19 AV			1.35 H	273	60.13	31.06
3	2483.50	54.69 PK	74.00	-19.31	1.35 H	273	23.55	31.14
4	2483.50	45.11 AV	54.00	-8.89	1.35 H	273	13.97	31.14
5	4924.00	45.53 PK	74.00	-28.47	1.32 H	147	8.90	36.63
6	4924.00	36.21 AV	54.00	-17.79	1.32 H	147	-0.42	36.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
	*2462.00	103.67 PK			1.06 V	163	72.61	31.06
2	*2462.00	100.01 AV			1.06 V	163	68.95	31.06
3	2483.50	58.94 PK	74.00	-15.06	1.06 V	163	27.80	31.14
4	2483.50	48.52 AV	54.00	-5.48	1.06 V	163	17.38	31.14
5	4924.00	48.42 PK	74.00	-25.58	1.04 V	298	11.79	36.63
6	4924.00	41.34 AV	54.00	-12.66	1.04 V	298	4.71	36.63

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



802.11g OFDM modulation

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.33 PK	74.00	-20.67	1.00 H	151	22.55	30.78
2	2390.00	43.96 AV	54.00	-10.04	1.00 H	151	13.18	30.78
3	*2412.00	93.79 PK			1.00 H	151	62.92	30.87
4	*2412.00	84.97 AV			1.00 H	151	54.10	30.87
5	2488.00	57.35 PK	74.00	-16.65	1.00 H	150	26.20	31.15
6	2488.00	46.50 AV	54.00	-7.50	1.00 H	150	15.35	31.15
7	4824.00	45.08 PK	74.00	-28.92	1.00 H	315	8.74	36.34
8	4824.00	32.56 AV	54.00	-21.44	1.00 H	315	-3.78	36.34

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.78 PK	74.00	-19.22	1.26 V	200	24.00	30.78
2	2390.00	44.59 AV	54.00	-9.41	1.26 V	200	13.81	30.78
3	*2412.00	100.89 PK			1.26 V	202	70.02	30.87
4	*2412.00	91.77 AV			1.26 V	202	60.90	30.87
5	2488.00	59.45 PK	74.00	-14.55	1.26 V	202	28.30	31.15
6	2488.00	48.85 AV	54.00	-5.15	1.26 V	202	17.70	31.15
7	4824.00	45.50 PK	74.00	-28.50	1.00 V	2	9.16	36.34
8	4824.00	32.72 AV	54.00	-21.28	1.00 V	2	-3.62	36.34

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 6	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	93.64 PK			1.39 H	273	62.68	30.96
2	*2437.00	84.67 AV			1.39 H	273	53.71	30.96
3	2514.00	43.35 PK	73.64	-30.29	1.30 H	270	12.11	31.24
4	2514.00	34.38 AV	64.67	-30.29	1.30 H	270	3.14	31.24
5	4874.00	45.65 PK	74.00	-28.35	1.45 H	175	9.17	36.48
6	4874.00	32.44 AV	54.00	-21.56	1.45 H	175	-4.04	36.48

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.65 PK			1.04 V	218	69.69	30.96
2	*2437.00	91.41 AV			1.04 V	218	60.45	30.96
3	2514.00	51.36 PK	80.65	-29.29	1.00 V	200	20.12	31.24
4	2514.00	42.12 AV	71.41	-29.29	1.00 V	200	10.88	31.24
5	4874.00	43.80 PK	74.00	-30.20	1.45 V	32	7.32	36.48
6	4874.00	30.82 AV	54.00	-23.18	1.45 V	32	-5.66	36.48

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*” : Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 11	FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS		24deg. C, 65%RH, 991hPa
TESTED BY	Jay Hsu	INPUT POWER (SYSTEM)		120Vac, 60 Hz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	93.99 PK			1.36 H	260	62.93	31.06
2	*2462.00	85.11 AV			1.36 H	260	54.05	31.06
3	2483.50	47.46 PK	74.00	-26.54	1.36 H	260	16.32	31.14
4	2483.50	33.57 AV	54.00	-20.43	1.36 H	260	2.43	31.14
5	4924.00	45.86 PK	74.00	-28.14	1.23 H	2	9.23	36.63
6	4924.00	32.83 AV	54.00	-21.17	1.23 H	2	-3.80	36.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.24 PK			1.31 V	237	69.18	31.06
2	*2462.00	91.67 AV			1.31 V	237	60.61	31.06
3	2483.50	48.70 PK	74.00	-25.30	1.31 V	237	17.56	31.14
4	2483.50	40.13 AV	54.00	-13.87	1.31 V	237	8.99	31.14
5	4924.00	44.63 PK	74.00	-29.37	1.31 V	0	8.00	36.63
6	4924.00	33.15 AV	54.00	-20.85	1.31 V	0	-3.48	36.63

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.





4.3.7 TEST RESULTS


802.11b DSSS modulation

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.16	0.5	PASS
6	2437	12.12	0.5	PASS
11	2462	12.16	0.5	PASS

CH1

CH6


CH11




**802.11g OFDM modulation**

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.36	0.5	PASS
6	2437	16.32	0.5	PASS
11	2462	16.32	0.5	PASS




CH1



CH6



CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2006
TEKTRONIX OSCILLOSCOPE	TDS1012	C037299	Nov. 28, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to peak the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



4.4.7 TEST RESULTS

802.11b DSSS modulation

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	31.623	15.00	30	PASS
6	2437	31.696	15.01	30	PASS
11	2462	31.989	15.05	30	PASS

802.11g OFDM modulation

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	22.594	13.54	30	PASS
6	2437	22.439	13.51	30	PASS
11	2462	22.491	13.52	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6.




4.5.7 TEST RESULTS

802.11b DSSS modulation


MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-16.16	8	PASS
6	2437	-16.26	8	PASS
11	2462	-16.39	8	PASS


CH1



CH6





CH11




**802.11g OFDM modulation**

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	21deg. C, 63%RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-16.08	8	PASS
6	2437	-16.29	8	PASS
11	2462	-15.98	8	PASS

CH1

CH6


CH11





4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded. The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6.



4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).



802.11b DSSS modulation



NOTE 1: The band edge emission plot on page 59 shows 48.27dBc between carrier maximum power and local maximum emission in restrict band (2.3862GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.50dBuV/m (Peak), so the maximum field strength in restrict band is $103.50 - 48.27 = 55.23$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 59 shows 53.26dBc between carrier maximum power and local maximum emission in restrict band (2.3864GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.54dBuV/m (Average), so the maximum field strength in restrict band is $100.54 - 53.26 = 47.28$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 60 shows 49.22dBc between carrier maximum power and local maximum emission in restrict band (2.4881GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 103.67dBuV/m (Peak), so the maximum field strength in restrict band is $103.67 - 49.22 = 54.45$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 61 shows 54.09dBc between carrier maximum power and local maximum emission in restrict band (2.4877GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.01dBuV/m (Average), so the maximum field strength in restrict band is $100.01 - 54.09 = 45.92$ dBuV/m which is under 54dBuV/m limit.











802.11g OFDM modulation



NOTE 1: The band edge emission plot on page 63 shows 44.19dBc between carrier maximum power and local maximum emission in restrict band (2.3300GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.89dBuV/m (Peak), so the maximum field strength in restrict band is $100.89 - 44.19 = 56.70$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 63 shows 52.01dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 91.77dBuV/m (Average), so the maximum field strength in restrict band is $91.77 - 52.01 = 39.76$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 64 shows 44.45dBc between carrier maximum power and local maximum emission in restrict band (2.4885GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.24dBuV/m (Peak), so the maximum field strength in restrict band is $100.24 - 44.45 = 55.79$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 65 shows 51.54dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 91.67dBuV/m (Average), so the maximum field strength in restrict band is $91.67 - 51.54 = 40.13$ dBuV/m which is under 54dBuV/m limit.









4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna type used in this product is Dipole antenna without antenna connector. The maximum Gain of the antenna is 2.2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST (TEST MODE A)



CONDUCTED EMISSION TEST (TEST MODE B)



RADIATED EMISSION TEST (TEST MODE A)



RADIATED EMISSION TEST (TEST MODE B)





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab

Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.