

CFL  
M31-400  
AC Protector  
Type 2 SPD  
CFL US CE  
Nominal Voltage - 277 V/480 Hz  
Max. Voltage - 600V  
Discharge Current - 3 kA  
Surge Voltage Rating - 1500 V  
IEC Max. Discharge Current - 10 kA

Diplexer 918 MHz  
SMR 900  
CD918/6SK-B1  
S/N 16061457

Diplexer 918 MHz  
SMR 900  
CD918/6SK-B1  
S/N 16061456

DANGER LIVE HEATSINK

CAUTION  
LIVE HEAT SINKS

LEP240F-36 D28  
120V  
CE

CINCON  
IN: 18-36VDC  
OUT: 5VDC  
EC8A11S

IN OUT  
LNA: MA860/2.3430K-A1  
Low Noise Amplifier  
700 ~ 1000 MHz

IN  
OUT  
C1  
R1  
R2  
R3  
R4  
R5  
R6  
R7  
R8  
R9  
R10  
R11  
R12  
R13  
R14  
R15  
R16  
R17  
R18  
R19  
R20  
R21  
R22  
R23  
R24  
R25  
R26  
R27  
R28  
R29  
R30  
R31  
R32  
R33  
R34  
R35  
R36  
R37  
R38  
R39  
R40  
R41  
R42  
R43  
R44  
R45  
R46  
R47  
R48  
R49  
R50  
R51  
R52  
R53  
R54  
R55  
R56  
R57  
R58  
R59  
R60  
R61  
R62  
R63  
R64  
R65  
R66  
R67  
R68  
R69  
R70  
R71  
R72  
R73  
R74  
R75  
R76  
R77  
R78  
R79  
R80  
R81  
R82  
R83  
R84  
R85  
R86  
R87  
R88  
R89  
R90  
R91  
R92  
R93  
R94  
R95  
R96  
R97  
R98  
R99  
R100