

Company: Aruba Networks, Inc.

Test of: APIN0204, APIN0205
To: FCC CFR 47 Part 15 Subpart E 15.407

Report No.: ARUB206-1_MPE Rev A

MPE TEST REPORT



MPE TEST REPORT

FROM



Test of: Aruba Networks, Inc. APIN0204, APIN0205

to

To: FCC CFR 47 Part 15 Subpart E 15.407

Test Report Serial No.: ARUB206-1_MPE Rev A

This report supersedes: NONE

Applicant: Aruba Networks, Inc.
1344 Crossman Ave.
Sunnyvale, California 94089
USA

Product Function: Wireless Access Point

Issue Date: 3rd May May 2016

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ²	Calculated Power Density @ 20cm	Minimum Separation Distance (cm)
2400 – 2483.5	7.5	5.62	21.63	145.55	8.10	0.16	20.00
5150.0 - 5250.0	3.30	2.14	27.73	593.55	10.05	0.25	20.00
5725.0 - 5850.0	3.30	2.14	27.95	624.40	10.31	0.27	20.00

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Assessment for simultaneous operation in 2.4 GHz and 5 GHz bands

The Aruba APIN0204, APIN0205 has two radio modules and can transmit simultaneously in the 2.4 GHz and 5 GHz bands. The following assessment is based on simultaneous operation in the 2.4 GHz and 5 GHz bands.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
2400 – 2483.5	7.5	5.62	21.63	145.55	8.10	20.00
5725.0 - 5850.0	3.30	2.14	27.95	624.40	10.31	20.00
Combined EIRP Total			2154.2 mW/EIRP		13.1	20.0



Title: Aruba Networks, Inc. APIN0204, APIN0205
To: FCC CFR 47 Part 15 Subpart E 15.407
Serial #: ARUB206-1_MPE Rev A
Issue Date: 3rd May 2016
Page: 4 of 5

Specification
Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §3.2 In addition to RSS-Gen, the requirements in Radio Standards Specification RSS-102 shall be met.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com