# Label

Label Position

HUAWEI
SOLAR INVERTER
Model: SUN2000-30KTL-US
Max. Input Voltage: 1000 Vdc
MPPT Voltage Range: 250 - 950 Vdc
Full Load MPPT Voltage Range: 560 - 850 Vdc
Max. Input Current: 25 A/25 A/25 A
Nominal Output Voltage: 480 Vac; 3Φ + ⏚ or 3Φ + N + ⏚
Output Voltage Range: 422 - 528 Vac
Output Rated Power: 30 kW
Max. Output Power: 33 kVA
Max. Output Current: 40 A
Nominal Output Frequency: 60 Hz
Operating Frequency Range: 59.3 - 60.5 Hz
Power Factor: 0.8(leading) - 0.8(lagging)
Operating Temperature Range: - 25 - +60 ℃ ( power derating above 45℃ )
AFCI: Type I
This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID: QIS30KTLUSPLC
C US
235284
华为技术有限公司
HUAWEI TECHNOLOGIES CO .LTD
中国制造
MADE IN CHINA
合格证/QUALIFICATION CARD
检验员/QC :00112208
日 期/DATE : 2017-03-08
HUAWEI
华为技术有限公司
HUAWEI TECHNOLOGIES CO., LTD.
中国制造
MADE IN CHINA
SN:21010730376TGA901415 Y SUN2000-30KTL-US-PLC