



			10	VN	5785.03	5.19	PASS
			0	VN	5785.03	5.19	PASS
			-10	VN	5785.02	3.46	PASS
			-20	VN	5785.04	6.91	PASS
			-30	VN	5785.04	6.91	PASS
			-40	VN	5785.05	8.64	PASS

Note 1: All the modulation and channels had been tested, but only the worst data recorded in the report.



## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### ANTENNA CONNECTOR

EUT has an external antenna with antenna connector, it will be installed in a specific environment and users cannot change the antenna.

### ANTENNA GAIN

The antenna gain of EUT is greater than 6 dBi.

**END OF REPORT**