



FCC SAR Exemption Evaluation Report

Product Name: Wearable Device

Model: B0

Report No.: SYBH(Z-SAR)008072015-2

FCC ID: QISB0

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>Sun Shanbin</i>
DATE	2015-07-08	2015-07-08

The test results of this test report relate exclusively to the item(s) tested . The HUAWEI does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of HUAWEI.

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518



※ ※ **Modified History** ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2015-07-08	Sun Shanbin

Table of Contents

1	EUT Description	4
1.1	General Description	4
2	Test specification(s).....	5
3	Testing laboratory	5
4	Applicant and Manufacturer.....	5
5	Application details	5
6	Ambient Condition.....	5
7	RF exposure limits	6
8	SAR Exemption Evaluation	7

1 EUT Description

Device Information:			
Product Name:	Wearable Device		
Model:	B0		
FCC ID :	QISB0		
Device Type :	Portable device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment / general population		
Hardware Version :	R4		
Software Version :	V21.00.05.02.00		
Antenna Type :	Internal Antenna		
Antenna Gain :	-0.61dBi		
Device Operating Configurations:			
Supporting Mode(s)	BT		
Test Modulation	GFSK		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	BT	2402-2480	2402-2480

Table 1: Device information and operating configuration

1.1 General Description

HUAWEI TalkBand B0 is a smart wrist band that integrates functions of sport assistant, sleep monitoring. It helps you learn about your health status. The B0 can connect to a phone or tablet through Bluetooth. Download and install the B0 app on the phone or tablet to easily manage the data of the B0. The B0 supports the following: (1) Step counting (2) Calory calculation (3) Sport target setting (4) Sleep statistics collection (5) Event reminder (6) Smart alarm

2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB447498 D01	General RF Exposure Guidance v05r02

3 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Zone G1,Huawei Industrial Base, Bantian Industry Area, Longgang District, Shenzhen, Guangdong, China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01

4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

5 Application details

Start Date of test	2015-07-08
End Date of test	2015-07-08

6 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

7 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain/Body/Arms/Legs)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 2: RF exposure limits

The limit applied in this test report is shown in **bold** letters

Notes:

- * The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time
- ** The Spatial Average value of the SAR averaged over the whole body.
- *** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation)

8 SAR Exemption Evaluation

Per FCC KDB 447498D01v05r02, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Exposure Condition	Band	P_{max} (dBm)*	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	Exclusion threshold	SAR evaluation
10g Extremity	BT	0	1.00	< 5	2.450	0.31	7.5	Not required

Table 3: Standalone SAR test exclusion for BT

Note:

- 1)* - Maximum possible output power(including tune-up tolerance) declared by manufacturer
- 2) The test separation distance for this device is ≤ 5 mm, so a distance of 5 mm is applied to determine SAR test exclusion per FCC KDB 447498D01.
- 3) The device does not support speaker mode for voice communication. So evaluation for next to mouth exposure condition is not required.

According to the table above, the device can meet the SAR test exclusion thresholds requirement of FCC KDB 447498 D01 and SAR evaluation is not required.

End