

FCC Test Report

FCC ID : QISB5142
Equipment : B43 TD-LTE Indoor CPE
Model No. : B5142
Brand Name : Huawei
Applicant : Huawei Technologies Co., Ltd.
Address : Administration Building, Headquarters of
Huawei Technologies Co., Ltd., Bantian,
Longgang District, Shenzhen, 518129, P.R.C
Standard : 47 CFR FCC Part 90 Subpart Z
Received Date : Sep. 19, 2014
Tested Date : Sep. 26 ~ Oct. 07, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

| | | |
|----------|---|-----------|
| 1 | GENERAL DESCRIPTION | 5 |
| 1.1 | Information..... | 5 |
| 1.2 | Local Support Equipment List | 8 |
| 1.3 | Test Setup Chart | 8 |
| 1.4 | The Equipment List | 9 |
| 1.5 | Test Standards | 10 |
| 1.6 | Measurement Uncertainty | 10 |
| 2 | TEST CONFIGURATION | 11 |
| 2.1 | Testing Condition and Location Information..... | 11 |
| 2.2 | The Worst Test Modes and Channel Details | 11 |
| 3 | TEST RESULTS..... | 12 |
| 3.1 | Equivalent Isotropically Radiated Power and Peak EIRP Power Density | 12 |
| 3.2 | Radiated Emissions..... | 26 |
| 3.3 | Conducted Emissions..... | 34 |
| 3.4 | Emission Mask | 39 |
| 3.5 | 26dBc Bandwidth | 56 |
| 3.6 | Frequency Stability..... | 61 |
| 4 | TEST LABORATORY INFORMATION | 63 |

Release Record

| Report No. | Version | Description | Issued Date |
|------------|---------|---------------|---------------|
| FW491904 | Rev. 01 | Initial issue | Oct. 15, 2014 |

Summary of Test Results

| FCC Rules | Test Items | Measured | Result |
|---------------------|---|--|--------|
| 2.1046 / 90.1321 | Equivalent Isotropically Radiated Power | Maximum EIRP: 0.736 W / 5MHz 0.787 W / 10MHz 0.773 W / 15MHz 0.721 W / 20MHz | Pass |
| 2.1046 / 90.1321 | Peak EIRP Power Density | Meet the requirement of limit | Pass |
| 2.1053 / 90.1323 | Radiated Emissions | Meet the requirement of limit | Pass |
| 2.1051 / 90.1323 | Conducted Emissions | Meet the requirement of limit | Pass |
| 90.210 | Emission Mask | Meet the requirement of limit | Pass |
| 2.1049(h) / 90.1323 | 26dBc Bandwidth | Meet the requirement of limit | Pass |
| 2.1055 / 90.213 | Frequency Stability | Meet the requirement of limit | Pass |

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

| | |
|----------------------------------|---|
| Operating Frequency (MHz) | Channel Bandwidth: 5MHz: 3652.5~3672.5 Channel Bandwidth: 10MHz: 3655.0~3670.0 Channel Bandwidth: 15MHz: 3657.5~3667.5 Channel Bandwidth: 20MHz: 3660.0~3665.0 |
| Uplink Modulation Type | QPSK, 16QAM |
| Downlink Modulation Type | QPSK, 16QAM, 64QAM |
| Duplex Mode | TDD |
| UE Category | 4 |
| H/W Version | Mother board: V01; daughter board: V00B |
| S/W Version | V100R001C00B020 |

1.1.2 Maximum EIRP & Emission Designator

| Channel Bandwidth | Modulation | Maximum EIRP (W) | Emission Designator |
|-------------------|------------|------------------|---------------------|
| 5MHz | QPSK | 0.695 | 4M46G7D |
| 5MHz | 16QAM | 0.736 | 4M48W7D |
| 10MHz | QPSK | 0.750 | 8M93G7D |
| 10MHz | 16QAM | 0.787 | 8M93W7D |
| 15MHz | QPSK | 0.764 | 13M4G7D |
| 15MHz | 16QAM | 0.773 | 13M4W7D |
| 20MHz | QPSK | 0.582 | 17M8G7D |
| 20MHz | 16QAM | 0.721 | 17M9W7D |

1.1.3 Antenna Details

| Ant. No. | Type | Connector | Gain (dBi) | Remarks |
|----------|-----------------------------|-----------|------------|---------|
| 1 | Directional PCB antenna - 1 | IPEX PLUG | 5.5 | - |

1.1.4 EUT Operational Condition

| | | | |
|-----------------------------|--|--|--|
| Power Supply Type | 12Vdc from adapter | | |
| Operational Voltage | <input checked="" type="checkbox"/> Vnom (120 V) | <input checked="" type="checkbox"/> Vmax (138 V) | <input checked="" type="checkbox"/> Vmin (102 V) |
| Operational Climatic | <input checked="" type="checkbox"/> Tnom (20°C) | <input checked="" type="checkbox"/> Tmax (55°C) | <input checked="" type="checkbox"/> Tmin (-10°C) |

1.1.5 Accessories

| Accessories | | |
|-------------|--------------|---|
| No. | Equipment | Description |
| 1 | Adapter 1 | Brand Name: APD Model Name: WB-18D12FU Power Rating: I/P: 100-240Vac, 50-60Hz, 0.5A O/P: 12Vdc, 1.5A Power Line: 1.5m non-shielded cable w/o core |
| 2 | Adapter 2 | Brand Name: AOEM Model Name: ADS0248-W 120150 Power Rating: I/P: 100-240Vac, 50-60Hz, 0.6A O/P: 12Vdc, 1.5A Power Line: 1.2m non-shielded cable w/o core |
| 3 | RJ45 cable 1 | EKSON, 1.5m non-shielded cable w/o core |
| 4 | RJ45 cable 2 | TUNG-LI, 1.5m non-shielded cable w/o core |


1.1.6 Operating Channel List

| Channel Bandwidth (MHz) | Channel | Frequency (MHz) |
|-------------------------|---------|-----------------|
| 5 | 44115 | 3652.5 |
| 5 | 44215 | 3662.5 |
| 5 | 44315 | 3672.5 |
| 10 | 44140 | 3655.0 |
| 10 | 44215 | 3662.5 |
| 10 | 44290 | 3670.0 |
| 15 | 44190 | 3657.5 |
| 15 | 44215 | 3662.5 |
| 15 | 44240 | 3667.5 |
| 20 | 44190 | 3660.0 |
| 20 | 44215 | 3662.5 |
| 20 | 44240 | 3665.0 |

1.2 Local Support Equipment List

| Support Equipment List | | | | | | |
|------------------------|-----------|-------|---------|--------|---------|---------------------------|
| No. | Equipment | Brand | Model | S/N | FCC ID | Signal cable / Length (m) |
| 1 | Notebook | DELL | E6430 | --- | FCC DoC | RJ45, 8m non-shielded |
| 2 | Telephone | HTT | HTT-806 | 186618 | --- | RJ11, 1.8m non-shielded |
| 3 | Telephone | HTT | HTT-806 | 187113 | --- | RJ11, 1.8m non-shielded |

1.3 Test Setup Chart



1.4 The Equipment List

| Test Item | Radiated Emission | | | | |
|-------------------------|----------------------------|-------------|------------------|------------------|-------------------|
| Test Site | 966 chamber1 / (03CH01-WS) | | | | |
| Instrument | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Until |
| Spectrum Analyzer | R&S | FSV40 | 101498 | Jan. 25, 2014 | Jan. 24, 2015 |
| Receiver | R&S | ESR3 | 101658 | Jan. 10, 2014 | Jan. 09, 2015 |
| Bilog Antenna | SCHWARZBECK | VULB9168 | VULB9168-522 | Sep. 05, 2014 | Sep. 04, 2015 |
| Horn Antenna 1G-18G | SCHWARZBECK | BBHA 9120 D | BBHA 9120 D 1096 | Feb. 13, 2014 | Feb. 12, 2015 |
| Horn Antenna 18G-40G | SCHWARZBECK | BBHA 9170 | BBHA 9170517 | Dec. 27, 2013 | Dec. 26, 2014 |
| Preamplifier | Burgeon | BPA-530 | SN:100219 | Sep. 09, 2014 | Sep. 08, 2015 |
| Preamplifier | Agilent | 83017A | MY39501308 | Dec. 16, 2013 | Dec. 15, 2014 |
| Preamplifier | EMC | EMC184045B | 980192 | Aug. 26, 2014 | Aug. 25, 2015 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16014/4 | Dec. 16, 2013 | Dec. 15, 2014 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16019/4 | Dec. 16, 2013 | Dec. 15, 2014 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16139/4 | Dec. 16, 2013 | Dec. 15, 2014 |
| LF cable 3M | Woken | CFD400NL-LW | CFD400NL-001 | Dec. 16, 2013 | Dec. 15, 2014 |
| LF cable 10M | Woken | CFD400NL-LW | CFD400NL-002 | Dec. 16, 2013 | Dec. 15, 2014 |
| Measurement Software | AUDIX | e3 | 6.120210g | NA | NA |

Note: Calibration Interval of instruments listed above is one year.

| | | | | | |
|--------------|-----|---------|--------|---------------|---------------|
| Loop Antenna | R&S | HFH2-Z2 | 100330 | Nov. 15, 2012 | Nov. 14, 2014 |
|--------------|-----|---------|--------|---------------|---------------|

Note: Calibration Interval of instruments listed above is two year.

| Test Item | RF Conducted | | | | |
|------------------------------------|--------------|------------------|-------------|------------------|-------------------|
| Test Site | (TH01-WS) | | | | |
| Instrument | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Until |
| Spectrum Analyzer | R&S | FSV40 | 101063 | Feb. 17, 2014 | Feb. 16, 2015 |
| Spectrum Analyzer | Agilent | N9010A | MY53400091 | Sep. 16, 2014 | Sep. 15, 2015 |
| TEMP&HUMIDITY CHAMBER | GIANT FORCE | GCT-225-40-SP-SD | MAF1212-002 | Dec. 11, 2013 | Dec. 10, 2014 |
| Power Meter | Anritsu | ML2495A | 1241001 | Sep. 11, 2014 | Sep. 10, 2015 |
| Power Sensor | Anritsu | MA2411B | 1207362 | Sep. 12, 2014 | Sep. 11, 2015 |
| Signal Generator | R&S | SMB100A | 175727 | Jan. 07, 2014 | Jan. 06, 2015 |
| Radio Communication Analyzer | Anritsu | MT8820C | 6201240341 | Mar. 18, 2014 | Mar. 17, 2015 |
| Measurement Software | Sporton | Sporton_1 | 1.3.30 | NA | NA |

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards.

47 CFR FCC Part 90 Subpart Z
 KDB 965270 D01 PwrMeas Part 90 Z Equipment v01
 ANSI C63.4-2003
 ANSI/TIA-603-C-2004
 KDB 971168 D01 Power Meas License Digital Systems v02r01
 KDB 412172 D01 Determining ERP and EIRP v01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

| Measurement Uncertainty | |
|--------------------------|-------------|
| Parameters | Uncertainty |
| Bandwidth | ±34.134 Hz |
| Conducted power | ±0.808 dB |
| Frequency error | ±34.134 Hz |
| Temperature | ±0.6 °C |
| Conducted emission | ±2.670 dB |
| AC conducted emission | ±2.92 dB |
| Radiated emission ≤ 1GHz | ±3.26 dB |
| Radiated emission > 1GHz | ±4.94 dB |

2 Test Configuration

2.1 Testing Condition and Location Information

| Test Item | Test Site | Ambient Condition | Tested By |
|--------------------|-----------|-------------------|------------|
| RF conducted | TH01-WS | 23°C / 62% | Felix Sung |
| Radiated Emissions | 03CH01-WS | 23°C / 64% | Haru Yang |

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

| Test item | Channel Bandwidth | Modulation | Test channel (MHz) |
|---|-------------------|---------------|--------------------------|
| Equivalent Isotropically Radiated Power Peak EIRP Power Density | 5 MHz | QPSK / 16QAM | 3652.5 / 3662.5 / 3672.5 |
| | 10 MHz | QPSK / 16QAM | 3655.0 / 3662.5 / 3670.0 |
| | 15 MHz | QPSK / 16QAM | 3657.5 / 3662.5 / 3667.5 |
| | 20 MHz | QPSK / 16QAM | 3660.0 / 3662.5 / 3665.0 |
| Radiated Emission ≤ 1GHz | 5 MHz | 16QAM | 3672.5 |
| | 10 MHz | 16QAM | 3655.0 |
| | 15 MHz | 16QAM | 3667.5 |
| | 20 MHz | 16QAM | 3665.0 |
| Radiated Emission > 1GHz | 5 MHz | 16QAM | 3652.5 / 3662.5 / 3672.5 |
| | 10 MHz | 16QAM | 3655.0 / 3662.5 / 3670.0 |
| | 15 MHz | 16QAM | 3657.5 / 3662.5 / 3667.5 |
| | 20 MHz | 16QAM | 3660.0 / 3662.5 / 3665.0 |
| Conducted Emissions Emission Mask 26dBc Bandwidth | 5 MHz | QPSK / 16QAM | 3652.5 / 3662.5 / 3672.5 |
| | 10 MHz | QPSK / 16QAM | 3655.0 / 3662.5 / 3670.0 |
| | 15 MHz | QPSK / 16QAM | 3657.5 / 3662.5 / 3667.5 |
| | 20 MHz | QPSK / 16QAM | 3660.0 / 3662.5 / 3665.0 |
| Frequency Stability | --- | Un-modulation | 3662.5 |
| NOTE: | | | |
| 1. Adapter 1 and Adapter 2 had been pretested and found that Adapter 1 was the worst case and was selected for final testing (Adapter 1: APD adapter; Adapter 2: AOEM adapter). | | | |
| 2. RJ45 cable 1 and RJ45 cable 2 had been pretested and found that RJ45 cable 2 was the worst case and was selected for final testing (RJ45 cable 1: EKSON; Adapter 2: TUNG-LI). | | | |

3 Test Results

3.1 Equivalent Isotropically Radiated Power and Peak EIRP Power Density

3.1.1 Limit of Equivalent Isotropically Radiated Power and Peak EIRP Power Density

Base and fixed stations are limited to 25 watts/25 MHz equivalent isotropically radiated power (EIRP), the peak EIRP power density shall not exceed 1 Watt in any one-mega hertz slice of spectrum.

Mobile and portable stations are limited to 1 watt/25 MHz EIRP. The peak EIRP density shall not exceed 40 milli watts in any one-megahertz slice of spectrum.

3.1.2 Test Procedures


For EIRP

1. Connect the DUT transmitter output to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
2. Tune the analyzer to the nominal center frequency of the emission bandwidth.
3. Set the span to twice the nominal EBW (span = 2 x EBW).
4. Set the resolution bandwidth (RBW) to approximately 1% of EBW.
5. Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
6. Select the average power (RMS) display detector.
7. Set the number of measurement points to ≥ 1001 .
8. Use auto-coupled sweep time.
9. Perform measurement over an interval of time when the transmission is continuous and at its maximum power level.
10. Utilize trace averaging over 100 traces in the power averaging.
11. Use the Channel Power function to determine the integrated power over the full EBW.
12. Record the band power level.
13. Adjust the recorded level by applying appropriate correction factors for the measurement set-up.
14. Determine the EIRP by adding the effective antenna gain to the adjusted power level.

For Peak EIRP Power Density

1. Connect the transmitter to the spectrum analyzer via coaxial cable (i.e., conducted measurement) while ensuring proper impedance matching.
2. Tune the analyzer to the nominal center frequency of the emission bandwidth.
3. Set the span to twice the nominal EBW (span = 2 x EBW).
4. Set the resolution bandwidth (RBW) to 1 MHz.
5. Set the video bandwidth (VBW) to 3 MHz
6. Select the average power (RMS) display detector.
7. Set the number of measurement points to ≥ 1001 .
8. Use auto-coupled sweep time.
9. Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
10. Utilize trace averaging over 100 traces in the power averaging.
11. Find the maximum trace amplitude (peak search) and record.
12. Adjust the recorded level by applying appropriate correction factors for the measurement set-up.
13. Determine the EIRP by adding the effective antenna gain to the adjusted power level.

3.1.3 Test Setup



3.1.4 Test Result of EIRP

Channel Bandwidth: 5MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44115 | 3652.5 | 1 | 0 | 22.61 | 5.5 | 28.11 | 0.647 | 5 |
| | | 1 | 24 | 22.83 | 5.5 | 28.33 | 0.681 | 5 |
| | | 12 | 6 | 22.30 | 5.5 | 27.80 | 0.603 | 5 |
| | | 25 | 0 | 22.18 | 5.5 | 27.68 | 0.586 | 5 |
| 44215 | 3662.5 | 1 | 0 | 22.50 | 5.5 | 28.00 | 0.631 | 5 |
| | | 1 | 24 | 22.58 | 5.5 | 28.08 | 0.643 | 5 |
| | | 12 | 6 | 22.36 | 5.5 | 27.86 | 0.611 | 5 |
| | | 25 | 0 | 22.17 | 5.5 | 27.67 | 0.585 | 5 |
| 44315 | 3672.5 | 1 | 0 | 22.05 | 5.5 | 27.55 | 0.569 | 5 |
| | | 1 | 24 | 22.92 | 5.5 | 28.42 | 0.695 | 5 |
| | | 12 | 6 | 22.31 | 5.5 | 27.81 | 0.604 | 5 |
| | | 25 | 0 | 22.07 | 5.5 | 27.57 | 0.571 | 5 |

Channel Bandwidth: 5MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44115 | 3652.5 | 1 | 0 | 22.71 | 5.5 | 28.21 | 0.662 | 5 |
| | | 1 | 24 | 22.91 | 5.5 | 28.41 | 0.693 | 5 |
| | | 12 | 6 | 22.69 | 5.5 | 28.19 | 0.659 | 5 |
| | | 25 | 0 | 22.68 | 5.5 | 28.18 | 0.658 | 5 |
| 44215 | 3662.5 | 1 | 0 | 22.76 | 5.5 | 28.26 | 0.670 | 5 |
| | | 1 | 24 | 23.06 | 5.5 | 28.56 | 0.718 | 5 |
| | | 12 | 6 | 22.92 | 5.5 | 28.42 | 0.695 | 5 |
| | | 25 | 0 | 22.79 | 5.5 | 28.29 | 0.675 | 5 |
| 44315 | 3672.5 | 1 | 0 | 22.60 | 5.5 | 28.10 | 0.646 | 5 |
| | | 1 | 24 | 23.17 | 5.5 | 28.67 | 0.736 | 5 |
| | | 12 | 6 | 23.04 | 5.5 | 28.54 | 0.714 | 5 |
| | | 25 | 0 | 22.98 | 5.5 | 28.48 | 0.705 | 5 |

Channel Bandwidth: 10MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44140 | 3655.0 | 1 | 0 | 22.45 | 5.5 | 27.95 | 0.624 | 10 |
| | | 1 | 49 | 23.10 | 5.5 | 28.60 | 0.724 | 10 |
| | | 25 | 12 | 22.22 | 5.5 | 27.72 | 0.592 | 10 |
| | | 50 | 0 | 21.98 | 5.5 | 27.48 | 0.560 | 10 |
| 44215 | 3662.5 | 1 | 0 | 22.54 | 5.5 | 28.04 | 0.637 | 10 |
| | | 1 | 49 | 23.16 | 5.5 | 28.66 | 0.735 | 10 |
| | | 25 | 12 | 22.31 | 5.5 | 27.81 | 0.604 | 10 |
| | | 50 | 0 | 22.11 | 5.5 | 27.61 | 0.577 | 10 |
| 44290 | 3670.0 | 1 | 0 | 22.58 | 5.5 | 28.08 | 0.643 | 10 |
| | | 1 | 49 | 23.25 | 5.5 | 28.75 | 0.750 | 10 |
| | | 25 | 12 | 22.43 | 5.5 | 27.93 | 0.621 | 10 |
| | | 50 | 0 | 22.18 | 5.5 | 27.68 | 0.586 | 10 |

Channel Bandwidth: 10MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|--------------|----------|-----------|
| 44140 | 3655.0 | 1 | 0 | 22.75 | 5.5 | 28.25 | 0.668 | 10 |
| | | 1 | 49 | 23.46 | 5.5 | 28.96 | 0.787 | 10 |
| | | 25 | 12 | 22.38 | 5.5 | 27.88 | 0.614 | 10 |
| | | 50 | 0 | 22.15 | 5.5 | 27.65 | 0.582 | 10 |
| 44215 | 3662.5 | 1 | 0 | 23.02 | 5.5 | 28.52 | 0.711 | 10 |
| | | 1 | 49 | 23.30 | 5.5 | 28.80 | 0.759 | 10 |
| | | 25 | 12 | 22.35 | 5.5 | 27.85 | 0.610 | 10 |
| | | 50 | 0 | 22.29 | 5.5 | 27.79 | 0.601 | 10 |
| 44290 | 3670.0 | 1 | 0 | 22.70 | 5.5 | 28.20 | 0.661 | 10 |
| | | 1 | 49 | 22.91 | 5.5 | 28.41 | 0.693 | 10 |
| | | 25 | 12 | 22.57 | 5.5 | 28.07 | 0.641 | 10 |
| | | 50 | 0 | 22.46 | 5.5 | 27.96 | 0.625 | 10 |

Channel Bandwidth: 15MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44165 | 3657.5 | 1 | 0 | 22.91 | 5.5 | 28.41 | 0.693 | 15 |
| | | 1 | 74 | 23.33 | 5.5 | 28.83 | 0.764 | 15 |
| | | 36 | 18 | 22.50 | 5.5 | 28.00 | 0.631 | 15 |
| | | 75 | 0 | 22.29 | 5.5 | 27.79 | 0.601 | 15 |
| 44215 | 3662.5 | 1 | 0 | 22.55 | 5.5 | 28.05 | 0.638 | 15 |
| | | 1 | 74 | 22.68 | 5.5 | 28.18 | 0.658 | 15 |
| | | 36 | 18 | 22.29 | 5.5 | 27.79 | 0.601 | 15 |
| | | 75 | 0 | 22.11 | 5.5 | 27.61 | 0.577 | 15 |
| 44265 | 3667.5 | 1 | 0 | 22.57 | 5.5 | 28.07 | 0.641 | 15 |
| | | 1 | 74 | 22.72 | 5.5 | 28.22 | 0.664 | 15 |
| | | 36 | 18 | 22.39 | 5.5 | 27.89 | 0.615 | 15 |
| | | 75 | 0 | 22.22 | 5.5 | 27.72 | 0.592 | 15 |

Channel Bandwidth: 15MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44165 | 3657.5 | 1 | 0 | 22.52 | 5.5 | 28.02 | 0.634 | 15 |
| | | 1 | 74 | 22.67 | 5.5 | 28.17 | 0.656 | 15 |
| | | 36 | 18 | 22.38 | 5.5 | 27.88 | 0.614 | 15 |
| | | 75 | 0 | 22.13 | 5.5 | 27.63 | 0.579 | 15 |
| 44215 | 3662.5 | 1 | 0 | 22.94 | 5.5 | 28.44 | 0.698 | 15 |
| | | 1 | 74 | 23.18 | 5.5 | 28.68 | 0.738 | 15 |
| | | 36 | 18 | 22.54 | 5.5 | 28.04 | 0.637 | 15 |
| | | 75 | 0 | 22.26 | 5.5 | 27.76 | 0.597 | 15 |
| 44265 | 3667.5 | 1 | 0 | 22.99 | 5.5 | 28.49 | 0.706 | 15 |
| | | 1 | 74 | 23.38 | 5.5 | 28.88 | 0.773 | 15 |
| | | 36 | 18 | 22.55 | 5.5 | 28.05 | 0.638 | 15 |
| | | 75 | 0 | 22.27 | 5.5 | 27.77 | 0.598 | 15 |


Channel Bandwidth: 20MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|-----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44190 | 3660.0 | 1 | 0 | 21.89 | 5.5 | 27.39 | 0.548 | 20 |
| | | 1 | 99 | 22.10 | 5.5 | 27.60 | 0.575 | 20 |
| | | 50 | 25 | 21.66 | 5.5 | 27.16 | 0.520 | 20 |
| | | 100 | 0 | 21.52 | 5.5 | 27.02 | 0.504 | 20 |
| 44215 | 3662.5 | 1 | 0 | 21.93 | 5.5 | 27.43 | 0.553 | 20 |
| | | 1 | 99 | 22.15 | 5.5 | 27.65 | 0.582 | 20 |
| | | 50 | 25 | 21.72 | 5.5 | 27.22 | 0.527 | 20 |
| | | 100 | 0 | 21.5 | 5.5 | 27.00 | 0.501 | 20 |
| 44240 | 3665.0 | 1 | 0 | 22.00 | 5.5 | 27.50 | 0.562 | 20 |
| | | 1 | 99 | 22.14 | 5.5 | 27.64 | 0.581 | 20 |
| | | 50 | 25 | 21.73 | 5.5 | 27.23 | 0.528 | 20 |
| | | 100 | 0 | 21.55 | 5.5 | 27.05 | 0.507 | 20 |


Channel Bandwidth: 20MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Output Power (dBm) | Max. Ant. Gain(dBi) | EIRP (dBm) | EIRP (W) | LIMIT (W) |
|---------|-------------------------|-----|------------|------------------------------|---------------------|------------|----------|-----------|
| 44190 | 3660.0 | 1 | 0 | 22.16 | 5.5 | 27.66 | 0.583 | 20 |
| | | 1 | 99 | 23.04 | 5.5 | 28.54 | 0.714 | 20 |
| | | 50 | 25 | 21.75 | 5.5 | 27.25 | 0.531 | 20 |
| | | 100 | 0 | 21.62 | 5.5 | 27.12 | 0.515 | 20 |
| 44215 | 3662.5 | 1 | 0 | 22.37 | 5.5 | 27.87 | 0.612 | 20 |
| | | 1 | 99 | 23.03 | 5.5 | 28.53 | 0.713 | 20 |
| | | 50 | 25 | 21.84 | 5.5 | 27.34 | 0.542 | 20 |
| | | 100 | 0 | 21.68 | 5.5 | 27.18 | 0.522 | 20 |
| 44240 | 3665.0 | 1 | 0 | 22.05 | 5.5 | 27.55 | 0.569 | 20 |
| | | 1 | 99 | 23.08 | 5.5 | 28.58 | 0.721 | 20 |
| | | 50 | 25 | 21.88 | 5.5 | 27.38 | 0.547 | 20 |
| | | 100 | 0 | 21.76 | 5.5 | 27.26 | 0.532 | 20 |

Worst Plots



Worst Plots



3.1.5 Test Result of Peak EIRP Density

Channel Bandwidth: 5MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44115 | 3652.5 | 1 | 0 | 23.392 | 5.5 | 28.892 | 0.775 | 1 |
| | | 1 | 24 | 23.197 | 5.5 | 28.697 | 0.741 | 1 |
| | | 12 | 6 | 20.633 | 5.5 | 26.133 | 0.410 | 1 |
| | | 25 | 0 | 18.233 | 5.5 | 23.733 | 0.236 | 1 |
| 44215 | 3662.5 | 1 | 0 | 23.496 | 5.5 | 28.996 | 0.794 | 1 |
| | | 1 | 24 | 23.044 | 5.5 | 28.544 | 0.715 | 1 |
| | | 12 | 6 | 20.314 | 5.5 | 25.814 | 0.381 | 1 |
| | | 25 | 0 | 18.279 | 5.5 | 23.779 | 0.239 | 1 |
| 44315 | 3672.5 | 1 | 0 | 23.206 | 5.5 | 28.706 | 0.742 | 1 |
| | | 1 | 24 | 23.402 | 5.5 | 28.902 | 0.777 | 1 |
| | | 12 | 6 | 20.569 | 5.5 | 26.069 | 0.404 | 1 |
| | | 25 | 0 | 17.777 | 5.5 | 23.277 | 0.213 | 1 |

Channel Bandwidth: 5MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44115 | 3652.5 | 1 | 0 | 24.208 | 5.5 | 29.708 | 0.935 | 1 |
| | | 1 | 24 | 24.034 | 5.5 | 29.534 | 0.898 | 1 |
| | | 12 | 6 | 21.054 | 5.5 | 26.554 | 0.452 | 1 |
| | | 25 | 0 | 17.754 | 5.5 | 23.254 | 0.212 | 1 |
| 44215 | 3662.5 | 1 | 0 | 24.373 | 5.5 | 29.873 | 0.971 | 1 |
| | | 1 | 24 | 23.983 | 5.5 | 29.483 | 0.888 | 1 |
| | | 12 | 6 | 21.111 | 5.5 | 26.611 | 0.458 | 1 |
| | | 25 | 0 | 18.375 | 5.5 | 23.875 | 0.244 | 1 |
| 44315 | 3672.5 | 1 | 0 | 24.295 | 5.5 | 29.795 | 0.954 | 1 |
| | | 1 | 24 | 24.394 | 5.5 | 29.894 | 0.976 | 1 |
| | | 12 | 6 | 20.775 | 5.5 | 26.275 | 0.424 | 1 |
| | | 25 | 0 | 18.869 | 5.5 | 24.369 | 0.273 | 1 |

Channel Bandwidth: 10MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44140 | 3655.0 | 1 | 0 | 23.094 | 5.5 | 28.594 | 0.723 | 1 |
| | | 1 | 49 | 22.998 | 5.5 | 28.498 | 0.708 | 1 |
| | | 25 | 12 | 17.498 | 5.5 | 22.998 | 0.199 | 1 |
| | | 50 | 0 | 14.587 | 5.5 | 20.087 | 0.102 | 1 |
| 44215 | 3662.5 | 1 | 0 | 23.167 | 5.5 | 28.667 | 0.736 | 1 |
| | | 1 | 49 | 23.104 | 5.5 | 28.604 | 0.725 | 1 |
| | | 25 | 12 | 17.611 | 5.5 | 23.111 | 0.205 | 1 |
| | | 50 | 0 | 14.957 | 5.5 | 20.457 | 0.111 | 1 |
| 44290 | 3670.0 | 1 | 0 | 23.073 | 5.5 | 28.573 | 0.720 | 1 |
| | | 1 | 49 | 23.111 | 5.5 | 28.611 | 0.726 | 1 |
| | | 25 | 12 | 17.539 | 5.5 | 23.039 | 0.201 | 1 |
| | | 50 | 0 | 15.013 | 5.5 | 20.513 | 0.113 | 1 |

Channel Bandwidth: 10MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44140 | 3655.0 | 1 | 0 | 24.112 | 5.5 | 29.612 | 0.915 | 1 |
| | | 1 | 49 | 24.134 | 5.5 | 29.634 | 0.919 | 1 |
| | | 25 | 12 | 17.821 | 5.5 | 23.321 | 0.215 | 1 |
| | | 50 | 0 | 14.752 | 5.5 | 20.252 | 0.106 | 1 |
| 44215 | 3662.5 | 1 | 0 | 24.011 | 5.5 | 29.511 | 0.894 | 1 |
| | | 1 | 49 | 24.215 | 5.5 | 29.715 | 0.936 | 1 |
| | | 25 | 12 | 17.902 | 5.5 | 23.402 | 0.219 | 1 |
| | | 50 | 0 | 14.852 | 5.5 | 20.352 | 0.108 | 1 |
| 44290 | 3670.0 | 1 | 0 | 24.255 | 5.5 | 29.755 | 0.945 | 1 |
| | | 1 | 49 | 24.29 | 5.5 | 29.79 | 0.953 | 1 |
| | | 25 | 12 | 17.275 | 5.5 | 22.775 | 0.189 | 1 |
| | | 50 | 0 | 14.805 | 5.5 | 20.305 | 0.107 | 1 |

Channel Bandwidth: 15MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44165 | 3657.5 | 1 | 0 | 22.738 | 5.5 | 28.238 | 0.666 | 1 |
| | | 1 | 74 | 23.032 | 5.5 | 28.532 | 0.713 | 1 |
| | | 36 | 18 | 15.754 | 5.5 | 21.254 | 0.133 | 1 |
| | | 75 | 0 | 12.539 | 5.5 | 18.039 | 0.064 | 1 |
| 44215 | 3662.5 | 1 | 0 | 22.813 | 5.5 | 28.313 | 0.678 | 1 |
| | | 1 | 74 | 23.75 | 5.5 | 29.25 | 0.841 | 1 |
| | | 36 | 18 | 15.749 | 5.5 | 21.249 | 0.133 | 1 |
| | | 75 | 0 | 12.625 | 5.5 | 18.125 | 0.065 | 1 |
| 44265 | 3667.5 | 1 | 0 | 22.891 | 5.5 | 28.391 | 0.690 | 1 |
| | | 1 | 74 | 23.128 | 5.5 | 28.628 | 0.729 | 1 |
| | | 36 | 18 | 16.303 | 5.5 | 21.803 | 0.151 | 1 |
| | | 75 | 0 | 12.377 | 5.5 | 17.877 | 0.061 | 1 |

Channel Bandwidth: 15MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offeset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|----|------------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44165 | 3657.5 | 1 | 0 | 24.095 | 5.5 | 29.595 | 0.911 | 1 |
| | | 1 | 74 | 24.088 | 5.5 | 29.588 | 0.909 | 1 |
| | | 36 | 18 | 15.587 | 5.5 | 21.087 | 0.128 | 1 |
| | | 75 | 0 | 12.845 | 5.5 | 18.345 | 0.068 | 1 |
| 44215 | 3662.5 | 1 | 0 | 24.072 | 5.5 | 29.572 | 0.906 | 1 |
| | | 1 | 74 | 23.95 | 5.5 | 29.45 | 0.881 | 1 |
| | | 36 | 18 | 15.648 | 5.5 | 21.148 | 0.130 | 1 |
| | | 75 | 0 | 12.64 | 5.5 | 18.14 | 0.065 | 1 |
| 44265 | 3667.5 | 1 | 0 | 24.112 | 5.5 | 29.612 | 0.915 | 1 |
| | | 1 | 74 | 24.164 | 5.5 | 29.664 | 0.926 | 1 |
| | | 36 | 18 | 15.75 | 5.5 | 21.25 | 0.133 | 1 |
| | | 75 | 0 | 12.551 | 5.5 | 18.051 | 0.064 | 1 |


Channel Bandwidth: 20MHz- QPSK

| Channel | Channel Frequency (MHz) | RB | RB Offset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|-----|-----------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44190 | 3660.0 | 1 | 0 | 22.238 | 5.5 | 27.738 | 0.594 | 1 |
| | | 1 | 99 | 22.557 | 5.5 | 28.057 | 0.639 | 1 |
| | | 50 | 25 | 13.595 | 5.5 | 19.095 | 0.081 | 1 |
| | | 100 | 0 | 10.936 | 5.5 | 16.436 | 0.044 | 1 |
| 44215 | 3662.5 | 1 | 0 | 22.195 | 5.5 | 27.695 | 0.588 | 1 |
| | | 1 | 99 | 22.547 | 5.5 | 28.047 | 0.638 | 1 |
| | | 50 | 25 | 14.064 | 5.5 | 19.564 | 0.090 | 1 |
| | | 100 | 0 | 11.16 | 5.5 | 16.66 | 0.046 | 1 |
| 44240 | 3665.0 | 1 | 0 | 22.319 | 5.5 | 27.819 | 0.605 | 1 |
| | | 1 | 99 | 22.602 | 5.5 | 28.102 | 0.646 | 1 |
| | | 50 | 25 | 14.034 | 5.5 | 19.534 | 0.090 | 1 |
| | | 100 | 0 | 11.447 | 5.5 | 16.947 | 0.050 | 1 |


Channel Bandwidth: 20MHz- 16QAM

| Channel | Channel Frequency (MHz) | RB | RB Offset | Conducted Power Density (dBm/MHz) | Max. Ant. Gain(dBi) | EIRP Peak Density (dBm/MHz) | EIRP Peak Density (W/MHz) | LIMIT (W/MHz) |
|---------|-------------------------|-----|-----------|-----------------------------------|---------------------|-----------------------------|---------------------------|---------------|
| 44190 | 3660.0 | 1 | 0 | 23.417 | 5.5 | 28.917 | 0.779 | 1 |
| | | 1 | 99 | 23.667 | 5.5 | 29.167 | 0.825 | 1 |
| | | 50 | 25 | 13.726 | 5.5 | 19.226 | 0.084 | 1 |
| | | 100 | 0 | 11.089 | 5.5 | 16.589 | 0.046 | 1 |
| 44215 | 3662.5 | 1 | 0 | 23.564 | 5.5 | 29.064 | 0.806 | 1 |
| | | 1 | 99 | 23.303 | 5.5 | 28.803 | 0.759 | 1 |
| | | 50 | 25 | 14.377 | 5.5 | 19.877 | 0.097 | 1 |
| | | 100 | 0 | 11.284 | 5.5 | 16.784 | 0.048 | 1 |
| 44240 | 3665.0 | 1 | 0 | 23.484 | 5.5 | 28.984 | 0.791 | 1 |
| | | 1 | 99 | 23.716 | 5.5 | 29.216 | 0.835 | 1 |
| | | 50 | 25 | 13.953 | 5.5 | 19.453 | 0.088 | 1 |
| | | 100 | 0 | 11.163 | 5.5 | 16.663 | 0.046 | 1 |

Worst Plots



Worst Plots



3.2 Radiated Emissions

3.2.1 Limit of Radiated Emissions


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. E.I.R.P = output power of step 4 + gain of substitution antenna – cable loss of RF cable.

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Test Result of Radiated Emissions below 1GHz

| Mode | | | | | | | |
|---|------------------|---------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:5MHz, 1RB, Offset 24, Channel:44315 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.I.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 47.46 | H | -54.66 | -13.00 | -41.66 | -51.42 | -43.41 | -11.25 |
| 94.02 | H | -48.70 | -13.00 | -35.70 | -38.22 | -49.09 | 0.39 |
| 105.66 | H | -48.63 | -13.00 | -35.63 | -38.46 | -48.62 | -0.01 |
| 224.97 | H | -54.69 | -13.00 | -41.69 | -42.84 | -59.07 | 4.38 |
| 275.41 | H | -58.32 | -13.00 | -45.32 | -47.97 | -62.60 | 4.28 |
| 358.83 | H | -60.64 | -13.00 | -47.64 | -53.97 | -65.04 | 4.40 |
| 47.46 | V | -45.98 | -13.00 | -32.98 | -36.10 | -34.73 | -11.25 |
| 105.66 | V | -39.22 | -13.00 | -26.22 | -30.05 | -39.21 | -0.01 |
| 353.98 | V | -56.52 | -13.00 | -43.52 | -50.57 | -60.93 | 4.41 |
| 425.76 | V | -55.39 | -13.00 | -42.39 | -49.88 | -59.58 | 4.19 |
| 475.23 | V | -58.24 | -13.00 | -45.24 | -53.83 | -62.34 | 4.10 |
| 701.24 | V | -60.22 | -13.00 | -47.22 | -60.75 | -63.99 | 3.77 |

| Mode | | | | | | | |
|--|------------------|---------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:10MHz, 1RB, Offset 49, Channel:44140 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.I.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 47.55 | H | -54.29 | -13.00 | -41.29 | -50.99 | -43.05 | -11.24 |
| 94.58 | H | -48.39 | -13.00 | -35.39 | -37.93 | -48.77 | 0.38 |
| 105.38 | H | -48.41 | -13.00 | -35.41 | -38.24 | -48.42 | 0.01 |
| 224.64 | H | -54.37 | -13.00 | -41.37 | -42.51 | -58.75 | 4.38 |
| 275.36 | H | -58.43 | -13.00 | -45.43 | -48.08 | -62.71 | 4.28 |
| 358.66 | H | -60.12 | -13.00 | -47.12 | -53.44 | -64.52 | 4.40 |
| 47.85 | V | -45.72 | -13.00 | -32.72 | -35.71 | -34.52 | -11.20 |
| 105.74 | V | -39.08 | -13.00 | -26.08 | -29.91 | -39.07 | -0.01 |
| 353.44 | V | -56.41 | -13.00 | -43.41 | -50.46 | -60.82 | 4.41 |
| 425.37 | V | -55.24 | -13.00 | -42.24 | -49.73 | -59.43 | 4.19 |
| 475.39 | V | -58.16 | -13.00 | -45.16 | -53.75 | -62.26 | 4.10 |
| 701.57 | V | -60.03 | -13.00 | -47.03 | -60.57 | -63.80 | 3.77 |

| Mode | | | | | | | |
|--|------------------|---------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:15MHz, 1RB, Offset 74, Channel:44265 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.I.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 47.05 | H | -54.99 | -13.00 | -41.99 | -52.07 | -43.68 | -11.31 |
| 94.76 | H | -48.35 | -13.00 | -35.35 | -37.89 | -48.72 | 0.37 |
| 105.31 | H | -48.52 | -13.00 | -35.52 | -38.35 | -48.53 | 0.01 |
| 224.78 | H | -54.73 | -13.00 | -41.73 | -42.88 | -59.11 | 4.38 |
| 275.37 | H | -58.56 | -13.00 | -45.56 | -48.21 | -62.84 | 4.28 |
| 358.24 | H | -60.24 | -13.00 | -47.24 | -53.55 | -64.64 | 4.40 |
| 47.55 | V | -45.32 | -13.00 | -32.32 | -35.42 | -34.08 | -11.24 |
| 105.48 | V | -39.64 | -13.00 | -26.64 | -30.48 | -39.64 | 0.00 |
| 353.67 | V | -56.13 | -13.00 | -43.13 | -50.18 | -60.54 | 4.41 |
| 425.32 | V | -55.28 | -13.00 | -42.28 | -49.77 | -59.47 | 4.19 |
| 475.49 | V | -58.67 | -13.00 | -45.67 | -54.26 | -62.77 | 4.10 |
| 701.72 | V | -60.18 | -13.00 | -47.18 | -60.72 | -63.95 | 3.77 |

| Mode | | | | | | | |
|--|------------------|---------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:20MHz, 1RB, Offset 99, Channel:44240 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.I.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 47.88 | H | -54.17 | -13.00 | -41.17 | -50.61 | -42.98 | -11.19 |
| 94.35 | H | -48.93 | -13.00 | -35.93 | -38.45 | -49.31 | 0.38 |
| 105.56 | H | -48.35 | -13.00 | -35.35 | -38.18 | -48.35 | 0.00 |
| 224.73 | H | -54.82 | -13.00 | -41.82 | -42.97 | -59.20 | 4.38 |
| 275.36 | H | -58.08 | -13.00 | -45.08 | -47.73 | -62.36 | 4.28 |
| 358.49 | H | -60.52 | -13.00 | -47.52 | -53.84 | -64.92 | 4.40 |
| 47.99 | V | -45.53 | -13.00 | -32.53 | -35.48 | -34.35 | -11.18 |
| 105.41 | V | -39.86 | -13.00 | -26.86 | -30.70 | -39.86 | 0.00 |
| 353.42 | V | -56.18 | -13.00 | -43.18 | -50.23 | -60.59 | 4.41 |
| 425.37 | V | -55.48 | -13.00 | -42.48 | -49.97 | -59.67 | 4.19 |
| 475.39 | V | -58.58 | -13.00 | -45.58 | -54.17 | -62.68 | 4.10 |
| 701.55 | V | -60.36 | -13.00 | -47.36 | -60.90 | -64.13 | 3.77 |

3.2.5 Test Result of Radiated Emissions above 1GHz

| Mode | | | | | | | |
|---|------------------|-------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:5MHz, 1RB, Offset 24, Channel:44115 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7309.44 | H | -40.87 | -13.00 | -27.87 | -62.63 | -43.69 | 2.82 |
| 10963.96 | H | -40.29 | -13.00 | -27.29 | -64.44 | -40.42 | 0.13 |
| 14618.47 | H | -47.91 | -13.00 | -34.91 | -74.60 | -49.17 | 1.26 |
| 7309.44 | V | -38.09 | -13.00 | -25.09 | -59.17 | -40.91 | 2.82 |
| 10963.96 | V | -38.16 | -13.00 | -25.16 | -61.24 | -38.29 | 0.13 |
| 14618.47 | V | -47.15 | -13.00 | -34.15 | -74.61 | -48.41 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:5MHz, 1RB, Offset 24, Channel:44215 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7329.34 | H | -41.24 | -13.00 | -28.24 | -63.02 | -44.07 | 2.83 |
| 10994.07 | H | -40.79 | -13.00 | -27.79 | -64.87 | -40.90 | 0.11 |
| 14658.33 | H | -48.35 | -13.00 | -35.35 | -75.08 | -49.61 | 1.26 |
| 7329.34 | V | -39.01 | -13.00 | -26.01 | -59.85 | -41.84 | 2.83 |
| 10994.07 | V | -38.30 | -13.00 | -25.30 | -61.36 | -38.41 | 0.11 |
| 14658.33 | V | -47.60 | -13.00 | -34.60 | -75.16 | -48.86 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:5MHz, 1RB, Offset 24, Channel:44315 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7349.32 | H | -42.07 | -13.00 | -29.07 | -63.86 | -44.91 | 2.84 |
| 11023.97 | H | -40.94 | -13.00 | -27.94 | -65.02 | -41.08 | 0.14 |
| 14698.36 | H | -48.20 | -13.00 | -35.20 | -74.97 | -49.46 | 1.26 |
| 7349.32 | V | -39.74 | -13.00 | -26.74 | -60.34 | -42.58 | 2.84 |
| 11023.97 | V | -39.00 | -13.00 | -26.00 | -62.13 | -39.14 | 0.14 |
| 14698.36 | V | -47.31 | -13.00 | -34.31 | -74.98 | -48.57 | 1.26 |

| Mode | | | | | | | |
|--|------------------|-------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:10MHz, 1RB, Offset 49, Channel:44140 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7318.85 | H | -40.64 | -13.00 | -27.64 | -62.41 | -43.47 | 2.83 |
| 10978.17 | H | -40.00 | -13.00 | -27.00 | -64.12 | -40.12 | 0.12 |
| 14637.56 | H | -48.60 | -13.00 | -35.60 | -75.31 | -49.86 | 1.26 |
| 7318.85 | V | -38.63 | -13.00 | -25.63 | -59.60 | -41.46 | 2.83 |
| 10978.17 | V | -38.10 | -13.00 | -25.10 | -61.17 | -38.22 | 0.12 |
| 14637.56 | V | -47.52 | -13.00 | -34.52 | -75.03 | -48.78 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:10MHz, 1RB, Offset 24, Channel:44215 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7333.82 | H | -41.06 | -13.00 | -28.06 | -62.85 | -43.90 | 2.84 |
| 11000.61 | H | -40.94 | -13.00 | -27.94 | -65.01 | -41.04 | 0.10 |
| 14667.34 | H | -48.44 | -13.00 | -35.44 | -75.18 | -49.70 | 1.26 |
| 7333.82 | V | -39.13 | -13.00 | -26.13 | -59.92 | -41.97 | 2.84 |
| 11000.61 | V | -37.39 | -13.00 | -24.39 | -60.45 | -37.49 | 0.10 |
| 14667.34 | V | -47.60 | -13.00 | -34.60 | -75.19 | -48.86 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:10MHz, 1RB, Offset 49, Channel:44290 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7348.83 | H | -41.32 | -13.00 | -28.32 | -63.11 | -44.16 | 2.84 |
| 11023.20 | H | -40.59 | -13.00 | -27.59 | -64.67 | -40.72 | 0.13 |
| 14697.76 | H | -48.16 | -13.00 | -35.16 | -74.93 | -49.42 | 1.26 |
| 7348.83 | V | -39.75 | -13.00 | -26.75 | -60.35 | -42.59 | 2.84 |
| 11023.20 | V | -37.86 | -13.00 | -24.86 | -60.98 | -37.99 | 0.13 |
| 14697.76 | V | -47.55 | -13.00 | -34.55 | -75.22 | -48.81 | 1.26 |

| Mode | | | | | | | |
|--|------------------|-------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:15MHz, 1RB, Offset 74, Channel:44165 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7328.33 | H | -41.10 | -13.00 | -28.10 | -62.88 | -43.93 | 2.83 |
| 10992.31 | H | -39.72 | -13.00 | -26.72 | -63.81 | -39.83 | 0.11 |
| 14656.56 | H | -48.51 | -13.00 | -35.51 | -75.24 | -49.77 | 1.26 |
| 7328.33 | V | -38.46 | -13.00 | -25.46 | -59.31 | -41.29 | 2.83 |
| 10992.31 | V | -38.66 | -13.00 | -25.66 | -61.73 | -38.77 | 0.11 |
| 14656.56 | V | -47.83 | -13.00 | -34.83 | -75.39 | -49.09 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:15MHz, 1RB, Offset 24, Channel:44215 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7338.33 | H | -41.18 | -13.00 | -28.18 | -62.97 | -44.02 | 2.84 |
| 11007.46 | H | -40.44 | -13.00 | -27.44 | -64.52 | -40.55 | 0.11 |
| 14676.46 | H | -48.43 | -13.00 | -35.43 | -75.18 | -49.69 | 1.26 |
| 7338.33 | V | -39.43 | -13.00 | -26.43 | -60.16 | -42.27 | 2.84 |
| 11007.46 | V | -37.90 | -13.00 | -24.90 | -60.98 | -38.01 | 0.11 |
| 14676.46 | V | -47.52 | -13.00 | -34.52 | -75.13 | -48.78 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:15MHz, 1RB, Offset 74, Channel:44265 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7348.38 | H | -41.48 | -13.00 | -28.48 | -63.28 | -44.32 | 2.84 |
| 11022.54 | H | -40.48 | -13.00 | -27.48 | -64.56 | -40.61 | 0.13 |
| 14696.62 | H | -48.45 | -13.00 | -35.45 | -75.22 | -49.71 | 1.26 |
| 7348.38 | V | -39.64 | -13.00 | -26.64 | -60.26 | -42.48 | 2.84 |
| 11022.54 | V | -38.39 | -13.00 | -25.39 | -61.51 | -38.52 | 0.13 |
| 14696.62 | V | -47.27 | -13.00 | -34.27 | -74.94 | -48.53 | 1.26 |

| Mode | | | | | | | |
|--|------------------|-------------|-------------|-------------|-------------------|-----------------------|------------------------|
| LTE Band 43, CB:20MHz, 1RB, Offset 99, Channel:44190 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7337.80 | H | -41.43 | -13.00 | -28.43 | -63.21 | -44.27 | 2.84 |
| 11006.66 | H | -41.03 | -13.00 | -28.03 | -65.11 | -41.14 | 0.11 |
| 14675.60 | H | -48.54 | -13.00 | -35.54 | -75.29 | -49.80 | 1.26 |
| 7337.80 | V | -39.62 | -13.00 | -26.62 | -60.36 | -42.46 | 2.84 |
| 11006.66 | V | -38.62 | -13.00 | -25.62 | -61.70 | -38.73 | 0.11 |
| 14675.60 | V | -47.70 | -13.00 | -34.70 | -75.31 | -48.96 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:20MHz, 1RB, Offset 24, Channel:44215 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7342.84 | H | -41.54 | -13.00 | -28.54 | -63.33 | -44.38 | 2.84 |
| 11014.29 | H | -41.79 | -13.00 | -28.79 | -65.86 | -41.91 | 0.12 |
| 14685.58 | H | -48.41 | -13.00 | -35.41 | -75.17 | -49.67 | 1.26 |
| 7342.84 | V | -39.91 | -13.00 | -26.91 | -60.59 | -42.75 | 2.84 |
| 11014.29 | V | -39.06 | -13.00 | -26.06 | -62.16 | -39.18 | 0.12 |
| 14685.58 | V | -47.38 | -13.00 | -34.38 | -75.02 | -48.64 | 1.26 |
| Mode | | | | | | | |
| LTE Band 43, CB:20MHz, 1RB, Offset 99, Channel:44240 | | | | | | | |
| Frequency (MHz) | Antenna Polarity | E.R.P (dBm) | Limit (dBm) | Margin (dB) | S.A Reading (dBm) | S.G Power Vaule (dBm) | Correction Factor (dB) |
| 7347.87 | H | -41.47 | -13.00 | -28.47 | -63.27 | -44.31 | 2.84 |
| 11021.86 | H | -41.62 | -13.00 | -28.62 | -65.70 | -41.75 | 0.13 |
| 14695.68 | H | -48.38 | -13.00 | -35.38 | -75.15 | -49.64 | 1.26 |
| 7347.87 | V | -40.27 | -13.00 | -27.27 | -60.89 | -43.11 | 2.84 |
| 11021.86 | V | -39.48 | -13.00 | -26.48 | -62.60 | -39.61 | 0.13 |
| 14695.68 | V | -47.57 | -13.00 | -34.57 | -75.23 | -48.83 | 1.26 |

3.3 Conducted Emissions


3.3.1 Limit of Conducted Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.3.2 Test Procedures

1. Lowest, middle and highest operating channels are tested for this item.
2. Scan frequency range is from 30MHz~40GHz.
3. Set RBW = 1MHz, VBW = 3MHz, detector = RMS, sweep time = auto.
4. Record the max trace value and capture the test plot of each sub frequency band.

3.3.3 Test Setup



3.3.4 Test Result of Conducted Emissions

