



Appendix F. FCC 3G SAR Measurement Procedures


Conducted Output Power:

The EUT was tested according to the requirements of the FCC 3G procedures and the 3.1.2.3.4.

A detailed analysis of the output power verification is provided as the table below:

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Mid. Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				1013	384	777
CDMA2000 Cellular	FCH	1	1	1	55	Full	All Up	24.58	24.53	24.25
		3	3	3	55	Full	All Up	24.68	24.61	24.28

CDMA2000 Setup Configuration:



Setup Configuration

1. The EUT was connected to System Simulator, Agilent 8960. Refer to the drawing of Setup Configuration.
2. The RF path losses were compensated into the measurements.
3. A call was established between EUT and System Simulator with following setting:
 - a. For 1xRTT, set the Radio Configuration and the Service Option
 - b. Set the Power Control to All Up Bits
4. The transmitted maximum output power was recorded.

Call Setup Screen			
Call Control	Active Cell Operating Mode		Call Params
Close Menu	Mobile Station Information		Cell Power
	ESN (Hex):		-86.00
	ESN (Dec):		dBm/1.23 MHz
	NCC:		Cell Band
	NMC:		US PCS
	NSIN:		Channel
	Slot Class:		1175
	Slot Cycle Index: ----		Protocol Rev
	Protocol Revision:		6 (IS-2000-0)
	FCH Service Option Setup		Value
Service Option f	Service Option	S055 (Loopback)	(Fud1, Rvs1)
Service Option f	S01 (Voice)	S09 (Loopback)	S055 (Loopback)
Service Option f	S02 (Loopback)	S055 (Loopback)	S055 (Loopback)
Service Option f	S03 (Voice)	S055 (Loopback)	FCH Service Option Setup
Service Option f	S06 (SNS)	S055 (Loopback)	
	S055 (Loopback)		
	S068 (Voice)		
	Active Cell	Sys Type: IS-2000	
	Idle		
	IntRef	Offset	1 of 4

1xRTT setting for Radio Configuration 1 with Service Option 55

