



# FCC Test Report

**Product Name: cdma2000 Digital Mobile Phone**

**Model Number: HUAWEI C8651/C8651/C8651+/C8651S/CM980**

**Report No: SYBH(Z-RF)014082011-2004  
FCC ID: QISC8651**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518



## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



<b>REGULATION</b>	<b>FCC CFR47 Part 2: Subpart J;</b>
	<b>FCC CFR47 Part 15: Subpart C;</b>
<b>START OF TEST</b>	<b>Aug.23, 2011</b>
<b>END OF TEST</b>	<b>Aug.25, 2011</b>
<b>Final Judgement:</b>	<b>Pass</b>

Approved By Aug.30, 2011 Dai Linjun *Dai Linjun*  
 Date Name Signature

Reviewed By Aug.30, 2011 Xuguangyi *Cousy XU*  
 Date Name Signature

Operator Aug.30, 2011 huangqiuliang *Huang Qiuliang*  
 Date Name Signature



## Contents

<b>1</b>	<b><u>Summary</u></b> .....	<b>5</b>
<b>2</b>	<b><u>Product Description</u></b> .....	<b>6</b>
2.1	PRODUCTION INFORMATION .....	6
2.2	MODIFICATION INFORMATION .....	6
<b>3</b>	<b><u>Test Site Description</u></b> .....	<b>7</b>
3.1	TESTING PERIOD .....	7
3.2	GENERAL SET UP DESCRIPTION .....	7
<b>4</b>	<b><u>Product Description</u></b> .....	<b>8</b>
4.1	TECHNICAL CHARACTERISTICS.....	8
4.2	EUT IDENTIFICATION LIST.....	10
<b>5</b>	<b><u>Main Test Instruments</u></b> .....	<b>11</b>
<b>6</b>	<b><u>Transmitter Measurements</u></b> .....	<b>12</b>
6.1	6DB BANDWIDTH MEASUREMENT .....	12
6.2	PEAK OUTPUT POWER .....	14
6.3	BAND EDGE SPURIOUS EMISSION.....	16
6.4	CONDUCTED RF SPURIOUS.....	18
6.5	POWER SPECTRAL DENSITY .....	20
6.6	RADIATED SPURIOUS EMISSION & SPURIOUS IN RESTRICTED BAND.....	22
6.7	CONDUCTED EMISSION AT POWER PORT.....	26
<b>7</b>	<b><u>System Measurement Uncertainty</u></b> .....	<b>28</b>
<b>8</b>	<b><u>Appendices</u></b> .....	<b>29</b>



# 1 Summary

The table below summarizes the measurements and results for the EUT. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

FCC Measurement Specification	Description	Result
15.247 (a) (2)	6dB bandwidth measurement	PASS
15.247 (b) (3)	Conducted Peak output power	PASS
15.247 (d)	Band edge compliance measurement	PASS
15.247 (d)	Conducted RF spurious	PASS
15.247 (e)	Power spectral density	PASS
15.247 (d) / 15.205 & 15.209	Radiated spurious emission & Radiated restricted band measurement	PASS
15.207	Conducted emission test for power port	PASS



## 2 Product Description

### 2.1 Production Information

#### 2.1.1 General Description

cdma2000 Digital Mobile Phone-HUAWEI C8651/C8651/C8651+/C8651S/CM980 is subscriber equipment in the CDMA/EVDO system. The frequency band is US Cellular. The Mobile Phone implements such functions as RF signal receiving/transmitting, CDMA2000 1x and 1XEV-DO protocol processing, voice, MMS service, GPS, AGPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service). It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices

**Note: Only WLAN function was considered in this report.**

#### 2.1.2 Support function and Service

The EUT support the function and service as follows:

Table 2 Service and Test mode List

Service Name	mode	Characteristic	Corresponding Test Mode	Note
Data	DSSS	Modulation: QPSK	TM1	
Data	OFDM	Modulation: 64QAM	TM2	
Data	OFDM	Modulation: 64QAM 16QAM,BPSK,QPSK	TM3	

### 2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable!				



### **3 Test Site Description**

The test site of:

***Huawei Technologies Co. Ltd.  
P.O. Box 518129  
Huawei base, bantian,  
Longgang District, Shenzhen, China***

#### **3.1 Testing Period**

The test have been performed during the period of

**Aug.23, 2011 to Aug.25, 2011**

#### **3.2 General Set up Description**

The WLAN digitally modulated systems of the EUT can Support 2.4GHz Band. For compliance with FCC regulation 47CFR part15 subpart C, we set the EUT as following test modes to do all compliance tests.

##### **WLAN MODE:**

**TM1:** DSSS mode ,QPSK Modulation,11Mbps data rate

**TM2:** OFDM mode,64QAM Modulation,54 Mbps data rate

**TM3:** OFDM mode,64QAM Modulation,65 Mbps data rate



## 4 Product Description

### 4.1 Technical Characteristics

#### 4.1.1 Frequency Range

Table 4 Frequency Range

Uplink band:	2400 to 2483.5 MHz	
Downlink band:	2400 to 2483.5 MHz	
Hop frequency support:	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO

#### 4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / raster

Channel spacing:	22 MHz
Channel raster:	5 MHz

#### 4.1.3 Antenna Information

Table 6 Antenna Information

Type:	Integrated / Internal
Maximum Gain(dBi):	-1.0 (from 2400MHz to 2500MHz)



#### 4.1.4 Environmental Requirements

Table 7 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%-95%

#### 4.1.5 Power Source

Table 8 Power Source

AC voltage nominal:	~120V
AC voltage range	~100V-240V
AC current maximal:	200mA

#### 4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

#### 4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 9 Applied RF module DC Voltages and Currents

Voltage:	== +3.6~4.2V
Current:	100mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)



## 4.2 EUT Identification List

### 4.2.1 Board Information

Table 10 Board Information

cdma2000 Digital Mobile Phone		
HUAWEI C8511/ C8511		
Hardware Version	Software Version	Serial Number
HC1C8651M	C8651V100R001C32B833	R6X2A11171900223

### 4.2.2 Adapter

AC/DCAdapter Model	HS-050040U6
Manufacturer	Huawei Technologies Co., Ltd.
Input Voltage	~100-240V 50/60Hz 0.2A
Output Voltage	5V  1A
Rated Power	5W

### 4.2.3 Battery

Name	Manufacture	Description
Rechargeable Li-ion	Huawei Technologies Co., Ltd.	Battery Model: HB5K1H Rated capacity: 1400mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V

### 4.2.4 FCC Identification

**Grantee Code:** QIS  
**Product Code:** C8651  
**FCC Identification:** QISC8651



## 5 Main Test Instruments

Table 11 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until
Power supply	KEITHLEY	2303	1288003	Sep.27,2011
Universal Radio Communication Tester	R&S	CMU200	105822	Oct.24,2011
Universal Radio Communication Tester	Agilent	E5515C	MY50260239	Aug.04,2012
Spectrum Analyzer	Agilent	E4440A	MY49420179	Apr.24,2012
Signal Analyzer	R&S	FSQ40	100025	Oct.09,2011
Signal Analyzer	R&S	FSQ31	200021	Sep.27,2011
Temperature Chamber	ESPEC	MW3030	611403	May.12,2012
Signal Generator	R&S	SMR40	100325	May.12,2012
Vector Signal Generator	R&S	SMU200A	104162	Sep.07,2011
Spectrum Analyzer	R&S	FSU26	EG26725	Mar.07,2012
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	919/1009	Dec.13.2011
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	979/917	Dec.13.2011
Horn Antenna	R & S	HF906	359287/005	May.07, 2012
Horn Antenna	R & S	HF906	359287/006	April.27, 2012
Broadband Antenna	SCHAFFNER	CBL 6112B	2536	Sep.21, 2011
Broadband Antenna	SCHAFFNER	CBL 6112B	2941	Jun.11, 2012
Test receiver	R&S	ESU26	36090302083	Jun.17.2012
Horn Antenna	ETS-LINDGREN	3160	60008	Sep.20.2011
Horn Antenna	ETS-LINDGREN	3160	60006	Oct.27.2011



## 6 Transmitter Measurements

### 6.1 6dB bandwidth measurement

#### 6.1.1 Test Conditions

Table 12 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No.1, 6, 11

#### 6.1.2 Test Specifications and Limits

##### 6.1.2.1 Specification

CFR 47 (FCC) part 15.247 (a) (2) and KDB 558074

##### 6.1.2.2 Supporting Standards

Table 13 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
---------------------	---

##### 6.1.2.3 Limits

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Table 14 Limits

Limits	≥ 500kHz
--------	----------

#### 6.1.3 Test Method and Setup

- (a) Connect test port of EUT to spectrum analyzer.
- (b) Set the EUT to transmit maximum output power at 2.4GHz, then set the measured frequency number and test the 6dB bandwidth with spectrum analyzer.

## Test setup




Figure 1. Test Set-up

## 6.1.4 Measurement Results

Table 15 Measurement Results

Test condition	Channel Position	Bandwidth Type	Channel Number	Frequency [GHz]	Measured Bandwidth [MHz]	Result
TM1	B	6dB Bandwidth	1	2.412	8.981	Pass
	M	6dB Bandwidth	6	2.437	9.166	Pass
	T	6dB Bandwidth	11	2.462	9.224	Pass
TM2	B	6dB Bandwidth	1	2.412	16.354	Pass
	M	6dB Bandwidth	6	2.437	16.257	Pass
	T	6dB Bandwidth	11	2.462	16.354	Pass
TM3	B	6dB Bandwidth	1	2.412	17.102	Pass
	M	6dB Bandwidth	6	2.437	17.242	Pass
	T	6dB Bandwidth	11	2.462	17.068	Pass

## 6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix A.

## 6.2 Peak output power

### 6.2.1 Test Conditions

Table 16 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No.1, 6, 11

### 6.2.2 Test Specifications and Limits

#### 6.2.2.1 Specification

CFR 47 (FCC) part 15.247 (b) (3) and KDB 558074

#### 6.2.2.2 Supporting Standards

Table 17 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.2.2.3 Limits

Compliance with part 15.247 (b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level.

Table 18 Limits

2.4GHz and 5.8GHz system using digital modulation	1 Watt / 30 dBm
---	-----------------

### 6.2.3 Test Method and Setup

- (a) Connect test port of EUT to spectrum analyzer.
- (b) Set the EUT to transmit maximum output power.
- (c) Then set the EUT to transmit at high, middle and low frequency and measure the conducted output power separately.

## Test setup




Figure 2. Test Set-up

## 6.2.4 Measurement Results

Table 19 Measurement Results

Test condition	Channel	Channel No.	Center Freq.[MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
TM1	Bottom	1	2412	19.11	< 30	Pass
	Middle	6	2437	18.12	< 30	Pass
	Top	11	2462	17.51	< 30	Pass
TM2	Bottom	1	2412	17.20	< 30	Pass
	Middle	6	2437	15.93	< 30	Pass
	Top	11	2462	15.18	< 30	Pass
TM3	Bottom	1	2412	12.86	< 30	Pass
	Middle	6	2437	12.25	< 30	Pass
	Top	11	2462	13.05	< 30	Pass

## 6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix B.



## 6.3 Band edge spurious emission

### 6.3.1 Test Conditions

Table 20 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No. 1, 11

### 6.3.2 Test Specifications and Limits

#### 6.3.2.1 Specification

CFR 47 (FCC) part 15.247(d) and KDB 558074

#### 6.3.2.2 Supporting Standards

Table 21 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.3.2.3 Limits

Compliance with part 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

Table 22 Limits

Band edge spurious:	20 dBc/100kHz
---------------------	---------------

### 6.3.3 Test Method and Setup

- (a) Connect test port of EUT to spectrum analyzer
- (b) Set the EUT to transmit maximum output power at 2.4GHz
- (c) Then set the EUT to transmit at high, low frequency and measure the conducted band edge spurious separately.

## Test setup




Figure 3. Test Set-up

## 6.3.4 Measurement Results

Table 23 Measurement Results

Test condition		Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Result
TM1	Low Edge	1	2412	5.39	-50.93	-14.61	Pass
	High Edge	11	2462	3.37	-42.49	-16.63	Pass
TM2	Low Edge	1	2412	0.28	-36.23	-19.72	Pass
	High Edge	11	2462	-1.23	-28.74	-21.23	Pass
TM3	Low Edge	1	2412	-2.79	-38.95	-22.79	Pass
	High Edge	11	2462	-4.37	-31.63	-24.37	Pass

## 6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix C.



## 6.4 Conducted RF spurious

### 6.4.1 Test Conditions

Table 24 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No.1, 6, 11

### 6.4.2 Test Specifications and Limits

#### 6.4.2.1 Specification

CFR 47 (FCC) part 15.247 (d) and KDB 558074

#### 6.4.2.2 Supporting Standards

Table 25 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.4.2.3 Limits

Compliance with part 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

Table 26 Limits

Band edge spurious:	20 dBc/100kHz
---------------------	---------------

### 6.4.3 Test Method and Setup

- Connect test port of EUT to spectrum analyzer
- Set the EUT to transmit maximum output power at 2.4GHz and.
- Then set the EUT to transmit at high, middle and low frequency and measure the conducted band edge spurious separately.

**Test setup**




Figure 4. Test Set-up

**6.4.4 Measurement Results**

Table 27 Measurement Results

Test condition	Test Frequency Range	Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Result
TM1	9kHz-26GHz	1	2412	10.39	-42.49	-9.61	Pass
	9kHz-26GHz	6	2437	9.86	-42.57	-10.14	Pass
	9kHz-26GHz	11	2462	8.42	-42.22	-11.58	Pass
TM2	9kHz-26GHz	1	2412	6.52	-42.54	-13.48	Pass
	9kHz-26GHz	6	2437	6.70	-42.53	-13.30	Pass
	9kHz-26GHz	11	2462	4.12	-42.61	-15.88	Pass
TM3	9kHz-26GHz	1	2412	4.14	-42.32	-15.86	Pass
	9kHz-26GHz	6	2437	2.08	-42.97	-17.92	Pass
	9kHz-26GHz	11	2462	1.63	-42.16	-18.37	Pass

**6.4.5 Conclusion**

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix D.



## 6.5 Power spectral density

### 6.5.1 Test Conditions

Table 28 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No.1, 6, 11

### 6.5.2 Test Specifications and Limits

#### 6.5.2.1 Specification

CFR 47 (FCC) part 15.247 (e) and KDB 558074

#### 6.5.2.2 Supporting Standards

Table 29 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.5.2.3 Limits

Compliance with part 15.247 (e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. The same method of determining the conducted output power shall be used to determine the power spectral density.

Table 30 Limits

Band edge spurious:	8 dBm/3kHz
---------------------	------------

### 6.5.3 Test Method and Setup

- (a) Connect test port of EUT to spectrum analyzer
- (b) Set the EUT to transmit maximum output power at 2.4GHz and.
- (c) Then set the EUT to transmit at high, middle and low frequency and measure the conducted band edge spurious separately.

**Test setup**




Figure 5. Test Set-up

**6.5.4 Measurement Results**

Table 31 Measurement Results

Test condition	Channel No.	Carrier Frequency [MHz]	Measured Power spectral density [dBm]	Limit [dBm]	Result
TM1	1	2412	-9.05	8	Pass
	6	2437	-9.75	8	Pass
	11	2462	-10.45	8	Pass
TM2	1	2412	-14.47	8	Pass
	6	2437	-15.33	8	Pass
	11	2462	-16.10	8	Pass
TM3	1	2412	-19.39	8	Pass
	6	2437	-19.92	8	Pass
	11	2462	-20.83	8	Pass

**6.5.5 Conclusion**

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix E.

## 6.6 Radiated spurious emission & spurious in restricted band

### 6.6.1 Test Conditions

Table 32 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	25 °C
Relative humidity:	55%
Test Configurations:	TM1/TM2/TM3 at channel No.1, 6, 11

### 6.6.2 Test Specifications and Limits

#### 6.6.2.1 Specification

CFR 47 (FCC) part 15.247 (d), 15.205 & 15.209 and KDB 558074

#### 6.6.2.2 Supporting Standards

Table 33 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI C63.4: 2003	Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

#### 6.6.2.3 Limits

According to part 15.247 (d) / 15.205 & 15.209, all spurious emission in the frequency range from 30MHz to 10<sup>th</sup> harmonics of carrier frequency should be meet the requirement of following table.

Table 34 Limits

Frequency (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance (meters)	Detector
0.009 - 0.490	2400/F(kHz)	20*lg(2400/F(kHz))	300	QP
0.490 - 1.705	24000/F(kHz)	20*lg(24000/F(kHz))	30	QP
1.705 - 30	30	29.5	30	QP
30 – 88	100	40	3	QP
88 – 216	150	43.5	3	QP
216 – 960	200	46	3	QP
960 -1000	500	54	3	QP
Above 1000	500	54	3	AV
Above 1000	500	74	3	PK

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table 42).

### 6.6.3 Test Method and Setup

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the

standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4. The Radiated Disturbance measurements were made using a Rohde and Schwarz Test Receiver and control software.

A preliminary scan and a final scan of the emissions were made by using test script of software; the emissions were measured using a Quasi-Peak Detector below 1GHz, Peak Detector and AV detector above 1GHz. The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

The EUT was communicated with the BTS simulator through Air interface. The EUT operated on the typical channel.

Measurement bandwidth: 30 MHz – 1000 MHz: 120 kHz

Measurement bandwidth: 1000 MHz – 10<sup>th</sup> Carrier Frequency: 1 MHz

**Test set up**




Figure 6. Test Set up

**6.6.4 Measurement Results**

Note 1: The following measurement results exceed the limit line is the carrier frequency.

Note 2: This test was carried out in all the test modes, here only the worst test result was shown.

**Measured Result of channel: 1 (2412MHz)**

Table 35 MEASUREMENT RESULT(30 MHz – 1000 MHz)

Frequency (MHz)	Level (dBμV/m)	Transd (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
57.600000	23.10	12.4	40.0	16.9	100.0	80.00	VERTICAL
160.680000	27.90	9.6	43.5	15.6	168.0	229.00	HORIZONTAL
240.000000	32.30	14.0	46.0	13.7	100.0	103.00	VERTICAL
319.980000	33.40	16.0	46.0	12.6	100.0	68.00	HORIZONTAL
400.020000	34.60	18.2	46.0	11.4	100.0	220.00	HORIZONTAL
792.000000	38.50	24.7	46.0	7.5	107.0	254.00	HORIZONTAL

Table 36 MEASUREMENT RESULT: PK Detector(Above1000 MHz)



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4624.500000	38.30	-4.3	74.0	35.7	200.0	330.00	HORIZONTAL
7407.500000	42.40	2.4	74.0	31.6	100.0	158.00	VERTICAL
10177.500000	44.20	6.4	74.0	29.8	100.0	276.00	VERTICAL
2310.000000	52.30	33.3	74.0	21.7	105.0	109.00	VERTICAL
2390.000000	54.60	33.5	74.0	19.4	135.0	77.00	HORIZONTAL
2483.500000	57.40	33.7	74.0	16.6	100.0	147.00	HORIZONTAL
2500.000000	53.40	33.8	74.0	20.6	100.0	281.00	HORIZONTAL

Table 37 MEASUREMENT RESULT: AVDetector(Above1000 MHz)

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4624.000000	26.00	-4.3	54.0	28.0	200.0	310.00	HORIZONTAL
7412.000000	29.80	2.6	54.0	24.2	200.0	94.00	VERTICAL
10179.000000	31.90	6.4	54.0	22.1	196.0	301.00	HORIZONTAL
2310.000000	40.50	33.3	54.0	13.5	154.0	38.00	VERTICAL
2390.000000	41.30	33.5	54.0	12.7	200.0	312.00	VERTICAL
2483.500000	44.50	33.7	54.0	9.5	191.0	70.00	VERTICAL
2500.000000	41.40	33.8	54.0	12.6	183.0	147.00	VERTICAL

**Measured Result of channel: 6 (2437MHz)**

Table 38 MEASUREMENT RESULT(30 MHz – 1000 MHz)

Frequency (MHz)	Level (dBµV/m)	Transd (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
60.960000	21.80	11.9	40.0	18.2	103.0	294.00	VERTICAL
160.680000	30.40	9.6	43.5	13.1	173.0	225.00	HORIZONTAL
319.980000	33.90	16.0	46.0	12.1	103.0	75.00	HORIZONTAL
400.020000	35.60	18.2	46.0	10.4	102.0	217.00	HORIZONTAL
480.000000	39.00	19.6	46.0	7.0	103.0	129.00	HORIZONTAL
792.000000	38.90	24.7	46.0	7.1	110.0	257.00	HORIZONTAL

Table 39 MEASUREMENT RESULT: PK Detector(Above1000 MHz)

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4874.000000	50.80	-3.4	74.0	23.2	100.0	4.00	VERTICAL
6300.500000	41.10	-0.3	74.0	32.9	100.0	359.00	VERTICAL
12806.500000	45.50	9.4	74.0	28.5	173.0	47.00	HORIZONTAL

Table 40 MEASUREMENT RESULT: AVDetector(Above1000 MHz)

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4874.000000	47.70	-3.4	54.0	6.3	101.0	348.00	VERTICAL
6079.000000	28.90	-0.7	54.0	25.1	200.0	111.00	VERTICAL
12806.000000	32.80	9.4	54.0	21.2	154.0	97.00	HORIZONTAL

**Measured Result of channel: 11 (2462MHz)**

Table 41 MEASUREMENT RESULT(30 MHz – 1000 MHz)

Frequency (MHz)	Level (dB $\mu$ V/m)	Transd (dB)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
57.600000	27.90	12.4	40.0	12.1	100.0	312.00	VERTICAL
160.680000	27.20	9.6	43.5	16.3	168.0	228.00	HORIZONTAL
240.000000	31.50	14.0	46.0	14.5	100.0	88.00	VERTICAL
319.980000	33.60	16.0	46.0	12.4	100.0	64.00	HORIZONTAL
792.000000	38.00	24.7	46.0	8.0	107.0	255.00	HORIZONTAL
902.400000	37.10	26.2	46.0	8.9	100.0	224.00	VERTICAL

Table 42 MEASUREMENT RESULT: PK Detector(Above1000 MHz)

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Height cm	Azimuth deg	Polarization
4258.500000	38.40	-5.1	74.0	35.6	100.0	77.00	VERTICAL
6064.500000	41.00	-0.9	74.0	33.0	164.0	107.00	HORIZONTAL
14462.000000	49.30	14.2	74.0	24.7	172.0	339.00	HORIZONTAL
2310.000000	52.40	33.3	74.0	21.6	164.0	100.00	VERTICAL
2390.000000	52.70	33.5	74.0	21.3	132.0	24.00	HORIZONTAL
2483.500000	57.30	33.7	74.0	16.7	173.0	122.00	HORIZONTAL
2500.000000	53.60	33.8	74.0	20.4	147.0	314.00	VERTICAL

Table 43 MEASUREMENT RESULT: AVDetector(Above1000 MHz)

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Height cm	Azimuth deg	Polarization
4269.000000	25.10	-4.8	54.0	28.9	199.0	359.00	HORIZONTAL
6063.500000	28.20	-0.9	54.0	25.8	169.0	220.00	VERTICAL
14516.000000	36.50	14.8	54.0	17.5	200.0	105.00	HORIZONTAL
2310.000000	40.90	33.3	54.0	13.1	100.0	37.00	VERTICAL
2390.000000	41.60	33.5	54.0	12.4	100.0	304.00	HORIZONTAL
2483.500000	45.80	33.7	54.0	8.2	104.0	13.00	VERTICAL
2500.000000	41.20	33.7	54.0	12.8	104.0	211.00	VERTICAL

## 6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix F.



## 6.7 Conducted Emission at Power Port

### 6.7.1 Test Conditions

Table 44 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Power port
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1 at channel No. 6

### 6.7.2 Test Specifications and Limits

#### 6.7.2.1 Specification

CFR 47 (FCC) part 15.207 and KDB 558074

#### 6.7.2.2 Supporting Standards

Table 45 Supporting Standards:

ANSI C63.4: 2003	Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
------------------	--

#### 6.7.2.3 Limits

Compliance with part15.207, conducted emission must meet the requirement of following table.

Table 46 Limits

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

Note: \* Decreases with the logarithm of the frequency.

### 6.7.3 Test Method and Setup

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4: 2009.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

The EUT was communicated with the BTS simulator through Air interface, the BTS simulator controls the Wireless Modem to transmitter the maximum power which defined in specification of product. The Wireless Modem operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

## Test Set-up

The EUT was setup in the screened chamber and operated under nominal conditions.




Figure 7. Test Set-up

## 6.7.4 Measurement Results

Table 47 MEASUREMENT RESULT:QP DECTER

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.162000	44.30	10.1	65	20.7	L1	FLO
0.216000	39.50	10.0	63	23.5	N	FLO
0.432000	35.00	10.1	57	22.0	N	FLO
2.322000	29.40	10.1	56	26.6	N	FLO
7.710000	28.00	10.2	60	32.0	N	FLO
23.986000	27.00	10.4	60	33.0	L1	FLO

Table 48 MEASUREMENT RESULT:AV DECTER

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.360000	27.90	10.0	49	21.1	N	FLO
0.428000	28.10	10.0	47	18.9	N	FLO
0.894000	25.60	10.1	46	20.4	N	FLO
2.142000	23.50	10.1	46	22.5	N	FLO
6.484000	21.80	10.2	50	28.2	N	FLO
28.358000	25.90	10.4	50	24.1	L1	FLO

## 6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix G.



## 7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 49 System Measurement Uncertainty

Items		Extended Uncertainty
20dB bandwidth measurement	Magnitude (%)	U=0.2%; k=2
Peak output power	Power(dBm)	U=0.39dB; k=2
Band edge compliance measurement	Disturbance Power(dBm)	U=2.0dB; k=2
Conducted RF spurious	Disturbance Power(dBm)	U=0.4dB; k=2
Power spectral density	Disturbance Power(dBm)	U=0.4dB; k=2
Radiated spurious emission & Radiated restricted band measurement	Field strength (dB $\mu$ V/m)	U=4.1dB; k=2 U=4.1dB; k=2
Conducted emission test for power port	Disturbance Voltage(dB $\mu$ V)	U=3.4dB; k=2



## 8 Appendices

Appendix A	Measurement Results 6dB bandwidth measurement
Appendix B	Measurement Results Peak output power
Appendix C	Measurement Results Band edge compliance measurement
Appendix D	Measurement Results Conducted RF spurious
Appendix E	Measurement Results Power spectral density
Appendix F	Measurement Results Radiated spurious emission
Appendix G	Measurement Results Conducted emission test for power port
Appendix H	Photos of Test Setup

(END OF REPORT)




# **Appendix A**

## 6dB bandwidth measurement

According to FCC Part 15.247 (a) (2)




# TM1 Channel 1 (2412MHz)






# Channel 6 (2437MHz)






# Channel 11 (2462MHz)






# TM2 Channel 1 (2412MHz)






# Channel 6 (2437MHz)






# Channel 11 (2462MHz)






# TM3 Channel 1 (2412MHz)






# Channel 6 (2437MHz)





# Channel 11 (2462MHz)






## **Appendix B**

# Conducted Peak output power

According to FCC Part 15.247 (b) (3)




# TM1 Channel 1 (2412MHz)






# Channel 6 (2437MHz)






# Channel 11 (2462MHz)






# TM2 Channel 1 (2412MHz)






# Channel 6 (2437MHz)






# Channel 11 (2462MHz)






# TM3 Channel 1 (2412MHz)






# Channel 6 (2437MHz)





# Channel 11 (2462MHz)






# **Appendix C**

## **Band edge spurious emission**

**According to FCC Part 15.247 (d)**




# TM1 Low edge






# High edge






# TM2 Low edge






# High edge






# TM3

## Low edge





# High edge






## Appendix D


# Conducted RF spurious


According to FCC Part 15.247 (d)



# TM1 Channel 1












# Channel 6












# Channel 11












# TM2 Channel 1












# Channel 6












# Channel 11












# TM3 Channel 1












## Channel 6












# Channel 11










# **Appendix E**

## Power spectral density

According to FCC Part 15.247 (e)




# TM1 Channel 1






# Channel 6






# Channel 11






# TM2 Channel 1






# Channel 6






# Channel 11






# TM3 Channel 1






# Channel 6





# Channel 11





## **Appendix F**


# Radiated spurious emission & spurious in restricted band

According to FCC Part 15.247 (d) & 15.205 & 15.209




Note: This test was carried out in all the test modes, here only the worst test result was shown.

## Channel 1 10kHz to 30MHz






## 30MHz to 1GHz



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Plarization
57.600000	23.10	12.4	40.0	16.9	100.0	80.00	VERTICAL
160.680000	27.90	9.6	43.5	15.6	168.0	229.00	HORIZONTAL
240.000000	32.30	14.0	46.0	13.7	100.0	103.00	VERTICAL
319.980000	33.40	16.0	46.0	12.6	100.0	68.00	HORIZONTAL
400.020000	34.60	18.2	46.0	11.4	100.0	220.00	HORIZONTAL
792.000000	38.50	24.7	46.0	7.5	107.0	254.00	HORIZONTAL



# 1GHz to 18GHz



Note: Signal suppressed with a 2.4 GHz band rejection filter

### MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4624.500000	38.30	-4.3	74.0	35.7	200.0	330.00	HORIZONTAL
7407.500000	42.40	2.4	74.0	31.6	100.0	158.00	VERTICAL
10177.500000	44.20	6.4	74.0	29.8	100.0	276.00	VERTICAL

### MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4624.000000	26.00	-4.3	54.0	28.0	200.0	310.00	HORIZONTAL
7412.000000	29.80	2.6	54.0	24.2	200.0	94.00	VERTICAL
10179.000000	31.90	6.4	54.0	22.1	196.0	301.00	HORIZONTAL




# 18GHz to 26GHz

Note: No peak found in pre- test.



## 2.30GHz to 2.51GHz



Note: The peak exceeds the limit line is carrier frequency.

### MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2310.000000	52.30	33.3	74.0	21.7	105.0	109.00	VERTICAL
2390.000000	54.60	33.5	74.0	19.4	135.0	77.00	HORIZONTAL
2483.500000	57.40	33.7	74.0	16.6	100.0	147.00	HORIZONTAL
2500.000000	53.40	33.8	74.0	20.6	100.0	281.00	HORIZONTAL


### MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2310.000000	40.50	33.3	54.0	13.5	154.0	38.00	VERTICAL
2390.000000	41.30	33.5	54.0	12.7	200.0	312.00	VERTICAL
2483.500000	44.50	33.7	54.0	9.5	191.0	70.00	VERTICAL
2500.000000	41.40	33.8	54.0	12.6	183.0	147.00	VERTICAL




# Channel 6

## 10 kHz to 30MHz






## 30MHz to 1GHz



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
60.960000	21.80	11.9	40.0	18.2	103.0	294.00	VERTICAL
160.680000	30.40	9.6	43.5	13.1	173.0	225.00	HORIZONTAL
319.980000	33.90	16.0	46.0	12.1	103.0	75.00	HORIZONTAL
400.020000	35.60	18.2	46.0	10.4	102.0	217.00	HORIZONTAL
480.000000	39.00	19.6	46.0	7.0	103.0	129.00	HORIZONTAL
792.000000	38.90	24.7	46.0	7.1	110.0	257.00	HORIZONTAL



# 1GHz to 18GHz



Note: Signal suppressed with a 2.4 GHz band rejection filter

**MEASUREMENT RESULT: PK Detector**

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4874.000000	50.80	-3.4	74.0	23.2	100.0	4.00	VERTICAL
6300.500000	41.10	-0.3	74.0	32.9	100.0	359.00	VERTICAL
12806.500000	45.50	9.4	74.0	28.5	173.0	47.00	HORIZONTAL

**MEASUREMENT RESULT: AVDetector**

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4874.000000	47.70	-3.4	54.0	6.3	101.0	348.00	VERTICAL
6079.000000	28.90	-0.7	54.0	25.1	200.0	111.00	VERTICAL
12806.000000	32.80	9.4	54.0	21.2	154.0	97.00	HORIZONTAL




# 18GHz to 26GHz

Note: No peak found in pre- test.




# Channel 11

## 10 kHz to 30 MHz






## 30MHz to 1GHz



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
57.600000	27.90	12.4	40.0	12.1	100.0	312.00	VERTICAL
160.680000	27.20	9.6	43.5	16.3	168.0	228.00	HORIZONTAL
240.000000	31.50	14.0	46.0	14.5	100.0	88.00	VERTICAL
319.980000	33.60	16.0	46.0	12.4	100.0	64.00	HORIZONTAL
792.000000	38.00	24.7	46.0	8.0	107.0	255.00	HORIZONTAL
902.400000	37.10	26.2	46.0	8.9	100.0	224.00	VERTICAL



# 1GHz to 18GHz



Note: Signal suppressed with a 2.4 GHz band rejection filter

### MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4258.500000	38.40	-5.1	74.0	35.6	100.0	77.00	VERTICAL
6064.500000	41.00	-0.9	74.0	33.0	164.0	107.00	HORIZONTAL
14462.000000	49.30	14.2	74.0	24.7	172.0	339.00	HORIZONTAL

### MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
4269.000000	25.10	-4.8	54.0	28.9	199.0	359.00	HORIZONTAL
6063.500000	28.20	-0.9	54.0	25.8	169.0	220.00	VERTICAL
14516.000000	36.50	14.8	54.0	17.5	200.0	105.00	HORIZONTAL




# 18GHz to 26GHz

Note: No peak found in pre- test.



## 2.30GHz to 2.51GHz



Note: The peak exceeds the limit line is carrier frequency.

### MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2310.000000	52.40	33.3	74.0	21.6	164.0	100.00	VERTICAL
2390.000000	52.70	33.5	74.0	21.3	132.0	24.00	HORIZONTAL
2483.500000	57.30	33.7	74.0	16.7	173.0	122.00	HORIZONTAL
2500.000000	53.60	33.8	74.0	20.4	147.0	314.00	VERTICAL

### MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2310.000000	40.90	33.3	54.0	13.1	100.0	37.00	VERTICAL
2390.000000	41.60	33.5	54.0	12.4	100.0	304.00	HORIZONTAL
2483.500000	45.80	33.7	54.0	8.2	104.0	13.00	VERTICAL
2500.000000	41.20	33.7	54.0	12.8	104.0	211.00	VERTICAL




# Appendix G

## Conducted Emission at Power Port

According to FCC Part 15.207



## Channel 6



### MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.162000	44.30	10.1	65	20.7	L1	FLO
0.216000	39.50	10.0	63	23.5	N	FLO
0.432000	35.00	10.1	57	22.0	N	FLO
2.322000	29.40	10.1	56	26.6	N	FLO
7.710000	28.00	10.2	60	32.0	N	FLO
23.986000	27.00	10.4	60	33.0	L1	FLO

### MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.360000	27.90	10.0	49	21.1	N	FLO
0.428000	28.10	10.0	47	18.9	N	FLO
0.894000	25.60	10.1	46	20.4	N	FLO
2.142000	23.50	10.1	46	22.5	N	FLO
6.484000	21.80	10.2	50	28.2	N	FLO
28.358000	25.90	10.4	50	24.1	L1	FLO