

P1528_OET65-GPRS (1 timeslot in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1909.8 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.17 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.4 V/m; Power Drift = 0.162 dB

Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.597 mW/g

Maximum value of SAR (measured) = 1.18 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-GPRS (1 timeslot in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1850.2 MHz

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.804 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 5.84 V/m; Power Drift = 0.162 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.905 mW/g; SAR(10 g) = 0.510 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (1 timeslot in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.841 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.92 V/m; Power Drift = 0.170 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.971 mW/g; SAR(10 g) = 0.546 mW/g

Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.08mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (2 timeslots in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.704 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.4 V/m; Power Drift = 0.170 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.806 mW/g; SAR(10 g) = 0.454 mW/g

Maximum value of SAR (measured) = 0.891 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (3 timeslots in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 3TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.772 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.69 V/m; Power Drift = 0.129 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.872 mW/g; SAR(10 g) = 0.490 mW/g

Maximum value of SAR (measured) = 0.964 mW/g



0 dB = 0.964mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (4 timeslots in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 4TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.704 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.35 V/m; Power Drift = 0.186 dB

Peak SAR (extrapolated) = 1.3 W/kg

SAR(1 g) = 0.805 mW/g; SAR(10 g) = 0.453 mW/g

Maximum value of SAR (measured) = 0.888 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (1 timeslot in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1909.8 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.862 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.98 V/m; Power Drift = -0.146 dB

Peak SAR (extrapolated) = 1.65 W/kg

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.568 mW/g

Maximum value of SAR (measured) = 1.13 mW/g



0 dB = 1.13mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (1 timeslot in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1850.2 MHz

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.781 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 5.56 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.914 mW/g; SAR(10 g) = 0.514 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.02 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (2 timeslots in uplink) with ThinkPad X301 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1909.8 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.720 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.49 V/m; Power Drift = 0.164 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.847 mW/g; SAR(10 g) = 0.476 mW/g

Maximum value of SAR (measured) = 0.943 mW/g



0 dB = 0.943mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (2 timeslots in uplink) with ThinkPad T61 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1850.2 MHz

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.650 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 5.23 V/m; Power Drift = 0.109 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.416 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.813 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (3 timeslots in uplink) with ThinkPad T61 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 3TS; Frequency: 1909.8 MHz

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.802 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.72 V/m; Power Drift = 0.167 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.922 mW/g; SAR(10 g) = 0.518 mW/g

Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.02mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (3 timeslots in uplink) with ThinkPad T61 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 3TS; Frequency: 1850.2 MHz

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.682 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 5.32 V/m; Power Drift = 0.174 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.783 mW/g; SAR(10 g) = 0.443 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.867 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

Date/Time: 1/15/2011 1:41:58 AM

P1528_OET65-EGPRS (4 timeslots in uplink) with ThinkPad T61 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 4TS; Frequency: 1909.8 MHz
Medium parameters used: $f = 1910$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/24/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.772 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.72 V/m; Power Drift = 0.106 dB

Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 0.888 mW/g; SAR(10 g) = 0.498 mW/g

Maximum value of SAR (measured) = 0.979 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

P1528_OET65-EGPRS (4 timeslots in uplink) with ThinkPad T61 front side-GSM1900

DUT: E188s-6

Communication System: HW -GSM/GPRS/EDGE 4TS; Frequency: 1850.2 MHz

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

. Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

. Sensor-Surface: 4mm (Mechanical Surface Detection)

. Electronics: DAE4 Sn852; Calibrated: 12/24/2010

. Phantom: SAM1; Type: SAM; Serial: TP-1475

. Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57


E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.650 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.14 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 1.2 W/kg

SAR(1 g) = 0.747 mW/g; SAR(10 g) = 0.422 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)**Maximum value of SAR (measured) = 0.834 mW/g****Additional information:**

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.1°C

Annex 2.3 WCDMA 850MHz body

Date/Time: 1/28/2011 8:27:31 AM

P1528_OET65-WCDMA with ThinkPad X301 front side-WCDMA850**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.360 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.03 V/m; Power Drift = 0.017 dB

Peak SAR (extrapolated) = 0.497 W/kg

SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.242 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.384 mW/g

**Additional information:**

position or distance of DUT to SAM:5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with 19cm USB cable rear side-WCDMA850

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.359 mW/g

E188s-6/body/Zoom Scan (6x6x6)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=8mm


Reference Value = 18.5 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 0.563 W/kg

SAR(1 g) = 0.359 mW/g; SAR(10 g) = 0.224 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.380 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 left side-WCDMA850

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.253 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 12.4 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.361 W/kg

SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.156 mW/g

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.257 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 right side-WCDMA850**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.961$ mho/m; $\epsilon_r = 54.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x10x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.382 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.7 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 0.551 W/kg

SAR(1 g) = 0.360 mW/g; SAR(10 g) = 0.230 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.394 mW/g

**Additional information:**

position or distance of DUT to SAM:5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 right side-WCDMA850**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 846.6 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.973$ mho/m; $\epsilon_r = 54.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x10x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.527 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.799 W/kg

SAR(1 g) = 0.518 mW/g; SAR(10 g) = 0.329 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.567 mW/g



0 dB = 0.567mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 right side-WCDMA850

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 826.4 MHz

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.958$ mho/m; $\epsilon_r = 54.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.513 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 16.6 V/m; Power Drift = 0.046 dB

Peak SAR (extrapolated) = 0.776 W/kg

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.326 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.555 mW/g



0 dB = 0.555mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-HSDPA with ThinkPad T61 right side-WCDMA850**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 846.6 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.973$ mho/m; $\epsilon_r = 54.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x10x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.480 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.741 W/kg

SAR(1 g) = 0.481 mW/g; SAR(10 g) = 0.306 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.526 mW/g

**Additional information:**

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-HSUPA with ThinkPad T61 right side-WCDMA850

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 846.6 MHz

Medium parameters used (interpolated): $f = 846.6$ MHz; $\sigma = 0.973$ mho/m; $\epsilon_r = 54.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(5.92, 5.92, 5.92); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM2; Type: SAM; Serial: TP-1474

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.319 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 13.2 V/m; Power Drift = -0.00816 dB

Peak SAR (extrapolated) = 0.493 W/kg

SAR(1 g) = 0.325 mW/g; SAR(10 g) = 0.207 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.354 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

Annex 2.4 WCDMA 1900MHz body

Date/Time:1/14/20111:59:53AM

P1528_OET65-WCDMA with ThinkPad X301 front side-WCDMA1900

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.835 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.26 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.926 mW/g; SAR(10 g) = 0.523 mW/g

Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.02mW/g

Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with 19cm USB cable rear side-WCDMA1900

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.772 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = 0.102 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.687 mW/g; SAR(10 g) = 0.341 mW/g

Maximum value of SAR (measured) = 0.762 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = 0.102 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.625 mW/g; SAR(10 g) = 0.344 mW/g

Maximum value of SAR (measured) = 0.692 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 left side-WCDMA1900

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.630 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.3 V/m; Power Drift = -0.168 dB

Peak SAR (extrapolated) = 0.971 W/kg

SAR(1 g) = 0.584 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.645 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad T61 right side-WCDMA1900

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.596 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18 V/m; Power Drift = -0.130 dB

Peak SAR (extrapolated) = 0.900 W/kg

SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.282 mW/g

Maximum value of SAR (measured) = 0.581 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad X301 front side-WCDMA1900**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 1907.6 MHz

Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.823 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.88 V/m; Power Drift = 0.197 dB

Peak SAR (extrapolated) = 1.48 W/kg

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.516 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.01 mW/g

**Additional information:**

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-WCDMA with ThinkPad X301 front side-WCDMA1900

DUT: E188s-6

Communication System: HW -UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.844 mW/g

E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 8.01 V/m; Power Drift = 0.199 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.951 mW/g; SAR(10 g) = 0.536 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.06 mW/g



Additional information:

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-HSDPA with ThinkPad X301 front side-WCDMA1900**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.919 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.29 V/m; Power Drift = 0.192 dB

Peak SAR (extrapolated) = 1.65 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.582 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.15 mW/g

**Additional information:**

position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C

P1528_OET65-HSUPA with ThinkPad X301 front side-WCDMA1900**DUT: E188s-6**

Communication System: HW -UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

Probe: ES3DV3 - SN3168; ConvF(4.61, 4.61, 4.61); Calibrated: 12/23/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn852; Calibrated: 12/24/2010

Phantom: SAM1; Type: SAM; Serial: TP-1475

Measurement SW: DASYS, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

E188s-6/body/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.631 mW/g


E188s-6/body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.3 V/m; Power Drift = 0.182 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.706 mW/g; SAR(10 g) = 0.397 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.785 mW/g

**Additional information:**


position or distance of DUT to SAM: 5 mm

ambient temperature: 22.0 °C; liquid temperature: 22.4°C


Annex 2.5 Z-axis scans

GSM 850


E188s-6 front side (1 timeslot) –GPRS 850 Channel 190




E188s-6 front side (2 timeslots) –GPRS 850 Channel 190




E188s-6 front side (3 timeslots) –GPRS 850 Channel 190




E188s-6 front side (4 timeslots) –GPRS 850 Channel 190




E188s-6 back side (1 timeslot) –GPRS 850 Channel 190




E188s-6 left side (1 timeslot) –GPRS 850 Channel 190




E188s-6 right side (1 timeslot) –GPRS 850 Channel 190




E188s-6 right side (1 timeslot) –GPRS 850 Channel 251




E188s-6 right side (1 timeslot) –GPRS 850 Channel 128




E188s-6 right side (1 timeslot) –EGPRS 850 Channel 190




E188s-6 right side (2 timeslots) –EGPRS 850 Channel 190




E188s-6 right side (3 timeslots) –EGPRS 850 Channel 190




E188s-6 right side (4 timeslots) –EGPRS 850 Channel 190



E188s-6 right side (1 timeslot) –EGPRS 850 Channel 251




E188s-6 right side (1 timeslot) –EGPRS 850 Channel 128




GSM 1900

E188s-6 rear side (1 timeslot) –GPRS 1900 Channel 661



E188s-6 rear side (2 timeslots) –GPRS 1900 Channel 661



E188s-6 rear side (3 timeslots) –GPRS 1900 Channel 661

