



## **MAXIMUM PERMISSIBLE EXPOSURE ESTIMATION For HUAWEI E270**

### **1 Introduction**

HUAWEI E270 HSDPA USB MODEM is subscriber equipment in the GSM system. The frequency band is 850M. The E270 implements such functions as RF signal receiving / Transmitting, HSDPA/UMTS/EDGE/GPRS/GSM protocol processing and data service etc. Externally it provides USB interface (to connect to the notebook etc.), USIM card interface and antenna interface. It has two internal antennas as default. E270 uses Qualcomm MSM7200 chipset and Zero-IF technologies.

### **2 Limits and Guidelines on Exposure to Electromagnetic Fields**

According to the FCC Part 2.1091, we know: mobile device (transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitters radiating structure(s) and the body of the user or nearby persons). And the Cellular radiotelephone service and PCS services are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more. The radiated power of 850M/1900M for E270 is 2W/1W, so for E270 only the 850M band needs to be subjected to routine the environmental evaluation for RF exposure.

Uncontrolled limits are used for general public. General population/uncontrolled exposure apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure. The exposure levels can be expressed in terms of power density, electric field strength, or magnetic field strength, as averaged over 30 minutes for the general public and 6 minutes for trained personnel. The exposure criterion is frequency dependent, and a chart covering the range from 3 kHz to 100 GHz can be found in NCRP No.86 (references IEEE C95.1-1999). Below are the limits.



Limits for Occupational/Controlled Exposure			
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )
0.3-3.0	614	16.3/f	(100)*
3.0-30	1842/f	16.3/f	(900/f <sup>2</sup> )*
30-300	61.4	0.163	1.0
300-1500	--	--	f/300
15,00-100,000	--	--	5

Limits for General Population/Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*
30-300	27.5	0.073	0.2
300-15,00	--	--	f/1500
15,00-100,000	--	--	1.0

For 850MHz:

Power density S [mW/cm<sup>2</sup>] for controlled area at 850 MHz

$$S = \frac{f(\text{MHz})}{300} = \frac{850}{300} = 2.83 \text{ mW/cm}^2$$

Power density S [mW/cm<sup>2</sup>] for uncontrolled area at 869 MHz

$$S = \frac{f(\text{MHz})}{1500} = \frac{850}{1500} = 0.566 \text{ mW/cm}^2$$

S= 0.566 mW/cm<sup>2</sup> = 5.66 W/m<sup>2</sup> for uncontrolled exposure

For 1900MHz:

Power density S [mW/cm<sup>2</sup>] for controlled area at 1850 MHz

S=5 mW/cm<sup>2</sup>

Power density S [mW/cm<sup>2</sup>] for uncontrolled area at 1850 MHz

S=1 mW/cm<sup>2</sup>

S= 1 mW/cm<sup>2</sup> = 10 W/m<sup>2</sup> for uncontrolled exposure



Reference levels are provided for exposure assessment to determine whether the basic restrictions on exposure of humans to electromagnetic fields are exceeded. The basic restrictions on exposure to electromagnetic fields are based directly on established health effects and biological considerations.

### 3 Location of EUT

The EUT uses one monopole antenna. The source of the radiation is mounted on terminal; generally the direction of the antenna position is uprightness tabletop. The highest level of emission would be expected in close vicinity of the antenna and in line of sight to the antenna.

### 4 Prediction of the Exposure to Electromagnetic Fields

Calculations can be made on a site by site basis to ensure the power density is below the limits given above, or guidelines can be done beforehand to ensure the minimum distances from the antenna is maintained through the site planning. The calculations are based on FCC OET 65 Appendix B.

#### 4.1 Calculation of the Safe Distance

Below method describes a theoretical approach to calculate possible exposure to electromagnetic radiation around a base station transceiver antenna. Precise statements are basically only possible either with measurements or complex calculations considering the complexity of the environment (e.g. soil conditions, near buildings and other obstacles) which causes reflections, scattering of electromagnetic fields.

The maximum output power (given in EIRP) of a base station is usually limited by license conditions of the network operator.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation. The calculations are based on FCC OET 65 Appendix B.

$$S = \frac{P(W) * G_{numeric}}{4 * r^2(m) * \pi}$$

Whereas:

P = Maximum output power in W of the site

G numeric = Numeric gain of the antenna relative to isotropic antenna

R = distance between the antenna and the point of exposure in meters



4.2 Technical Description E270

850MHz Technical Specification:

Input power to antenna:	2.00W (RMS 33.02 dBm) for GSM850MHz 2.00W (RMS 32.96 dBm) for GPRS850MHz (one timeslot) 0.423W (RMS 26.26 dBm) for EDGE850MHz (one timeslot) 0.207W (RMS 23.16 dBm) for WCDMA850MHz
Transmitter frequency band:	GSM850
Number of antenna ports:	1
Antenna system and type (typical)	PIFA
Frequency range:	Uplink:824 M~849M; Downlink:869 M~894M
Gain:	<2dBi (GSM850)
Mechanical specification (Height)	39.97mm for GSM850

1900MHz Technical Specification:

Input power to antenna:	0.979 W (RMS 29.91 dBm) for GSM1900MHz 0.979W (RMS 29.91 dBm) for GPRS1900MHz (one timeslot) 0.343W (RMS 25.35 dBm) for EDGE1900MHz (one timeslot) 0.207W (RMS 23.15 dBm) for WCDMA1900MHz
Transmitter frequency band	GSM1900
Number of antenna ports:	1
Antenna system and type (typical)	PIFA
Frequency range:	Uplink:1850 M~1910M; Downlink:1930 M~1990M



Gain:	<2.7dBi (GSM1900)
Mechanical specification (Height)	39.97mm for GSM1900

#### 4.3 Estimation of compliance boundary

##### **GSM 850M:**

For the final determination of the compliance boundary the model for far-field calculation is used since this overestimates the field strength in the near-field region. Thus the calculated compliance boundary should be rather more conservative and on the safe side.

For EUT the following compliance boundary is calculated:

Power at antenna connector BTS: **32.96 dBm (one timeslot)**

Note: Here the power is for one timeslot, so the factual power should be divided by 8.

Antenna-cable attenuation: **0 dB**

Antenna gain: **2 dBi (1.58)**

##### **Compliance boundary**

**For GSM 850MHz band:**

$$S = \frac{P(W) * G_{numeric}}{4 * r^2(m) * \pi}$$

$$S = \frac{2 * 1.58}{8 * 4 * 0.2^2(m) * \pi}$$

**S=0.786 W/m2 <5.66 W/m2**

**For GRPS850MHz,**

$$S = \frac{2 * 1.58}{8 * 4 * 0.2^2(m) * \pi}$$

**S=0.786 W/m2 <5.66 W/m2**

**For EDGE850MHz,**

$$S = \frac{0.423 * 1.58}{8 * 4 * 0.2^2(m) * \pi}$$

**S=0.166 W/m2 <5.66 W/m2**



For WCDMA850MHz,

$$S = \frac{0.207 * 1.58}{4 * 0.2^2(m) * \pi}$$

**S=0.65 W/m<sup>2</sup> <5.66 W/m<sup>2</sup>**

**For GPRS and EDGE, the transmitter support multi-timeslot, but the conducted ERP will decrease 2dB when add one uplink timeslot, so we can get the following conclusion:**

**The power(dB) decrease 2dB, the power(W) should be divide by 1.58(102/10)**

**For two timeslot:**

$$S_{\text{two timeslot}} = \frac{P / 1.58 * G}{8 * r^2(m) * \pi} * 2 = S_{\text{one timeslot}} * 2 / 1.58 = 1.27 S_{\text{one timeslot}}$$

**For three timeslot:**

$$S_{\text{three timeslot}} = \frac{P / 2.51 * G}{8 * r^2(m) * \pi} * 3 = S_{\text{one timeslot}} * 3 / 2.51 = 1.2 S_{\text{one timeslot}}$$

**For four timeslot:**

$$S_{\text{two timeslot}} = \frac{P / 4 * G}{8 * r^2(m) * \pi} * 4 = S_{\text{one timeslot}} * 4 / 4 = S_{\text{one timeslot}}$$

**The two timeslot's S is the biggest.**

**For GPRS850:**

$$S_{\text{two timeslot}} = 1.27 S_{\text{one timeslot}} = 1.27 * 0.786 = 0.99 < 5.66 \text{ W/m}^2$$

**For EDGE850:**

$$S_{\text{two timeslot}} = 1.27 S_{\text{one timeslot}} = 1.27 * 0.166 = 0.21 < 5.66 \text{ W/m}^2$$

**GSM 1900M:**

For the final determination of the compliance boundary the model for far-field calculation is used since this overestimates the field strength in the near-field region. Thus the calculated compliance boundary should be rather more conservative and on the safe side.

For EUT the following compliance boundary is calculated:

Power at antenna connector BTS: **29.91 dBm(one timeslot)**

Note: Here the power is for one timeslot, so the factual power should be divided by 8.

Antenna-cable attenuation: **0 dB**

Input power to antenna: **29.5 dBm (0.891W)**

Antenna gain: **2.7 dBi (1.86)**

**Compliance boundary**

**For GSM 1900MHz band:**

$$S = \frac{P(W) * G_{\text{numeric}}}{4 * r^2(m) * \pi}$$



$$S = \frac{0.891 * 1.86}{8 * 4 * 0.2^2(m) * \pi}$$

$$S=0.412 \text{ W/m}^2 < 10 \text{ W/m}^2$$

**For GRPS1900MHz,**

$$S = \frac{0.891 * 1.86}{8 * 4 * 0.2^2(m) * \pi}$$

$$S=0.412 \text{ W/m}^2 < 10 \text{ W/m}^2$$

**For EDGE1900MHz,**

$$S = \frac{0.343 * 1.86}{8 * 4 * 0.2^2(m) * \pi}$$

$$S=0.159 \text{ W/m}^2 < 10 \text{ W/m}^2$$

**For WCDMA1900MHz,**

$$S = \frac{0.207 * 1.86}{4 * 0.2^2(m) * \pi}$$

$$S=0.766 \text{ W/m}^2 < 10 \text{ W/m}^2$$

The timeslot's calculation is same with 850MHz.

The two timeslot's S is the biggest.

**For GPRS1900:**

$$S_{\text{two timeslot}}=1.27 \quad S_{\text{one timeslot}}=1.27*0.412=0.53 < 10 \text{ W/m}^2$$

**For EDGE1900:**

$$S_{\text{two timeslot}}=1.27 \quad S_{\text{one timeslot}}=1.27*0.59=0.75 < 10 \text{ W/m}^2$$

Conclusion:

The equipment meets the limits.