

Office of Engineering and Technology

[OET Home Page](#)

[FCC](#) > [FCC E-filing](#) > [Inquiry System Home Page](#) > Inquiry Confirmation

[FCC Site Map](#)

Site Options

[Knowledge DataBase Search](#)

[Detail Criteria Search](#)

[Submit An Inquiry](#)

[Reply to an Inquiry Response](#)

[Category List](#)

[FAQ Search](#)

[View Instructions](#)

Related Sites

[Equipment Authorization System \(EAS\)](#)

[Telecommunications Certification Bodies \(TCB\)](#)

Inquiry Tracking Number: **611854**
Date of Submission: **08/17/2007**
Subject: **SAR Body Test Question**
Question: **Gentlemen,**

We have a product which can best be described as a postage stamp size transmitter which functions as a data modem. It is supplied with two standard length USB cables - one more than 20cm and the other less than 20cm. Consequently, full body SAR testing seems to be appropriate.

The SAR laboratory has performed measurements at 1.5cm spacing - same as any belt-worn cellphone. However, for this case, it does not appear that it would be appropriate. Do you agree or not?

Please provide guidance for best body worn spacing to use for testing.

Best Regards,

Bill

Please send any comments or suggestions for this site to [OET Systems Support](#)

Federal Communications
Commission
445 12th Street, SW
Washington, DC 20554
[More FCC Contact Information...](#)

Phone: 888-CALL-FCC (225-5322)
TTY: 888-TELL-FCC (835-5322)
Fax: 202-418-0232
E-mail: fccinfo@fcc.gov

- [Privacy Policy](#)
- [Web Policies & Notices](#)
- [Customer Service Standards](#)
- [Freedom of Information Act](#)