



FCC Test Report

Product Name: HSPA+ USB Stick

Model Number: E353s-81

Report No: SYBH(Z-RF)010062011-2001

FCC ID: QISE353S-81

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518



Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Notice 2

Modification Information:

Table 1 Modification Information

Modification Information	1	
	2	
	3	<i>Not Applicable!</i>
	4	
	5	
	6	
	7	



Contents

1	<u>Summary</u>	6
2	<u>Product Description</u>	7
2.1	PRODUCTION INFORMATION	7
2.2	MODIFICATION INFORMATION	7
3	<u>Test Site Description</u>	8
3.1	TESTING PERIOD	8
3.2	GENERAL SET UP DESCRIPTION	8
4	<u>Product Description</u>	9
4.1	TECHNICAL CHARACTERISTICS.....	9
4.2	EUT IDENTIFICATION LIST.....	11
5	<u>Main Test Instruments</u>	12
6	<u>Transmitter Measurements</u>	13
6.1	EFFECTIVE RADIATED POWER OF TRANSMITTER (ERP).....	13
6.2	CONDUCTED POWER OF TRANSMITTER	16
6.3	MODULATION CHARACTERISTICS.....	18
6.4	OCCUPIED BANDWIDTH.....	20
6.5	BAND EDGES COMPLIANCE	22
6.6	SPURIOUS EMISSION AT ANTENNA TERMINAL.....	24
6.7	RADIATED SPURIOUS EMISSIONS	26
6.8	FREQUENCY STABILITY	29
7	<u>System Measurement Uncertainty</u>	32
8	<u>Appendices</u>	33

1 Summary

The table below summarizes the measurements and results for the EUT. Detailed results and descriptions are shown in the following pages.

Table 2 Summary of results

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
2.1046	22.913	Effective Radiated Power of Transmitter	PASS
2.1046	22.913	Conducted Power of Transmitter	PASS
2.1047	/	Modulation Characteristics	PASS
2.1049	/	Occupied Bandwidth	PASS
2.1051	22.917	Band Edges compliance	PASS
2.1051	22.917	Spurious Emission at Antenna Terminal	PASS
2.1053	22.917	Radiated Spurious Emissions	PASS
2.1055	22.355	Frequency Stability	PASS



2 Product Description

2.1 Production Information

2.1.1 General Description

E353s-81 HSPA+/WCDMA/EDGE/GPRS/GSM dual mode USB Stick is subscriber equipment in the UMTS/GSM system. E353s-81 implement such functions as RF signal receiving/transmitting, HSPA+/WCDMA and EDGE/GPRS/GSM protocol processing, data service etc. Externally it provides USB interface (to connect to the notebook etc.), USIM card interface and Micro SD card interface. E353s-81 has an internal antenna as default.

2.1.2 Support function and Service

The EUT support the function and service as follows:

Table 3 Service and Test mode List

Service Name	Characteristic	Corresponding Test Mode	Note
Voice and data	Modulation: GMSK	TM1	GPRS/GSM
Data	Modulation: 8PSK	TM2	EDGE

Note: * The specified GPRS test conditions & settings are defined in 3GPP TS51.010 V5.4.0 and the EDGE test conditions & settings are defined in 3GPP TS51.010 V5.4.0.

2.2 Modification Information

For original equipment, following table is not application.

Table 4 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable				



3 Test Site Description

The test site of:

***Huawei Technologies Co. Ltd.
P.O. Box 518129
Huawei base, Bantian,
Longgang District, Shenzhen, China***

3.1 Testing Period

The test have been performed during the period of

Jun.20, 2011 –Jun.22, 2011

3.2 General Set up Description

TM1: GPRS/GSM Mode with GMSK Modulation

TM2: EDGE Mode with 8PSK Modulation



4 Product Description

4.1 Technical Characteristics

4.1.1 Frequency Range

Table 5 Frequency Range

Uplink band:	824 to 849 MHz
Downlink band:	869 to 894 MHz

4.1.2 Channel Spacing / Separation

Table 6 Channel Spacing / Separation

	EDGE/GPRS/GSM
Channel Raster	200kHz
Channel spacing:	200kHz

4.1.3 Type of Emission

Table 7 Type of Emission

	GPRS/GSM	EDGE
Emission Designation:	300KGXW	300KG7W

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

4.1.4 Environmental Requirements

Table 8 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%-95%RH

4.1.5 Power Source

Table 9 Power Source

AC voltage nominal:	~ 120 V
AC voltage range	~ 100 V to ~ 240 V
AC current maximal:	650mA

4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 10 Applied RF module DC Voltages and Currents

Voltage:	== +2.8V
Current:	100mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)



4.2 EUT Identification List

4.2.1 Board Information

Table 11 Board Information

HSPA+ USB Stick		
E353s-81		
Board and Module		
Equipment Designation / Description	Serial Number	
Main Board	B7V2A11160100013	

4.2.2 FCC Identification

Grantee Code: QIS
Product Code: E353s-81
FCC Identification: QISE353S-81



5 Main Test Instruments

Table 12 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until
Universal Radio Communication Tester	R&S	CMW 500	103216	Nov.26,2011
Power supply	KEITHLEY	2303	1288003	Sep.27,2011
Universal Radio Communication Tester	R&S	CMU200	105822	Oct.24,2011
Wireless Communication Test set	Agilent	N4010A	MY49081592	Dec.14,2011
Universal Radio Communication Tester	Agilent	E5515C	MY50260239	Aug.04,2011
Signal Analyzer	R&S	FSQ31	200021	Sep.27,2011
Temperature Chamber	WEISS	WKL64	24600294	Jan.25,2012
Signal generator	Agilent	E8257D	MY49281095	Jul.09.2011
Vector Signal Generator	R&S	SMU200A	104162	Sep.07,2011
Test receiver	R&S	ESU26	36090302083	Jun.24.2011
EMI Test receiver	R&S	FSQ43	100048	Jun.23,2011
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	919/1009	Dec.13,2011
Tunable Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	979/917	Dec.13,2011
Horn Antenna	R & S	HF906	359287/005	May.07, 2012
Horn Antenna	R & S	HF906	359287/006	Apr.27, 2012
Horn Antenna	R & S	HF906	100684	Jun.28,2011
Broadband Antenna	SCHAFFNER	CBL 6112B	2536	Sep.21, 2011
Broadband Antenna	SCHAFFNER	CBL 6112B	2941	Jun.20, 2012
Broadband Antenna	SCHAFFNER	VULB 9163	9163-357	Sep.28,2011
Horn Antenna	ETS-LINDGREN	3160	60008	Sep.20,2011
Horn Antenna	ETS-LINDGREN	3160	91989	Sep.28,2011

6 Transmitter Measurements

6.1 Effective Radiated Power of Transmitter (ERP)

6.1.1 Test Conditions

Table 13 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	25 °C
Relative humidity:	55%
Test Configurations:	TM1/TM2 at frequency Bottom, Middle, Top

6.1.2 Test Specifications and Limits

6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 22.913

6.1.2.2 Supporting Standards

Table 14 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.1.2.3 Limits

Compliance with part 22.913, mobile/portable stations are limited to 7 watts ERP peak power.
 The calculated longitude ERP by following formula: $ERP(dBm) = 10 \cdot \log(ERP_{in\ mwatts})$.

Table 15 Limits

Maximum Output Power (Watts)	< 7 Watts
Maximum Output Power (dBm)	< 38.5 dBm


6.1.3 Test Method and Setup

- (a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, ERP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the air interface. The band class is set as GSM850M.
- (b) Test the Radiated maximum output power by the CMU200 received from test antenna.
- (c) Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step (b) on CMU200, and record the

power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.

Test setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP




Figure 1. Test Set-up

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

BenQ Joy book S72

6.1.4 Measurement Results

6.1.4.1 Pre-test Results

Table 16 Measurement Results

TEST CONDITIONS		RF Output Power (EIRP)					
		Channel512(B) 1850.2MHz		Channel661 (M) 1880MHz		Channel810(T) 1909.8MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	Tnom (25 °C) Vnom (3.7V)	31.62	38.5	31.34	38.5	31.26	38.5
TM2	Tnom (25 °C) Vnom (3.7V)	24.87	38.5	24.70	38.5	24.83	38.5

6.1.4.2 Substitution Results

Table 17 Substitution Results

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substitution Antenna Type	SGP [dBm]	Substitution Gain [dBd]	Cable Loss [dB]	Substitution Level (ERP) [dBm]	Limit [dBm]	Result
TM1	824.2	31.62	Dipole Ant.	35.08	-2.95	0.6	31.53	38.5	Pass
TM1	837	31.34	Dipole Ant	35.03	-3.06	0.6	31.37	38.5	Pass
TM1	848.8	31.26	Dipole Ant	34.92	-3.11	0.6	31.21	38.5	Pass
TM2	824.2	24.87	Dipole Ant	28.32	-2.95	0.6	24.77	38.5	Pass
TM2	837	24.70	Dipole Ant	28.39	-3.06	0.6	24.73	38.5	Pass
TM2	848.8	24.83	Dipole Ant	28.46	-3.11	0.6	24.75	38.5	Pass

Note: a, For get the ERP (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

NOTE: SGP- Signal Generator Level

b, A GSM signal with bandwidth of 200kHz signal with bandwidth of 5MHz is created by the vector generator R&S SMU200A.

c, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 200kHz for TM1 and TM2.

6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.2 Conducted Power of Transmitter

6.2.1 Test Conditions

Table 18 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	52 %
Test Configurations:	TM1/TM2 at frequency Bottom, Middle, Top

6.2.2 Test Specifications and Limits

6.2.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 22 subpart H

6.2.2.2 Supporting Standards

Table 19 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.2.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a mobile station transmitter exceed 7 W. The calculated longitude ERP by following formula:

$$ERP(dBm) = 10 * \log(ERP_{in\ mwatts}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$P_{cod.}(dBm) = ERP(dBm) - Gain(dBd).$$

and $Gain(dBd) = Gain(dBi) - 2.15dB$

Table 20 Limits

Maximum Output Power (Watts)	< 7 Watts(38.5dBm)
Antenna Gain(dBi):	1.40
Antenna Gain(dBd):	-0.75
Maximum Conducted Output Power (dBm)	< 39.25dBm

6.2.3 Test Method and Setup

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the antenna connector. The band class is set as GSM850M.

(b) Test the Conducted maximum output power by the CMU200.

Test setup




Figure 2. Test Set-up

6.2.4 Measurement Results

Table 21 Measurement Results

TEST CONDITIONS		RF Output Power (Conducted)					
		Channel128(B) 824.2MHz		Channel192 (M) 837MHz		Channel251(T) 848.8MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	T _{nom} (25 °C)	32.37	39.25	32.09	39.25	32.01	39.25
	V _{nom} (3.7V)						
TM2	T _{nom} (25 °C)	25.62	39.25	25.45	39.25	25.58	39.25
	V _{nom} (3.7V)						

6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.3 Modulation Characteristics

6.3.1 Test Conditions

Table 22 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	52 %
Test Configurations:	TM1/TM2 at frequency Middle

6.3.2 Test Specifications and Limits

6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 22 subpart H

6.3.2.2 Supporting Standards

Table 23 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 22 subpart H.

Table 24 Limits

Limits	Not applicable
--------	----------------

6.3.3 Test Method and Setup

Connect the EUT to Wireless Communication Test Set R&S CMU200 via the antenna connector. The band class is set as GSM850M; the EUT's output is matched with 50 Ω loads, test method was according to 3GPP TS 51.010. The waveform quality and constellation of the EUT was tested.

Test setup




Figure 3. Test Set-up

6.3.4 Measurement Results

Table 25 Measurement Results

		Modulation Characteristic	
TEST CONDITIONS		Channel192(M) 837MHz	
		Measured	
		TM1	TM2
T_{nom} (25 °C)	V_{nom} (3.7V)	Refer to Appendix A	Refer to Appendix A

6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix A.

6.4 Occupied Bandwidth

6.4.1 Test Conditions

Table 26 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	55 %
Test Configurations:	TM1/TM2 at frequency Bottom, Middle, Top

6.4.2 Test Specifications and Limits

6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and part 22 subpart H.

6.4.2.2 Supporting Standards

Table 27 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.4.2.3 Limits

No specific occupied bandwidth requirement in part 22 subpart H, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 28 Limits

Upper /lower frequency limits	0.5% of the mean power
-------------------------------	------------------------

6.4.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSQ31 via the one RF connector. The band class is set as GSM850M; The EUT was controlled to transmit maximum power. Measure and record the occupied bandwidth of the EUT by the R&S FSQ31.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g) & (h).

(g) Transmitter in which the modulating base band comprises not more than three independent channels - when modulated by the full complement of signals for which the transmitter is rated. The level of modulation for each channel should be set to that prescribed in rule parts applicable to the

services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer’s maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

For TM1/TM2 following RBW and VBW are employed:

Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)

Video bandwidth (VBW): 10 kHz

Test Set-up




Figure 4. Test Set-up

6.4.4 Measurement Results

Table 29 Measurement Results

TEST CONDITIONS		Occupied Bandwidth					
		Channel128 (B) 824.2MHz		Channel192 (M) 837MHz		Channel251 (T) 848.8MHz	
		Measured (kHz)		Measured (kHz)		Measured (kHz)	
		TM1	TM2	TM1	TM2	TM1	TM2
T_{nom} (25 °C)	99%	246.79	245.19	243.59	246.79	241.99	253.21
V_{nom} (3.7V)							

6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix B.

6.5 Band Edges Compliance

6.5.1 Test Conditions

Table 30 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55 %
Test Configurations:	TM1/TM2 at frequency Bottom, Top

6.5.2 Test Specifications and Limits

6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.5.2.2 Supporting Standards

Table 31 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.5.2.3 Limits

Compliance with part 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P(W)$. (Whereas P is the rated power of the EUT in Watt).

Table 32 Limits

	TM1	TM2
Rated Power:	33 dBm	27 dBm
Required attenuation:	$43 + 10 \log(2) = 46$, 33 dBm - 46 dB	$43 + 10 \log(0.5) = 40$, 27 dBm - 40 dB
Absolute level	- 13 dBm	- 13 dBm

6.5.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSQ31 via the one RF connector, the band class is set as GSM850M. The EUT was controlled to transmit maximum power. Measure and record band edges compliance of the EUT by the R&S FSQ31.

The limit is -13dBm.

For TM1/TM2 following RBW and VBW are employed:
Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)
Video bandwidth (VBW): 10 kHz

Test Set-up




Figure 5. Test Set-up

6.5.4 Measurement Results

Table 33 Measurement Results outside Band Edges

Band	Frequency of Band edges [MHz]	Channel Number	Test Mode	Spurious Level measured [dBm]	FCC limit	Result
T_{nom} (25 °C), V_{nom} (3.7V)						
Cellular	824.2	128	TM1	<-13(See appendix C)	- 13 dBm	Pass
	848.8	251	TM1	<-13(See appendix C)	- 13 dBm	Pass
	824.2	128	TM2	<-13(See appendix C)	- 13 dBm	Pass
	848.8	251	TM2	<-13(See appendix C)	- 13 dBm	Pass

6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix C.

6.6 Spurious Emission at Antenna Terminal

6.6.1 Test Conditions

Table 34 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	50 %
Test Configurations:	TM1/TM2 at frequency Bottom, Middle, Top

6.6.2 Test Specifications and Limits

6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.6.2.2 Supporting Standards

Table 35 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.6.2.3 Limits

Compliance with part 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT in Watt).

Table 36 Limits

	TM1	TM2
Rated Power:	33dBm	27 dBm
Required attenuation:	$43 + 10 \log(2) = 46$, 33 dBm - 46 dB	$43 + 10 \log(0.5) = 40$, 27 dBm - 40 dB
Absolute level	- 13 dBm	- 13 dBm

6.6.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSQ31 via the one RF connector, the band class is set as GSM850M. The EUT was controlled to transmit maximum power. Measure and record the Conducted Spurious Emission of the EUT by the R&S FSQ31.

According to part 22.917, the defined measurement bandwidth as following:

22.917 (b) Measurement procedure: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30 MHz up to 1 GHz: 100 kHz;
Measurement bandwidth (RBW) for 1 GHz up to 12.75 GHz: 1 MHz;

Test Set-up




Figure 6. Test Set-up

6.6.4 Measurement Results

Table 37 Measurement Results

Channel Number	Test Mode	Test Range (Frequency)	Output Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
Channel 128(B)	TM1	9 kHz~12.75GHz	33	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM2	9 kHz~12.75GHz	27	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 192(M)	TM1	9 kHz~12.75GHz	33	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM2	9 kHz~12.75GHz	27	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 251(T)	TM1	9 kHz~12.75GHz	33	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM2	9 kHz~12.75GHz	27	<- 13 dBm (See appendix D)	- 13 dBm	Pass

6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix D.

6.7 Radiated Spurious Emissions

6.7.1 Test Conditions

Table 38 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2 at frequency Middle

6.7.2 Test Specifications and Limits

6.7.2.1 Specification

CFR 47 (FCC) part 2.1053 and part 22.917

6.7.2.2 Supporting Standards

Table 39 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0.0:2005	Digital cellular telecommunications system Mobile Station (MS) conformance specification;
3GPP TS 34.121 V8.7.0:2009	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.7.2.3 Limits

Compliance with part 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT).

Table 40 Limits

Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm – 37 dB
Absolute level	- 13 dBm

6.7.3 Test Method and Setup

A test site fulfilling the requirements of ITU-R Recommendation SM329-11 was used. The EUT was placed on a non-conducting support in the anechoic chamber and was operated from a power source via an RF filter to avoid radiation from the power leads.

According to part 22.917, the defined measurement bandwidth as following:

22.917 (b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.


Measurement bandwidth (RBW) for 9 kHz up to 30 MHz: 10 kHz;
 Measurement bandwidth (RBW) for 30MHz up to 1GHz: 100k Hz;
 Measurement bandwidth (RBW) for 1GHz up to 18GHz: 1MHz;

Test Set-up

Step 1:


For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the BTS simulator via the air interface.

Test the Radiated maximum output power by the Test Receiver from test antenna.



Step 2:

Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step1 on Test Receiver, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.





Test should be performed in normal voltage condition.

No peak found in pre- test. All frequency points' margin is bigger than 20dB, so the substitution method isn't used.

Calculation Sample:

Table 41 Substitution Results

Freq. [MHz]	Measurement Value [dBm]	Substitution Antenna Type	Gain [dBd]	Cable Loss [dB]	Signal Generator Level [dBm]	Substitution Level [dBm]	FCC limit [dBm]	Result

Note: For get the E.R.P. (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{E.R.P. [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

NOTE: SGP- Signal Generator Level

6.7.4 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix_E

6.8 Frequency Stability

6.8.1 Test Conditions

Table 42 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	See below
Relative humidity:	55 % at 25 °C
Test Configurations:	TM1/TM2 at frequency Middle

6.8.2 Test Specifications and Limits

6.8.2.1 Specification

CFR 47 (FCC) part 2.1055 and part 22.355

6.8.2.2 Supporting Standards

Table 43 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS51.010 V5.4.0	Digital cellular telecommunications system; Mobile Station (MS) conformance specification;

6.8.2.3 Limits

According to part 22.355, from 821MHz to 896MHz, for mobile device, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances 2.5ppm.

6.8.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30 ° to +50 ° centigrade for all equipment except that specified in subparagraphs
- (2) and (3) of paragraph 2.1055

(a) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(b) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer. Mobile phone can work normally from 3.6V to 4.2V, test below is done according to this limit.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the

equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

(c) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

The EUT can only work in such extreme voltage 3.6V and 4.2V, so here the EUT is tested in the 3.6V and 4.2V.

Test Set up

Connect the EUT to the Wireless Communication test set CMU200 via the connector. Then measure the frequency error by the Wireless Communication test set CMU200. The EUT's output is matched with a 50 Ω load.




Figure 7. Test Set-up

6.8.4 Measurement Results

6.8.4.1 Measurement Results vs. Variation of Temperature

- **TM1, 3.7V DC Channel No.192(837.0MHz)**

Table 44 Measurement Results vs. Variation of Temperature

Temperature	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	33	837.0	16	Pass
-20 °C	33	837.0	-10	Pass
-10 °C	33	837.0	-18	Pass
0 °C	33	837.0	12	Pass
+10 °C	33	837.0	-6	Pass
+20 °C	33	837.0	5	Pass
+30 °C	33	837.0	-11	Pass
+40 °C	33	837.0	-10	Pass
+50 °C	33	837.0	-13	Pass

● **TM2, 3.7V DC Channel No.192(837.0MHz)**

Table 45 Measurement Results vs. Variation of Temperature

Temperature	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	27	837.0	-9	Pass
-20 °C	27	837.0	-11	Pass
-10 °C	27	837.0	14	Pass
0 °C	27	837.0	-8	Pass
+10 °C	27	837.0	17	Pass
+20 °C	27	837.0	-12	Pass
+30 °C	27	837.0	12	Pass
+40 °C	27	837.0	-11	Pass
+50 °C	27	837.0	-17	Pass

6.8.4.2 Measurement Results vs. Variation of Voltage

● **TM1, 25 °C ,Channel No. 192(837.0MHz)**

Table 46 Measurement Results vs. Variation of Voltage

Voltage	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.6	33	837.0	-15	Pass
3.7	33	837.0	-13	Pass
4.2	33	837.0	7	Pass

● **TM2, 25 °C ,Channel No. 192(837.0MHz)**

Table 47 Measurement Results vs. Variation of Voltage

Voltage	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.6	27	837.0	11	Pass
3.7	27	837.0	-9	Pass
4.2	27	837.0	-3	Pass

6.8.5 Conclusion

The equipment **PASSED** the requirement of this clause.



7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 48 System Measurement Uncertainty

Items		Extended Uncertainty
Effective Radiated Power of Transmitter	ERP (dBm)	U=3dB; k=2
Band Width	Magnitude (%)	U=0.2%; k=2
Band Edge Compliance	Disturbance Power(dBm)	U=2.0dB; k=2
Conducted Spurious Emission at Antenna Terminal	Disturbance Power(dBm)	U=2.0dB; k=2
Frequency Stability	Frequency Accuracy(ppm)	U=0.21ppm; k=2
Field Strength of Spurious Radiation	ERP(dBm)	U=2.2dB; k=2



8 Appendices

Appendix A	Measurement Results Modulation Characteristics	3 pages
Appendix B	Measurement Results Occupied Bandwidth	7 Pages
Appendix C	Measurement Results Band Edges	5 Pages
Appendix D	Measurement Results Spurious Emission at Antenna Terminal	25 Pages
Appendix E	Measurement Results Radiated Spurious Emissions	7 Pages
Appendix F	Photos of Radiated Spurious Emissions	4 Pages

(END OF REPORT)




Appendix A

Modulation Characteristics According to FCC Part 2.1047 & Part22 Subpart H




TM1:GPRS/GSM Channel 192





TM2:EDGE Channel 192





Appendix B

Occupied Bandwidth


According to FCC Part 2.1049 & Part 22 Subpart H



TM1:GPRS/GSM Channel 128




Ref 35 dBm Att 35 dB *RBW 3 kHz *VBW 10 kHz SWT 115 ms
 Marker 1 [T1] 6.71 dBm 824.185576923 MHz





TM2:EDGE Channel 128






TM1:GPRS/GSM Channel 192



*RBW 3 kHz Marker 1 [T1] 5.83 dBm
 *VBW 10 kHz
 Ref 35 dBm Att 35 dB SWT 115 ms 837.027243590 MHz






TM2:EDGE Channel 192



*RBW 3 kHz Marker 1 [T1]
 *VBW 10 kHz 20.32 dBm
 Ref 35 dBm Att 35 dB SWT 115 ms 836.951923077 MHz






TM2:EDGE Channel 251



Ref 35 dBm Att 35 dB *RBW 3 kHz *VBW 10 kHz SWT 115 ms

Marker 1 [T1] 18.62 dBm 848.881730769 MHz





Appendix C

Band Edges Compliance According to FCC Part 2.1051 & 22.917




TM1:GPRS/GSM

Left Edge

Channel 128



*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -34.97 dBm
Ref 35 dBm Att 55 dB SWT 225 ms 823.970000000 MHz






Right Edge Channel 251



*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -35.22 dBm
Ref 35 dBm Att 55 dB SWT 225 ms 849.005000000 MHz






TM2:EDGE

Left Edge

Channel 128



*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -26.18 dBm
Ref 35 dBm Att 55 dB SWT 225 ms 823.975000000 MHz






Right Edge Channel 251



Ref 35 dBm Att 55 dB *RBW 3 kHz *VBW 10 kHz SWT 225 ms
Marker 1 [T1] -20.39 dBm
849.005000000 MHz





Appendix D

Spurious Emission at Antenna Terminal


According to FCC Part 2.1051 & 22.917



TM1:GPRS/GSM Channel 128




Ref 35 dBm Att 55 dB *RBW 1 kHz *VBW 10 kHz SWT 145 ms
Marker 1 [T1] -37.87 dBm
9.000000000 kHz






*RBW 10 kHz Marker 1 [T1]
*VBW 30 kHz -33.83 dBm
SWT 300 ms 150.000000000 kHz






*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 13.70 dBm
Ref 35 dBm Att 55 dB SWT 100 ms 825.897435897 MHz





*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -15.37 dBm
SWT 70 ms 2.713541667 GHz






Channel 192




*RBW 1 kHz Marker 1 [T1]
*VBW 10 kHz -37.38 dBm
SWT 145 ms 9.000000000 kHz






* RBW 10 kHz Marker 1 [T1]
* VBW 30 kHz -32.48 dBm
SWT 300 ms 150.000000000 kHz






*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 13.19 dBm
Ref 35 dBm Att 55 dB SWT 100 ms 838.333333333 MHz





*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -16.17 dBm
SWT 70 ms 2.581730769 GHz






Channel 251




Ref 35 dBm Att 55 dB *RBW 1 kHz *VBW 10 kHz SWT 145 ms
Marker 1 [T1] -37.38 dBm
9.451923077 kHz






*RBW 10 kHz Marker 1 [T1]
*VBW 30 kHz -33.04 dBm
SWT 300 ms 150.000000000 kHz





*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 13.26 dBm
SWT 100 ms 849.214743590 MHz






*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -15.21 dBm
SWT 70 ms 2.751201923 GHz

Ref 35 dBm

Att 55 dB



Start 1 GHz

1.175 GHz/

Stop 12.75 GHz




TM2:EDGE Channel 128




Ref 35 dBm Att 55 dB *RBW 1 kHz *VBW 10 kHz SWT 145 ms

Marker 1 [T1] -37.19 dBm
10.129807692 kHz






*RBW 10 kHz Marker 1 [T1]
*VBW 30 kHz -33.22 dBm
SWT 300 ms 197.836538462 kHz





*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 27.20 dBm
SWT 100 ms 825.897435897 MHz






*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -14.96 dBm
SWT 70 ms 2.883012821 GHz

Ref 35 dBm

Att 55 dB



Start 1 GHz

1.175 GHz/


Stop 12.75 GHz



Channel 192




*RBW 1 kHz Marker 1 [T1]
*VBW 10 kHz -35.89 dBm
SWT 145 ms 10.581730769 kHz






*RBW 10 kHz Marker 1 [T1]
*VBW 30 kHz -31.51 dBm
Ref 35 dBm Att 55 dB SWT 300 ms 197.836538462 kHz





*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 28.07 dBm
Ref 35 dBm Att 55 dB SWT 100 ms 838.333333333 MHz






*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -15.66 dBm
SWT 70 ms 2.657051282 GHz

Ref 35 dBm

Att 55 dB



Start 1 GHz

1.175 GHz/

Stop 12.75 GHz




Channel 251



*RBW 1 kHz Marker 1 [T1]
*VBW 10 kHz -36.92 dBm
SWT 145 ms 10.129807692 kHz


Ref 35 dBm

Att 55 dB






*RBW 10 kHz Marker 1 [T1]
*VBW 30 kHz -31.95 dBm
SWT 300 ms 197.836538462 kHz






*RBW 100 kHz Marker 1 [T1]
*VBW 300 kHz 29.08 dBm
SWT 100 ms 849.214743590 MHz





*RBW 1 MHz Marker 1 [T1]
*VBW 3 MHz -15.56 dBm
SWT 70 ms 2.826522436 GHz





Appendix E


Radiated spurious emission

According to FCC Part 2.1053& Part 22.917




GPRS 850

(9kHz~30MHz)






(30MHz~2GHz)






(2GHz~18GHz)






EDGE 850

(9kHz~30MHz)






(30MHz~2GHz)





(2GHz~18GHz)





Appendix F

Photos of Radiated Spurious Emissions




Photos of Test Setup



1 Radiated Spurious Emissions



Radiated Spurious Emission (below 2GHz)



Radiated Spurious Emission (2GHz to18GHz)