



FCC RF Test Report

Product Name: Mobile WiFi

Model Number: E589u-512


**Report No: SYBH(Z-RF)011072012-2003
FCC ID: QISE589u-512**

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China
Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Operated By	<u>Jul., 18, 2012</u>	<u>Huang Qiuliang</u>	<u>Huang Qiuliang</u>
	Date	Name	Signature

Contents

1	<u>General Information</u>	5
1.1	APPLIED STANDARD	5
1.2	TEST LOCATION	5
1.3	TEST ENVIRONMENTAL CONDITION	5
2	<u>Summary</u>	6
3	<u>Product Description</u>	7
3.1	PRODUCT INFORMATION	7
4	<u>Test Description</u>	8
4.1	SUPPORTED FREQUENCY RANGE	8
4.2	TRANSMITTER / RECEIVER CHARACTERISTICS	8
4.3	ANTENNA GAIN	8
5	<u>General Test Conditions / Configurations</u>	9
5.1	RF CHANNELS UNDER TEST	9
5.2	TEST MODES	9
5.3	TEST ENVIRONMENT	10
5.4	TEST SETUP	11
5.5	TEST CONDITIONS	15
6	<u>Main Test Instruments</u>	16
7	<u>Test Results</u>	17
8	<u>Measurement Uncertainty</u>	17

General Information

1.1 Applied Standard	
Applied Rules:	47 CFR FCC Part 2:2011, Subpart J 47 CFR FCC Part 27:2011, Subpart C&L ANSI/TIA 603C:2004 KDB 971168 D01 Power Meas License Digital Systems v01
1.2 Test Location	
Test Location 1:	Reliability Laboratory of Huawei Technologies Co., Ltd.
Address:	Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China
1.3 Test Environmental Condition	
Ambient Temperature:	20 – 25 °C
Ambient Relative Humidity:	45 – 55 %
Atmospheric Pressure:	101 kPa

1 Summary

Table 1 Summary of Band 4 results

Test Case	FCC Part No.	Requirements	Result
Band 4			
Transmitter Output Power	2.1046 & 27.50(d)	Peak EIRP not exceed 1 W Peak-to-average ratio not exceed 13 dB	Pass
Modulation Characteristics	2.1047	Digital modulation	Pass
Occupied Bandwidth	2.1049	(Not specified)	Pass
Band Edges Compliance	2.1051 & 27.53(h)	Below -13 dBm/1%*EBW, in 1 MHz range	Pass
Spurious Emission at Antenna Terminals	2.1051 & 27.53(h)	Below -13 dBm/1 kHz, 9 kHz to 150 kHz Below -13 dBm/10 kHz, 150 kHz to 30 MHz Below -13 dBm/1 MHz, 30 MHz to 10 th harmonics	Pass
Field Strength of Spurious Radiation	2.1053 & 27.53(h)	Below -13 dBm/1 MHz	Pass
Frequency Stability	2.1055 & 27.54	Stay within the authorized bands of operation	Pass

2 Product Description

2.1 Product Information

2.1.1 General Description

E589u-512 is a LTE/UMTS/GSM triple mode and WiFi Wireless mobile Router; it can be used as a WiFi Access Point based on standard of IEEE802.11b/g/n. It supports 3G WCDMA and 4G LTE wireless internet accessing function. About 3G WCDMA wireless mode, it supports WCDMA and HSDPA/HSUPA/HSPA+/DC-HSPA+, operating in Band2 and Band 5, and the 4G LTE, operating in Band2, Band4 and Band7. The WiFi frequency is 2.4GHz.

E589u-512 supports 1Tx2Rx for 3G WCDMA and 4G LTE, WiFi only supports 1Tx1Rx.

2.1.2 Board Information

Table 2 Board Information

Mobile WiFi		
E589u-512		
Board		
Hardware Version	Hardware Version	Hardware Version
CL1E589M22	CL1E589M22	CL1E589M22

2.1.3 Adapter Technical Data

AC/DCAdapter Model	HW-050200U3W
Manufacturer	HUAWEI
Input Voltage	100-240V1 ~50/60Hz, 0.5A MAX
Output Voltage	== 5.0V 2.0A

2.1.4 Battery Technical Data

Name	Qty.	Manufacture	Description
Li-ion Battery	1	HUAWEI	Battery Model: HB5P1H Rated capacity: 3000mAh Nominal Voltage: == +3.7V Charging Voltage: == +4.2V

3 Test Description

3.1 Supported Frequency Range

Characteristics	Description
Downlink	2110 to 2155 MHz;
Uplink	1710 to 1755 MHz;

3.2 Transmitter / Receiver Characteristics

Characteristics	Description
System Type	LTE
TX Output Power (per Antenna Port)	LTE system: 23dBm
Channel Spacing(s) / Bandwidth(s)	LTE system: 5 MHz, 10 MHz, 15 MHz, 20 MHz
Designation of Emissions	LTE system: 4M53G7D (5 MHz ,QPSK modulation), 4M54W7D (5 MHz ,16QAM modulation), 8M95G7D (10 MHz QPSK modulation), 8M92W7D (10 MHz 16QAM modulation), 13M4G7D (15MHz QPSK modulation), 13M4W7D (15MHz 16QAM modulation), 17M9G7D (20 MHz QPSK modulation), 17M9W7D (20 MHz 16QAM modulation),

3.3 Antenna Gain

Rated Antenna Gain(dBi) to LTE Band 4	3.64
---------------------------------------	------

4 General Test Conditions / Configurations

4.1 RF Channels under Test

Test Mode	TX / RX	RF Channel		
		Low (L)	Middle (M)	High (H)
LTE Band 4	TX (5M)	Channel 19975	Channel 20175	Channel 20375
		1712.5 MHz	1732.5 MHz	1752.5 MHz
	TX (10M)	Channel 20000	Channel 20175	Channel 20350
		1715.0 MHz	1732.5 MHz	1750.0 MHz
	TX (15M)	Channel 20025	Channel 20175	Channel 20325
		1717.5 MHz	1732.5 MHz	1747.5 MHz
	TX (20M)	Channel 20050	Channel 20175	Channel 20300
		1720 MHz	1732.5 MHz	1745 MHz
	RX (5M)	Channel 1975	Channel 2175	Channel 2375
		2112.5 MHz	2132.5 MHz	2152.5 MHz
	RX (10M)	Channel 2000	Channel 2175	Channel 2350
		2115.0 MHz	2132.5 MHz	2150.0 MHz
	RX (15M)	Channel 2025	Channel 2175	Channel 2325
		2117.5 MHz	2132.5 MHz	2147.5 MHz
	RX (20M)	Channel 2050	Channel 2175	Channel 2300
		2120 MHz	2132.5 MHz	2145 MHz

4.2 Test Modes

Test Mode	Test Modes Description
TM6	LTE QPSK modulation
TM7	LTE 16QAM modulation



4.3 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.6V
	VN	3.7V
	VH	4.2V


NOTE: VL= lower extreme test voltage
VN= nominal voltage
VH= upper extreme test voltage
TN= normal temperature

4.4 Test Setup

4.4.1 General Test Setup Configurations

Configuration	Description
Test Antenna Ports	Until otherwise declared, all TX tests are ONLY performed at the main Transmitter antenna port (e.g. TRXA, TXA and so on) of the EUT, and all RX tests are ONLY performed at the main Receiver antenna port (e.g. TRXA, RXA and so on) of the EUT.
Multiple RF Sources	Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements.


4.4.2 Test Setup 1



Note

A peak to average ratio measurement is performed at the conducted port of the EUT. For LTE signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

4.4.3 Test Setup 2



4.4.4 Test Setup 3

NOTE1: Effective radiated power (ERP) or Effective Isotropic radiated power (EIRP) refers to the EUT radiation power output, assuming all emissions are radiated from half-wave dipole antennas or horn antennas.

NOTE2: The EUT was set on insulator 80cm above the Ground Plane. The setup and test methods were according to ANSI-TIA-603C 2004. The measurements were carried through with a Rohde and Schwarz Test Receiver and control software.


Step 1: Pre-test to find the Maximum ERP or EIRP

1. Connect the test system according to the following figure. EUT is running for 30 minutes before test, and measurement instruments are warming-up for 30 minutes.
2. Set up communication link between Universal radio communication tester and EUT, set EUT working frequency, and control EUT to transmit at maximum power.
3. Set the center frequency of the signal analyzer or receiver to the EUT's operating frequency, the RBW is equal to the emission bandwidth of the signal. Set RMS detector for the test, and the span is

equal to 2 times of emission bandwidth, the other settings should remain automatic. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°. The receiver antenna has two polarizations V and H. A portable or small unlicensed wireless device shall be placed on a non-metallic test fixture or other non-metallic support during testing. The supporting fixture shall permit orientation of the EUT in each of three orthogonal (x, y, z) axis positions such that emissions from the EUT are maximized. Measure the EUT maximum RF power and record the result.


4. Changing EUT working frequency and measuring the RF power at channel L, M, H respectively.

Complete the test data.



Step 2: Substitution method to verify the maximum ERP or EIRP

1. Measurement setup is according to the following figure. EUT was substituted by antenna, and the polarization is identical with the test antenna; the signal generator was connected to the substitution antenna.
2. The radiated output power, measured by signal analyzer set, is the same as recorded in above. Then this power level is matched by a signal from a calibrated signal generator which is substituted for EUT. The power supplied by the generator is then equal to the ERP or EIRP after corrected by the antenna gain and cable loss.



4.5 Test Conditions

Test Case	Test Conditions	
Transmitter Output Power	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1 & Test Setup 3
	Detector	RMS
	RF Channels (TX)	L, M, H
	Test Mode	TM6/TM7
Modulation Characteristics	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	RF Channels (TX)	M
	Test Mode	TM6/TM7
Occupied Bandwidth	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	L, M, H
	Test Mode	TM6/TM7
Band Edges Compliance	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	RMS
	RF Channels (TX)	L, H
	Test Mode	TM6/TM7
Spurious Emission at Antenna Terminals	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 1
	Detector	PK
	RF Channels (TX)	L, M, H
	Test Mode	TM6
Field Strength of Spurious Radiation	Test Configuration	Ambient Temperature & Rated Voltage
	Test Setup	Test Setup 3
	Detector	PK
	RF Channels (TX)	M
	Test Mode	TM6
Frequency Stability	Test Configuration	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) VL, VH and VN Voltage at Ambient Temperature.
	Test Setup	Test Setup 2
	RF Channels (TX)	M
	Test Mode	TM6

5 Main Test Instruments

Table 3 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until
Power supply	KEITHLEY	2303	1288003	Sep.27,2012
Universal Radio Communication Tester	R&S	CMU200	117341	Jan.12.2013
Universal Radio Communication Tester	Agilent	E5515C	MY50260239	Aug.31,2012
Spectrum Analyzer	Agilent	E4440A	MY49420179	Jul.17,2012
Signal Analyzer	R&S	FSQ31	200021	Sep.27,2012
Temperature Chamber	WEISS	WKL64	24600294	Feb.13,2013
Signal generator	Agilent	E8257D	MY49281095	Jul.08.2013
Spectrum analyzer	R&S	FSU3	200474	Mar., 05, 2013
Spectrum analyzer	R&S	FSU43	100144	Mar., 05, 2013
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100304	Apr., 05, 2013
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100391	Apr., 05, 2013
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-521	Jul., 07, 2013
Pyramidal Horn Antenna(26GHz-40GHz)	ETS-Lindgren	3160-10	00123940	Feb., 27, 2013
Pyramidal Horn Antenna(18GHz-26.5GHz)	ETS-Lindgren	3160-09	00125912	Feb.,27, 2013
Universal Radio Communication Tester	R & S	CMW500	20347676	Sept., 07, 2012
Universal Radio Communication Tester	Anritsu	MT8820C	6200971028	May., 04, 2013

6 Test Results

No.	Test Item	Test Result
1	Transmitter Output Power	Appendix A
2	Modulation Characteristics	Appendix B
3	Occupied Bandwidth	Appendix C
4	Band Edges Compliance	Appendix D
5	Spurious Emission at Antenna Terminals	Appendix E
6	Field Strength of Spurious Radiation	Appendix F
7	Frequency Stability	Appendix G
8	Photos of Test Setup	Appendix H

NOTE: There is no test data in Appendix H, only Photos of Test Setup for Field Strength of Spurious Radiation.

7 Measurement Uncertainty

For a 95% confidence level ($k=2$), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Transmitter Output Power	Power (dBm)	$U = 0.39$ dB
Occupied Bandwidth	Magnitude (%)	$U = 0.2\%$
Band Edge Compliance	Disturbance Power (dBm)	$U = 2.0$ dB
Conducted Spurious Emissions	Disturbance Power (dBm)	$U = 2.0$ dB
Field Strength of Spurious Radiation	ERP (dBm)	$U = 4.6$ dB (30 MHz – 1GHz) $U = 3.0$ dB (above 1 GHz)
Frequency Stability	Frequency Accuracy (ppm)	$U = 0.21$ ppm

-----The END-----



Appendix A

Transmitter Output Power

According to FCC Part 2.1046 & Part 27 Subpart C&L



Conducted Power of Transmitter

Table 1 Measurement Results (LTE) BAND 4

TM6 & TM7 RF Output Power(Conducted) BAND 4			
Test Mode	TN/VN		
	Modulation	RB	Measured (dBm)
Channel (L) 5MHz(BW)	QPSK	1RB#0	22.21
		1RB#max	22.31
		12RB#6	21.18
		Full	21.19
	16QAM	1RB#0	21.38
		1RB#max	21.45
		12RB#6	20.09
		Full	20.16
Channel (L) 10MHz(BW)	QPSK	1RB#0	21.99
		1RB#max	22.25
		25RB#13	21.17
		Full	21.21
	16QAM	1RB#0	20.79
		1RB#max	20.94
		25RB#13	20.29
		Full	20.19
Channel (L) 15MHz(BW)	QPSK	1RB#0	22.26
		1RB#max	22.43
		36RB#18	21.19
		Full	21.17
	16QAM	1RB#0	21.16
		1RB#max	21.25
		36RB#18	20.16
		Full	20.32



Channel (L) 20MHz(BW)	QPSK	1RB#0	22.15
		1RB#max	22.31
		50RB#25	21.32
		Full	21.34
	16QAM	1RB#0	21.29
		1RB#max	21.51
		50RB#25	20.29
		Full	20.47
Channel (M) 5MHz(BW)	QPSK	1RB#0	22.4
		1RB#max	22.43
		12RB#6	21.22
		Full	21.24
	16QAM	1RB#0	21.17
		1RB#max	21.08
		12RB#6	20.05
		Full	20.39
Channel (M) 10MHz(BW)	QPSK	1RB#0	22.35
		1RB#max	22.16
		25RB#13	21.27
		Full	21.26
	16QAM	1RB#0	21.64
		1RB#max	21.55
		25RB#13	20.41
		Full	20.26
Channel (M) 15MHz(BW)	QPSK	1RB#0	22.31
		1RB#max	22.21
		36RB#18	21.3
		Full	21.23
	16QAM	1RB#0	21.65
		1RB#max	21.58



		36RB#18	20.28
		Full	20.32
Channel (M) 20MHz(BW)	QPSK	1RB#0	22.47
		1RB#max	22.13
		50RB#25	21.24
		Full	21.25
	16QAM	1RB#0	21.55
		1RB#max	21.32
		50RB#25	20.18
		Full	20.29
Channel (H) 5MHz(BW)	QPSK	1RB#0	22.16
		1RB#max	21.98
		12RB#6	20.91
		Full	20.9
	16QAM	1RB#0	21.35
		1RB#max	21.11
		12RB#6	20.07
		Full	20.01
Channel (H) 10MHz(BW)	QPSK	1RB#0	21.79
		1RB#max	21.6
		25RB#13	21.07
		Full	21.01
	16QAM	1RB#0	20.89
		1RB#max	20.67
		25RB#13	20.04
		Full	20.01
Channel (H) 15MHz(BW)	QPSK	1RB#0	22.25
		1RB#max	21.92
		36RB#18	21.05
		Full	21.01



	16QAM	1RB#0	21.21
		1RB#max	20.97
		36RB#18	20.07
		Full	19.99
Channel (H) 20MHz(BW)	QPSK	1RB#0	22.27
		1RB#max	21.83
		50RB#25	21.12
		Full	21.1
	16QAM	1RB#0	21.68
		1RB#max	21.22
		50RB#25	20.24
		Full	20.15



Peak-to-Average Ratio

Table 2 Measurement Results (LTE) BAND 4

Peak-to-Average Ratio				
Test Mode	TN/VN			
	Modulation	RB	Measured (dB)	Limit (dB)
Channel (L) 5MHz(BW)	QPSK	1RB#0	5.60	13
		1RB#max	5.62	13
		12RB#6	5.61	13
		Full	5.65	13
	16QAM	1RB#0	6.45	13
		1RB#max	6.43	13
		12RB#6	6.42	13
		Full	6.50	13
Channel (L) 10MHz(BW)	QPSK	1RB#0	5.42	13
		1RB#max	5.41	13
		25RB#13	5.40	13
		Full	5.43	13
	16QAM	1RB#0	6.32	13
		1RB#max	6.30	13
		25RB#13	6.31	13
		Full	6.34	13
Channel (L) 15MHz(BW)	QPSK	1RB#0	5.82	13
		1RB#max	5.84	13
		36RB#18	5.83	13
		Full	5.88	13
	16QAM	1RB#0	6.28	13
		1RB#max	6.27	13
		36RB#18	6.30	13
		Full	6.31	13
Channel (L) 20MHz(BW)	QPSK	1RB#0	5.59	13
		1RB#max	5.58	13
		50RB#25	5.61	13
		Full	5.63	13
	16QAM	1RB#0	6.34	13
		1RB#max	6.31	13



		50RB#25	6.34	13
		Full	6.36	13
Channel (M) 5MHz(BW)	QPSK	1RB#0	5.61	13
		1RB#max	5.63	13
		12RB#6	5.66	13
		Full	5.67	13
	16QAM	1RB#0	6.49	13
		1RB#max	6.46	13
		12RB#6	6.43	13
		Full	6.51	13
Channel (M) 10MHz(BW)	QPSK	1RB#0	5.41	13
		1RB#max	5.44	13
		25RB#13	5.41	13
		Full	5.45	13
	16QAM	1RB#0	6.33	13
		1RB#max	6.31	13
		25RB#13	6.30	13
		Full	6.35	13
Channel (M) 15MHz(BW)	QPSK	1RB#0	5.88	13
		1RB#max	5.86	13
		36RB#18	5.79	13
		Full	5.90	13
	16QAM	1RB#0	6.34	13
		1RB#max	6.29	13
		36RB#18	6.30	13
		Full	6.35	13
Channel (M) 20MHz(BW)	QPSK	1RB#0	5.61	13
		1RB#max	5.57	13
		50RB#25	5.62	13
		Full	5.67	13
	16QAM	1RB#0	6.34	13
		1RB#max	6.33	13
		50RB#25	6.36	13
		Full	6.38	13
Channel (H) 5MHz(BW)	QPSK	1RB#0	5.62	13
		1RB#max	5.62	13
		12RB#6	5.61	13
		Full	5.64	13

	16QAM	1RB#0	6.42	13
		1RB#max	6.47	13
		12RB#6	6.41	13
		Full	6.48	13
Channel (H) 10MHz(BW)	QPSK	1RB#0	5.41	13
		1RB#max	5.42	13
		25RB#13	5.40	13
		Full	5.43	13
	16QAM	1RB#0	6.34	13
		1RB#max	6.36	13
		25RB#13	6.31	13
		Full	6.36	13
Channel (H) 15MHz(BW)	QPSK	1RB#0	5.81	13
		1RB#max	5.83	13
		36RB#18	5.78	13
		Full	5.87	13
	16QAM	1RB#0	6.30	13
		1RB#max	6.28	13
		36RB#18	6.27	13
		Full	6.31	13
Channel (H) 20MHz(BW)	QPSK	1RB#0	5.63	13
		1RB#max	5.57	13
		50RB#25	5.61	13
		Full	5.64	13
	16QAM	1RB#0	6.31	13
		1RB#max	6.33	13
		50RB#25	6.32	13
		Full	6.35	13

Effective Isotropic Radiated Power of Transmitter (EIRP)

Table 3 Substitution Results (LTE) BAND 4

Test Mode			Meas. Level [dBm]	Substitution Antenna Type	SGP[dBm]	Substitution Gain [dBi]	Cable Loss [dB]	Substitution Level (EIRP) [dBm]	FCC limit [dBm]	Result
Channel	Modulation	RB								
Channel (L) 5MHz(BW)	QPSK	1 RB/#0	25.85	Horn Ant.	22.26	4.5	1	25.76	30	Pass
		1 RB/#max	25.95	Horn Ant.	22.33	4.5	1	25.83	30	Pass
		12 RB/#6	24.82	Horn Ant.	21.27	4.5	1	24.77	30	Pass
		Full	24.83	Horn Ant.	21.29	4.5	1	24.79	30	Pass
	16QAM	1 RB/#0	25.02	Horn Ant.	21.51	4.5	1	25.01	30	Pass
		1 RB/#max	25.09	Horn Ant.	21.56	4.5	1	25.06	30	Pass
		12 RB/#6	23.73	Horn Ant.	20.18	4.5	1	23.68	30	Pass
		Full	23.80	Horn Ant.	20.26	4.5	1	23.76	30	Pass
Channel (L) 10MHz(BW)	QPSK	1 RB/#0	25.63	Horn Ant.	22.09	4.5	1	25.59	30	Pass
		1 RB/#max	25.89	Horn Ant.	22.29	4.5	1	25.79	30	Pass
		25 RB/#13	24.81	Horn Ant.	21.27	4.5	1	24.77	30	Pass
		Full	24.85	Horn Ant.	21.26	4.5	1	24.76	30	Pass
	16QAM	1 RB/#0	24.43	Horn Ant.	20.85	4.5	1	24.35	30	Pass
		1 RB/#max	24.58	Horn Ant.	20.96	4.5	1	24.46	30	Pass



		25 RB/#13	23.93	Horn Ant.	20.35	4.5	1	23.85	30	Pass
		Full	23.83	Horn Ant.	20.29	4.5	1	23.79	30	Pass
Channel (L) 15MHz(BW)	QPSK	1 RB/#0	25.90	Horn Ant.	22.38	4.5	1	25.88	30	Pass
		1 RB/#max	26.07	Horn Ant.	22.53	4.5	1	26.03	30	Pass
		36 RB/#18	24.83	Horn Ant.	21.28	4.5	1	24.78	30	Pass
		Full	24.81	Horn Ant.	21.29	4.5	1	24.79	30	Pass
	16QAM	1 RB/#0	24.80	Horn Ant.	21.19	4.5	1	24.69	30	Pass
		1 RB/#max	24.89	Horn Ant.	21.26	4.5	1	24.76	30	Pass
		36 RB/#18	23.80	Horn Ant.	20.27	4.5	1	23.77	30	Pass
		Full	23.96	Horn Ant.	20.35	4.5	1	23.85	30	Pass
Channel (L) 20MHz(BW)	QPSK	1 RB/#0	25.79	Horn Ant.	22.15	4.5	1	25.65	30	Pass
		1 RB/#max	25.95	Horn Ant.	22.34	4.5	1	25.84	30	Pass
		50 RB/#25	24.96	Horn Ant.	21.41	4.5	1	24.91	30	Pass
		Full	24.98	Horn Ant.	21.35	4.5	1	24.85	30	Pass
	16QAM	1 RB/#0	24.93	Horn Ant.	21.45	4.5	1	24.95	30	Pass
		1 RB/#max	25.15	Horn Ant.	21.62	4.5	1	25.12	30	Pass
		50 RB/#25	23.93	Horn Ant.	20.42	4.5	1	23.92	30	Pass
		Full	24.11	Horn Ant.	20.65	4.5	1	24.15	30	Pass
Channel (M)	QPSK	1 RB/#0	26.04	Horn Ant.	22.52	4.5	1	26.02	30	Pass



5MHz(BW)		1 RB/#max	26.07	Horn Ant.	22.53	4.5	1	26.03	30	Pass
		12 RB/#6	24.86	Horn Ant.	21.29	4.5	1	24.79	30	Pass
		Full	24.88	Horn Ant.	21.27	4.5	1	24.77	30	Pass
	16QAM	1 RB/#0	24.81	Horn Ant.	21.19	4.5	1	24.69	30	Pass
		1 RB/#max	24.72	Horn Ant.	21.21	4.5	1	24.71	30	Pass
		12 RB/#6	23.69	Horn Ant.	20.05	4.5	1	23.55	30	Pass
		Full	24.03	Horn Ant.	20.5	4.5	1	24.00	30	Pass
Channel (M) 10MHz(BW)	QPSK	1 RB/#0	25.99	Horn Ant.	22.39	4.5	1	25.89	30	Pass
		1 RB/#max	25.80	Horn Ant.	22.23	4.5	1	25.73	30	Pass
		25 RB/#13	24.91	Horn Ant.	21.28	4.5	1	24.78	30	Pass
		Full	24.90	Horn Ant.	21.31	4.5	1	24.81	30	Pass
	16QAM	1 RB/#0	25.28	Horn Ant.	21.66	4.5	1	25.16	30	Pass
		1 RB/#max	25.19	Horn Ant.	21.67	4.5	1	25.17	30	Pass
		25 RB/#13	24.05	Horn Ant.	20.52	4.5	1	24.02	30	Pass
		Full	23.90	Horn Ant.	20.31	4.5	1	23.81	30	Pass
Channel (M) 15MHz(BW)	QPSK	1 RB/#0	25.95	Horn Ant.	22.39	4.5	1	25.89	30	Pass
		1 RB/#max	25.85	Horn Ant.	22.29	4.5	1	25.79	30	Pass
		36 RB/#18	24.94	Horn Ant.	22.32	4.5	1	25.82	30	Pass
		Full	24.87	Horn Ant.	21.29	4.5	1	24.79	30	Pass



	16QAM	1 RB/#0	25.29	Horn Ant.	21.66	4.5	1	25.16	30	Pass
		1 RB/#max	25.22	Horn Ant.	21.71	4.5	1	25.21	30	Pass
		36 RB/#18	23.92	Horn Ant.	20.34	4.5	1	23.84	30	Pass
		Full	23.96	Horn Ant.	20.45	4.5	1	23.95	30	Pass
Channel (M) 20MHz(BW)	QPSK	1 RB/#0	26.11	Horn Ant.	22.58	4.5	1	26.08	30	Pass
		1 RB/#max	25.77	Horn Ant.	22.14	4.5	1	25.64	30	Pass
		50 RB/#25	24.88	Horn Ant.	21.29	4.5	1	24.79	30	Pass
		Full	24.89	Horn Ant.	21.26	4.5	1	24.76	30	Pass
	16QAM	1 RB/#0	25.19	Horn Ant.	21.66	4.5	1	25.16	30	Pass
		1 RB/#max	24.96	Horn Ant.	21.31	4.5	1	24.81	30	Pass
		50 RB/#25	23.82	Horn Ant.	20.25	4.5	1	23.75	30	Pass
		Full	23.93	Horn Ant.	20.32	4.5	1	23.82	30	Pass
Channel (H) 5MHz(BW)	QPSK	1 RB/#0	25.80	Horn Ant.	21.96	4.8	1	25.76	30	Pass
		1 RB/#max	25.62	Horn Ant.	21.79	4.8	1	25.59	30	Pass
		12 RB/#6	24.55	Horn Ant.	20.69	4.8	1	24.49	30	Pass
		Full	24.54	Horn Ant.	20.59	4.8	1	24.39	30	Pass
	16QAM	1 RB/#0	24.99	Horn Ant.	21.04	4.8	1	24.84	30	Pass
		1 RB/#max	24.75	Horn Ant.	20.89	4.8	1	24.69	30	Pass
		12 RB/#6	23.71	Horn Ant.	19.78	4.8	1	23.58	30	Pass



		Full	23.65	Horn Ant.	19.79	4.8	1	23.59	30	Pass
Channel (H) 10MHz(BW)	QPSK	1 RB/#0	25.43	Horn Ant.	21.59	4.8	1	25.39	30	Pass
		1 RB/#max	25.24	Horn Ant.	21.35	4.8	1	25.15	30	Pass
		25 RB/#13	24.71	Horn Ant.	20.86	4.8	1	24.66	30	Pass
		Full	24.65	Horn Ant.	20.71	4.8	1	24.51	30	Pass
	16QAM	1 RB/#0	24.53	Horn Ant.	20.59	4.8	1	24.39	30	Pass
		1 RB/#max	24.31	Horn Ant.	20.53	4.8	1	24.33	30	Pass
		25 RB/#13	23.68	Horn Ant.	19.74	4.8	1	23.54	30	Pass
		Full	23.65	Horn Ant.	19.75	4.8	1	23.55	30	Pass
Channel (H) 15MHz(BW)	QPSK	1 RB/#0	25.89	Horn Ant.	22.05	4.8	1	25.85	30	Pass
		1 RB/#max	25.56	Horn Ant.	21.71	4.8	1	25.51	30	Pass
		36 RB/#18	24.69	Horn Ant.	20.79	4.8	1	24.59	30	Pass
		Full	24.65	Horn Ant.	20.76	4.8	1	24.56	30	Pass
	16QAM	1 RB/#0	24.85	Horn Ant.	20.91	4.8	1	24.71	30	Pass
		1 RB/#max	24.61	Horn Ant.	20.73	4.8	1	24.53	30	Pass
		36 RB/#18	23.71	Horn Ant.	19.83	4.8	1	23.63	30	Pass
		Full	23.63	Horn Ant.	19.78	4.8	1	23.58	30	Pass
Channel (H) 20MHz(BW)	QPSK	1 RB/#0	25.91	Horn Ant.	22.08	4.8	1	25.88	30	Pass
		1 RB/#max	25.47	Horn Ant.	21.56	4.8	1	25.36	30	Pass



		50 RB/#25	24.76	Horn Ant.	20.93	4.8	1	24.73	30	Pass
		Full	24.74	Horn Ant.	20.88	4.8	1	24.68	30	Pass
	16QA M	1 RB/#0	25.32	Horn Ant.	21.48	4.8	1	25.28	30	Pass
		1 RB/#max	24.86	Horn Ant.	21.02	4.8	1	24.82	30	Pass
		50 RB/#25	23.88	Horn Ant.	20.01	4.8	1	23.81	30	Pass
		Full	23.79	Horn Ant.	19.94	4.8	1	23.74	30	Pass

Note: a, For getting the EIRP (Efficient Isotropic Radiated Power) in substitution method, the following formula should be taken to calculate it,

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

b, SGP=Signal Generator Level

-----END-----




Appendix B


Modulation Characteristics

According to FCC Part 2.1047& Part 27 Subpart C&L


Test Mode = TM6
Channel Bandwidth = Lowest (5 MHz)
Channel = M
QPSK/full RBs




Channel Bandwidth = 10 MHz
Channel = M
QPSK/full RBs




Channel Bandwidth = 15 MHz
Channel = M
QPSK/full RBs




Channel Bandwidth = Highest (20 MHz)
Channel = M
QPSK/full RBs




Test Mode = TM7
Channel Bandwidth = Lowest (5 MHz)
Channel = M
16QAM/full RBs




Channel Bandwidth = 10 MHz
Channel = M
16QAM/full RBs



Channel Bandwidth = 15 MHz
Channel = M
16QAM/full RBs



Channel Bandwidth = Highest (20 MHz)
Channel = M
16QAM/full RBs



END



Appendix C

Occupied Bandwidth

According to FCC part 2.1049 & Part 27 Subpart C&L



TABLE OF CONTENTS

TABLE OF CONTENTS	2
TABLE 1 MEASUREMENT RESULTS (LTE) BAND 4	4
1 FOR BAND 4	5
1.1 TEST MODE=TM6	5
1.1.1 Channel Bandwidth = Lowest (5 MHz)	5
1.1.1.1 Channel = B	5
1.1.1.1.1 QPSK/full RBs	5
1.1.1.2 Channel =M	6
1.1.1.2.1 QPSK/full RBs	6
1.1.1.3 Channel =T	7
1.1.1.3.1 QPSK/full RBs	7
1.1.2 Channel Bandwidth = 10 MHz	8
1.1.2.1 Channel = B	8
1.1.2.1.1 QPSK/full RBs	8
1.1.2.2 Channel =M	9
1.1.2.2.1 QPSK/full RBs	9
1.1.2.3 Channel =T	10
1.1.2.3.1 QPSK/full RBs	10
1.1.3 Channel Bandwidth = 15 MHz	11
1.1.3.1 Channel = B	11
1.1.3.1.1 QPSK/full RBs	11
1.1.3.2 Channel =M	12
1.1.3.2.1 QPSK/full RBs	12
1.1.3.3 Channel =T	13
1.1.3.3.1 QPSK/full RBs	13
1.1.4 Channel Bandwidth = Highest (20 MHz)	14
1.1.4.1 Channel = B	14
1.1.4.1.1 QPSK/full RBs	14
1.1.4.2 Channel =M	15
1.1.4.2.1 QPSK/full RBs	15
1.1.4.3 Channel =T	16
1.1.4.3.1 QPSK/full RBs	16
1.2 TEST MODE=TM7	17
1.2.1 Channel Bandwidth = Lowest (5 MHz)	17
1.2.1.1 Channel = B	17
1.2.1.1.1 16QAM /full RBs	17
1.2.1.2 Channel =M	18
1.2.1.2.1 16QAM /full RBs	18
1.2.1.3 Channel =T	19
1.2.1.3.1 16QAM /full RBs	19
1.2.2 Channel Bandwidth = 10 MHz	20
1.2.2.1 Channel = B	20
1.2.2.1.1 16QAM /full RBs	20
1.2.2.2 Channel =M	21
1.2.2.2.1 16QAM /full RBs	21
1.2.2.3 Channel =T	22
1.2.2.3.1 16QAM /full RBs	22
1.2.3 Channel Bandwidth = 15 MHz	23
1.2.3.1 Channel = B	23
1.2.3.1.1 16QAM /full RBs	23
1.2.3.2 Channel =M	24



1.2.3.2.1	16QAM /full RBs	24
1.2.3.3	Channel =T	25
1.2.3.3.1	16QAM /full RBs	25
1.2.4	<i>Channel Bandwidth = Highest (20 MHz)</i>	26
1.2.4.1	Channel = B	26
1.2.4.1.1	16QAM /full RBs	26
1.2.4.2	Channel =M.....	27
1.2.4.2.1	16QAM /full RBs	27
1.2.4.3	Channel =T	28
1.2.4.3.1	16QAM /full RBs	28



Result Table

NOTE: All relevant operation modes have been tested, and the full RB data is included in this report.

Table 1 Measurement Results (LTE) BAND 4

Test Mode	Carrier Conf.	RF Ch.	Occupied Bandwidth [MHz]	Verdict
TM6	5 MHz	L	4.4399	Pass
		M	4.3872	Pass
		H	4.4387	Pass
	10 MHz	L	8.8594	Pass
		M	8.8896	Pass
		H	8.8790	Pass
	15 MHz	L	13.2022	Pass
		M	13.1824	Pass
		H	13.2176	Pass
	20 MHz	L	17.6490	Pass
		M	17.7032	Pass
		H	17.7718	Pass
TM7	5 MHz	L	4.4642	Pass
		M	4.4338	Pass
		H	4.3882	Pass
	10 MHz	L	8.8854	Pass
		M	8.8770	Pass
		H	8.8919	Pass
	15 MHz	L	13.3958	Pass
		M	13.2937	Pass
		H	13.3183	Pass
	20 MHz	L	17.7938	Pass
		M	17.9739	Pass
		H	17.7775	Pass




1 For Band 4

1.1 Test Mode=TM6

1.1.1 Channel Bandwidth = Lowest (5 MHz)

1.1.1.1 Channel = B


1.1.1.1.1 QPSK/full RBs





1.1.1.2 Channel =M


1.1.1.2.1 QPSK/full RBs





1.1.1.3 Channel =T

1.1.1.3.1 QPSK/full RBs






1.1.2 Channel Bandwidth = 10 MHz

1.1.2.1 Channel = B


1.1.2.1.1 QPSK/full RBs





1.1.2.2 Channel =M


1.1.2.2.1 QPSK/full RBs





1.1.2.3 Channel =T

1.1.2.3.1 QPSK/full RBs






1.1.3 Channel Bandwidth = 15 MHz

1.1.3.1 Channel = B


1.1.3.1.1 QPSK/full RBs





1.1.3.2 Channel =M


1.1.3.2.1 QPSK/full RBs





1.1.3.3 Channel =T

1.1.3.3.1 QPSK/full RBs






1.1.4 Channel Bandwidth = Highest (20 MHz)

1.1.4.1 Channel = B


1.1.4.1.1 QPSK/full RBs





1.1.4.2 Channel =M


1.1.4.2.1 QPSK/full RBs





1.1.4.3 Channel =T

1.1.4.3.1 QPSK/full RBs






1.2 Test Mode=TM7

1.2.1 Channel Bandwidth = Lowest (5 MHz)

1.2.1.1 Channel = B


1.2.1.1.1 16QAM /full RBs





1.2.1.2 Channel =M


1.2.1.2.1 16QAM /full RBs





1.2.1.3 Channel =T

1.2.1.3.1 16QAM /full RBs






1.2.2 Channel Bandwidth = 10 MHz

1.2.2.1 Channel = B


1.2.2.1.1 16QAM /full RBs





1.2.2.2 Channel =M


1.2.2.2.1 16QAM /full RBs





1.2.2.3 Channel =T

1.2.2.3.1 16QAM /full RBs






1.2.3 Channel Bandwidth = 15 MHz

1.2.3.1 Channel = B


1.2.3.1.1 16QAM /full RBs





1.2.3.2 Channel =M


1.2.3.2.1 16QAM /full RBs





1.2.3.3 Channel =T

1.2.3.3.1 16QAM /full RBs






1.2.4 Channel Bandwidth = Highest (20 MHz)

1.2.4.1 Channel = B


1.2.4.1.1 16QAM /full RBs





1.2.4.2 Channel =M


1.2.4.2.1 16QAM /full RBs





1.2.4.3 Channel =T

1.2.4.3.1 16QAM /full RBs





Appendix D

Band Edges Compliance

According to FCC Part 2.1051 & 27 Subpart C&L



TABLE OF CONTENTS

APPENDIX D	1
TABLE OF CONTENTS.....	2
1 FOR BAND 4	4
1.1 TEST MODE=TM6.....	4
1.1.1 Channel Bandwidth = Lowest (5 MHz)	4
1.1.1.1 Channel= L	4
1.1.1.1.1 QPSK/1RB #0	4
1.1.1.1.2 QPSK/Partial RBs /RB #0.....	5
1.1.1.1.3 QPSK/full RBs.....	6
1.1.1.2 Channel= H.....	7
1.1.1.2.1 QPSK/1RB #max.....	7
1.1.1.2.2 QPSK/Partial RBs /RB #max	8
1.1.1.2.3 QPSK/full RBs.....	9
1.1.2 Channel Bandwidth = 10 MHz.....	10
1.1.2.1 Channel= L	10
1.1.2.1.1 QPSK/1RB #0	10
1.1.2.1.2 QPSK/Partial RBs /RB #0.....	11
1.1.2.1.3 QPSK/full RBs.....	12
1.1.2.2 Channel= H.....	13
1.1.2.2.1 QPSK/1RB #max.....	13
1.1.2.2.2 QPSK/Partial RBs /RB #max	14
1.1.2.2.3 QPSK/full RBs.....	15
1.1.3 Channel Bandwidth = 15 MHz.....	16
1.1.3.1 Channel= L	16
1.1.3.1.1 QPSK/1RB #0	16
1.1.3.1.2 QPSK/Partial RBs /RB #0.....	17
1.1.3.1.3 QPSK/full RBs.....	18
1.1.3.2 Channel= H.....	19
1.1.3.2.1 QPSK/1RB #max.....	19
1.1.3.2.2 QPSK/Partial RBs /RB #max	20
1.1.3.2.3 QPSK/full RBs.....	21
1.1.4 Channel Bandwidth = Highest (20 MHz)	22
1.1.4.1 Channel= L	22
1.1.4.1.1 QPSK/1RB #0	22
1.1.4.1.2 QPSK/Partial RBs /RB #0.....	23
1.1.4.1.3 QPSK/full RBs.....	24
1.1.4.2 Channel= H.....	25
1.1.4.2.1 QPSK/1RB #max.....	25
1.1.4.2.2 QPSK/Partial RBs /RB #max	26
1.1.4.2.3 QPSK/full RBs.....	27
1.2 TEST MODE=TM7.....	28
1.2.1 Channel Bandwidth = Lowest (5 MHz)	28
1.2.1.1 Channel= L	28
1.2.1.1.1 QPSK/1RB #0	28
1.2.1.1.2 QPSK/Partial RBs /RB #0.....	29
1.2.1.1.3 QPSK/full RBs.....	30
1.2.1.2 Channel= H.....	31
1.2.1.2.1 QPSK/1RB #max.....	31
1.2.1.2.2 QPSK/Partial RBs /RB #max	32
1.2.1.2.3 QPSK/full RBs.....	33
1.2.2 Channel Bandwidth = 10 MHz.....	34



1.2.2.1	Channel= L	34
1.2.2.1.1	QPSK/1RB #0	34
1.2.2.1.2	QPSK/Partial RBs /RB #0.....	35
1.2.2.1.3	QPSK/full RBs.....	36
1.2.2.2	Channel= H.....	37
1.2.2.2.1	QPSK/1RB #max.....	37
1.2.2.2.2	QPSK/Partial RBs /RB #max	38
1.2.2.2.3	QPSK/full RBs.....	39
1.2.3	Channel Bandwidth = 15 MHz.....	40
1.2.3.1	Channel= L	40
1.2.3.1.1	QPSK/1RB #0	40
1.2.3.1.2	QPSK/Partial RBs /RB #0.....	41
1.2.3.1.3	QPSK/full RBs.....	42
1.2.3.2	Channel= H.....	43
1.2.3.2.1	QPSK/1RB #max.....	43
1.2.3.2.2	QPSK/Partial RBs /RB #max	44
1.2.3.2.3	QPSK/full RBs.....	45
1.2.4	Channel Bandwidth = Highest (20 MHz).....	46
1.2.4.1	Channel= L	46
1.2.4.1.1	QPSK/1RB #0	46
1.2.4.1.2	QPSK/Partial RBs /RB #0.....	47
1.2.4.1.3	QPSK/full RBs.....	48
1.2.4.2	Channel= H.....	49
1.2.4.2.1	QPSK/1RB #max.....	49
1.2.4.2.2	QPSK/Partial RBs /RB #max	50
1.2.4.2.3	QPSK/full RBs.....	51




1 For Band 4

1.1 Test Mode=TM6

1.1.1 Channel Bandwidth = Lowest (5 MHz)

1.1.1.1 Channel= L


1.1.1.1.1 QPSK/1RB #0



Date: 9.JUL.2012 22:50:00




1.1.1.1.2 QPSK/Partial RBs /RB #0



Date: 9.JUL.2012 22:50:34



1.1.1.1.3 QPSK/full RBs




Date: 9.JUL.2012 22:51:15



1.1.1.2 Channel= H


1.1.1.2.1 QPSK/1RB #max



Date: 9.JUL.2012 22:55:59




1.1.1.2.2 QPSK/Partial RBs /RB #max



Date: 9.JUL.2012 22:55:41



1.1.1.2.3 QPSK/full RBs




Date: 9.JUL.2012 22:55:20

1.1.2 Channel Bandwidth = 10 MHz

1.1.2.1 Channel= L


1.1.2.1.1 QPSK/1RB #0



Date: 9.JUL.2012 23:01:32




1.1.2.1.2 QPSK/Partial RBs /RB #0



Date: 9.JUL.2012 23:01:17



1.1.2.1.3 QPSK/full RBs




Date: 9.JUL.2012 23:00:42



1.1.2.2 Channel= H


1.1.2.2.1 QPSK/1RB #max



Date: 9.JUL.2012 22:58:17




1.1.2.2.2 QPSK/Partial RBs /RB #max



Date: 9.JUL.2012 22:58:04



1.1.2.2.3 QPSK/full RBs




Date: 9.JUL.2012 22:57:39



1.1.3 Channel Bandwidth = 15 MHz

1.1.3.1 Channel= L


1.1.3.1.1 QPSK/1RB #0



Date: 9.JUL.2012 23:05:05




1.1.3.1.2 QPSK/Partial RBs /RB #0



Date: 9.JUL.2012 23:04:53



1.1.3.1.3 QPSK/full RBs




Date: 9.JUL.2012 23:04:28



1.1.3.2 Channel= H


1.1.3.2.1 QPSK/1RB #max



Date: 9.JUL.2012 23:08:24




1.1.3.2.2 QPSK/Partial RBs /RB #max



Date: 9.JUL.2012 23:09:31



1.1.3.2.3 QPSK/full RBs




Date: 9.JUL.2012 23:09:49



1.1.4 Channel Bandwidth = Highest (20 MHz)

1.1.4.1 Channel= L


1.1.4.1.1 QPSK/1RB #0



Date: 9.JUL.2012 23:24:27




1.1.4.1.2 QPSK/Partial RBs /RB #0



Date: 9.JUL.2012 23:24:52



1.1.4.1.3 QPSK/full RBs




Date: 9.JUL.2012 23:25:07



1.1.4.2 Channel= H

1.1.4.2.1 QPSK/1RB #max



Date: 9.JUL.2012 23:11:51