



FCC Test Report

Product Name: EVDO Rev.A USB Stick

Model Number: HUAWEI EC1705

Report No: SYBHZ(R)E056022010EB-2
FCC ID: QISEC1705

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice



1.	The laboratory has obtained the accreditation of China National Accreditation Committee for Laboratories (CNAL), and accreditation number: L0310.
2.	The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3.	The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4.	The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is C1758, R1672, and T153.
5.	The test report is invalid if not marked with "exclusive stamp for the test report".
6.	Any copy of the test report is invalid if not re-marked with the "exclusive stamp for the test report".
7.	The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8.	The test report is invalid if there is any evidence of erasure and/or falsification.
9.	If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10.	Normally, the test report is only responsible for the samples that have undergone the test.
11.	Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Huawei Technologies Co Ltd
Huawei Industrial Base,
Bantian Longgang
Shenzhen 518128, P.R China
Tel: +86 755 89651014
Fax: +86 755 89652518



REPORT ON **FCC Test of EVDO Rev.A USB Stick**
M/N: HUAWEI EC1705

Report No: SYBHZ(R)E056022010EB-2

REGULATION **FCC CFR47 Part 2: Subpart J;**
FCC CFR47 Part 22: Subpart H;
FCC CFR47 Part 15: Subpart B;

CONCLUSION **Pass**

General Manager Apr. 07, 2010 张兴海
Date Name signature



Technical Responsibility For Area of Testing Apr. 07, 2010 余辉
Date Name signature



Test Lab Engineer Apr. 07, 2010 胡俊
Date Name signature





Contents

1	<u>Summary</u>	5
2	<u>Product Description</u>	6
2.1	PRODUCTION INFORMATION	6
2.2	MODIFICATION INFORMATION.....	6
3	<u>Test Site Description</u>	7
3.1	TESTING PERIOD	7
3.2	GENERAL SET UP DESCRIPTION	7
4	<u>Product Description</u>	8
4.1	TECHNICAL CHARACTERISTICS	8
4.2	EUT IDENTIFICATION LIST	10
5	<u>Main Test Instruments</u>	11
6	<u>Transmitter Measurements</u>	12
6.1	EFFECTIVE RADIATED POWER OF TRANSMITTER (ERP).....	12
6.2	CONDUCTED OUTPUT POWER	16
6.3	MODULATION CHARACTERISTICS	19
6.4	OCCUPIED BANDWIDTH.....	21
6.5	BAND EDGES COMPLIANCE	24
6.6	SPURIOUS EMISSION AT ANTENNA TERMINAL	26
6.7	FREQUENCY STABILITY	29
7	<u>System Measurement Uncertainty</u>	34
8	<u>Appendixes</u>	35



1 Summary

The table below summarizes the measurements and results for the HUAWEI EC1705 EVDO Rev.A USB Stick. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
2.1046	22.913	Effective Radiated Power of Transmitter	PASS
2.1046	22.913	Conducted Power of Transmitter	PASS
2.1047		Modulation Characteristics	PASS
2.1049		Occupied Bandwidth	PASS
2.1051	22.917	Band Edges Compliance	PASS
2.1051	22.917	Spurious Emission at Antenna Terminals	PASS
2.1053	22.917	Radiated Spurious Emissions	PASS
2.1055	22.355	Frequency Stability	PASS

Note: The Radiated Spurious Emissions' test results are shown in the EMC report.



2 Product Description

2.1 Production Information

2.1.1 General Description

HUAWEI EC1705 USB Stick is a subscriber equipment in the CDMA and CDMA2000 1x EVDO Rev.A/Rev.0 system and supports 800MHz frequency band. By using the QSC6085 chipset and Zero-IF technologies, the USB Stick implements such functions as RF signal reception/transmission, CDMA protocol process, CDMA2000 1xEV-DO Rev.A/Rev.0 protocol processing, high-rate packet data services. Externally they provide USB interface (to connect to the notebook etc.).

2.1.2 Support function and Service

The HUAWEI EC1705 USB Stick support the function and service as follows:

Table 2 Service and Test mode List

Service Name	Characteristic	Corresponding Test Mode	Note (Corresponding coding and transmission rates)
data and SMS	Modulation: QPSK	TM1	
data and SMS	Modulation: HPSK	TM3	
Data(EV-DO)	Default Access Channel MAC	Subtype 0	Modulation: HPSK
data(EV-DO)	Enhanced Access Channel MAC	Subtype 2	The R-Data packet size determines the modulation format, R-Data Packet Size: 128, 256, 512, 768 or 1024 Modulation: BPSK R-Data Packet Size: 1536 , 2048, 3072, 4096, 6144 or 8192 Modulation: QPSK R-Data Packet Size: 12288 Modulation: 8-PSK

Note: * The test conditions and settings are defined in ANSI/TIA-98-E section 1.3, 3GPP2 c.s0033-0-v2.0 and 3GPP2 C.S0033-A-v1.0.

2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable!				



3 Test Site Description

The test site of:

Huawei Technologies Co. Ltd.
P.O. Box 518129
Huawei base, bantian,
Longgang District, Shenzhen, China

3.1 Testing Period

The test have been performed during the period of

Apr. 01, 2010 to Apr. 06, 2010

3.2 General Set up Description

HUAWEI EC1705 USB Stick can Support Cellular Band, and Support the CDMA2000 1x standard and the CDMA2000 1xEV-DO Rev. A standard. During this measurement, HUAWEI EC1705 USB Stick works in CDMA / EV-DO mode and Cellular Band.

CDMA MODE:

TM1: Forward Traffic Channel Radio Configuration 1, Reverse Traffic Channel Radio Configuration 1

TM3: Forward Traffic Channel Radio Configuration 3, Reverse Traffic Channel Radio Configuration 3

Parameter	Units	Value
\hat{I}_{or}	dBm/1.23 MHz	-104
$\frac{Pilot Ec}{I_{or}}$	dB	-7
$\frac{Traffic Ec}{I_{or}}$	dB	-7.4

EVDO MODE:

Current Physical Layer Subtype:

Subtype 0* indicates that the protocol subtype assigned to the Access Channel MAC protocol is Default Access Channel MAC and its Subtype ID number is 0x0000.

Subtype 2* indicates that the protocol subtype assigned to the Access Channel MAC protocol is Enhanced Access Channel MAC and its Subtype ID number is 0x0002

Note: *The test settings are defined in 3GPP2 C.S0033



4 Product Description

4.1 Technical Characteristics

4.1.1 Frequency Range

Table 4 Frequency Range

Uplink band:	824 to 849 MHz
Downlink band:	869 to 894 MHz

4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

Channel spacing:	30 KHz
Channel separation:	1.23 MHz

4.1.3 Type of Emission

Table 6 Type of Emission

Emission Designation:	1M25F9W
-----------------------	----------------

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

4.1.4 Environmental Requirements

Table 7 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%~95%RH

4.1.5 Power Source

Table 8 Power Source

AC voltage nominal:	 5V; Supplied by USB port of notebook
AC voltage range	 4.75 - 5.25V
AC current maximal:	500mA

4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033 (9)

Please reference the document Tune-up Procedure in TCF.

4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033 (8)

The voltage and current in the final RF stage is:

Table 9 Applied DC Voltages and Currents

Voltage:	 +5V
Current:	500mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)



4.2 EUT Identification List

4.2.1 Board Information

Table 10 Board Information

EVDO Rev.A USB Stick		
HUAWEI EC1705		
Board and Module		
Model name	Serial Number	Remarks
HUAWEI EC1705	8059791E	CE1EC1705M001

4.2.2 Adapter Technical Data

Not Applicable.

4.2.3 Battery Technical Data

Not Applicable.

4.2.4 FCC Identification

FCC Identification: QISEC1705



5 Main Test Instruments

Table 11 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until (MM.DD.YYYY)
EMI Test receiver	R&S	ESIB 26	100318	11.17, 2010
Broadband Antenna	Schaffner	CBL 6112B	2941	4.17, 2011
Horn Antenna	R & S	HF906	359287/006	6.19.2010
Tunable Dipole	Schwarzbeck	D69250- UHAP/D69250-VHAP	979/917	11.20.2010
Signal Generator	R&S	SMR 40	100325	5.12, 2010
Vector Signal Generator	R&S	SMU200A	3605064030	06.14.2010
Power Supply	Agilent	66311B	MY43006371	04.26.2011
Climate Chamber	WEISS	WK11-600/70	5922602844001 0	9.26.2010
Universal Radio Communication Tester	R&S	CMU200	113164	06.17.2010
Spectrum Analyzer	R&S	FSU26	200002	03.07.2011

6 Transmitter Measurements

6.1 Effective Radiated Power of Transmitter (ERP)

6.1.1 Test Conditions

Table 12 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	23.5°C
Relative humidity:	55%
Test Configurations:	CDMA TM1 and TM3 at frequency B、 M、 T EVDO Subtype 0 and Subtype 2 at frequency B、 M、 T

6.1.2 Test Specifications and Limits

6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 22.913

6.1.2.2 Supporting Standards

Table 13 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.1.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a mobile station transmitter exceed 7 W. And calculate longitude ERP by following formula: $ERP(\text{dBm}) = 10 \cdot \log(ERP_{\text{in watts}})$.

Table 14 Limits

Maximum Output Power (Watts)	< 7 Watts
Maximum Output Power (dBm)	< 38.5 dBm

6.1.3 Test Method and Setup

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, ERP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the HUAWEI EC1705 USB Stick to the wireless communication tester CMU 200 via the air interface. The band class is set as US Cellular.


(b) Test the Radiated maximum output power by the CMU 200 received from test antenna.

(c) Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal

generator to get the same received power recorded in step (b) on CMU 200, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.

Test setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP




Figure 1. Test Set-up

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.



6.1.4 Measurement Results

Table 15 Measurement Results

TEST CONDITIONS		RF Output Power					
		Channel1013(B) 824.7MHz		Channel 384(M) 836.52MHz		Channel777(T) 848.31MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	Tnorm (24 °C) Vnorm (5 V)	20.08	38.5	20.13	38.5	20.16	38.5
TM3	Tnorm (24 °C) Vnorm (5 V)	20.24	38.5	20.10	38.5	20.11	38.5
Subtype 0	Tnorm (24 °C) Vnorm (5 V)	20.28	38.5	20.20	38.5	20.27	38.5
Subtype 2	Tnorm (24 °C) Vnorm (5 V)	20.16	38.5	20.36	38.5	20.34	38.5

6.1.4.1 Substitution Results

Table 16 Substitution Results

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substitution Antenna Type	SGP [dBm]	Substitution Gain [dBd]	Cable Loss [dB]	Substitution Level (ERP)	FCC limit [dBm]	Result
							[dBm]		
TM1	824.7	20.08	Dipole Ant.	23.34	-2.75	0.6	19.99	38.5	Pass
TM1	836.52	20.13	Dipole Ant.	23.37	-2.87	0.6	19.90	38.5	Pass
TM1	848.31	20.16	Dipole Ant.	23.42	-2.85	0.6	19.97	38.5	Pass
TM3	824.7	20.24	Dipole Ant.	23.36	-2.75	0.6	20.01	38.5	Pass
TM3	836.52	20.10	Dipole Ant.	23.33	-2.87	0.6	19.86	38.5	Pass
TM3	848.31	20.11	Dipole Ant.	23.43	-2.85	0.6	19.98	38.5	Pass
Subtype 0	824.7	20.28	Dipole Ant.	23.45	-2.75	0.6	20.10	38.5	Pass
Subtype 0	836.52	20.20	Dipole Ant.	23.61	-2.87	0.6	20.14	38.5	Pass
Subtype 0	848.31	20.27	Dipole Ant.	23.52	-2.85	0.6	20.07	38.5	Pass
Subtype 2	824.7	20.16	Dipole Ant.	23.36	-2.75	0.6	20.01	38.5	Pass
Subtype 2	836.52	20.36	Dipole Ant.	23.61	-2.87	0.6	20.14	38.5	Pass
Subtype 2	848.31	20.34	Dipole Ant.	23.72	-2.85	0.6	20.27	38.5	Pass

Note: a, For get the ERP (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

NOTE: SGP- Signal Generator Level

b, A CDMA signal with bandwidth of 1.23MHz is created by the vector generator R&S SMU200A.

c, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 1.23MHz.

6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.



6.2 Conducted output power

6.2.1 Test Conditions

Table 17 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	23.5°C
Relative humidity:	55%
Test Configurations:	CDMA TM1 and TM3 at frequency B、 M 、 T EVDO Subtype 0 and Subtype 2 at frequency B、 M 、 T

6.2.2 Test Specifications and Limits

6.2.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 22.913

6.2.2.2 Supporting Standards

Table 18 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.2.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a mobile station transmitter exceed 7 W. The calculated longitude ERP by following formula:

$$ERP(\text{dBm})= 10*\log (ERP_{\text{in watts}}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$P_{\text{cod}}(\text{dBm})=ERP(\text{dBm})- \text{Gain}(\text{dBd}).$$

and $\text{Gain}(\text{dBd})= \text{Gain}(\text{dBi})- 2.15\text{dB}$

Table 19 Limits

Maximum Output Power (Watts)	< 7 Watts=38.5 dBm
Antenna Gain(dBi):	-1.7
Antenna Gain(dBd):	-3.85
Maximum Conducted Output Power (dBm)	< 42.35 dBm

6.2.3 Test Method and Setup

(a)For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the HUAWEI EC1705 USB Stick to the wireless communication tester CMU 200 via the antenna connector. The band class is set as US Cellular.

(b)Test the Conducted maximum output power by the CMU 200.

Test setup




Figure 2. Test Set-up

6.2.4 Measurement Results

Table 20 Measurement Results

TEST CONDITIONS		RF Output Power					
		Channel1013(B) 824.7MHz		Channel 384(M) 836.52MHz		Channel777(T) 848.31MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	Tnorm (24 °C) Vnorm (5 V)	23.93	42.35	23.98	42.35	24.01	42.35
TM3	Tnorm (24 °C) Vnorm (5 V)	24.09	42.35	23.95	42.35	23.96	42.35
Subtype 0	Tnorm (24 °C) Vnorm (5 V)	24.13	42.35	24.05	42.35	24.12	42.35
Subtype 2	Tnorm (24 °C) Vnorm (5 V)	24.01	42.35	24.21	42.35	24.19	42.35

6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.3 Modulation Characteristics

6.3.1 Test Conditions

Table 21 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	22 °C
Relative humidity:	52 %
Test Configurations:	CDMA mode TM1 and TM3 at frequency M EVDO mode Subtype 0 and Subtype 2 at frequency M

6.3.2 Test Specifications and Limits

6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 22 subpart H.

6.3.2.2 Supporting Standards

Table 22 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations.

6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 22 subpart H.

Table 23 Limits

Limits	Not applicable
--------	----------------

6.3.3 Test Method and Setup

Connect the HUAWEI EC1705 USB Stick to Universal Radio Communication Tester CMU200 via the antenna connector. The band class is set as US Cellular; the HUAWEI EC1705 USB Stick's output is matched with 50 Ω load, test method was according to ANSI/TIA-98-E. The waveform quality and constellation of the HUAWEI EC1705 USB Stick was tested.

Test setup




Figure 3. Test Set-up

6.3.4 Measurement Results

Table 24 Measurement Results

TEST CONDITIONS		Modulation Characteristic	
		Channel 384(M)	
		836.52Mhz	
		Measured	
		CDMA Mode	EVDO Mode
		TM1 & TM3	Subtype 0 & Subtype 2
T _{norm} (25 °C)	V _{norm} (5V)	Refer to Appendix A	Refer to Appendix A

6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix A.

6.4 Occupied Bandwidth

6.4.1 Test Conditions

Table 25 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	55 %
Test Configurations:	CDMA TM1 and TM3 at frequency B、 M 、 T EVDO Mode Subtype 0 and Subtype 2 at frequency B、 M 、 T

6.4.2 Test Specifications and Limits

6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and part 22 subpart H.

6.4.2.2 Supporting Standards

Table 26 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations.

6.4.2.3 Limits

No specific occupied bandwidth requirement in part 22 subpart H, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 27 Limits

Upper /lower frequency limits	0.5% of the mean power
-------------------------------	------------------------

6.4.3 Test Method and Setup

HUAWEI EC1705 USB Stick was connected to the wireless signal analyzer R&S FSU26 via the one RF connector. The band class is set as US Cellular; HUAWEI EC1705 USB Stick was controlled to transmit maximum power. Measure and record the occupied bandwidth of the HUAWEI EC1705 USB Stick by the R&S FSU26.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g)&(h).

(g) Transmitter in which the modulating base band comprises not more than three independent

channels - when modulated by the full complement of signals for which the transmitter is rated. The level of modulation for each channel should be set to that prescribed in rule parts applicable to the services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer's maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

Measurement bandwidth (RBW): 30 kHz (Resolution bandwidth)
Video bandwidth (VBW): 300 kHz

Test Set-up




Figure 4. Test Set-up



6.4.4 Measurement Results

Table 28 Measurement Results

TEST CONDITIONS		Occupied Bandwidth											
		Channel1013(B) 824.7MHz				Channel 384(M) 836.52MHz				Channel777(T) 848.31MHz			
		Measured (MHz)				Measured (MHz)				Measured (MHz)			
		CDMA		EVDO		CDMA		EVDO		CDMA		EVDO	
		TM1	TM3	Subtype 0	Subtype 2	TM1	TM3	Subtype 0	Subtype 2	TM1	TM3	Subtype 0	Subtype 2
T_{norm} (24 °C)	V_{norm} (5 V)	1.29	1.28	1.29	1.28	1.29	1.28	1.29	1.29	1.29	1.28	1.28	1.29

6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.
 For the measurement results refer to appendix B.

6.5 Band Edges Compliance

6.5.1 Test Conditions

Table 29 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	23.5°C
Relative humidity:	55 %
Test Configurations:	CDMA TM1 and TM3 at frequency B、 T EVDO Mode Subtype 0 and Subtype 2 at frequency B、 T

6.5.2 Test Specifications and Limits

6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.5.2.2 Supporting Standards

Table 30 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations.

6.5.2.3 Limits

Compliance with 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT).

Table 31 Limits

Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm – 37 dB
Absolute level	- 13 dBm

6.5.3 Test Method and Setup

HUAWEI EC1705 USB Stick was connected to the wireless signal analyzer R&S FSU26 via the one RF connector, the band class is set as Cellular. HUAWEI EC1705 USB Stick was controlled to transmit maximum power. Measure and record band edges compliance of the HUAWEI EC1705 USB Stick by the R&S FSU26.

RBW of 20 kHz (1% of 2MHz) was used up to 5MHz away from the band edge. So the FCC rules specify that RBW of 100kHz for measurements of emissions >1MHz away from the band edges ,the limit was adjusted with -13dBm to -20dBm to compensate for the reduced measurement bandwidth.

Test Set-up




Figure 5. Test Set-up

6.5.4 Measurement Results at Band Edges

Table 32 Measurement Results outside Band Edges-- Single Carrier

Band	Frequency of Band edges [MHz]	Channel Number	Test Mode	Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
US Cellular	$T_{norm} (25\text{ }^{\circ}\text{C}), V_{norm} (5\text{V})$						
	824	1013 (B)	TM1 & TM3	24	<-13(See appendix C)	- 13 dBm	Pass
	869	777 (T)	TM1 & TM3	24	<-13(See appendix C)	- 13 dBm	Pass

Band	Frequency of Band edges [MHz]	Channel Number	Test Mode	Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
US Cellular	$T_{norm} (25\text{ }^{\circ}\text{C}), V_{norm} (5\text{V})$						
	824	1013 (B)	Subtype 0 & Subtype 2	24	<-13(See appendix C)	- 13 dBm	Pass
	869	777 (T)	Subtype 0 & Subtype 2	24	<-13(See appendix C)	- 13 dBm	Pass

6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.
 For the measurement results refer to appendix C.



6.6 Spurious Emission at Antenna Terminal

6.6.1 Test Conditions

Table 33 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	20°C
Relative humidity:	50 %
Test Configurations:	CDMA TM1 and TM3 at frequency B/M/T EVDO Mode Subtype 0 and Subtype 2 at frequency B/M/T

6.6.2 Test Specifications and Limits

6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.6.2.2 Supporting Standards

Table 34 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations. Release C

6.6.2.3 Limits

Compliance with part 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT).

Table 35 Limits

Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm – 37 dB
Absolute level	- 13 dBm

6.6.3 Test Method and Setup

HUAWEI EC1705 USB Stick was connected to the wireless signal analyzer R&S FSU26 via the one RF connector, the band class is set as US Cellular. HUAWEI EC1705 USB Stick was controlled to transmit maximum power.

Measure and record the Conducted Spurious Emission of the HUAWEI EC1705 USB Stick by the R&S FSU26

According to part 22.917, the defined measurement bandwidth as following:

22.917(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 1 GHz: 100 kHz;

Measurement bandwidth (RBW) for 1GHz up to 12.75GHz: 1MHz;

Test Set-up




Figure 6. Test Set-up

6.6.4 Measurement Results at Conducted Spurious Emission

Table 36 Measurement Results

Channel Number	Test Mode	Test Range (Frequency)	Output Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
Channel 1013(B)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 0	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 2	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 384 (M)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 0	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 2	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 777 (T)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 0	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	Subtype 2	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass

6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix D.

6.7 Frequency Stability

6.7.1 Test Conditions

Table 37 Test Conditions

Preconditioning:	1 hour
Measured at:	Antenna connector
Ambient temperature:	See below
Relative humidity:	54% at 25°C
Test Configurations:	TM1 and TM3 at frequency M

6.7.2 Test Specifications and Limits

6.7.2.1 Specification

CFR 47 (FCC) part 2.1055 and part 22.355

6.7.2.2 Supporting Standards

Table 38 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
EIA/TIA-98E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations.

6.7.2.3 Limits

According to part 22.355, from 821MHz to 869MHz, for mobile device, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances 2.5ppm.

6.7.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in subparagraphs (2) and (3) of paragraph 2.1055

(b) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(d) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply

voltage and at each extreme also shall be shown.

(e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

Test Setup

Connect the EUT to the Wireless Communication test set CMU 200 via the connector. Then measure the frequency error by the Wireless Communication test set CMU 200. The EUT's output is matched with a 50 Ω load.




Figure 7. Test Set up

6.7.4 Measurement Results

6.7.4.1 Measurement Results vs. Variation of Temperature

- TM1, 5V DC Channel No.384(836.52MHz)

Table 39 Measurement Results vs. Variation of Temperature—TM1

Temperature	Normal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.52	-35	Pass
-20 °C	836.52	-23	Pass
-10 °C	836.52	19	Pass
0 °C	836.52	-14	Pass
+10 °C	836.52	-10	Pass
+20 °C	836.52	-4	Pass
+30 °C	836.52	-9	Pass
+40 °C	836.52	-14	Pass
+50 °C	836.52	-15	Pass



● **TM3, 5V DC Channel No.384(836.52MHz)**

Table 40 Measurement Results vs. Variation of Temperature—TM3

Temperature	Normal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.52	-35	Pass
-20 °C	836.52	-26	Pass
-10 °C	836.52	-18	Pass
0 °C	836.52	-13	Pass
+10 °C	836.52	-7	Pass
+20 °C	836.52	-5	Pass
+30 °C	836.52	10	Pass
+40 °C	836.52	13	Pass
+50 °C	836.52	-14	Pass

● **Subtype 0, 5V DC Channel No.384(836.52MHz)**

Table 41 Measurement Results vs. Variation of Temperature—EVDO

Temperature	Normal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.52	32	Pass
-20 °C	836.52	-23	Pass
-10 °C	836.52	-16	Pass
0 °C	836.52	-14	Pass
+10 °C	836.52	-7	Pass
+20 °C	836.52	-5	Pass
+30 °C	836.52	-9	Pass
+40 °C	836.52	-14	Pass
+50 °C	836.52	-18	Pass



● Subtype 2, 5V DC Channel No.384(836.52MHz)

Table 42 Measurement Results vs. Variation of Temperature – EVDO

Temperature	Norminal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	836.52	-31	Pass
-20 °C	836.52	-21	Pass
-10 °C	836.52	-18	Pass
0 °C	836.52	-13	Pass
+10 °C	836.52	-8	Pass
+20 °C	836.52	-9	Pass
+30 °C	836.52	9	Pass
+40 °C	836.52	-13	Pass
+50 °C	836.52	-18	Pass

6.7.4.2 Measurement Results vs. Variation of Voltage

● TM1, 25 °C ,Channel No. 384(836.52MHz)

Table 43 Measurement Results vs. Variation of Voltage—TM1

Voltage	Norminal Frequency (MHz)	Measured Frequency Error(Hz)	Result
4.75 V	836.52	25	Pass
5 V	836.52	24	Pass
5.25 V	836.52	24	Pass

● TM3, 25 °C ,Channel No. 384(836.52MHz)

Table 44 Measurement Results vs. Variation of Voltage—TM3

Voltage	Norminal Frequency (MHz)	Measured Frequency Error(Hz)	Result
4.75 V	836.52	24	Pass
5 V	836.52	24	Pass
5.25 V	836.52	24	Pass



● Subtype 0 , 25 °C ,Channel No. 384(836.52MHz)

Table 45 Measurement Results vs. Variation of Voltage –EVDO

Voltage	Norminal Frequency (MHz)	Measured Frequency Error(Hz)	Result
4.75 V	836.52	28	Pass
5 V	836.52	28	Pass
5.25 V	836.52	28	Pass

● Subtype 2 , 25 °C ,Channel No. 384(836.52MHz)

Table 46 Measurement Results vs. Variation of Voltage –EVDO

Voltage	Norminal Frequency (MHz)	Measured Frequency Error(Hz)	Result
4.75 V	836.52	28	Pass
5 V	836.52	28	Pass
5.25 V	836.52	28	Pass

6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 47 System Measurement Uncertainty

Items		Extended Uncertainty
Effective Radiated Power of Transmitter	ERP(dBm)	U=3dB; k=2
Band Width	Magnitude (%)	U=0.2%; k=2
Band Edge Compliance	Disturbance Power(dBm)	U=2.0dB; k=2
Conducted Spurious Emission at Antenna Terminal	Disturbance Power(dBm)	U=2.0dB; k=2
Frequency Stability	Frequency Accuracy(ppm)	U=0.21ppm; k=2
Field Strength of Spurious Radiation	ERP(dBm)	U=3dB; k=2
Conducted Output Power	Power(dBm)	U=0.39dB; k=2
Conducted Emission at Power Port	Disturbance Voltage(dB μ V)	U=4dB; k=2
Radiated Emission of enclosure at ideal mode	Field strength (dB μ V/m)	U=5dB; k=2



8 Appendixes

Appendix A	Measurement Results Modulation Characteristics	7 pages
Appendix B	Measurement Results Occupied Bandwidth	13 Pages
Appendix C	Measurement Results Band Edges	13 Pages
Appendix D	Measurement Results Spurious Emission at Antenna Terminal	73 Pages