

## Declaration of Electromagnetic Field Health Compliance

To whom it may concern,

As to the product **eMeter** made by Huawei Technologies Co., Ltd., we declare that it complies with the following standards(s):

Nr.	Standard
1	47CFR FCC Part 1 (10-1-14 Edition) & OET Bulletin 65

The compliance is demonstrated based on the following calculation model assessment:

- The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

- $P$  = input power of the antenna.
- $G$  = antenna gain relative to an isotropic antenna.
- $\theta, \phi$  = elevation and azimuth angles.
- $R$  = distance from the antenna to the point of investigation.

- For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Where:

- $S_i$  = the power density when the  $f$  is  $i$ .
- $S_{Limit,i}$  = the reference level requirement for power density when  $f$  is  $i$ .

- The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is based on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation
RF Source #1	$f$ = 2400 to 2483.5 MHz
	$S_{Limit,i}$ = 10 W/m <sup>2</sup>
	$P$ = 0.0008 W (= -1.0 dBm, measured max peak value)
	$G_{(\theta, \phi)}$ = 3.388 (= 5.3 dBi, rated max)



RF Source	Calculation
	$\theta, \phi$ = The worst condition is considered, i.e. the max $G$ is used. $R \geq 0.2$ m $S_i \leq \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2} = 0.005$ W/m <sup>2</sup> $\frac{S_i}{S_{Limit,i}} \leq 0.005$
RF Source(s) Combination	$\sum_i \frac{S_i}{S_{Limit,i}} \leq 0.0005$ (Less than 1, so complied)
NOTE:	Actually, the exposure can be considered as “low power / inherently compliant” without testing based on that the emissions is limited to a level that cannot exceed the basic restriction.

Person responsible for making this declaration:

Zhang Weimin  
 RF Engineer, EMC Lab  
 Reliability Laboratory of Huawei Technologies Co., Ltd.  
 April 22, 2015