



FCC Maximum Permissible Exposure (MPE) Estimation Report

**Product Name: UMTS Enhanced Pico Base Station
Model Number: ePico3801**

**Report No: SYBH(R)015092009EB-3
FCC ID: QISEPICO3801**

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518



Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



REPORT ON FCC Maximum Permissible Exposure (MPE) Estimation of UMTS Enhanced Pico Base Station

Model Number: ePico3801


Report No: SYBH(R)015092009EB-3

FCC ID: QISEPICO3801

REGULATION FCC 47CFR Part 1 (10-1-08 Edition)
 FCC 47CFR Part 2 (10-1-08 Edition)
 OET Bulletin 65 (Edition 97-01)

CONCLUSION **COMPLIANT**

General Manager	2009-10-22	张兴海	
	Date (y-m-d)	Name	

Technical Responsibility For Area of Testing	2009-10-22	胡俊	
	Date (y-m-d)	Name	

Test Lab Engineer	2009-10-22	张卫民	
	Date (y-m-d)	Name	



Contents

1	<u>EUT Information</u>	5
1.1	PRODUCT DESCRIPTION	5
1.2	TECHNICAL DESCRIPTION OF EUT	5
2	<u>FCC RF Exposure Requirements</u>	6
2.1	FCC ROUTINE ENVIRONMENTAL EVALUATION.....	6
2.2	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	8
3	<u>RF Exposure Evaluation</u>	9
3.1	PREDICTION OF THE EXPOSURE TO ELECTROMAGNETIC FIELDS.....	9
3.2	CALCULATION OF THE SAFE DISTANCE	9



1 EUT Information

1.1 Product Description

The ePico is integrated with all NodeB functions and part of the RNC functions. After connected to a office LAN, the ePico communicates with the UMTS AG, hereafter referred to as AG, through xDSL fixed network, public network, and UMTS network. Through the AG, the ePico interacts with the NEs on the Core Network (CN), completing the signaling and services of the UMTS network.

1.2 Technical Description of EUT

Table 1. Service and Test Mode List

Operating frequency band:	Cellular Band: Uplink (RX): 824 to 849 MHz Downlink (TX): 869 to 894 MHz PCS Band: Uplink (RX): 1850 to 1910 MHz Downlink (TX): 1930 to 1990 MHz
Maximum power input to the antenna:	Cellular Band: Rated max.: 24 dBm Measured max.: 23.43 dBm PCS Band: Rated max.: 24 dBm Measured max.: 24.17 dBm (Note: refer to FCC/RF test report for the measured output power)
Antenna Information:	Antenna type: Internal or External, Omni-directional Antenna gain (max.): 6 dBi Typical antenna gain margin: 3 dB (Note: If other antennas with higher gain are used, the report should be re-estimated.)



2 FCC RF Exposure Requirements

2.1 FCC Routine Environmental Evaluation

Base Transceiver Station (BTS) emit RF radiation (Radiation Hazard). Although there is no scientific evidence of possible health risks to persons living near to BTSs some recommendations are giving below for the installation and operation of BTSs. Operators of BTSs are required to obey the local regulation for erecting base station transceivers.

The Federal Communications Commission (FCC) 47CFR §1.1307 requires operator to perform an Environmental Assessment. The objective of the Environmental Evaluation is to ensure that human exposure to RF energy does not go beyond the maximum permissible levels stated in the standard.

As specified in 47CFR §1.1307 and OET Bulletin 65, the Environmental Evaluations are required if the BTS fall into the categories listed in Table 1 of 47CFR §1.1307 and Table 2 of OET Bulletin 65, also summarized and listed in Table 2 below. Other BTS s are categorically excluded from making such studies or preparing an EA, except as indicated in paragraphs (c) and (d) of §1.1307.

Table 2. BTSs Subject To Routine Environmental Evaluation

Service (title 47 CFR rule part)	Evaluation required if:
Cellular Radiotelephone Service (subpart H of part 22)	Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP). Building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP).
Personal Communications Services (part 24)	(1) Narrowband PCS (subpart D): Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP). Building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP). (2) Broadband PCS (subpart E): Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP). Building-mounted antennas: total power of all channels > 2000 W ERP (3280 W EIRP).
Miscellaneous Wireless Communications Services (part 27 except subpart M).	(1) For the 1390–1392 MHz, 1392–1395 MHz, 1432–1435 MHz, 1670–1675 MHz, and 2385–2390 MHz bands: Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP). Building-mounted antennas: total power of all channels > 2000 W ERP (3280 W EIRP). (2) For the 698–746 MHz, 746–764 MHz, 776–794 MHz, 2305–2320 MHz, and 2345–2360 MHz bands: Total power of all channels > 1000 W ERP (1640 W EIRP).
Broadband Radio Service and Educational Broadband Service (subpart M of part 27).	Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP. Building-mounted antennas: power > 1640 W EIRP. BRS and EBS licensees are required to attach a label to subscriber transceiver or transverter antennas that: (1) provides adequate notice regarding potential radiofrequency safety hazards, e.g., information regarding the safe minimum separation distance required between users and transceiver antennas; and (2) references the applicable FCC-adopted limits for radiofrequency exposure specified in §1.1310.



- Note 1: “Building-mounted antennas” means antennas mounted in or on a building structure that is occupied as a workplace or residence.
- Note 2: The term “power” refers to total operating power of the transmitting operation in question in terms of ERP, EIRP or PEP.
- Note 3: For the case of the Cellular Radiotelephone Service (47CFR Part 22 subpart H), the Personal Communications Service (47CFR Part 24) and the Specialized Mobile Radio Service (47CFR Part 90), the phrase “total power of all channels” means the sum of the ERP or EIRP of all co-located simultaneously operating transmitters owned and operated by a single licensee.
- Note 4: When applying the criteria of this table, radiation in all directions should be considered. For the case of transmitting facilities using sectorized transmitting antennas, applicants and licensees should apply the criteria to all transmitting channels in a given sector, noting that for a highly directional antenna there is relatively little contribution to ERP or EIRP summation for other directions.

2.2 Maximum Permissible Exposure (MPE)

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The FCC's MPE limits for field strength and power density are given in 47CFR §1.1310 (also in Table 1 of OET Bulletin 65). These limits (also list in Table 3 below) are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table 3. Limits For Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30
f = frequency in MHz		*Plane-wave equivalent power density		

3 RF Exposure Evaluation

3.1 Prediction of the Exposure to Electromagnetic Fields

As mentioned in OET Bulletin 65, a theoretical approach to calculate possible exposure to electromagnetic radiation around BTS antenna. Precise statements are basically only possible either with measurements or complex calculations considering the complexity of the environment (e.g. soil conditions, near buildings and other obstacles) which causes reflections, scattering of electromagnetic fields.

The maximum output power (given in EIRP) of a BTS is usually limited by license conditions of the network operator.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2} \quad (1)$$

Where:

- S = power density
- P = power input to the antenna
- G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the centre of radiation of the antenna

3.2 Calculation of the Safe Distance

Calculations can be made on a site by site basis to ensure the power density is below the limits given in section 2.2, or guidelines can be done beforehand to ensure the minimum distances from the antenna is maintained through the site planning.

For the EUT (refer to section 1), the power density at safe distance of R = 20cm can be calculated as Table 4:

Table 4. Power density calculation

Cellular Band:	f(TX) = 869 to 894 MHz P = 23.43 dBm = 0.220 W G = 6 dBi = 3.98 numeric S (limit) = $f/1500 = 869/1500 \text{ mW/cm}^2 = 5.8 \text{ W/m}^2$ Population/uncontrolled exposure, for the safety distance of R = 20cm: S = $1.74 \text{ W/m}^2 < S \text{ (limit)}$
PCS Band:	f(TX) = 1930 to 1990 MHz P = 24.17 dBm = 0.261 W G = 6 dBi = 3.98 numeric S (limit) = $1.0 \text{ mW/cm}^2 = 10 \text{ W/m}^2$ Population/uncontrolled exposure, for the safety distance of R = 20cm: S = $2.07 \text{ W/m}^2 < S \text{ (limit)}$



-
-
- | | |
|---------|---|
| Note 1: | The minimum antenna feed line (if external antenna used) loss is taken into account. |
| Note 2: | It is assumed that the RF exposure evaluation is base on the far-field and the MPE is over-estimated. |
| Note 3: | MPE limits that are provided to the customer and only serve as a guideline. The site license holder is ultimately responsible for MPE compliance at a given site. |
| Note 4: | If other antennas with higher gain are used, the report should be re-estimated. |

END