

# FCC Part15.247 Test Report

Product Name : GSM Mobile Phone  
Model No. : HUAWEI ES8100  
Marketing Name : HUAWEI ES8100/ES8100  
FCC ID : QISES8100

Applicant : Huawei Technologies Co., Ltd.

Address : Administration Building, Huawei Base, Bantian, Longgang  
District, Shenzhen 518129

Date of Receipt : 05/12/2011  
Test Date : 05/12/2011~ 23/12/2011  
Issued Date : 29/12/2011  
Report No. : 11CS009R-RF-US-P06V01  
Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

# Test Report Certification

Issued Date : 29/12/2011

Report No. : 11CS009R-RF-US-P06V01



Product Name : GSM Mobile Phone  
 Applicant : Huawei Technologies Co., Ltd.  
 Address : Administration Building, Huawei Base, Bantian, Longgang District, Shenzhen 518129  
 Manufacturer : Huawei Technologies Co., Ltd.  
 Address : Administration Building, Huawei Base, Bantian, Longgang District, Shenzhen 518129  
 Model No. : HUAWEI ES8100  
 Marketing Name : HUAWEI ES8100/ES8100  
 FCC ID : QISES8100  
 EUT Voltage : DC: 3.7V  
 Trade Name : HUAWEI  
 Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2008  
 ANSI C63.4: 2009  
 ANSI C63.10: 2009  
 Test Result : Complied  
 Performed Location : Suzhou EMC Laboratory  
 No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou, China  
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
 FCC Registration Number: 800392

Documented By : Alice Ni  
 (Engineering ADM: Alice Ni)  
 Reviewed By : Robin Wu  
 (Engineering Supervisor: Robin Wu)  
 Approved By : Marlin Chen  
 (Engineering Manager: Marlin Chen)

## Laboratory Information

We, **QuietTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

<b>Taiwan R.O.C.</b>	<b>: BSMI, NCC, TAF</b>
<b>Germany</b>	<b>: TUV Rheinland</b>
<b>Norway</b>	<b>: Nemko, DNV</b>
<b>USA</b>	<b>: FCC, NVLAP</b>
<b>Japan</b>	<b>: VCCI</b>

The related certificate for our laboratories about the test site and management system can be downloaded from QuietTek Corporation's Web Site : <http://www.quietek.com/tw/ctg/cts/accreditations.htm>  
 The address and introduction of QuietTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>  
 If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

### HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.  
 TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : [service@quietek.com](mailto:service@quietek.com)



### LinKou Testing Laboratory :

No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen, Lin-Kou Shiang, Taipei, Taiwan, R.O.C.  
 TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : [service@quietek.com](mailto:service@quietek.com)



### Suzhou (China) Testing Laboratory :

No. 99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou,China.  
 TEL : +86-512-6251-5088 / FAX : +86-512-6251-5098 E-Mail : [service@quietek.com](mailto:service@quietek.com)



**TABLE OF CONTENTS**

Description	Page
1. General Information.....	7
1.1. EUT Description .....	7
1.2. Mode of Operation .....	10
1.3. Tested System Details.....	11
1.4. Configuration of Tested System .....	12
1.5. EUT Exercise Software .....	13
2. Technical Test.....	14
2.1. Summary of Test Result .....	14
2.2. Test Environment .....	15
3. Conducted Emission .....	16
3.1. Test Equipment .....	16
3.2. Test Setup .....	16
3.3. Limit.....	17
3.4. Test Procedure .....	17
3.5. Uncertainty .....	17
3.6. Test Result .....	18
4. Radiated Emission .....	20
4.1. Test Equipment .....	20
4.2. Test Setup .....	21
4.3. Limit.....	22
4.4. Test Procedure .....	22
4.5. Uncertainty .....	22
4.6. Test Result .....	23
5. 20dB Bandwidth .....	26
5.1. Test Equipment .....	26
5.2. Test Setup .....	26
5.3. Limit.....	26
5.4. Test Procedure .....	27
5.5. Uncertainty .....	27
5.6. Test Result .....	28
6. Carrier Frequency Separation .....	34
6.1. Test Equipment .....	34
6.2. Test Setup .....	34
6.3. Limit.....	34
6.4. Test Procedure .....	35
6.5. Uncertainty .....	35
6.6. Test Result .....	36

7.	Number of Hopping Frequencies .....	42
7.1.	Test Equipment .....	42
7.2.	Test Setup .....	42
7.3.	Limit.....	42
7.4.	Test Procedure .....	43
7.5.	Uncertainty .....	43
7.6.	Test Result .....	44
8.	Time of Occupancy (Dwell Time).....	53
8.1.	Test Equipment .....	53
8.2.	Test Setup .....	53
8.3.	Limit.....	53
8.4.	Test Procedure .....	54
8.5.	Uncertainty .....	54
8.6.	Test Result .....	55
9.	Peak Output Power .....	61
9.1.	Test Equipment .....	61
9.2.	Test Setup .....	61
9.3.	Limit.....	61
9.4.	Test Procedure .....	62
9.5.	Uncertainty .....	62
9.6.	Test Result .....	63
10.	Band-edge Compliance of RF Conducted Emissions .....	69
10.1.	Test Equipment .....	69
10.2.	Test Setup .....	69
10.3.	Limit.....	69
10.4.	Test Procedure .....	70
10.5.	Uncertainty .....	70
10.6.	Test Result .....	71
11.	Spurious RF Conducted Emissions.....	75
11.1.	Test Equipment .....	75
11.2.	Test Setup .....	75
11.3.	Limit.....	75
11.4.	Test Procedure .....	76
11.5.	Uncertainty .....	76
11.6.	Test Result .....	77
12.	Radiated Emission Band Edge.....	28
12.1.	Test Equipment .....	83
12.2.	Test Setup .....	84

12.3. Limit.....84  
12.4. Test Procedure .....84  
12.5. Uncertainty .....85  
12.6. Test Result .....86

## 1. General Information

### 1.1. EUT Description

Product Name	GSM Mobile Phone
Model No.	HUAWEI ES8100
Hardware Version	ELEPHANT-V2.0
Software Version	ES8100V100R001C00B204SP00
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
<b>GPS</b>	
Operate Frequency	1575.42MHz
Type of modulation	BPSK
<b>2G</b>	
Support Band	GSM850/PCS1900
GPRS Type	Class B
GPRS Class	Class 12
Tx Frequency Range	GSM 850: 824~849MHz PCS 1900: 1850~1910MHz
Rx Frequency Range	GSM 850: 869~894MHz PCS 1900: 1930~1990MHz
Release Version	R99
Type of modulation	GMSK for GSM/GPRS
Antenna Gain	-2.4dBi for GSM850 -2.2dBi for PCS1900
<b>Bluetooth</b>	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.1+EDR
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Gain	-2dBi
<b>Wi-Fi</b>	
Wi-Fi Frequency	2412~2462MHz
Type of modulation	802.11b: DSSS; 802.11g: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps

Antenna Gain	-2dBi
<b>Components</b>	
Headset Model Number	HT-1350002-39K001
Battery	Brand name: HUAWEI Model No. : HB4H1 Voltage and Capacitance: DC 3.7V 1000mAh
Adapter #1	Brand name: HUAWEI Model No. : HS-050040E5 Input: AC 100V-240V 50/60Hz, 0.2A Output: DC 5 V/400mA
Adapter #2	Brand name: HUAWEI Model No. : HS-050040U6 Input: AC 100V-240V 50/60Hz, 0.2A Output: DC 5 V/400mA

Note : Adapter #1 is used for RF test.

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

**1.2. Mode of Operation**

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The report number is 11CS009R-HP-US-P01V01.

**1.3. Tested System Details**

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



**1.5. EUT Exercise Software**

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Execute the software provided by applicant on the phone.
4	Select test channel and test mode to test.

## 2. Technical Test

### 2.1. Summary of Test Result

No deviations from the test standards

Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No

**2.2. Test Environment**

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

### 3. Conducted Emission


#### 3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100726	2012.04.23
Two-Line V-Network	R&S	ENV216	100043	2012.04.29
Two-Line V-Network	R&S	ENV216	100044	2012.09.07
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2012.05.05
50ohm Termination	SHX	TF2	07081401	2012.09.22
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2012.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

#### 3.2. Test Setup



**3.3. Limit**

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**3.4. Test Procedure**

According to FCC ANSI C63.4: 2009 & ANSI C63.10: 2009.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

**3.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 2.02$  dB


### 3.6. Test Result

Engineer: Nancy	
Site: TR1	Time: 2011/12/09 - 15:32
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Line
EUT: GSM Mobile phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.190	50.511	40.652	-13.526	64.037	9.858	QP
2		0.190	32.119	22.261	-21.918	54.037	9.858	AV
3		0.250	44.244	34.376	-17.514	61.757	9.867	QP
4		0.250	27.329	17.462	-24.428	51.757	9.867	AV
5		0.314	38.131	28.256	-21.733	59.864	9.876	QP
6		0.314	18.119	8.244	-31.745	49.864	9.876	AV
7		0.506	39.483	29.577	-16.517	56.000	9.906	QP
8		0.506	23.667	13.762	-22.333	46.000	9.906	AV
9		0.630	38.715	28.850	-17.285	56.000	9.864	QP
10		0.630	22.104	12.240	-23.896	46.000	9.864	AV
11		5.746	35.550	25.659	-24.450	60.000	9.891	QP
12		5.746	17.185	7.294	-32.815	50.000	9.891	AV

Engineer: Nancy	
Site: TR1	Time: 2011/12/09 - 15:39
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101044(0.009-30MHz)	Polarity: Neutral
EUT: GSM Mobile phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.190	48.721	38.795	-15.315	64.037	9.926	QP
2		0.190	26.349	16.423	-27.687	54.037	9.926	AV
3		0.250	42.675	32.751	-19.082	61.757	9.925	QP
4		0.250	23.650	13.725	-28.107	51.757	9.925	AV
5		0.314	40.372	30.415	-19.492	59.864	9.957	QP
6		0.314	20.631	10.674	-29.233	49.864	9.957	AV
7		0.378	37.275	27.287	-21.048	58.323	9.989	QP
8		0.378	18.218	8.230	-30.105	48.323	9.989	AV
9		0.446	35.848	25.815	-21.102	56.949	10.033	QP
10		0.446	18.215	8.183	-28.734	46.949	10.033	AV
11		5.658	30.901	20.762	-29.099	60.000	10.139	QP
12		5.658	19.127	8.987	-30.873	50.000	10.139	AV

## 4. Radiated Emission

### 4.1. Test Equipment

#### Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2012.10.18
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2012.05.05
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2012.01.14

#### Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2012.04.23
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Preamplifier	Quietek	AP-025C	CHM-0511006	2012.05.05
Preamplifier	Quietek	AP-180C	CHM-0602013	2012.05.05
Bilog Type Antenna	Schaffner	CBL6112B	2932	2012.10.18
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
High-Pass Filter	Wainwright	WHKX2.8/18G-12SS	SN1	2012.03.03
Band Reject Filter	Wainwright	WRCG2400/2485-2375 /2510-60/11SS	SN9	2012.03.03
High-Pass Filter	Wainwright	WHKX7.0/18G-8SS	SN16	2012.03.03
Low-Pass Filter	Wainwright	WLKS4500-9SS	SN2	2012.03.03
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2012.05.05
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2012.01.14

**4.2. Test Setup**

Below 1GHz Test Setup:



Above 1GHz Test Setup:



**4.3. Limit**

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

**4.4. Test Procedure**

According to ANSI C63.10: 2009.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

**4.5. Uncertainty**

The measurement uncertainty above 1G is defined as  $\pm 3.9$  dB  
 below 1G is defined as  $\pm 3.8$  dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK\_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.0	101.9	-6.6	95.3	Fundamental	/	PK
	H	148.8	3.4	11.6	15.0	46	-31.0	QP
	H	384.0	2.5	17.1	19.6	46	-26.4	QP
	H	3176.0	44.1	-5.7	38.4	54(Note)	-15.6	PK
	V	4804.0	45.3	-2.1	43.2	54(Note)	-10.8	PK
	H	7206.0	41.8	3.4	45.2	54(Note)	-8.8	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.0	103.2	-6.6	96.6	Fundamental	/	PK
	V	124.1	4.7	12.9	17.6	46	-28.4	QP
	V	380.1	1.4	17.1	18.5	46	-27.5	QP
	V	3116.5	44.3	-5.9	38.4	54(Note)	-15.6	PK
	V	4882.0	43.4	-1.9	41.5	54(Note)	-12.5	PK
	H	7323.0	42.0	3.3	45.3	54(Note)	-8.7	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.0	104.7	-6.7	98.0	Fundamental	/	PK
	H	148.8	3.4	11.6	15.0	46	-31.0	QP
	H	455.8	1.2	18.8	20.0	46	-26.0	QP
	H	3320.5	44.8	-5.5	39.3	54(Note)	-14.7	PK
	V	4960.0	42.2	-1.8	40.4	54(Note)	-13.6	PK
	V	7440.0	41.9	3.4	45.3	54(Note)	-8.7	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK\_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.0	100.3	-6.6	93.7	Fundamental	/	PK
	V	133.3	4.0	12.6	16.6	46	-29.4	QP
	V	340.4	3.7	15.9	19.6	46	-26.4	QP
	V	3227.0	43.6	-5.6	38.0	54(Note)	-16.0	PK
	V	4804.0	41.9	-2.1	39.8	54(Note)	-14.2	PK
	V	7206.0	41.5	3.4	44.9	54(Note)	-9.1	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.1	102.0	-6.6	95.4	Fundamental	/	PK
	H	275.4	2.7	14.2	16.9	46	-29.1	QP
	H	524.7	1.4	20.4	21.8	46	-24.2	QP
	V	3176.0	43.8	-5.7	38.1	54(Note)	-15.9	PK
	V	4882.0	42.7	-1.9	40.8	54(Note)	-13.2	PK
	H	7323.0	41.3	3.3	44.6	54(Note)	-9.4	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.0	103.2	-6.7	96.5	Fundamental	/	PK
	V	226.9	3.6	11.5	15.1	46	-30.9	QP
	V	439.8	2.4	18.5	20.9	46	-25.1	QP
	H	3320.5	44.3	-5.5	38.8	54(Note)	-15.2	PK
	H	4960.0	41.5	-1.8	39.7	54(Note)	-14.3	PK
	H	7440.0	41.6	3.4	45.0	54(Note)	-9.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmitter-3Mbps(8DPSK\_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.0	100.0	-6.6	93.4	Fundamental	/	PK
	H	256.5	2.4	14.5	16.9	46	-29.1	QP
	H	292.8	2.2	14.8	17.0	46	-29.0	QP
	V	3176.0	43.3	-5.7	37.6	54(Note)	-16.4	PK
	V	4804.0	41.9	-2.1	39.8	54(Note)	-14.2	PK
	V	7206.0	41.0	3.4	44.4	54(Note)	-9.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.1	101.8	-6.6	95.2	Fundamental	/	PK
	V	263.7	2.7	14.4	17.1	46	-28.9	QP
	V	539.2	5.0	20.9	25.9	46	-20.1	QP
	H	3227.0	43.1	-5.6	37.5	54(Note)	-16.5	PK
	H	4882.0	41.9	-1.9	40.0	54(Note)	-14.0	PK
	H	7323.0	41.5	3.3	44.8	54(Note)	-9.2	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.0	103.4	-6.7	96.7	Fundamental	/	PK
	H	275.4	2.7	14.2	16.9	46	-29.1	QP
	H	568.8	1.9	21.3	23.2	46	-22.8	QP
	V	3320.5	43.6	-5.5	38.1	54(Note)	-15.9	PK
	V	4960.0	42.0	-1.8	40.2	54(Note)	-13.8	PK
	H	7440.0	42.1	3.4	45.5	54(Note)	-8.5	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

## 5. 20dB Bandwidth


### 5.1 Test Equipment

20dB Bandwidth / TR8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 5.2 Test Setup



### 5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

## 5.4 Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW  $\cong$  1% of the 20dB bandwidth

VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

## 5.5 Uncertainty

The measurement uncertainty is defined as  $\pm 1$  kHz

5.6 Test Result


Product	:	GSM Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	933.78	889.94
39	2441	938.34	899.36
78	2480	966.40	905.08


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1239.0	1150.8
39	2441	1191.0	1144.7
78	2480	1203.0	1160.1


### Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1238.0	1161.6
39	2441	1254.0	1159.6
78	2480	1241.0	1149.1


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



## 6. Carrier Frequency Separation


### 6.1. Test Equipment

Carrier Frequency Separation / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 6.2. Test Setup



### 6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

#### 6.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\cong$  1% of the span

Video (or Average) Bandwidth VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### 6.5. Uncertainty


The measurement uncertainty is defined as  $\pm$  1 kHz

6.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	: GSM Mobile Phone
Test Item	: Carrier Frequency Separation
Test Site	: TR-8
Test Mode	: Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


### Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


### Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



## 7. Number of Hopping Frequencies


### 7.1. Test Equipment

Number of Hopping Frequencies / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 7.2. Test Setup



### 7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

#### 7.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\cong$  1% of the span

VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.


#### 7.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1$  kHz


7.6. Test Result

Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)


Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



## 8. Time of Occupancy (Dwell Time)


### 8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 8.2. Test Setup



### 8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

#### 8.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW  $\cong$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

#### 8.5. Uncertainty

The measurement uncertainty is defined as  $\pm 0.1$  us

8.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps(8DPSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	122.656	< 400	Pass

Test Time Period:  $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec:  $40/50$ msec= $800$  hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec:  $[(383.3 \mu s \times 800)/79] \times 31.6 = 122.656$  msec

Channel 39 (2441MHz)-(3DH1)






Product	:	GSM Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps(8DPSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	261.280	< 400	Pass

Test Time Period:  $0.4 * 79 = 31.6$ sec, Hopping Times Within 1sec:  $20/50$ msec= $400$ hops/sec.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec:  $[(1.633 \text{ ms} * 400) / 79] * 31.6 = 261.280$  msec

**Channel 39 (2441MHz) - (3DH3)**






Product	: GSM Mobile Phone
Test Item	: Time of Occupancy (Dwell Time)
Test Site	: TR-8
Test Mode	: Transmitter-3Mbps(8DPSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	298.168	< 400	Pass

Test Time Period:  $0.4 * 79 = 31.6 \text{sec}$ , Hopping Times Within 1sec:  $13/50 \text{msec} = 260 \text{hops/sec}$ .

- 2441MHz, The Maximum Occupancy Time Within 31.6sec:  $[(2.867 \text{ ms} * 260) / 79] * 31.6 = 298.168 \text{ msec}$

**Channel 39 (2441MHz) - (3DH5)**





## 9. Peak Output Power


### 9.1. Test Equipment

Peak Output Power / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 9.2. Test Setup



### 9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

#### 9.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

#### 9.5. Uncertainty


The measurement uncertainty is defined as  $\pm 1.0$  dB

9.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-4.91	30.00	Pass
39	2441	-3.68	30.00	Pass
78	2480	-1.62	30.00	Pass


DH5 2402MHz



DH5 2441MHz




DH5 2480MHz




Product	:	GSM Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-4.96	30.00	Pass
39	2441	-3.76	30.00	Pass
78	2480	-1.52	30.00	Pass


### 2DH5 2402MHz



2DH5 2441MHz




2DH5 2480MHz




Product	: GSM Mobile Phone
Test Item	: Power Output
Test Mode	: Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-4.93	30.00	Pass
39	2441	-3.69	30.00	Pass
78	2480	-1.62	30.00	Pass


### 3DH5 2402MHz



3DH5 2441MHz



3DH5 2480MHz



## 10. Band-edge Compliance of RF Conducted Emissions


### 10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 10.2. Test Setup



### 10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

#### 10.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW  $\cong$  1% of the span

VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


#### 10.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1.0$  dB


10.6. Test Result

Product	: GSM Mobile Phone
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	: GSM Mobile Phone
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

### Channel 00 (2402MHz)




### Channel 78 (2480MHz)




Product	: GSM Mobile Phone
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 3: Transmitter-3Mbps(8DPSK_DH5)

### Channel 00 (2402MHz)





### Channel 78 (2480MHz)



Product	: GSM Mobile Phone
Test Item	: Band-edge Compliance of RF Conducted Emissions
Test Mode	: Mode 1: Transmitter-1Mbps(GFSK_DH5)

### Hopping Mode



## 11. Spurious RF Conducted Emissions


### 11.1. Test Equipment

Spurious RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 11.2. Test Setup



### 11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

#### **11.4. Test Procedure**

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\cong$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.


#### **11.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 1.0$  dB


11.6. Test Result

Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




**12. Radiated Emission Band Edge**

**12.1. Test Equipment**

Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2012.04.23
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Preamplifier	Quietek	AP-025C	CHM-0511006	2012.05.05
Preamplifier	Quietek	AP-180C	CHM-0602013	2012.05.05
Bilog Type Antenna	Schaffner	CBL6112B	2932	2012.10.18
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2012.05.05
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2012.01.14

**12.2. Test Setup**



**12.3. Limit**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

**12.4. Test Procedure**

According to ANSI C63.10: 2009.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being

corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

## 12.5. Uncertainty

The measurement uncertainty above 1G is defined as  $\pm 3.9 \text{ dB}$   
below 1G is defined as  $\pm 3.8 \text{ dB}$


**12.6. Test Result**

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 17:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.317	47.892	-32.683	74.000	-6.575	PK
2	*	2402.023	95.308	101.890	N/A	N/A	-6.581	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 17:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.279	33.854	-26.721	54.000	-6.575	AV
2	*	2402.070	79.773	86.355	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.158	47.733	-32.842	74.000	-6.575	PK
2	*	2401.744	94.161	100.743	N/A	N/A	-6.581	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.182	33.757	-26.818	54.000	-6.575	AV
2	*	2401.884	78.189	84.771	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 17:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	97.984	104.716	N/A	N/A	-6.732	PK
2		2483.500	47.608	54.353	-26.392	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 17:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	81.588	88.320	N/A	N/A	-6.732	AV
2		2483.500	32.965	39.710	-21.035	54.000	-6.745	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:30
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	94.503	101.235	N/A	N/A	-6.732	PK
2		2483.500	44.855	51.600	-29.145	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	79.424	86.156	N/A	N/A	-6.732	AV
2		2483.500	30.975	37.720	-23.025	54.000	-6.745	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.454	47.029	-33.546	74.000	-6.575	PK
2	*	2401.977	93.749	100.331	N/A	N/A	-6.581	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.064	33.639	-26.936	54.000	-6.575	AV
2	*	2402.070	76.040	82.622	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.632	47.207	-33.368	74.000	-6.575	PK
2	*	2402.163	92.500	99.082	N/A	N/A	-6.582	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:45
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.079	33.654	-26.921	54.000	-6.575	AV
2	*	2402.070	75.255	81.837	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.991	96.492	103.224	N/A	N/A	-6.732	PK
2		2483.500	48.051	54.796	-25.949	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	77.829	84.561	N/A	N/A	-6.732	AV
2		2483.500	30.634	37.379	-23.366	54.000	-6.745	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	92.893	99.625	N/A	N/A	-6.732	PK
2		2483.500	41.881	48.626	-32.119	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	75.521	82.253	N/A	N/A	-6.732	AV
2		2483.500	29.063	35.808	-24.937	54.000	-6.745	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 18:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.694	47.269	-33.306	74.000	-6.575	PK
2	*	2401.930	93.418	100.000	N/A	N/A	-6.581	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:03
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.109	33.684	-26.891	54.000	-6.575	AV
2	*	2401.977	75.696	82.278	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.424	46.999	-33.576	74.000	-6.575	PK
2	*	2401.837	92.474	99.056	N/A	N/A	-6.581	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	27.066	33.641	-26.934	54.000	-6.575	AV
2	*	2402.070	75.484	82.066	N/A	N/A	-6.581	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.002	96.675	103.407	N/A	N/A	-6.732	PK
2		2483.500	44.426	51.171	-29.574	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.090	78.174	84.906	N/A	N/A	-6.732	AV
2		2483.500	31.324	38.069	-22.676	54.000	-6.745	AV

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:17
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.024	92.816	99.548	N/A	N/A	-6.732	PK
2		2483.500	41.580	48.325	-32.420	74.000	-6.745	PK

Engineer: Nancy	
Site: AC5	Time: 2011/12/13 - 19:21
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 3: Transmit at channel 2480MHz By 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.090	76.668	83.400	N/A	N/A	-6.732	AV
2		2483.500	30.135	36.880	-23.865	54.000	-6.745	AV