



FCC Test Report

Product Name:Fixed Wireless Terminal

Model Number: ETS2225

Report No: SYBH(R)E055122008EB-2
FCC ID: QISETS2225

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Huawei Technologies Co Ltd
Huawei Industrial Base,
Bantian Longgang
Shenzhen 518128, P.R China
Tel: +86 755 89651014
Fax: +86 755 89652518



REPORT ON

FCC Test of ETS2225 Fixed Wireless Terminal

M/N:ETS2225

Report No: Report No: SYBHZ(R)E055122008EB-2

REGULATION

FCC CFR47 Part 2: Subpart J;

FCC CFR47 Part 22: Subpart H;

CONCLUSION

Pass

General Manager

2008.12.24
Date

张兴海
Name

signature



Technical Responsibility For Area of Testing

2008.12.24
Date

余 辉
Name

signature

Test Lab Engineer

2008.12.24
Date

胡 俊
Name

signature



Contents

1	<u>Summary</u>	5
2	<u>Product Description</u>	6
2.1	PRODUCTION INFORMATION	6
2.2	MODIFICATION INFORMATION	6
3	<u>Test Site Description</u>	7
3.1	TESTING PERIOD	7
3.2	GENERAL SET UP DESCRIPTION	7
4	<u>Product Description</u>	8
4.1	TECHNICAL CHARACTERISTICS	8
4.2	EUT IDENTIFICATION LIST	10
5	<u>Main Test Instruments</u>	11
6	<u>Transmitter Measurements</u>	12
6.1	EFFECTIVE RADIATED POWER OF TRANSMITTER (ERP)	12
6.2	CONDUCTED OUTPUT POWER	15
6.3	MODULATION CHARACTERISTICS	17
6.4	OCCUPIED BANDWIDTH	19
6.5	BAND EDGES COMPLIANCE	21
6.6	SPURIOUS EMISSION AT ANTENNA TERMINAL	23
6.7	FREQUENCY STABILITY	25
7	<u>System Measurement Uncertainty</u>	29
8	<u>Appendixes</u>	30

1 Summary

The table below summarizes the measurements and results for the ETS2225 Fixed Wireless Terminal. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
2.1046	22.913	Effective Radiated Power of Transmitter	PASS
2.1046	22.913	Conducted Power of Transmitter	PASS
2.1047		Modulation Characteristics	PASS
2.1049		Occupied Bandwidth	PASS
2.1051	22.917	Band Edges compliance	PASS
2.1051	22.917	Spurious Emission at Antenna Terminal	PASS
2.1053	22.917	Radiated Spurious Emission	See Note
2.1055	22.355	Frequency Stability	PASS

Note: The Radiated Spurious Emissions' test results are shown in the EMC report.

2 Product Description

2.1 Production Information

2.1.1 General Description

ETS2225 Fixed Wireless Terminal is subscriber equipment in the CDMA system. The frequency band is US Cellular. The ETS2225 Fixed Wireless Terminal implements such functions as RF signal receiving / Transmitting, CDMA protocol processing, voice and SMS service etc. The ETS2225 Fixed Wireless Terminal uses QSC6010 chipset and Zero-IF technologies.

2.1.2 Support function and Service

The ETS2225 Fixed Wireless Terminal support the function and service as follows:

Table 2 Service and Test mode List

Service Name	Characteristic	Corresponding Test Mode	Note
voice and data	Modulation: QPSK	TM1*	
voice and data	Modulation: HPSK	TM3*	

Note: * Refer to ANSI/TIA-98-E section 1.3 for the information of TM (Test Mode) .

2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable!				

3 Test Site Description

The test site of:

***Huawei Technologies Co. Ltd.
P.O. Box 518129
Huawei base, bantian,
Longgang District, Shenzhen, China***

3.1 Testing Period

The test have been performed during the period of

Dec.10, 2008 to Dec.20,2008

3.2 General Set up Description

ETS2225 Fixed Wireless Terminal can only support CDMA mode and US Cellular Band. During this measurement, the ETS2225 Fixed Wireless Terminal just works in CDMA mode and US Cellular Band.

TM1: Forward Traffic Channel Radio Configuration 1, Reverse Traffic Channel Radio Configuration 1

TM3: Forward Traffic Channel Radio Configuration 3, Reverse Traffic Channel Radio Configuration 3

Parameter	Units	Value
$\hat{I}_{or}$	dBm/1.23 MHz	-104
$\frac{\text{Pilot } E_c}{I_{or}}$	dB	-7
$\frac{\text{Traffic } E_c}{I_{or}}$	dB	-7.4

4 Product Description

4.1 Technical Characteristics

4.1.1 Frequency Range

Table 4 Frequency Range

Uplink band:	824 to 849 MHz
Downlink band:	869 to 894 MHz

4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

Channel spacing:	1.23 MHz
Channel raster:	30 KHz

4.1.3 Type of Emission

Table 6 Type of Emission

Emission Designation:	1M23F9W
-----------------------	---------

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

4.1.4 Environmental Requirements

Table 7 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%-95%RH

4.1.5 Power Source

Table 8 Power Source

AC voltage nominal:	~120V
AC voltage range	~90-240V
AC current maximal:	500mA

4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 9 Applied RF module DC Voltages and Currents

Voltage:	 +2.85V
Current:	150mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)

4.2 EUT Identification List

4.2.1 Board Information

Table 10 Board Information

Fixed Wireless Terminal		
ETS2225		
Board and Module		
Equipment Designation / Description	Serial Number	Remarks
Module board	020CFL1053800127	WLR2SEAU
Interface board	0284291053800143	WLR2PIPU
Battery	20060670000070	NA

4.2.2 Adapter Technical Data

AC/DCAdapter Model: HF-120050E3
 Manufacturer: Dongguan Shilong Fuhua Electronic Co.,Ltd.
 Input Voltage: ~90-240V ;50/60Hz
 Output Voltage:  +12V

AC/DCAdapter Model: HF-120050E3
 Manufacturer: Shenzhen OCT Xinqiao Techonoly Co.,Ltd.
 Input Voltage: ~90-240V ;50/60Hz
 Output Voltage:  +12V

AC/DCAdapter Model: HF-120050E3
 Manufacturer: Shenzhen Moso Power Supply Techonoly Co.,Ltd.
 Input Voltage: ~90-240V ;50/60Hz
 Output Voltage:  +12V

4.2.3 Battery Technical Data

Type: NI-MH Battery
 Manufacturer: Huawei Technologies Co.,Ltd.
 Battery Model: HGB-2A10x3
 Rated capacity: 1000mAH
 Nominal Voltage:  +3.7V
 Charging Voltage:  +4.2V

4.2.4 FCC Identification

Grantee Code: QIS
 Product Code: ETS2225
 FCC Identification: QISETS2225

5 Main Test Instruments

Table 11 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until (MM.DD.YYYY)
Test Receiver Display Unit	R&S	ESMI 804.8932.52	829214/011	04.22.2009
Test Receiver RF Unit	R&S	ESMI 1032.5640.53	829550/008	04.22.2009
Receiver	R&S	ESIB 26	100318	05.21.2009
Receiver	R&S	ESCS30	830245/018	05.29.2009
Pre-Amplifier	Agilent	8447D	2944A10146	05.21.2009
Pre-Amplifier	Agilent	83017A	3950M00246	05.21.2009
Loop Antenna	Schwarzbeck	FMZB1516	1516115	05.29.2009
BiLog Antenna	Schaffner	CBL 6112B	2747	02.25.2009
BiLog Antenna	Schaffner	CBL 6112B	2536	06.07.2009
Horn Antenna	ETS-Lindgren	3117	00062549	06.05.2009
Horn Antenna	ETS-Lindgren	3116	00031541	03.20.2009
Dipole	Schwarzbeck	D69250-UHAP/D69250-VHAP	979/917	08.27.2009
Signal Generator	R&S	SMT06	830264/009	09.29.2009
Signal Generator	R&S	SMR 40	100325	09.09.2009
Artificial Mains Network	R&S	ENV4200	100001	07.20.2009
Power Supply	Keithley	2306	1045337	09.14.2009
Climate Chamber	WEISS	WK11-180	58226049470010	12.09.2009
Universal Radio Communication Tester	R&S	CMU200	108522	05.29.2009
Wireless communication test set	Agilent	8960	GB45360866	11.20.2009
Spectrum Analyzer	Agilent	PSA E4440A	MY46187137	11.24.2009
Vector Generator	R&S	SMU 200A	101717	06.20.2009

6 Transmitter Measurements

6.1 Effective Radiated Power of Transmitter (ERP)

6.1.1 Test Conditions

Table 12 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1 and TM3 at frequency B,M,T

6.1.2 Test Specifications and Limits

6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 22.913

6.1.2.2 Supporting Standards

Table 13 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.1.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a ETS2225 Fixed Wireless Terminal transmitter exceed 7 W. The calculated longitude ERP by following formula: $ERP(dBm) = 10 \cdot \log(ERP_{in\ mwatts})$.

Table 14 Limits


Maximum Output Power (Watts)	< 7 Watts
Maximum Output Power (dBm)	< 38.5 dBm

6.1.3 Test Method and Setup

- For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, ERP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the ETS2225 Fixed Wireless Terminal to the wireless communication tester Agilent 8960 via the air interface. The band class is set as US Cellular.
- Test the Radiated maximum output power by the Agilent 8960 received from test antenna.
- Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step (b) on Agilent 8960, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.

Test setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP




Figure 1. Test Set-up

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

6.1.4 Measurement Results

Table 15 Measurement Results

TEST CONDITIONS		RF Output Power(ERP)					
		Channel1013(B) 824.7MHz		Channel283(M) 833.49Mhz		Channel777(T) 848.31MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	T _{nom} (25 °C)	24.42	38.5	24.36	38.5	25.09	38.5
	V _{nom} (3.7 V)						
TM3	T _{nom} (25 °C)	24.42	38.5	24.12	38.5	24.82	38.5
	V _{nom} (3.7 V)						

6.1.4.1 Substitution Results

Table 16 Substitution Results

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substitution Antenna Type	SGP [dBm]	Substitution Gain [dBd]	Cable Loss [dB]	Substitution Level (ERP) [dBm]	Limit [dBm]	Result
TM1	824.7	24.42	Dipole Ant.	27.49	-2.95	0.6	23.94	38.5	Pass
TM1	833.49	24.36	Dipole Ant.	27.6	-3.02	0.6	23.98	38.5	Pass
TM1	848.31	25.09	Dipole Ant.	28.39	-3.11	0.6	24.68	38.5	Pass
TM3	824.7	24.42	Dipole Ant.	27.87	-2.95	0.6	24.32	38.5	Pass
TM3	833.49	24.12	Dipole Ant.	27.52	-3.02	0.6	23.90	38.5	Pass
TM3	848.31	24.82	Dipole Ant.	28	-3.11	0.6	24.29	38.5	Pass

Note: a, For get the ERP (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

NOTE: SGP- Signal Generator Level

b, A CDMA signal with bandwidth of 1.23MHz is created by the vector generator R&S SMU200A.

c, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 1.23MHz.

6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.2 Conducted output power

6.2.1 Test Conditions

Table 17 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1 and TM3 at frequency B,M,T

6.2.2 Test Specifications and Limits

6.2.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 22.913

6.2.2.2 Supporting Standards

Table 18 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.2.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a mobile station transmitter exceed 7 W. The calculated longitude ERP by following formula:

$$ERP(dBm) = 10 \cdot \log(ERP_{in \text{ mwatts}}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$P_{cod.}(dBm) = ERP(dBm) - Gain(dBd).$$

and $Gain(dBd) = Gain(dBi) - 2.15dB$

Table 19 Limits

Maximum Output Power (Watts)	< 7 Watts
Antenna Gain(dBd):	-0.15
Maximum Conducted Output Power (dBm)	< 38.65dBm

6.2.3 Test Method and Setup

(a)For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the Mobile Station to the wireless communication tester Agilent 8960 via the antenna connector. The band class is set as US Cellular.

(b)Test the Conducted maximum output power by the Agilent 8960.

Test setup




Figure 2. Test Set-up

6.2.4 Measurement Results

Table 20 Measurement Results

TEST CONDITIONS		RF Output Power(ERP)					
		Channel1013(B) 824.7MHz		Channel283(M) 833.49Mhz		Channel777(T) 848.31MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	T _{nom} (25 °C) V _{nom} (3.7V)	24.42	38.5	24.36	38.5	25.09	38.5
TM3	T _{nom} (25 °C) V _{nom} (3.7 V)	24.42	38.5	24.12	38.5	24.82	38.5

6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.3 Modulation Characteristics

6.3.1 Test Conditions

Table 21 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	47 %
Test Configurations:	TM1 and TM3 at frequency M

6.3.2 Test Specifications and Limits

6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 22 subpart H.

6.3.2.2 Supporting Standards

Table 22 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 22 subpart H.

Table 23 Limits

Limits	Not applicable
--------	----------------

6.3.3 Test Method and Setup

Connect the ETS2225 Fixed Wireless Terminal to Universal Radio Communication Tester CMU200 via the antenna connector. The band class is set as US Cellular; the ETS2225 Fixed Wireless Terminal's output is matched with 50 Ω loads, test method was according to ANSI/TIA-98-E. The waveform quality and constellation of the ETS2225 Fixed Wireless Terminal were tested.

Test setup




Figure 3. Test Set-up

6.3.4 Measurement Results

Table 24 Measurement Results

TEST CONDITIONS		Modulation Characteristic	
		Channel283(M) 833.49MHz	
		Measured	
		TM1	TM3
T _{nom} (25 °C)	V _{nom} (3.7V)	Refer to Appendix A	Refer to Appendix A

6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix A.

6.4 Occupied Bandwidth

6.4.1 Test Conditions

Table 25 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	55 %
Test Configurations:	TM1 and TM3 at frequency B,M,T

6.4.2 Test Specifications and Limits

6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and part 22 subpart H.

6.4.2.2 Supporting Standards

Table 26 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.4.2.3 Limits

No specific occupied bandwidth requirement in part 22 subpart H, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 27 Limits

Upper /lower frequency limits	0.5% of the mean power
-------------------------------	------------------------

6.4.3 Test Method and Setup

ETS2225 Fixed Wireless Terminal was connected to the wireless signal analyzer PSA E4440A via the one RF connector. The band class is set as US Cellular; ETS2225 Fixed Wireless Terminal was controlled to transmit maximum power. Measure and record the occupied bandwidth of the ETS2225 Fixed Wireless Terminal by the Agilent E4440A.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g)&(h).

(g) Transmitter in which the modulating base band comprises not more than three independent channels - when modulated by the full complement of signals for which the transmitter is rated. The level of modulation for each channel should be set to that prescribed in rule parts applicable to the services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer's maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

Measurement bandwidth (RBW): 30 kHz (Resolution bandwidth)
Video bandwidth (VBW): 300 kHz

Test Set-up




Figure 4. Test Set-up

6.4.4 Measurement Results

Table 28 Measurement Results

TEST CONDITIONS		Occupied Bandwidth					
		Channel 1013 (B) 824.7MHz		Channel283 (M) 833.49MHz		Channel 777 (T) 848.31MHz	
		Measured (MHz)		Measured (MHz)		Measured (MHz)	
		TM1	TM3	TM1	TM3	TM1	TM3
T _{nom} (25 °C)	V _{nom} (3.7V)	1.2657	1.2702	1.2644	1.2747	1.2599	1.2517

6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix B.

6.5 Band Edges Compliance

6.5.1 Test Conditions

Table 29 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55 %
Test Configurations:	TM1 and TM3 at frequency B, T

6.5.2 Test Specifications and Limits

6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.5.2.2 Supporting Standards

Table 30 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.5.2.3 Limits

Compliance with 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT in Watt).

Table 31 Limits

Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm – 37 dB
Absolute level	- 13 dBm

6.5.3 Test Method and Setup

ETS2225 Fixed Wireless Terminal was connected to the wireless signal analyzer PSA E4440A via the one RF connector, the band class is set as US Cellular. ETS2225 Fixed Wireless Terminal was controlled to transmit maximum power. Measure and record Band edge compliance of the ETS2225 Fixed Wireless Terminal by the Agilent PSA E4440A.

Measurement bandwidth (RBW): 20 kHz (Resolution bandwidth)
Video bandwidth (VBW): 200 kHz

Test Set-up




Figure 5. Test Set-up

6.5.4 Measurement Results

Table 32 Measurement Results outside Band Edges-- Single Carrier

Band	Frequency of Band edges [MHz]	Channel Number	Test Mode	Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
US Cellular	T_{nom} (25 °C), V_{nom} (3.7V)						
	824	1013 (B)	TM1 & TM3	24	<-13(See appendix C)	- 13 dBm	Pass
	849	777 (T)	TM1 & TM3	24	<-13(See appendix C)	- 13 dBm	Pass

6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix C.

6.6 Spurious Emission at Antenna Terminal

6.6.1 Test Conditions

Table 33 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	50 %
Test Configurations:	TM1 and TM3 at frequency B,M,T

6.6.2 Test Specifications and Limits

6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 22.917

6.6.2.2 Supporting Standards

Table 34 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98-E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.6.2.3 Limits

Compliance with part 22.917, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT in Watt).

Table 35 Limits

Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log (0.25) = 37$, 24 dBm – 37 dB
Absolute level	- 13 dBm

6.6.3 Test Method and Setup

ETS2225 Fixed Wireless Terminal was connected to the wireless signal analyzer PSA E4440A via the one RF connector, the band class is set as US Cellular. ETS2225 Fixed Wireless Terminal was controlled to transmit maximum power.

Measure and record the Conducted Spurious Emission of the ETS2225 Fixed Wireless Terminal by the Agilent PSA E4440A.

According to part 22.917, the defined measurement bandwidth as following:

22.917(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30 MHz up to 1 GHz: 100 kHz;
Measurement bandwidth (RBW) for 1GHz up to 12.75GHz: 1MHz;

Test Set-up




Figure 6. Test Set-up

6.6.4 Measurement Results

Table 36 Measurement Results

Channel Number	Test Mode	Test Range (Frequency)	Output Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
Channel 1013(B)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 283(M)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 777(T)	TM1	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
	TM3	9 kHz ~12.75GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass

6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix D.

6.7 Frequency Stability

6.7.1 Test Conditions

Table 37 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	See below
Relative humidity:	55 % at 25 °C
Test Configurations:	TM1 and TM3 at frequency M

6.7.2 Test Specifications and Limits

6.7.2.1 Specification

CFR 47 (FCC) part 2.1055 and part 22.355

6.7.2.2 Supporting Standards

Table 38 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA-98E: 2003	Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations

6.7.2.3 Limits

According to part 22.355, from 821MHz to 896MHz, for mobile device, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances 2.5ppm.

6.7.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in subparagraphs
- (2) and (3) of paragraph 2.1055

(a) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(b) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

(c) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

The EUT can only work in such extreme voltage 3.5V and 4.2V, so here the EUT is tested in the 3.5V and 4.2V.

Test Set up

Connect the ETS2225 Fixed Wireless Terminal to the Wireless Communication test set 8960 via the connector. Then measure the frequency error by the Wireless Communication test set 8960. The ETS2225 Fixed Wireless Terminal's output is matched with a 50 Ω loads.




Figure 7. Test Set up

6.7.4 Measurement Results

6.7.4.1 Measurement Results vs. Variation of Temperature

- TM1, 3.7V DC Channel No.283(833.49MHz)

Table 39 Measurement Results vs. Variation of Temperature—TM1

Temperature	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	24	833.49	3	Pass
-20 °C	24	833.49	2	Pass
-10 °C	24	833.49	-6	Pass
0 °C	24	833.49	0	Pass
+10 °C	24	833.49	-2	Pass
+20 °C	24	833.49	1	Pass
+30 °C	24	833.49	-5	Pass
+40 °C	24	833.49	2	Pass
+50 °C	24	833.49	-3	Pass




Figure 8. TM1 Test Graph

● TM3, 3.7V DC Channel No.283(833.49MHz)

Table 40 Measurement Results vs. Variation of Temperature—TM3

Temperature	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	24	833.49	4	Pass
-20 °C	24	833.49	-3	Pass
-10 °C	24	833.49	4	Pass
0 °C	24	833.49	5	Pass
+10 °C	24	833.49	-2	Pass
+20 °C	24	833.49	7	Pass
+30 °C	24	833.49	6	Pass
+40 °C	24	833.49	-4	Pass
+50 °C	24	833.49	1	Pass




Figure 9. TM3 Test Graph

6.7.4.2 Measurement Results vs. Variation of Voltage

- TM1, 25 °C ,Channel No. **283(833.49MHz)**

Table 41 Measurement Results vs. Variation of Voltage—TM1

Voltage	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5	24	833.49	-4	Pass
3.7	24	833.49	7	Pass
4.2	24	833.49	1	Pass

- TM3, 25 °C ,Channel No. **283(833.49MHz)**

Table 42 Measurement Results vs. Variation of Voltage—TM3

Voltage	Power (dBm)	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
3.5	24	833.49	5	Pass
3.7	24	833.49	-6	Pass
4.2	24	833.49	2	Pass

6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 43 System Measurement Uncertainty

Items		Extended Uncertainty
Effective Radiated Power of Transmitter	ERP(dBm)	U=3dB; k=2
Band Width	Magnitude (%)	U=0.2%; k=2
Band Edge Compliance	Disturbance Power (dBm)	U=2.0dB; k=2
Conducted Spurious Emission at Antenna Terminal	Disturbance Power (dBm)	U=2.0dB; k=2
Frequency Stability	Frequency Accuracy(ppm)	U=0.21ppm; k=2
Field Strength of Spurious Radiation	ERP(dBm)	U=2.2dB; k=2
Conducted Output Power	Power(dBm)	U=0.39dB; k=2



8 Appendixes

Appendix A	Measurement Results Modulation Characteristics	7 pages
Appendix B	Measurement Results Occupied Bandwidth	7 pages
Appendix C	Measurement Results Band Edges	5 pages
Appendix D	Measurement Results Spurious Emission at Antenna Terminal	25 pages

----- END OF REPORT -----