



FCC Test Report

Product Name: Cordless Phone

Model Number: HUAWEI ETS8321

Report No: SYBH(R)082052008EB-2
FCC ID: QISETS8321

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



REPORT ON **FCC Test of HUAWEI ETS8321 Cordless Phone**
 M/N: ETS8321

Report No: SYBH(R)082052008EB-2

REGULATION **FCC CFR47 Part 2: Subpart J;**
 FCC CFR47 Part 24: Subpart E;

Final Judgement: Pass

General Manager

2008.05.21

张兴海

Date

Name

signature



Technical Responsibility
For Area of Testing

2008.05.19

余 辉

Date

Name

signature

A handwritten signature in black ink, which appears to be "余辉" (Yu Hui).

Test Lab Engineer

2008.05.17

胡 俊

Date

Name

signature

A handwritten signature in black ink, which appears to be "胡俊" (Hu Jun).

Contents

| | | |
|----------|---|-----------|
| 1 | <u>Summary</u> | 5 |
| 2 | <u>Product Description</u> | 6 |
| 2.1 | PRODUCTION INFORMATION | 6 |
| 2.2 | MODIFICATION INFORMATION..... | 6 |
| 3 | <u>Test Site Description</u> | 7 |
| 3.1 | TESTING PERIOD | 7 |
| 3.2 | GENERAL SET UP DESCRIPTION | 7 |
| 4 | <u>Product Description</u> | 8 |
| 4.1 | TECHNICAL CHARACTERISTICS | 8 |
| 4.2 | EUT IDENTIFICATION LIST | 10 |
| 5 | BOARD INFORMATION | 错误！未定义书签。 |
| 6 | <u>Main Test Instruments</u> | 11 |
| 7 | <u>Transmitter Measurements</u> | 12 |
| 7.1 | EFFECTIVE RADIATED POWER OF TRANSMITTER (EIRP)..... | 12 |
| 7.2 | CONDUCTED POWER OF TRANSMITTER..... | 15 |
| 7.3 | MODULATION CHARACTERISTICS | 17 |
| 7.4 | OCCUPIED BANDWIDTH..... | 19 |
| 7.5 | BAND EDGES COMPLIANCE | 21 |
| 7.6 | SPURIOUS EMISSION AT ANTENNA TERMINAL | 23 |
| 7.7 | FREQUENCY STABILITY | 25 |
| 8 | <u>System Measurement Uncertainty</u> | 28 |
| 9 | <u>Appendices</u> | 29 |



1 Summary

The table below summarizes the measurements and results for the HUAWEI GSM Cordless Phone. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

| FCC Measurement Specification | FCC Limits Part(s) | Description | Result |
|--------------------------------------|---------------------------|--|---------------|
| 2.1046 | 24.232 | Effective Radiated Power of Transmitter | PASS |
| 2.1046 | 24.232 | Conducted Power of Transmitter | PASS |
| 2.1047 | | Modulation Characteristics | PASS |
| 2.1049 | | Occupied Bandwidth | PASS |
| 2.1051 | 24.238 | Band Edges Compliance | PASS |
| 2.1051 | 24.238 | Spurious Emission at Antenna Terminal | PASS |
| 2.1055 | 24.235 | Frequency Stability | PASS |
| 2.1053 | 22.917 | Radiated Spurious Emissions | PASS |

Note : The Radiated Spurious Emissions' test results are shown in the EMC report.



2 Product Description

2.1 Production Information

2.1.1 General Description

HUAWEI ETS8321 Cordless Phone is subscriber equipment in the GSM system. The GSM frequency band includes 850M and PCS 1900M, ETS8321 implements such functions as RF signal receiving/transmitting, GSM protocol processing, voice and SMS service etc. Externally it provides Mini-USB interface (to connect to the PC etc.), SIM card interface.

2.1.2 Support function and Service

The HUAWEI GSM Cordless Phone support the function and service as follows:

Table 2 Service and Test mode List

| Service Name | Characteristic | Corresponding Test Mode | Note |
|----------------|------------------|-------------------------|------|
| Voice and data | Modulation: GMSK | TM1 | GSM |

2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

| Model Number | Board/Module | Original Version | New Version | Modify Information |
|----------------|--------------|------------------|-------------|--------------------|
| Not applicable | | | | |
| | | | | |
| | | | | |
| | | | | |



3 Test Site Description

The test site of:

***Huawei Technologies Co. Ltd.
P.O. Box 518129
Huawei base, bantian,
Longgang District, Shenzhen, China***

The test site description has been submitted to  and registration granted under the registration number **97456** on Aug 20.2006. The test site has been accredited by



and the accredited number is **2174.01** in Jan of 2006.

3.1 Testing Period

The test have been performed during the period of

May. 01, 2008 –May. 16, 2008

3.2 General Set up Description

Cordless Phone can support GSM 850M and US PCS Band. During this measurement, the Cordless Phone just works in GSM 850M and US PCS Band.

TM1: GSM Mode with GMSK Modulation



4 Product Description

4.1 Technical Characteristics

4.1.1 Frequency Range

Table 4 Frequency Range

| | |
|----------------|-----------------|
| Uplink band: | 1850 to 1910MHz |
| Downlink band: | 1930 to 1990MHz |

4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

| | |
|-----------------|----------|
| | GSM1900M |
| Channel spacing | 200kHz |
| Channel raster: | 200kHz |

4.1.3 Type of Emission

Table 6 Type of Emission

| | |
|-----------------------|---------|
| | GSM |
| Emission Designation: | 300kGXW |

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202



4.1.4 Environmental Requirements

Table 7 Environmental Requirements

| | |
|----------------------|----------|
| Minimum temperature: | -10 °C |
| Maximum temperature: | + 55 °C |
| Relative Humidity: | 5%-95%RH |

4.1.5 Power Source

Table 8 Power Source

| | |
|---------------------|------------|
| AC voltage nominal: | ~120V |
| AC voltage range | ~100V-240V |
| AC current maximal: | 0.5A |

4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 9 Applied RF module DC Voltages and Currents

| | |
|----------|---|
| Voltage: |  2.85V |
| Current: | 2A According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8) |



4.2 EUT Identification List

4.2.1 Board Information

Table10 Board Information

| ETS8321 Cordless Phone | | |
|-------------------------------------|------------------|----------|
| ETS8321 | | |
| Board and Module | | |
| Equipment Designation / Description | Serial Number | Remarks |
| -Module board | 020CFL1067800157 | MG43TCPU |
| -Interface board | 0284291067800181 | WG43MIPU |
| -Battery | 20060520000541 | NA |

4.2.2 Adapter Technical Data

| | |
|--------------------|--|
| AC/DCAdapter Model | TPCA-053065U |
| Manufacturer | Tech-Power International CO.,Ltd. |
| Input Voltage | 100-240V ~50/60Hz 0.2 A |
| Output Voltage |  5.3V 650mA |
| Rated Power | <2W |
| AC/DCAdapter Model | XQLCHW04A |
| Manufacturer | Xinqiao electronic Techonoly Co.,Ltd. |
| Input Voltage | 100-240V ~50/60Hz 0.15 A |
| Output Voltage |  5.3V 650mA |
| Rated Power | <2W |

4.2.3 Battery Technical Data

| | |
|-------------------|---|
| Type: | Rechargeable NiMH Battery |
| Manufacturer: | Huawei Technologies Co., Ltd. |
| Battery Model: | HBC85S |
| Rated capacity: | 850mAH |
| Nominal Voltage: |  +3.7V |
| Charging Voltage: |  +4.2V |

4.2.4 FCC Identification

| | |
|---------------------|------------|
| Grantee Code: | QIS |
| Product Code: | ETS8321 |
| FCC Identification: | QISETS8321 |

5 Main Test Instruments

Table 10 Main Test Equipments

| Equipment Description | Manufacturer | Model | Serial Number | Calibrated until (MM.DD.YYYY) |
|--------------------------------------|--------------|-------------------------|---------------|-------------------------------|
| Test Receiver Display Unit | R&S | ESMI 804.8932.52 | 829214/011 | 08.23.2008 |
| Test Receiver RF Unit | R&S | ESMI 1032.5640.53 | 829550/008 | 08.23.2008 |
| Receiver | R&S | ESIB 26 | 100318 | 08.29.2008 |
| Receiver | R&S | ESCS30 | 830245/018 | 08.29.2008 |
| Pre-Amplifier | Agilent | 8447D | 2944A10146 | 08.21.2008 |
| Pre-Amplifier | Agilent | 83017A | 3950M00246 | 09.04.2008 |
| Loop Antenna | Schwarzbeck | FMZB1516 | 1516115 | 11.20.2008 |
| BiLog Antenna | Schaffner | CBL 6112B | 2536 | 09.25.2008 |
| Horn Antenna | ETS-Lindgren | 3117 | 00062533 | 11.05.2008 |
| Horn Antenna | ETS-Lindgren | 3116 | 00031541 | 11.20.2008 |
| Dipole | Schwarzbeck | D69250-UHAP/D69250-VHAP | 979/917 | 08.27.2008 |
| Signal Generator | R&S | SMT06 | 830264/009 | 09.29.2008 |
| Signal Generator | R&S | SMU200A | 3605062518 | 10.08.2008 |
| Signal Generator | R&S | SMR 40 | 100325 | 12.09.2008 |
| Power Supply | Keithley | 2306 | 1045337 | 07.20.2008 |
| Climate Chamber | WEISS | ACS-1 | 3604040034 | 08.14.2008 |
| Universal Radio Communication Tester | R&S | CMU200 | 108035 | 07.04.2008 |
| Wireless communication test set | Agilent | 8960 | GB43461081 | 11.15.2008 |
| Power Splitter | Agilent | 11667B | 3586M000159 | 07.20.2008 |
| Spectrum Analyzer | Agilent | E4440A | N/A | 09.26.2008 |

6 Transmitter Measurements

6.1 Effective Isotropic Radiated Power of Transmitter (EIRP)

6.1.1 Test Conditions

Table 11 Test Conditions

| | |
|----------------------|--------------------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | enclosure |
| Ambient temperature: | 25 |
| Relative humidity: | 55% |
| Test Configurations: | TM1 at frequency Bottom、 Middle、 Top |

6.1.2 Test Specifications and Limits

6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and part 24.232

6.1.2.2 Supporting Standards

Table 12 Supporting Standards:

| | |
|---------------------------|---|
| ANSI/TIA-603-C:2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |

6.1.2.3 Limits

Compliance with part 22.913, in no any case may the peak power of a mobile station transmitter exceed 7 W. And calculate longitude ERP by following formula : $ERP(dBm) = 10 * \log(ERP_{in\ mwatts})$. $EIRP(dBm) = ERP(dBm) + 2.15dB$.

Table 13 Limits

| | |
|------------------------------|-----------|
| Maximum Output Power (Watts) | < 2 Watts |
| Maximum Output Power (dBm) | < 33 dBm |


6.1.3 Test Method and Setup

- For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the Cordless Phone to the wireless communication tester R&S CMU200 via the air interface. The band class is set as PCS.
- Test the Radiated maximum output power by the CMU200 received from test antenna.
- Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step (b) on CMU200, and record the

power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated..

Test setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum EIRP




Figure 1. Test Set-up

NOTE: Effective Isotropic radiated power (EIRP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

There is a constant difference of 2.15 dB between EIRP and ERP.

$EIRP (dBm) = ERP (dBm) + 2.15$ (ITU-R Recommendation SM.329-10).

6.1.4 Measurement Results

6.1.4.1 Pre-test Results

Table 14 Measurement Results

| TEST CONDITIONS | | RF Output Power (EIRP) | | | | | |
|-----------------|---|----------------------------|-------|---------------------------|-------|----------------------------|-------|
| | | Channel512(B) 1850.2MHz | | Channel661 (M) 1880MHz | | Channel810(T) 1909.8MHz | |
| | | dBm | | dBm | | dBm | |
| | | Measured | Limit | Measured | Limit | Measured | Limit |
| TM1 | T _{nom} (25 °C) V _{nom} (3.7V) | 29.28 | 33 | 29.27 | 33 | 29.32 | 33 |

6.1.4.2 Substitution Results

Table 15 Substitution Results

| Test Mode | Freq. [MHz] | Meas. Level [dBm] | Substitution Antenna Type | SGP [dBm] | Substitution Gain [dBi] | Cable Loss [dB] | Substitution Level (EIRP) [dBm] | Limit [dBm] | Result |
|-----------|-------------|-------------------|---------------------------|-----------|-------------------------|-----------------|---------------------------------|-------------|--------|
| TM1 | 1850.2 | 29.28 | Dipole Ant. | 25.62 | 4.6 | 1.0 | 29.22 | 33 | Pass |
| TM1 | 1880.0 | 29.27 | Dipole Ant. | 25.59 | 4.6 | 1.0 | 29.19 | 33 | Pass |
| TM1 | 1909.8 | 29.32 | Dipole Ant. | 25.15 | 4.8 | 1.0 | 28.95 | 33 | Pass |

Note: a, For get the EIRP in substitution method, the following formula should take to calculate it,

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

NOTE: SGP- Signal Generator Level

b, A GSM signal with bandwidth of 200kHz are created by the vector generator R&S SMU200A.

c, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 200kHz for TM1.

6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.2 Conducted Power of Transmitter

6.2.1 Test Conditions

Table 16 Test Conditions

| | |
|----------------------|--------------------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | 25 °C |
| Relative humidity: | 52 % |
| Test Configurations: | TM1 at frequency Bottom、 Middle、 Top |

6.2.2 Test Specifications and Limits

6.2.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 24 subpart E

6.2.2.2 Supporting Standards

Table 17 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.2.2.3 Limits

Compliance with part 24.232, in no any case may the peak power of a mobile station transmitter exceed 2 W. The calculated longitude EIRP by following formula:

$$EIRP(dBm) = 10 * \log(EIRP_{in\ mW}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$P_{cod}(dBm) = EIRP(dBm) - Gain(dBi).$$

and $Gain(dBi) = Gain(dBd) + 2.15dB$

Table 18 Limits

| | |
|--------------------------------------|---------------------|
| Maximum Output Power (Watts) | < 2 Watts (33dBm) |
| Antenna Gain(dBi): | 2.5 |
| Maximum Conducted Output Power (dBm) | < 30.5dBm |

6.2.3 Test Method and Setup

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the Cordless Phone to the wireless communication tester CMU200 via the antenna connector. The band class is set as PCS Cellular.

(b) Test the Conducted maximum output power by the CMU200.

Test setup




Figure 2. Test Set-up

6.2.4 Measurement Results

Table 19 Measurement Results

| TEST CONDITIONS | | RF Output Power(Conducted) | | | | | |
|-----------------|---|----------------------------|-------|---------------------------|-------|----------------------------|-------|
| | | Channel512(B) 1850.2MHz | | Channel661 (M) 1880MHz | | Channel810(T) 1909.8MHz | |
| | | dBm | | dBm | | dBm | |
| | | Measured | Limit | Measured | Limit | Measured | Limit |
| TM1 | T _{nom} (25 °C) V _{nom} (3.7V) | 29.28 | 30.5 | 29.27 | 30.5 | 29.32 | 30.5 |

6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.3 Modulation Characteristics

6.3.1 Test Conditions

Table 20 Test Conditions

| | |
|----------------------|-------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | 25 °C |
| Relative humidity: | 52 % |
| Test Configurations: | TM1 at frequency Middle |

6.3.2 Test Specifications and Limits

6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and part 24 subpart E

6.3.2.2 Supporting Standards

Table 21 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 24 subpart E.

Table 22 Limits

| | |
|--------|----------------|
| Limits | Not applicable |
|--------|----------------|

6.3.3 Test Method and Setup

Connect the Cordless Phone to Universal Radio Communication Tester CMU200 via the antenna connector. The frequency band is set as PCS; the Cordless Phone's output is matched with 50 Ω load, test method was according to 3GPP TS 51.010. The waveform quality and constellation of the Cordless Phone was tested.

Test setup




Figure 3. Test Set-up

6.3.4 Measurement Results

Table 23 Measurement Results

| | | Modulation Characteristic |
|-------------------|------------------|---------------------------|
| TEST CONDITIONS | | Channel661(M) 1880MHz |
| | | Measured |
| | | TM1 |
| T_{nom} (25 °C) | V_{nom} (3.7V) | Refer to Appendix A |

6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix A.

6.4 Occupied Bandwidth

6.4.1 Test Conditions

Table 24 Test Conditions

| | |
|----------------------|--------------------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | 25 °C |
| Relative humidity: | 55 % |
| Test Configurations: | TM1 at frequency Bottom, Middle, Top |

6.4.2 Test Specifications and Limits

6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and part 24 subpart E

6.4.2.2 Supporting Standards

Table 25 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.4.2.3 Limits

No specific occupied bandwidth requirement in part 24 subpart E, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 26 Limits

| | |
|-------------------------------|------------------------|
| Upper /lower frequency limits | 0.5% of the mean power |
|-------------------------------|------------------------|

6.4.3 Test Method and Setup

Cordless Phone was connected to the Spectrum Analyzer AGILENT E4440A via the one RF connector. The band class is set as PCS; The EUT was controlled to transmit maximum power. Measure and record the occupied bandwidth of the EUT by the AGILENT E4440A.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g)&(h).

(g) Transmitter in which the modulating base band comprises not more than three independent channels - when modulated by the full complement of signals for which the transmitter is rated. The

level of modulation for each channel should be set to that prescribed in rule parts applicable to the services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer's maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

For TM1 following RBW and VBW are employed:
 Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)
 Video bandwidth (VBW): 10 kHz

Test Set-up




Figure 4. Test Set-up

6.4.4 Measurement Results

Table 27 Measurement Results

| TEST CONDITIONS | | Occupied Bandwidth | | |
|---|-----|-----------------------------|---------------------------|-----------------------------|
| | | Channel512 (B) 1850.2MHz | Channel661 (M) 1880MHz | Channel810 (T) 1909.8MHz |
| | | Measured (kHz) | Measured (kHz) | Measured (kHz) |
| | | TM1 | TM1 | TM1 |
| T _{nom} (25 °C) V _{nom} (3.7V) | 99% | 244.25 | 247.55 | 244.09 |

6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.
 For the measurement results refer to appendix B.

6.5 Band Edges Compliance

6.5.1 Test Conditions

Table 28 Test Conditions

| | |
|----------------------|------------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | 25°C |
| Relative humidity: | 55 % |
| Test Configurations: | TM1 at frequency Bottom、 Top |

6.5.2 Test Specifications and Limits

6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 24.238

6.5.2.2 Supporting Standards

Table 29 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.5.2.3 Limits

Compliance with part 24.238, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P (W)$. (Whereas P is the rated power of the EUT in Watt).

Table 30 Limits for GPRS

| | |
|-----------------------|--|
| | TM1 |
| Rated Power: | 30 dBm |
| Required attenuation: | $43 + 10 \log (1) = 43$, 30 dBm - 43 dB |
| Absolute level | - 13 dBm |

6.5.3 Test Method and Setup

The EUT was connected to the Spectrum Analyzer AGILENT E4440A via the one RF connector, the band class is set as PCS. The EUT was controlled to transmit maximum power. Measure and record band edges compliance of the EUT by the AGILENT E4440A.

The limit is -13dBm.

For TM1 following RBW and VBW are employed:
 Measurement bandwidth (RBW): 3 kHz (Resolution bandwidth)
 Video bandwidth (VBW): 10 kHz

Test Set-up




Figure 5. Test Set-up

6.5.4 Measurement Results

Table 31 Measurement Results outside Band Edges-- Single Carrier

| Band | Frequency of Band edges [MHz] | Channel Number | Test Mode | Spurious Level measured [dBm] | FCC limit | Result |
|---|-------------------------------|----------------|-----------|-------------------------------|-----------|--------|
| $T_{nom} (25\text{ }^{\circ}\text{C}), V_{nom} (3.7\text{V})$ | | | | | | |
| PCS | 1850.2 | 512 | TM1 | <-13(See appendix C) | - 13 dBm | Pass |
| | 1909.8 | 810 | TM1 | <-13(See appendix C) | - 13 dBm | Pass |

6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.
 For the measurement results refer to appendix C.

6.6 Spurious Emission at Antenna Terminal

6.6.1 Test Conditions

Table 32 Test Conditions

| | |
|----------------------|--------------------------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | 25°C |
| Relative humidity: | 50 % |
| Test Configurations: | TM1 at frequency Bottom, Middle ,Top |

6.6.2 Test Specifications and Limits

6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and part 24.238

6.6.2.2 Supporting Standards

Table 33 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Recommended GSM/EDGE MS conformance specification |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.6.2.3 Limits

Compliance with part 24.238, all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT in Watt).

Table 34 Limits for GPRS Mode

| | |
|-----------------------|---|
| | TM1 |
| Rated Power: | 30 dBm |
| Required attenuation: | $43 + 10 \log(1) = 43$, 30 dBm - 43 dB |
| Absolute level | - 13 dBm |

6.6.3 Test Method and Setup

The EUT was connected to the Spectrum analyzer AGILENT E4440A via the one RF connector, the band class is set as PCS. The EUT was controlled to transmit maximum power. Measure and record the Conducted Spurious Emission of the EUT by the AGILENT E4440A.

According to part 24.238, the defined measurement bandwidth as following:

24.238 (b) Measurement procedure: Compliance with these provisions is based on the use of

measurement instrumentation employing a resolution bandwidth of 1 MHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
 Measurement bandwidth (RBW) for 150 kHz up to 30MHz: 10 kHz;
 Measurement bandwidth (RBW) for 30 MHz up to 20GHz: 1MHz;

Test Set-up




Figure 6. Test Set-up

6.6.4 Measurement Results

Table 35 Measurement Results

| Channel Number | Test Mode | Test Range (Frequency) | Output Power [dBm] | Spurious Level measured [dBm] | FCC limit | Result |
|----------------|-----------|------------------------|--------------------|-------------------------------|-----------|--------|
| Channel 512(B) | TM1 | 9 kHz~20GHz | 30 | <- 13 dBm (See appendix D) | - 13 dBm | Pass |
| Channel 661(M) | TM1 | 9 kHz~20GHz | 30 | <- 13 dBm (See appendix D) | - 13 dBm | Pass |
| Channel 810(T) | TM1 | 9 kHz~20GHz | 30 | <- 13 dBm (See appendix D) | - 13 dBm | Pass |

6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.
 For the measurement results refer to appendix D.

6.7 Frequency Stability

6.7.1 Test Conditions

Table 36 Test Conditions

| | |
|----------------------|--------------------|
| Preconditioning: | 0.5 hour |
| Measured at: | Antenna connector |
| Ambient temperature: | See below |
| Relative humidity: | 55 % at 25 °C |
| Test Configurations: | TM1 at frequency M |

6.7.2 Test Specifications and Limits

6.7.2.1 Specification

CFR 47 (FCC) part 2.1055 and part 24.235

6.7.2.2 Supporting Standards

Table 37 Supporting Standards:

| | |
|----------------------------|--|
| ANSI/TIA-603-C: 2004 | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards |
| 3GPP TS51.010 V6.1.0:2005 | Digital cellular telecommunications system Mobile Station (MS) conformance specification; |
| 3GPP TS 34.121 V7.5.0:2007 | Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD); |

6.7.2.3 Limits

No specific frequency stability requirement in part 2.1055 and part 24.235.

6.7.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30 ° to +50 ° centigrade for all equipment except that specified in subparagraphs (2) and (3) of paragraph 2.1055

(b) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(d) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply

voltage and at each extreme also shall be shown.

(e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

The EUT can only work in such extreme voltage 3.6V and 4.2V, so here the EUT is tested in the 3.6V 3.7V and 4.2V.

Test Set up

Connect the EUT to the Wireless Communication test set 8960 via the connector. Then measure the frequency error by the Wireless Communication test set 8960. The EUT's output is matched with a 50 Ω load.




Figure 7. Test Set up

6.7.4 Measurement Results

6.7.4.1 Measurement Results vs. Variation of Temperature

- **TM1, 3.7V DC Channel No.661(1880.0MHz)**

Table 38 Measurement Results vs. Variation of Temperature

| Temperature | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|-------------|-------------|-------------------------|------------------------------|--------|
| -30 °C | 30 | 1880.0 | 4 | Pass |
| -20 °C | 30 | 1880.0 | 11 | Pass |
| -10 °C | 30 | 1880.0 | -2 | Pass |
| 0 °C | 30 | 1880.0 | 8 | Pass |
| +10 °C | 30 | 1880.0 | 16 | Pass |
| +20 °C | 30 | 1880.0 | -9 | Pass |
| +30 °C | 30 | 1880.0 | -11 | Pass |
| +40 °C | 30 | 1880.0 | 7 | Pass |
| +50 °C | 30 | 1880.0 | -11 | Pass |




Figure 8. TM1 Test Graph

6.7.4.2 Measurement Results vs. Variation of Voltage

- TM1, 25 °C ,Channel No. 661(1880.0MHz)

Table 39 Measurement Results vs. Variation of Voltage

| Voltage | Power (dBm) | Nominal Frequency (MHz) | Measured Frequency Error(Hz) | Result |
|---------|-------------|-------------------------|------------------------------|--------|
| 3.6 | 30 | 1880.0 | 12 | Pass |
| 3.7 | 30 | 1880.0 | 18 | Pass |
| 4.2 | 30 | 1880.0 | 3 | Pass |

6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.



7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 40 System Measurement Uncertainty

| Items | | Extended Uncertainty |
|---|---------------------------|----------------------|
| Effective Isotropically Radiated Power of Transmitter | EIRP (dBm) | U=3dB; k=2 |
| Band Width | Magnitude (%) | U = 0.2%; k=2 |
| Band Edge Compliance | Disturbance Power (dBm) | U = 2.0dB; k=2 |
| Conducted Spurious Emission at Antenna Terminal | Disturbance Power (dBm) | U = 2.0dB; k=2 |
| Frequency Stability | Frequency Accuracy(ppm) | U = 0.21ppm; k=2 |



8 Appendices

| | | |
|------------|---|----------|
| Appendix A | Measurement Results Modulation Characteristics | 4 pages |
| Appendix B | Measurement Results Occupied Bandwidth | 4 pages |
| Appendix C | Measurement Results Band Edges Compliance | 3 pages |
| Appendix D | Measurement Results Spurious Emission at Antenna Terminal | 13 pages |