



Appendix for test report



1Appendix_A: Effective (Isotropic) Radiated Power Output Data

Part I - Test Results

Test Band	Test Mode	Test Channel	Measured[dBm]	ERP(EIRP)[dBm]	Limit [dBm]	Verdict
GSM850	GSM/TM1	LCH	32.06	30.91	38.5	PASS
		MCH	32.09	30.94	38.5	PASS
		HCH	32.17	31.02	38.5	PASS
GSM1900	GSM/TM1	LCH	29.51	30.51	33	PASS
		MCH	29.84	30.84	33	PASS
		HCH	29.88	30.88	33	PASS

Note1:

a, For getting the ERP (Efficient Radiated Power) or EIRP (Efficient Isotropic Radiated Power) in substitution method, the following formula should be taken to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

b, SGP=Signal Generator Level

Note2: RBW > emission bandwidth, VBW > 3 x RBW.

Detector: RMS



2Appendix_B: Peak-to-Average Ratio

(Void)

3Appendix_C: Modulation Characteristics

(Void)

4Appendix_D: Bandwidth

(Void)

5Appendix_E: Band Edges Compliance

(Void)

6Appendix_F: Spurious Emission at Antenna Terminal

(Void)

7Appendix_G: Field Strength of Spurious Radiation

(Void)

8Appendix_H: Frequency Stability

(Void)

END