



Appendix for test report



1 Appendix_A: Effective (Isotropic) Radiated Power Output Data

Part I - Test Results

Test Band	Test Mode	Test Channel	Measured[dBm]	ERP [dBm]	Limit [dBm]	Verdict
WCDMA850	UMTS/TM1	LCH	24.03	18.18	38.5	PASS
		MCH	24.06	18.21	38.5	PASS
		HCH	24.08	18.23	38.5	PASS

Note1:

a, For getting the ERP (Efficient Radiated Power) or EIRP (Efficient Isotropic Radiated Power) in substitution method, the following formula should be taken to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$

b, SGP=Signal Generator Level

Note2:

$$\text{SET Span} = 1.5 * \text{OBW}$$

$$\text{SET RBW} = 1\% \text{ of the OBW, not to exceed 1MHz}$$

$$\text{SET VBW} \geq 3 * \text{RBW}$$

SET Sweep time = auto - couple.

Detector: RMS



2Appendix_B: Peak-to-Average Ratio

Part I - Test Results

Test Band	Test Mode	Test Channel	Measured[dB]	Limit [dB]	Verdict
WCDMA850	UMTS/TM1	LCH	3.04	13	PASS
		MCH	3.18	13	PASS
		HCH	3.01	13	PASS

3Appendix_C: Modulation Characteristics


Part I - Test Plots

3.1 For UMTS

3.1.1 Test Band = WCDMA850

3.1.1.1 Test Mode = UMTS/TM1

3.1.1.1.1 Test Channel = MCH





4Appendix_D: Bandwidth

Part I - Test Results

Test Band	Test Mode	Test Channel	Occupied Bandwidth [MHz]	Emission Bandwidth [MHz]	Verdict
WCDMA850	UMTS/TM1	LCH	4.13	4.69	Pass
		MCH	4.13	4.69	Pass
		HCH	4.14	4.71	Pass




Part II - Test Plots

4.1 For UMTS

4.1.1 Test Band = WCDMA850


4.1.1.1 Test Mode = UMTS/TM1

4.1.1.1.1 Test Channel = LCH






4.1.1.1.2 Test Channel = MCH





4.1.1.1.3 Test Channel = HCH





5Appendix_E: Band Edges Compliance

Part I - Test Plots

5.1 For UMTS

5.1.1 Test Band = WCDMA850

5.1.1.1 Test Mode = UMTS/TM1

5.1.1.1.1 Test Channel = LCH



5.1.1.1.2 Test Channel = HCH





6Appendix_F: Spurious Emission at Antenna Terminal

NOTE: For the averaged unwanted emissions measurements, the measurement points in each sweep is greater than twice the Span/RBW in order to ensure bin-to-bin spacing of $< RBW/2$ so that narrowband signals are not lost between frequency bins. As to the present test item, the "Measurement Points = $k * (Span / RBW)$ " with k between 4 and 5, which results in an acceptable level error of less than 0.5 dB.




Part I - Test Plots


6.1 For UMTS


6.1.1 Test Band = WCDMA850

6.1.1.1 Test Mode = UMTS/TM1

6.1.1.1.1 Test Channel = LCH













6.1.1.1.2 Test Channel = MCH















6.1.1.1.3 Test Channel = HCH











7Appendix_G: Field Strength of Spurious Radiation

Note: We tested all modes, but the data presented below is the worst case.

9kHz~150kHz, RBW = 200Hz, VBW = 600 Hz, Detector: PK

150kHz~30MHz, RBW = 9kHz, VBW = 30k Hz, Detector: PK

30MHz~1GHz, RBW = 100 kHz, VBW = 300 kHz. Detector: PK


Above 1GHz, RBW = 1 MHz, VBW = 3 MHz. Detector: PK

Part I - Test Plots


7.1 For UMTS

7.1.1 Test Band = WCDMA850_ANT1


7.1.1.1 Test Mode = UMTS/TM1



Copy of FCC PART22 W CDMA850_L




Copy of FCC PART22 W CDMA850_H




7.1.2 Test Band = WCDMA850_ANT2


7.1.2.1 Test Mode = UMTS/TM1



Copy of FCC PART22 W CDMA850_L



Copy of FCC PART22 W CDMA850_H



8Appendix_H: Frequency Stability

8.1 For UMTS

8.1.1 Frequency Error vs. Voltage:

Test Band	Test Mode	Test Channel	Test Temp.	Test Volt.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
WCDMA850	UMTS/TM1	LCH	TN	VL	2.66	0.00322	PASS
				VN	7.87	0.00952	PASS
				VH	0.26	0.00031	PASS
		MCH	TN	VL	-7.48	-0.00894	PASS
				VN	8.24	0.00985	PASS
				VH	-1.01	-0.00121	PASS
		HCH	TN	VL	-0.32	-0.00038	PASS
				VN	-0.31	-0.00037	PASS
				VH	1.77	0.00209	PASS

8.1.2 Frequency Error vs. Temperature:

Test Band	Test Mode	Test Channel	Test Volt.	Test Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
WCDMA850	UMTS/TM1	LCH	VN	-30	-6.5	-0.00787	PASS
				-20	3.94	0.00477	PASS
				-10	-0.05	-0.00006	PASS
				0	5.92	0.00716	PASS
				10	2.99	0.00362	PASS
				20	2.43	0.00294	PASS
				30	5.23	0.00633	PASS
				40	2.5	0.00303	PASS
		MCH	VN	-30	12.44	0.01487	PASS
				-20	10.8	0.01291	PASS
				-10	16.14	0.0193	PASS
				0	4.17	0.00499	PASS
				10	6.96	0.00832	PASS
				20	0.14	0.00017	PASS
				30	19.32	0.0231	PASS
				40	17.38	0.02078	PASS



Test Band	Test Mode	Test Channel	Test Volt.	Test Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Verdict
				50	7.43	0.00888	PASS
		HCH	VN	-30	-0.23	-0.00027	PASS
				-20	1.94	0.00229	PASS
				-10	1.75	0.00207	PASS
				0	3.11	0.00367	PASS
				10	-1.89	-0.00223	PASS
				20	0.55	0.00065	PASS
				30	1.04	0.00123	PASS
				40	0.5	0.00059	PASS
				50	5.75	0.00679	PASS

END