



Appendix B T-coil Measurement Plots

Table of contents
T-coil Measurement Plots of CDMA BC0
T-coil Measurement Plots of CDMA BC1

Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC0-384CH**DUT: H892L; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, CDMA2000 (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -7.59 dBA/m

BWC Factor = 0.16 dB

Location: 8.3, -8.3, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 40.14 dB

ABM1 comp = -8.07 dBA/m

BWC Factor = 0.16 dB

Location: 8.3, 4.2, 3.7 mm



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC0-384CH**DUT: H892L; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, CDMA2000 (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 3.77 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 45.98 dB

ABM1 comp = 3.77 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm



0 dB = 1.543 A/m = 3.77 dBA/m

Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC0-384CH

DUT: H892L; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, CDMA2000 (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -2.05 dBA/m

BWC Factor = 10.80 dB

Location: 4.2, 0, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 38.45 dB

ABM1 comp = -2.05 dBA/m

BWC Factor = 10.80 dB

Location: 4.2, 0, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:


Diff = 1.09 dB

BWC Factor = 10.80 dB

Location: 4.2, 0, 3.7 mm



0 dB = 1.543 A/m = 3.77 dBA/m



Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC1-600CH

DUT: H892L; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, CDMA2000 (0); Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -4.59 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, -8.3, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 42.82 dB

ABM1 comp = -4.59 dBA/m

BWC Factor = 0.15 dB

Location: 12.5, -8.3, 3.7 mm



0 dB = 0.5893 A/m = -4.59 dBA/m

Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC1-600CH**DUT: H892L; Type: Smart Phone; Serial: SAR1**

Communication System: UID 0, CDMA2000 (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 1.00 dBA/m

BWC Factor = 0.15 dB

Location: 8.3, 0, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM SNR(x,y,z) (13x13x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 29.38

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm


Cursor:

ABM1/ABM2 = 42.84 dB

ABM1 comp = -1.26 dBA/m

BWC Factor = 0.15 dB

Location: 4.2, -4.2, 3.7 mm



0 dB = 1.122 A/m = 1.00 dBA/m

Test Laboratory: HUAWEI SAR/HAC Lab

HAC-T-Coil-H892L-CDMA BC1-600CH

DUT: H892L; Type: Smart Phone; Serial: SAR1

Communication System: UID 0, CDMA2000 (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3126; ; Calibrated: 2014-8-8
- Sensor-Surface: 0mm (Fix Surface), z = 3.0
- Electronics: DAE4 Sn851; Calibrated: 2014-7-24
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA; Serial: 1053
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -4.53 dBA/m

BWC Factor = 10.80 dB

Location: 4.2, -4.2, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 38.35 dB

ABM1 comp = -4.53 dBA/m

BWC Factor = 10.80 dB

Location: 4.2, -4.2, 3.7 mm

T-Coil scan (scan for ANSI C63.19-2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)

(1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 57.53

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.80 dB


Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 0.87 dB

BWC Factor = 10.80 dB

Location: 4.2, -4.2, 3.7 mm



0 dB = 1.122 A/m = 1.00 dBA/m

