

EMC TEST REPORT


Report No. : EME-060530
Model No. : EchoLife HG520,
EchoLife HG520e,
SmartAX MT 880W
Issued Date : Jun. 12, 2006

Applicant : Huawei Technologies Co., Ltd
Bantian, Longgang District, Shenzhen, Guandong 518129
P.R.C.

Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan

This test report consists of 46 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

Project Engineer



Marx Yan

Reviewed By



Jerry Liu

Table of Contents

Summary of Tests4

1. General information5

 1.1 Identification of the EUT5

 1.2 Additional information about the EUT.....5

 1.3 Antenna description.....6

 1.4 Peripherals equipment6

2. Test specifications7

 2.1 Test standard.....7

 2.2 Operation mode7

 2.3 Test equipment7

3. Minimum 6dB Bandwidth test8

 3.1 Operating environment.....8

 3.2 Test setup & procedure.....8

 3.3 Measured data of Minimum 6dB Bandwidth test results8

4. Maximum Output Power test15

 4.1 Operating environment.....15

 4.2 Test setup & procedure.....15

 4.3 Measured data of Maximum Output Power test results15

5. Radiated Emission test16

 5.1 Operating environment.....16

 5.2 Test setup & procedure.....16

 5.3 Emission limits.....17

 5.4 Radiated spurious emission test data.....18

 5.4.1 Measurement results: frequencies equal to or less than 1 GHz.....18

 5.4.2 Measurement results: frequency above 1GHz19

6. Power Spectrum Density test25

 6.1 Operating environment.....25

 6.2 Test setup & procedure.....25

 6.3 Measured data of Power Spectrum Density test results25

7. Emission on the band edge.....32

 7.1 Operating environment.....32

 7.2 Test setup & procedure.....32

 7.3 Test Result33

7.3.1 Conducted Method33

7.3.2 Radiated Method41

8. Power Line Conducted Emission test §FCC 15.20743

8.1 Operating environment.....43

8.2 Test setup & procedure.....43

8.3 Emission limit44

8.4 Uncertainty of Conducted Emission44

8.5 Power Line Conducted Emission test data.....45

Summary of Tests**Home Gateway-Model: EchoLife HG520
FCC ID: QISHG520C1**

Test	Reference	Results
Minimum 6dB Bandwidth test	15.247(a)(2)	Pass
Maximum Output Power test	15.247(b)	Pass
Radiated Spurious Emission test	15.205, 15.209	Pass
Power Spectrum Density test	15.247(e)	Pass
Emission on the Band Edge test	15.247(d)	Pass
AC Power Line Conducted Emission test	15.207	Pass

1. General information

1.1 Identification of the EUT

Applicant	: Huawei Technologies Co., Ltd
Product	: Home Gateway
Model No.	: EchoLife HG520
FCC ID.	: QISHG520C1
Frequency Range	: 2400MHz~2483.5MHz
Channel Number	: 13 channels
Frequency of Each Channel	: 2412MHz, 2417MHz, 2422MHz, 2427MHz, 2432MHz, 2437MHz, 2442MHz, 2447MHz, 2452MHz, 2457MHz, 2462MHz
Type of Modulation	: DSSS, OFDM
Rated Power	: 1. 120Vac 60Hz with adapter (Model: AM-121200A) 2. 120Vac, 60Hz with adapter (Model: TEAC-48-121200U)
Power Cord	: N/A
Sample Received	: Apr. 28, 2006
Test Date(s)	: Jun. 6, 2006 ~ Jun. 9, 2006

A FCC DoC report has been generated for the client.

1.2 Additional information about the EUT

The EUT is a Home Gateway, and was defined as information technology equipment.

According to the hardware aspect, we verified the models listed as below are series model to EchoLife HG520 (EUT), the difference please refer to the following table:

Model Number	Difference
EchoLife HG520	Ethernet 4ports with USB
EchoLife HG520e	Ethernet 4ports without USB
SmartAX MT880W	Ethernet 1port with USB

For more detail features, please refer to User's manual as file name "Installation guide.pdf"

1.3 Antenna description

Main Antenna

The EUT uses a permanently connected antenna.

Antenna Gain: 2dBi max

Antenna Type: Dipole antenna

Connector Type: MHF

Replace Antenna

The EUT uses a permanently connected antenna.

Antenna Gain: 2dBi max

Antenna Type: Dipole antenna

Connector Type: MHF

Secondary Antenna

The EUT uses a permanently connected antenna.

Antenna Gain: 0dBi max

Antenna Type: PCB printed antenna

Connector Type: N/A

1.4 Peripherals equipment

Peripherals	Manufacturer	Product No.	Serial No.	FCC ID
PC	HP	DTPC-16	SG20400794	FCC DoC Approved
Notebook PC	DELL	PP05L	CN-5G5152-48643-498-6810	FCC DoC Approved
Notebook PC	IBM	2887	99XML12	FCC DoC Approved
Modem	Dynalink	V1456VQE	00V230A00051494	FCC DoC Approved
CO Router	D-Link	DAS-3224	N/A	FCC DoC Approved
PRINTER	HP	DeskJet 850	SG5CQ170C0	FCC DoC Approved

2. Test specifications

2.1 Test standard

The EUT was performed according to the procedures in FCC Part 15 Subpart C Section § 15.205, §15.207, §15.209, §15.247 and ANSI C63.4/2003.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band were all meet limit requirement, thus we evaluate the EUT pass the specified test.

2.2 Operation mode

The EUT operated under Tx mode during all the tests.

Verifying two adapters (models: AM-121200A and TEAC-48-121200U). The worst conducted emission was found in TEAC-48-121200U.

2.3 Test equipment

Equipment	Brand	Frequency range	Model No.	Intertek ID No.	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	9kHz~2.75GHz	ESCS 30	EC303	04/16/2007
EMI Test Receiver	Rohde & Schwarz	20Hz~26.5GHz	ESMI	EC317	08/07/2006
Spectrum Analyzer	Rohde & Schwarz	9kHz~30GHz	FSP 30	EC353	07/24/2006
Spectrum Analyzer	Rohde & Schwarz	20Hz~40GHz	FSEK 30	EC365	11/01/2006
Horn Antenna	SCHWARZBECK	1GHz~18GHz	BBHA 9120 D	EC371	12/22/2007
Horn Antenna	SCHWARZBECK	14GHz~40GHz	BBHA 9170	EC351	07/08/2007
Bilog Antenna	SCHWARZBECK	25MHz~2GHz	VULB 9168	EC347	12/23/2007
Pre-Amplifier	MITEQ	100MHz~26.5GHz	919981	EC373	02/11/2007
Wideband Peak Power Meter/ Sensor	Anritsu	100MHz~18GHz	ML2497A/MA2491A	EC396	11/10/2006
Controller	HDGmbH	N/A	CM 100	EP346	N/A
Antenna Tower	HDGmbH	N/A	MA 240	EP347	N/A
LISN	Rohde & Schwarz	9KHz~30MHz	ESH3-Z5	EC344	01/13/2007

Note: 1. The above equipments are within the valid calibration period.

2. The test antennas (receiving antenna) are calibration per 3 years.

3. Minimum 6dB Bandwidth test

3.1 Operating environment

Temperature: 24
 Relative Humidity: 53 %
 Atmospheric Pressure: 1023 hPa

3.2 Test setup & procedure

The minimum 6dB bandwidth per FCC §15.247(a)(2) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 100kHz, and the SPAN>>RBW. The test was performed at 3 channels (lowest, middle and highest channel). The minimum 6-dB modulation bandwidth is in the following Table.

3.3 Measured data of Minimum 6dB Bandwidth test results

802.11b(DSSS Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	11.60	> 500kHz
6 (middle)	2437	11.60	> 500kHz
11 (highest)	2462	13.12	> 500kHz


802.11g(OFDM Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	16.52	> 500kHz
6 (middle)	2437	16.56	> 500kHz
11 (highest)	2462	16.52	> 500kHz

Please see the plot below.


Test Mode: 802.11b(DSSS Modulation) operating mode

	Max/Ref Lvl	Delta 2 [T1]	RBW	100 kHz	RF Att	10 dB
	20 dBm	0.22 dB	VBW	100 kHz		
	2 dBm	11.60000000 MHz	SWT	5 ms	Unit	dBm



Title: 6dB Bandwidth
 Comment A: Channel 01 at 802.11b mode
 Date: 06.JUN.2006 17:20:11


	Max/Ref Lvl Delta 2 [T1]	RBW 100 kHz	RF Att 10 dB
	20 dBm 0.08 dB	VBW 100 kHz	
	2 dBm 11.60000000 MHz	SWT 5 ms	Unit dBm



Title: 6dB Bandwidth
 Comment A: Channel 06 at 802.11b mode
 Date: 06.JUN.2006 17:31:24


Test Mode: 802.11g(OFDM Modulation) operating mode

	Max/Ref Lvl	Delta 2 [T1]	RBW	100 kHz	RF Att	10 dB
	20 dBm	-0.26 dB	VBW	100 kHz		
	2 dBm	16.52000000 MHz	SWT	5 ms	Unit	dBm




Title: 6dB Bandwidth
 Comment A: Channel 01 at 802.11g mode
 Date: 06.JUN.2006 17:35:05

	Max/Ref Lvl	Delta 2 [T1]	RBW	100 kHz	RF Att	10 dB
	20 dBm	-0.09 dB	VBW	100 kHz		
	2 dBm	16.56000000 MHz	SWT	5 ms	Unit	dBm



Title: 6dB Bandwidth
 Comment A: Channel 06 at 802.11g mode
 Date: 06.JUN.2006 17:39:46

	Max/Ref Lvl	Delta 2 [T1]	RBW	100 kHz	RF Att	10 dB
	20 dBm	1.17 dB	VBW	100 kHz		
	2 dBm	16.52000000 MHz	SWT	5 ms	Unit	dBm



Title: 6dB Bandwidth
 Comment A: Channel 11 at 802.11g mode
 Date: 06.JUN.2006 17:42:45

4. Maximum Output Power test

4.1 Operating environment

Temperature: 25
 Relative Humidity: 56 %
 Atmospheric Pressure: 1023 hPa

4.2 Test setup & procedure

The power output per FCC §15.247(b) was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Power was read directly and cable loss correction (2dB) was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel).

4.3 Measured data of Maximum Output Power test results

802.11b(DSSS Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	2	16.50	18.50	70.79	30
6 (middle)	2437	2	16.44	18.44	69.82	30
11 (highest)	2462	2	16.25	18.25	66.83	30

802.11g(OFDM Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	2	17.77	19.77	94.84	30
6 (middle)	2437	2	17.75	19.75	94.41	30
11 (highest)	2462	2	17.61	19.61	91.41	30

Remark:

Conducted Peak Output Power = Reading + C.L.


5. Radiated Emission test

5.1 Operating environment

Temperature: 25
Relative Humidity: 55 %
Atmospheric Pressure: 1023 hPa

5.2 Test setup & procedure

The Diagram below shows the test setup, which is utilized to make these measurements.



Radiated emissions were investigated cover the frequency range from 30MHz to 1000MHz using a receiver RBW of 120kHz record QP reading, and the frequency over 1GHz using a spectrum analyzer RBW of 1MHz and 10Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1MHz RBW/VBW) recorded also on the report.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent 3 meter reading using inverse scaling with distance.

The EUT configuration please refer to the “Spurious set-up photo.pdf”.

5.3 Emission limits

The spurious Emission shall test through the 10th harmonic. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Frequency (MHz)	Limits (dB μ V/m@3m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

Uncertainty was calculated in accordance with NAMAS NIS 81.

Expanded uncertainty (k=2) of radiated emission measurement is 4.98 dB.

5.4 Radiated spurious emission test data

The radiated spurious emissions at

Frequency(MHz)	Margin
49.40000	-3.66

are less than uncertainty. This is within the stated measurement uncertainty, this may affect compliance determined in other test arrangements.

5.4.1 Measurement results: frequencies equal to or less than 1 GHz

The test was performed on EUT under 802.11b/g continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11b Tx channel 1.

EUT : EchoLife HG520
Worst Case : 802.11b Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Antenna high (cm)	Turn Table angle (degree)
V	49.40000	QP	12.84	23.50	36.34	40.00	-3.66	150	79
V	105.66000	QP	7.64	25.28	32.92	43.50	-10.58	150	255
V	288.02000	QP	13.70	19.82	33.52	46.00	-12.49	150	146
V	373.38000	QP	15.06	22.74	37.80	46.00	-8.20	150	157
V	499.48000	QP	18.43	16.10	34.53	46.00	-11.48	150	254
V	623.64000	QP	20.75	15.88	36.63	46.00	-9.37	150	211
H	125.00000	QP	11.62	22.90	34.52	43.50	-8.99	-8.99	254
H	373.38000	QP	15.48	24.08	39.56	46.00	-6.45	-6.45	123
H	398.60000	QP	16.74	20.38	37.12	46.00	-8.88	-8.88	98
H	627.52000	QP	21.55	18.53	40.08	46.00	-5.93	-5.93	56
H	670.20000	QP	21.52	17.49	39.01	46.00	-7.00	-7.00	188
H	862.26000	QP	24.12	15.52	39.64	46.00	-6.36	-6.36	210

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

5.4.2 Measurement results: frequency above 1GHz

EUT : EchoLife HG520
Test Condition : 802.11b Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4800.00	PK	V	36.07	37.77	53.31	55.01	74	-18.99	150	146
4800.00	AV	V	36.07	37.77	51.58	53.28	54	-0.72	150	157

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV
3GHz-14GHz: 27dBuV
14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV
3GHz-14GHz: 16dBuV
14GHz-26.5GHz: 28dBuV

EUT : EchoLife HG520
 Test Condition : 802.11b Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4860.00	PK	V	36.07	37.77	52.24	53.94	74	-20.06	150	146
4860.00	AV	V	36.07	37.77	50.26	51.96	54	-2.04	150	157

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : EchoLife HG520
Test Condition : 802.11b Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4920.00	PK	V	36.07	37.77	49.61	51.31	74	-22.69	150	146
4920.00	AV	V	36.07	37.77	46.95	48.65	54	-5.35	150	157

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : EchoLife HG520
 Test Condition : 802.11g Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4800.00	PK	V	36.07	37.77	50.64	52.34	74	-21.66	150	98
4800.00	AV	V	36.07	37.77	38.4	40.1	54	-13.9	150	56
7230.00	PK	V	36.18	43.97	52.54	60.33	74	-13.67	150	188
7230.00	AV	V	36.18	43.97	39.46	47.25	54	-6.75	150	210

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV
 3GHz-14GHz: 27dBuV
 14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV
 3GHz-14GHz: 16dBuV
 14GHz-26.5GHz: 28dBuV

EUT : EchoLife HG520
 Test Condition : 802.11g Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4860.00	PK	V	36.07	37.77	51.3	53	74	-21	150	98
4860.00	AV	V	36.07	37.77	37.38	39.08	54	-14.92	150	56
4860.00	PK	V	36.18	43.97	54.74	62.53	74	-11.47	150	188
4860.00	AV	V	36.18	43.97	40.38	48.17	54	-5.83	150	210

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : EchoLife HG520
Test Condition : 802.11g Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
4920.00	PK	V	36.07	37.77	49.61	51.31	74	-22.69	150	98
4920.00	AV	V	36.07	37.77	46.95	48.65	54	-5.35	150	56
4920.00	PK	V	36.07	37.77	49.05	50.75	74	-23.25	150	188
4920.00	AV	V	36.07	37.77	35.78	37.48	54	-16.52	150	210
7380.00	PK	V	36.18	43.97	52.87	60.66	74	-13.34	150	98
7380.00	AV	V	36.18	43.97	38.96	46.75	54	-7.25	150	56

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. Harmonics spurious emission test results which are far under the limit are not shown on the above table.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

6. Power Spectrum Density test

6.1 Operating environment

Temperature: 24
 Relative Humidity: 55 %
 Atmospheric Pressure 1023 hPa

6.2 Test setup & procedure

The power spectrum density per FCC §15.247(e) was measured from the antenna port of the EUT using a 50ohm spectrum analyzer with the resolution bandwidth set at 3kHz, the video bandwidth set at 10kHz, a span of 300kHz, and the sweep time set at 100 seconds. Power Density was read directly correction was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel). The Power Spectral Density measured result is in the following table.

6.3 Measured data of Power Spectrum Density test results

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-14.29	8
6 (middle)	2437	-14.53	8
11 (highest)	2462	-14.74	8


Test Mode: 802.11g (OFDM Modulation) operating mode

Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-17.53	8
6 (middle)	2437	-17.32	8
11 (highest)	2462	-17.96	8

Please see the plot below.


Test Mode: 802.11b (DSSS Modulation) operating mode

	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	13 dBm	-14.29 dBm	VBW	10 kHz		
	2 dBm	2.41136363 GHz	SWT	100 s	Unit	dBm




Title: Power Spectrum Density
 Comment A: Channel 01 at 802.11b mode
 Date: 06.JUN.2006 17:20:30

	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	13 dBm	-14.53 dBm	VBW	10 kHz		
	2 dBm	2.43636242 GHz	SWT	100 s	Unit	dBm




Title: Power Spectrum Density
 Comment A: Channel 06 at 802.11b mode
 Date: 06.JUN.2006 17:31:42



Title: Power Spectrum Density
 Comment A: Channel 11 at 802.11b mode
 Date: 06.JUN.2006 17:28:03


Test Mode: 802.11g (OFDM Modulation) operating mode

	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	13 dBm	-17.53 dBm	VBW	10 kHz		
	2 dBm	2.40728327 GHz	SWT	100 s	Unit	dBm




Title: Power Spectrum Density
 Comment A: Channel 01 at 802.11g mode
 Date: 06.JUN.2006 17:35:24

	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	13 dBm	-17.32 dBm	VBW	10 kHz		
	2 dBm	2.43854499 GHz	SWT	100 s	Unit	dBm



Title: Power Spectrum Density
 Comment A: Channel 06 at 802.11g mode
 Date: 06.JUN.2006 17:40:06



Title: Power Spectrum Density
 Comment A: Channel 11 at 802.11g mode
 Date: 06.JUN.2006 17:43:04

7. Emission on the band edge

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.1 Operating environment

Temperature:	24	
Relative Humidity:	53	%
Atmospheric Pressure	1023	hPa

7.2 Test setup & procedure

The output of EUT was connected to spectrum analyzer via a 50ohm cable.


The setting of spectrum analyzer is:

Peak:	RBW = 100kHz ;	VBW = 100kHz
Average:	RBW = 1MHz ;	VBW = 10Hz


7.3 Test Result

7.3.1 Conducted Method


Test Mode: 802.11b(DSSS Modulation) operating mode




Title: Band Edge
 Comment A: Channel 01 at 802.11b mode
 F1=2390MHz F2=2400MHz (Peak Detect)
 Date: 06.JUN.2006 17:21:06



Title: Band Edge
 Comment A: Channel 01 at 802.11b mode
 F1=2390MHz F2=2400MHz (Average Detect)
 Date: 06.JUN.2006 17:22:07




Title: Band Edge
 Comment A: Channel 11 at 802.11b mode
 F1=2483.5MHz (Peak Detect)
 Date: 06.JUN.2006 17:29:14




Title: Band Edge
 Comment A: Channel 11 at 802.11b mode
 F1=2483.5MHz (Average Detect)
 Date: 06.JUN.2006 17:30:09

Test Mode: 802.11g(OFDM Modulation) operating mode


	Delta 1 [T1]	RBW	100 kHz	RF Att	0 dB
Ref Lvl	-49.02 dB	VBW	100 kHz	Unit	dBm
12 dBm	-23.72739078 MHz	SWT	28 ms		




Title: Band Edge
 Comment A: Channel 01 at 802.11g mode
 F1=2390MHz F2=2400MHz (Peak Detect)
 Date: 06.JUN.2006 17:36:02



Title: Band Edge
 Comment A: Channel 01 at 802.11g mode
 F1=2390MHz F2=2400MHz (Average Detect)
 Date: 06.JUN.2006 17:37:02



Title: Band Edge
 Comment A: Channel 11 at 802.11g mode
 F1=2483.5MHz (Peak Detect)
 Date: 06.JUN.2006 17:44:47



Title: Band Edge
 Comment A: Channel 11 at 802.11g mode
 F1=2483.5MHz (Average Detect)
 Date: 06.JUN.2006 17:45:41

7.3.2 Radiated Method

Test Mode: 802.11b(DSSS Modulation) operating mode

Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	108.79	55.49	53.3	74	-20.7
	AV	105.03	59.17	45.86	54	-8.14
11 (highest)	PK	110.37	56.85	53.52	74	-20.48
	AV	106.59	59.03	47.56	54	-6.44

Remark: 1. $C = A - B$

2. $E = C - D$

Test Mode: 802.11g(OFDM Modulation) operating mode

Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	111.08	49.02	62.06	74	-11.94
	AV	101.34	51.01	50.33	54	-3.67
11 (highest)	PK	108.12	49.8	58.32	74	-15.68
	AV	98.66	52.81	45.85	54	-8.15


Remark: 1. $C = A - B$
2. $E = C - D$

8. Power Line Conducted Emission test §FCC 15.207

8.1 Operating environment

Temperature: 22
Relative Humidity: 55 %
Atmospheric Pressure 1023 hPa

8.2 Test setup & procedure



The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement. The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

The EUT configuration please refer to the “Conducted set-up photo.pdf”.

8.3 Emission limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

*Decreases with the logarithm of the frequency.

8.4 Uncertainty of Conducted Emission

Expanded uncertainty (k=2) of conducted emission measurement is ± 2.6 dB.

8.5 Power Line Conducted Emission test data


The test was performed the 802.11b and 802.11g normal operating modes, the worst case was occurred at 802.11g normal operating mode.

Phase : Line
 EUT : EchoLife HG520
 Worst case : Normal operating mode
 Adapter : TEAC-47-121200U

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.169	0.00	35.84	65.01	10.50	55.01	-29.17	-44.51
0.246	0.00	26.26	61.90	5.84	51.90	-35.64	-46.06
0.471	0.00	35.62	56.50	35.49	46.50	-20.88	-11.01
1.204	0.00	23.46	56.00	19.01	46.00	-32.54	-26.99
15.618	0.12	27.09	60.00	23.00	50.00	-32.91	-27.00
20.808	0.14	29.41	60.00	25.55	50.00	-30.59	-24.45

Remark:

1. Correction Factor (dB)= LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Phase : Neutral
 EUT : EchoLife HG520
 Worst case : Normal operating mode
 Adapter : TEAC-47-121200U

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level Av (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.169	0.00	35.61	65.01	10.73	55.01	-29.40	-44.28
0.242	0.00	25.82	62.03	5.84	52.03	-36.21	-46.19
0.470	0.00	31.18	56.52	31.01	46.52	-25.34	-15.51
1.206	0.00	17.89	56.00	15.76	46.00	-38.11	-30.24
15.619	0.12	23.87	60.00	19.56	50.00	-36.13	-30.44
20.808	0.14	27.80	60.00	23.87	50.00	-32.20	-26.13

Remark:

1. Correction Factor (dB)= LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)

