



Appendix for Testreport



Appendix A: DTS (6 dB) Bandwidth

In this document, the "DTS6dBBW" refers to the measured "DTS (6 dB) Bandwidth" value. In this Appendix, the "fc(DTS6dBBW)" refers to the centre of the measured "DTS6dBBW". The introduction of the "fc(DTS6dBBW)" is due to that other measurements use it as the spectrum analyzer setting.

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain, and used as respective results for each chain.


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	DTS6dBBW[KHz]	Verdict
TM1_Ch0	L	2402	0.68	pass
TM1_Ch19	M	2440	0.68	pass
TM1_Ch39	H	2480	0.68	pass




Part II - Test Plots

2.1 TM1_Ch0_L






2.2 TM1_Ch19_M





2.3 TM1_Ch39_H





Appendix B: Occupied Bandwidth

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain, and used as respective results for each chain.

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Occupied Bandwidth [MHz]	Verdict
TM1_Ch0	L	2402	1.07	pass
TM1_Ch19	M	2440	1.07	pass
TM1_Ch39	H	2480	1.07	pass




Part II - Test Plots

2.1 TM1_Ch0_L






2.2 TM1_Ch19_M





2.3 TM1_Ch39_H





Appendix C: Duty cycle


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Duty cycle [%]
TM1_Ch19	M	2440	65



Part II - Test Plots

2.1 TM1_Ch19_M





Appendix D: Maximum Conducted Average Output Power

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Power[dBm]	Verdict
TM1_Ch0	L	2402	1.87	pass
TM1_Ch19	M	2440	2.84	pass
TM1_Ch39	H	2480	-0.16	pass



Part II - Test Plots

2.1 TM1_ Ch0_L





2.3 TM1_ Ch19_M





2.5 TM1_Ch39_H



Frequency

Auto Tune

Center Freq
2.480000000 GHz

Start Freq
2.478000000 GHz

Stop Freq
2.482000000 GHz

CF Step
400.000 kHz
Auto Man

Freq Offset
0 Hz



Appendix E: Maximum Power Spectral Density Level

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	PD[MHz]	Verdict
TM1_Ch0	L	2402	-11.35	pass
TM1_Ch19	M	2440	-10.42	pass
TM1_Ch39	H	2480	-11.87	pass




Part II - Test Plots

2.1 TM1_Ch0_L





2.2 TM1_Ch19_M





2.3 TM1_Ch39_H





Appendix F: Band Edges Compliance


Part I - Test Results

Test Mode	Test Channel	Frequency [MHz]	Carrier Power[dBm]	Max.Spurious Level[dBm]	Verdict
TM1_Ch0	L	2402	1.69	-49.27	pass
TM1_Ch39	H	2480	-0.19	-49.73	pass




Part II - Test Plots

2.1 TM1_Ch0_L





2.2 TM1_Ch39_H



Appendix G: Unwanted Emissions into Non-Restricted Frequency

Bands

In this Appendix, the "Pref", which is used as the reference level, refers to the peak power level in any 100 kHz bandwidth within the fundamental emission, the "Puw" refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \times \lg(100 [kHz]/\text{narrower RBW [kHz]})$. As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain and used as respective results for each chain, due to the relative-limit requirement.

In the result table, the "< Limit" denotes that "The Puw [dBm] is less than Pref[dBm]-30[dBm], see test plots for detailed".

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Pref[dBm]	Puw[dBm]	Verdict
TM1_Ch0	L	2402	1.71	<limit	pass
TM1_Ch19	M	2440	2.78	<limit	pass
TM1_Ch39	H	2480	-0.14	<limit	pass



Part II - Test Plots


2.1 TM1_Ch0_L


Pref:








Puw:

















2.2 TM1_Ch19_M


Pref:








P_{uw}:

















2.3 TM1_Ch39_H


Pref:








Puw:
















Appendix H: Radiated Spurious Emission & Spurious in Restricted Band

Note: We tested all modes, but the data presented below is the worst case.

Below 1GHz, RBW = 100 kHz, VBW = 300 kHz.

Above 1GHz, RBW = 1 MHz, VBW = 3 MHz.

The simultaneous transmission has been considered


3.1 Part 1: Testing Range of “9 kHz to 30MHz”

NOTE1: No peak found in the Test Range of “9 kHz to 30MHz”

3.2 Part 2: Testing Range of “30 MHz to 1 GHz”

Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
31.164000	31.28	40.00	-8.72	100.0	V	240.0	14.6
40.088000	29.03	40.00	-10.97	100.0	V	221.0	15.4
94.990000	24.07	43.50	-19.43	100.0	V	0.0	13.1
178.992000	29.02	43.50	-14.48	100.0	V	288.0	11.5
437.012000	28.21	46.00	-17.79	100.0	V	142.0	18.7
939.084000	37.46	46.00	-8.54	100.0	H	2.0	25.9

3.3 Part 3: Testing Range of “1GHz to 3GHz”

Note 1: The testing range of “1GHz to 3 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.


Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).

Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.

Test Mode:


3.4.1 Test Mode: TM1

3.4.1.1 Channel 0



Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2390.000000	---	26.91	54.00	-27.09	100.0	H	213.0	-7.8
2390.000000	36.64	---	74.00	-37.36	100.0	H	213.0	-7.8


3.4.1.2 Channel 39



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2483.500000	---	36.97	54.00	-17.03	100.0	H	201.0	-0.4
2483.500000	44.99	---	74.00	-29.01	100.0	H	201.0	-0.4

3.4 Part 4: Testing Range of “3 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “3 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “3 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).




3.5 Part 5: Testing Range of “18 GHz to 26.5 GHz”

NOTE: No peak found in the Test Range of “18 GHz to 26.5GHz”

Appendix I: Conducted Emission at Power Port

Note: RBW =9 kHz, VBW = 30 kHz



Frequency (MHz)	QuasiPea k	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.157203	47.30	---	65.61	-18.31	N	ON	9.7
0.157487	---	23.29	55.60	-32.31	N	ON	9.7
0.214022	39.57	---	63.05	-23.48	L1	ON	9.7
0.230336	---	19.13	52.44	-33.31	L1	ON	9.7
0.687298	---	23.66	46.00	-22.34	N	ON	9.7
0.701237	35.28	---	56.00	-20.72	N	ON	9.7
1.354081	---	21.95	46.00	-24.05	N	ON	9.7
1.370887	32.07	---	56.00	-23.93	N	ON	9.7
2.392545	---	19.32	46.00	-26.68	N	ON	9.7
2.461746	24.54	---	56.00	-31.46	N	ON	9.7
3.480478	20.47	---	56.00	-35.53	N	ON	9.7
3.551412	---	16.28	46.00	-29.73	N	ON	9.7

END