



Appendix for test report



1Appendix_A: Effective (Isotropic) Radiated Power Output Data

Part I - Test Results

VOID



2Appendix_B: Peak-to-Average Ratio

Part I - Test Results

VOID



3Appendix_C: Modulation Characteristics

Part I - Test Plots

VOID



4Appendix_D: Bandwidth

Part I - Test Results

VOID



5Appendix_E: Band Edges Compliance

Part I - Test Plots

VOID



6Appendix_F: Spurious Emission at Antenna Terminal

NOTE: For the averaged unwanted emissions measurements, the measurement points in each sweep is greater than twice the Span/RBW in order to ensure bin-to-bin spacing of $< RBW/2$ so that narrowband signals are not lost between frequency bins. As to the present test item, the "Measurement Points = $k * (Span / RBW)$ " with k between 4 and 5, which results in an acceptable level error of less than 0.5 dB.

Part I - Test Plots

VOID

7Appendix_G: Field Strength of Spurious Radiation

Note: We tested all modes, but the data presented below is the worst case.

9kHz~150kHz, VBW = 200Hz, VBW = 600 Hz, Detector: PK

150kHz~30MHz, VBW = 9kHz, VBW = 30k Hz, Detector: PK

30MHz~1GHz, RBW = 100 kHz, VBW = 300 kHz. Detector: PK


Above 1GHz, RBW = 1 MHz, VBW = 3 MHz. Detector: PK

Part I - Test Plots


7.1 For UMTS

7.1.1 Test Band = WCDMA850


7.1.1.1 Test Mode = UMTS/TM1



Copy of FCC PART22 W CDMA850_L



Copy of FCC PART22 W CDMA850_H





8Appendix_H: Frequency Stability

Part I - Test Plots

VOID

END