



## FCC Part22H&24E&27L Test Report

Product Name : CDMA 1X Mobile Phone  
Model No. : HUAWEI M636  
FCC ID : QISM636

Applicant : HUAWEI TECHNOLOGIES CO., LTD.  
Address : Bantian, Longgang District, Shenzhen, 518129  
Guangdong, P. R. China

Date of Receipt : 22/03/2012  
Test Date : 23/03/2012~ 28/03/2012  
Issued Date : 06/04/2012  
Report No. : 123S066R-HP-US-P07V01  
Report Version : V 1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

# Test Report Certification

Issued Date : 06/04/2012

Report No. : 123S066R-HP-US-P07V01



Product Name : CDMA 1X Mobile Phone

Applicant : HUAWEI TECHNOLOGIES CO., LTD.

Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.  
R. China

Manufacturer : HUAWEI TECHNOLOGIES CO., LTD.

Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.  
R. China

Model No. : HUAWEI M636

FCC ID : QISM636

EUT Voltage : DC 3.7V

Brand Name : HUAWEI

Applicable Standard : FCC CFR Title 47 Part 2, TIA/EIA 603-C  
FCC Part22 Subpart H, FCC Part24 Subpart E  
FCC Part27 Subpart L

Test Result : Complied

Performed Location : Suzhou EMC Laboratory  
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech  
Development Zone., Suzhou, China  
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
FCC Registration Number: 800392

Documented By : Alice Ni  
(Engineering ADM: Alice Ni)

Reviewed By : Robin Wu  
(Engineering Supervisor: Robin Wu)

Approved By : Marlin Chen  
(Engineering Manager: Marlin Chen)

**Laboratory Information**

We, **QuietTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

<b>Taiwan R.O.C.</b>	<b>:</b>	<b>BSMI, NCC, TAF</b>
<b>Germany</b>	<b>:</b>	<b>TUV Rheinland</b>
<b>Norway</b>	<b>:</b>	<b>Nemko, DNV</b>
<b>USA</b>	<b>:</b>	<b>FCC, NVLAP</b>
<b>Japan</b>	<b>:</b>	<b>VCCI</b>

The related certificate for our laboratories about the test site and management system can be downloaded from QuietTek Corporation's Web Site : <http://www.quietek.com/tw/ctg/cts/accreditations.htm>  
The address and introduction of QuietTek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

**HsinChu Testing Laboratory :**

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.  
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : [service@quietek.com](mailto:service@quietek.com)

**LinKou Testing Laboratory :**

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.  
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : [service@quietek.com](mailto:service@quietek.com)

**Suzhou Testing Laboratory :**

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China  
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : [service@quietek.com](mailto:service@quietek.com)

TABLE OF CONTENTS

Description	Page
1. General Information .....	6
1.1. EUT Description .....	6
1.2. Mode of Operation .....	8
1.3. Tested System Details .....	9
1.4. Configuration of Tested System .....	10
1.5. EUT Exercise Software .....	11
2. Technical Test .....	12
2.1. Summary of Test Result .....	12
2.2. Test Environment .....	13
3. Peak Output Power .....	14
3.1. Test Equipment .....	14
3.2. Test Setup .....	15
3.3. Limit .....	15
3.4. Test Procedure .....	16
3.5. Uncertainty .....	18
3.6. Test Result .....	19
3.7. Test Photograph .....	23
4. Modulation Characteristic .....	24
4.1. Test Equipment .....	25
4.2. Test Setup .....	25
4.3. Limit .....	26
4.4. Uncertainty .....	26
4.5. Test Result .....	26
5. Occupied Bandwidth .....	27
5.1. Test Equipment .....	27
5.2. Test Setup .....	27
5.3. Limit .....	28
5.4. Test Procedure .....	28
5.5. Uncertainty .....	28
5.6. Test Result .....	29
6. Spurious Emission At Antenna Terminals (+/- 1MHz) .....	35
6.1. Test Equipment .....	35
6.2. Test Setup .....	35
6.3. Limit .....	36
6.4. Test Procedure .....	36
6.5. Uncertainty .....	36

6.6. Test Result..... 37

7. Spurious Emission ..... 40

7.1. Test Equipment..... 40

7.2. Test Setup..... 41

7.3. Limit..... 42

7.4. Test Procedure ..... 42

7.5. Uncertainty ..... 43

7.6. Test Result..... 44

7.7. Test Photograph ..... 56

8. Frequency Stability Under Temperature & Voltage Variations..... 58

8.1. Test Equipment..... 58

8.2. Test Setup..... 58

8.3. Limit..... 59

8.4. Test Procedure ..... 59

8.5. Uncertainty ..... 59

8.6. Test Result..... 60

1. General Information

1.1. EUT Description

Product Name	CDMA 1X Mobile Phone
Model No.	HUAWEI M636
MEID	A000003368E63B
Hardware Version	VER.B
Software Version	M636C45B109
Device Category	Portable
<b>CDMA</b>	
Support Band	CDMA2000 1X BC0/BC1/BC15
Uplink	BC0: 824~849MHz BC1: 1850~1910MHz BC15: 1710~1755MHz
Downlink	BC0: 869~894MHz BC1: 1930~1990MHz BC15: 2110~2155MHz
Antenna Type	Internal
Type of Modulation	QPSK
Peak Antenna Gain	BC0: 2.3dBi BC1: 3.7dBi BC15: 3.2dBi
<b>GPS</b>	
Operate Frequency	1575.42MHz
Type of modulation	BPSK
Antenna Gain	-3.5dBi
<b>Bluetooth</b>	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.0
Type of modulation	FHSS
Data Rate	1Mbps(GFSK)
Antenna Gain	-5.18dBi
<b>Components</b>	
Battery #1	Manufacturer: Harbin Coslight Power Co., Ltd. M/N: HB4A1H Rated Voltage and Capacitance: 3.7V/900mAh

Battery #2	Manufacturer: BYD M/N: HB4A1H Rated Voltage and Capacitance: 3.7V/900mAh
Adapter #1	Manufacturer: HKA M/N: HS-050040U5 Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 400mA
Adapter #2	Manufacturer: BYD M/N: HS-050040U5 Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 400mA

**1.2. Mode of Operation**

QuieTek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: CDMA 2000 1X BC0 Link
Mode 2: CDMA 2000 1X BC1 Link
Mode 3: CDMA 2000 1X BC15 Link

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For the ERP/EIRP and radiated emission test, every axis (X, Y, Z) was verified, and show the worst result on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The report number is 123S066R-HP-US-P01V02.

**1.3. Tested System Details**

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	CMU200	R&S	CMU200	N/A	N/A

### 1.4. Configuration of Tested System



**1.5. EUT Exercise Software**

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	EUT Communicate with CMU200, then select channel to test.

**2. Technical Test**

**2.1. Summary of Test Result**

- No deviations from the test standards
- Deviations from the test standards as below description:

For CDMA 2000 1X BC0 (FCC Part 22H & Part 2)

Emission			
Performed Item	Normative References	Test Performed	Deviation
Peak Output Power	FCC Part 22.913(a)(2) and Part 2.1046	Yes	No
Modulation Characteristic	FCC Part 2.1047	Yes	No
Occupied Bandwidth	FCC Part 2.1049	Yes	No
Spurious Emission At Antenna Terminals (+/- 1MHz)	FCC Part 22.917(a) and Part 2.1049	Yes	No
Spurious Emission	FCC Part 22.917(a) and Part 2.1051, 2.1053	Yes	No
Frequency Stability Under Temperature & Voltage Variations	FCC Part 22.355 and Part 2.1055	Yes	No

For CDMA 2000 1X BC1 (FCC Part 24E & Part 2)

Emission			
Performed Item	Normative References	Test Performed	Deviation
Peak Output Power	FCC Part 24.232(c) and Part 2.1046	Yes	No
Modulation Characteristic	FCC Part 2.1047	Yes	No
Occupied Bandwidth	FCC Part 2.1049	Yes	No
Spurious Emission At Antenna Terminals (+/- 1MHz)	FCC Part 24.238(a) and Part 2.1049	Yes	No
Spurious Emission	FCC Part 24.238(a) and Part 2.1051, 2.1053	Yes	No
Frequency Stability Under Temperature & Voltage Variations	FCC Part 24.235 and Part 2.1055	Yes	No

For CDMA 2000 1X BC15 (FCC Part 27L & Part 2)

Emission			
Performed Item	Normative References	Test Performed	Deviation
Peak Output Power	FCC Part 27.50(d)(4) and Part 2.1046	Yes	No
Modulation Characteristic	FCC Part 2.1047	Yes	No
Occupied Bandwidth	FCC Part 2.1049	Yes	No
Spurious Emission At Antenna Terminals (+/- 1MHz)	FCC Part 27.53(h) and Part 2.1049	Yes	No
Spurious Emission	FCC Part 27.53(h) and Part 2.1051, 2.1053	Yes	No
Frequency Stability Under Temperature & Voltage Variations	FCC Part 27.54 and Part 2.1055	Yes	No

**2.2. Test Environment**

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	23
Humidity (%RH)	25-75	52
Barometric pressure (mbar)	860-1060	950-1000

### 3. Peak Output Power


#### 3.1. Test Equipment

Peak Output Power / AC-5


Instrument	Manufacturer	Type No.	Serial No	Cali. Due Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
PSG Analog Signal Generator	Agilent	E8257D	MY44321116	2012.04.23
Preamplifier	QuieTek	AP-025C	CHM-0503006	2012.05.05
Preamplifier	Miteq	NSP1800-25	1364185	2012.05.05
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2012.10.18
Half Wave Tuned Dipole Antenna	COM-POWER	AD-100	40137	2013.11.24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	737	2013.11.24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2013.01.10

**3.2. Test Setup**

Conducted Power Measurement:



Radiated Power Measurement:



**3.3. Limit**

**For FCC Part 22.913(a)(2):**

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

**For FCC Part 24.232(c):**

The EIRP of mobile transmitters and auxiliary test transmitters must not exceed 2 Watts.

**For FCC Part 27.50(d)(4):**

The EIRP of mobile transmitters and auxiliary test transmitters must not exceed 1 Watts.

### 3.4. Test Procedure

**Conducted Power Measurement:**

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- c) EUT Communicate with CMU200, then selects a channel for testing.
- d) Add a correction factor to the display of spectrum, and then test.

**Radiated Power Measurement:**

- e) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- f) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- g) The output of the test antenna shall be connected to the measuring receiver.
- h) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- i) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- j) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- k) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- l) The maximum signal level detected by the measuring receiver shall be noted.
- m) The transmitter shall be replaced by a substitution antenna.
- n) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- o) The substitution antenna shall be connected to a calibrated signal generator.
- p) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- q) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- r) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- s) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.

- t) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- u) Test site anechoic chamber refer to ANSI C63.4: 2009.

**Base station simulator settings for each test mode:**

1. For 1xRTT

Use CDMA2000 Rev 6 protocol in R&S CMU200.

- 1) Test for Reverse/Forward TCH RC1, Reverse/Forward TCH RC2, and RC3 Reverse FCH and demodulation of RC 3, 4 and 5.
  - a. Set up a call using Fundamental Channel Test Mode 1 (RC1, SO 2) with 9600 bps data rate only.
  - b. As per C.S0011 or TIA/EIA-98-F Table 4.4.5.2-1, set the test parameters as shown in Table 4-1.
  - c. Send continuously '0' power control bits to the Gobi2000 Module.
  - d. Measure the output power at Gobi2000 Module antenna connector as recorded on the power meter with values corrected for cables losses.
  - e. Repeat step b through d for Fundamental Channel Test Mode:
    - i. RC1, SO55
    - ii. RC2, SO9
    - iii. RC2, SO55
    - iv. RC3, SO55
- 2) Test for RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3, 4 and 5.
  - a. Set up a call using Supplemental Channel Test Mode 3 (RC 3, SO 32) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
  - b. As per C.S0011 or TIA/EIA-98-F Table 4.4.5.2-2, set the test parameters as shown in Table 4-2.
  - c. Send alternating '0' and '1' power control bit to the Gobi2000 Module
  - d. Determine the active channel configuration. If the desired channel configuration is not the active channel configuration, increase  $\hat{\rho}$  by 1 dB and repeat the verification. Repeat this step until the desired channel configuration becomes active.
  - e. Measure the output power at the Gobi2000 Module antenna connector.
  - f. Decrease  $\hat{\rho}$  by 0.5 dB.
  - g. Determine the active channel configuration. If the active channel configuration is the desired channel configuration, measure the output power at the Gobi2000 Module antenna connector.
  - h. Repeat step f and g until the output power no longer increases or the desired channel

configuration is no longer active. Record the highest output power achieved with the desired channel configuration active.

- i. Repeat step a through h ten times and average the result.

**Table 4-1 Parameters for Max. Power with a single traffic code channel, SR1**

Parameter	Units	Value
$\hat{I}_{or}$	dBm/1.23 MHz	-104
(Pilot $E_c$ ) / $I_{or}$	dB	-7
(Traffic $E_c$ ) / $I_{or}$	dB	-7.4

**Table 4-2 Parameters for Max. Power with multiple traffic code channel, SR1**

Parameter	Units	Value
(Pilot $E_c$ ) / $I_{or}$	dB	-7
(Traffic $E_c$ ) / $I_{or}$	dB	-7.4

### 3.5. Uncertainty

The measurement uncertainty is defined as for Conducted Power Measurement  $\pm 1.2$  dB, for Radiated Power Measurement  $\pm 3.2$  dB

3.6. Test Result

CDMA 2000 1X BC0 Link

Mode	Test Case			BC0 (850MHz) Channel					
	Num.	FWD RC/TAP	REV RC/TAP	Conducted Power (dBm)			ERP (dBm)		
				1013	384	777	1013	384	777
1x	1	RC1	RC1 (SO2)	25.02	24.18	24.72	---	---	---
	2	RC1	RC1 (SO55)	<b>25.06</b>	<b>24.33</b>	<b>24.74</b>	26.62	25.33	25.96
	3	RC2	RC2 (SO9)	24.80	24.14	24.64	---	---	---
	4	RC2	RC2 (SO55)	24.77	24.30	24.61	---	---	---
	5	RC3	RC3 (SO55)	24.98	24.20	24.70	---	---	---
	6	RC3	RC3 (SO32)	24.92	24.13	24.68	---	---	---

CDMA 2000 1X BC1 Link

Mode	Test Case			BC1 (1900MHz) Channel					
	Num.	FWD RC/TAP	REV RC/TAP	Conducted Power (dBm)			EIRP (dBm)		
				25	600	1175	25	600	1175
1x	1	RC1	RC1 (SO2)	22.69	23.15	23.30	---	---	---
	2	RC1	RC1 (SO55)	<b>22.73</b>	<b>23.29</b>	<b>23.45</b>	26.19	25.30	27.31
	3	RC2	RC2 (SO9)	22.70	23.25	23.34	---	---	---
	4	RC2	RC2 (SO55)	22.66	23.15	23.33	---	---	---
	5	RC3	RC3 (SO55)	22.71	23.19	23.31	---	---	---
	6	RC3	RC3 (SO32)	22.69	23.28	23.38	---	---	---

Note: The maximum PAR for CDMA2000 1X BC1 is 3.9dB less than 13 dB.

CDMA 2000 1X BC15 Link

Mode	Test Case			BC15 (1700MHz) Channel					
	Num.	FWD RC/TAP	REV RC/TAP	Conducted Power (dBm)			EIRP (dBm)		
				25	450	875	25	450	875
1x	1	RC1	RC1 (S02)	23.95	22.85	22.74	---	---	---
	2	RC1	RC1 (S055)	<b>23.97</b>	<b>23.01</b>	<b>22.87</b>	23.45	22.28	24.71
	3	RC2	RC2 (S09)	23.86	22.81	22.71	---	---	---
	4	RC2	RC2 (S055)	23.92	22.98	22.84	---	---	---
	5	RC3	RC3 (S055)	23.96	22.93	22.85	---	---	---
	6	RC3	RC3 (S032)	23.93	22.90	22.79	---	---	---

Note: The maximum PAR for CDMA2000 1X BC15 is 3.3dB less than 13 dB

Radiated Measurement

CDMA 2000 1X BC0 Link

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 1013 (824.7MHz)								
824.70	-5.28	H	29.2	2.56	-0.02	26.62	38.50	-11.88
824.70	-16.83	V	18.42	2.56	-0.02	15.84	38.50	-22.66
Middle Channel 384 (836.52MHz)								
836.52	-6.83	H	27.82	2.59	0.10	25.33	38.50	-13.17
836.52	-17.38	V	18.13	2.59	0.10	15.64	38.50	-22.86
High Channel 777 (848.31MHz)								
848.31	-6.36	H	28.37	2.54	0.13	25.96	38.50	-12.54
848.31	-18.72	V	16.62	2.54	0.13	14.21	38.50	-24.29

CDMA 2000 1X BC1 Link

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 25(1851.25MHz)								
1851.25	20.40	H	18.46	2.67	10.40	26.19	33.00	-6.81
1851.25	8.96	V	6.83	2.67	10.40	14.56	33.00	-18.44
Middle Channel 600 (1880MHz)								
1880.00	19.50	H	17.55	2.68	10.43	25.30	33.00	-7.70
1880.00	8.31	V	6.02	2.68	10.43	13.77	33.00	-19.23
High Channel 1175 (1908.75MHz)								
1908.75	21.37	H	19.56	2.69	10.44	27.31	33.00	-5.69
1908.75	10.90	V	8.66	2.69	10.44	16.41	33.00	-16.59

CDMA 2000 1X BC15 Link

Frequency (MHz)	SA Reading (dBm)	Ant. Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 25 (1711.25MHz)								
1711.25	18.47	H	15.83	2.53	10.15	23.45	30.00	-6.55
1711.25	12.59	V	9.33	2.53	10.15	16.95	30.00	-13.05
Middle Channel 450 (1732.50MHz)								
1732.50	17.36	H	14.62	2.54	10.20	22.28	30.00	-7.72
1732.50	10.45	V	7.35	2.54	10.20	15.01	30.00	-14.99
High Channel 875 (1753.75MHz)								
1753.75	19.80	H	17.02	2.55	10.24	24.71	30.00	-5.29
1753.75	12.29	V	9.31	2.55	10.24	17.00	30.00	-13.00


## 4. Modulation Characteristic

### 4.1. Test Equipment

Modulation Characteristic / AC-6

Instrument	Manufacturer	Type No.	Serial No	Cal. Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC6-TH	2013.01.10

### 4.2. Test Setup



**4.3. Limit**

N/A

**4.4. Uncertainty**

The measurement uncertainty is defined as 0.1%

**4.5. Test Result**

The modulation of CDMA was verified and confirmed compliance with requirement.


## 5. Occupied Bandwidth

### 5.1. Test Equipment

Occupied Bandwidth / AC-6

Instrument	Manufacturer	Type No.	Serial No	Cali. Due Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC6-TH	2013.01.10

### 5.2. Test Setup



**5.3. Limit**

N/A

**5.4. Test Procedure**

Using Occupied Bandwidth measurement function of spectrum analyzer, and setting as follows:

For CDMA2000 1X BC0/BC1/BC15 test --- RBW = 30 kHz and VBW = 100 kHz

**5.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 10$  Hz

## 5.6. Test Result

Product	CDMA 1X Mobile Phone		
Test Item	Occupied Bandwidth		
Test Mode	Mode 1: CDMA 2000 1X BC0 Link		
Date of Test	2012/03/27	Test Site	AC-6

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
1013	824.70	1439.0	1282.1
384	836.52	1426.0	1275.4
777	848.31	1430.0	1279.1

Figure Channel 1013 (824.70MHz)




Figure Channel 384 (836.52MHz)





Figure Channel 777 (848.31MHz)



Product	CDMA 1X Mobile Phone		
Test Item	Occupied Bandwidth		
Test Mode	Mode 2: CDMA 2000 1X BC1 Link		
Date of Test	2012/03/27	Test Site	AC-6

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
25	1851.25	1419.0	1277.7
600	1880.00	1429.0	1276.6
1175	1908.75	1430.0	1282.7

**Figure Channel 25 (1851.25MHz)**




Figure Channel 600 (1880MHz)





Figure Channel 1175 (1908.75MHz)



Product	CDMA 1X Mobile Phone		
Test Item	Occupied Bandwidth		
Test Mode	Mode 3: CDMA 2000 1X BC15 Link		
Date of Test	2012/03/27	Test Site	AC-6

Channel No.	Frequency (MHz)	-26dB Occupied Bandwidth (kHz)	99% Occupied Bandwidth (kHz)
25	1711.25	1455.0	1292.2
450	1732.50	1422.0	1283.0
875	1753.75	1441.0	1284.7

**Figure Channel 25 (1711.25MHz)**




Figure Channel 450 (1732.50MHz)





Figure Channel 875 (1753.75MHz)




**6. Spurious Emission At Antenna Terminals (+/- 1MHz)**

**6.1. Test Equipment**

Spurious Emission At Antenna Terminals (+/- 1MHz) / AC-6

Instrument	Manufacturer	Type No.	Serial No	Cali. Due Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC6-TH	2013.01.10

**6.2. Test Setup**



**6.3. Limit**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

**6.4. Test Procedure**

In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.


**6.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 1.2$  dB.

## 6.6. Test Result

Product	CDMA 1X Mobile Phone		
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)		
Test Mode	Mode 1: CDMA 2000 1X BC0 Link		
Date of Test	2012/03/27	Test Site	AC-6

**Figure Channel 1013 (824.70MHz)**




**Figure Channel 777 (848.31MHz)**




Product	CDMA 1X Mobile Phone		
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)		
Test Mode	Mode 2: CDMA 2000 1X BC1 Link		
Date of Test	2012/03/27	Test Site	AC-6

**Figure Channel 25 (1851.25MHz)**




**Figure Channel 1175 (1908.75MHz)**




Product	CDMA 1X Mobile Phone		
Test Item	Spurious Emission At Antenna Terminals (+/- 1MHz)		
Test Mode	Mode 3: CDMA 2000 1X BC15 Link		
Date of Test	2012/03/27	Test Site	AC-6

**Figure Channel 25 (1711.25MHz)**



**Figure Channel 875 (1753.75MHz)**



**7. Spurious Emission**


**7.1. Test Equipment**

Spurious Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No	Cali. Due Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
PSG Analog Signal Generator	Agilent	E8257D	MY44321116	2012.04.23
Preamplifier	QuieTek	AP-025C	CHM-0503006	2012.05.05
Preamplifier	Miteq	NSP1800-25	1364185	2012.05.05
Bilog Antenna	Teseq GmbH	CBL6112D	27612	2012.10.18
Half Wave Tuned Dipole Antenna	COM-POWER	AD-100	40137	2013.11.24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	737	2013.11.24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2013.01.10

### 7.2. Test Setup


Conducted Spurious Emission Measurement:



Radiated Spurious Measurement: below 1GHz



Radiated Spurious Measurement: above 1GHz



### 7.3. Limit

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10\log(P)$  dB.

### 7.4. Test Procedure

#### Conducted Spurious Measurement:

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMU200 by a Directional Couple.
- c) EUT Communicate with CMU200, then select a channel for testing.
- d) Add a correction factor to the display of spectrum, and then test.
- e) The resolution bandwidth of the spectrum analyzer was set at 1 MHz, sufficient scans were taken to show the out of band Emission if any up to 10<sup>th</sup> harmonic.

#### Radiated Spurious Measurement:

- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.
- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the

- frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
  - f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
  - g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
  - v) The maximum signal level detected by the measuring receiver shall be noted.
  - h) The transmitter shall be replaced by a substitution antenna.
  - i) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
  - j) The substitution antenna shall be connected to a calibrated signal generator.
  - k) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
  - l) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
  - m) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
  - n) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
  - o) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
  - p) The frequency range was checked up to 10<sup>th</sup> harmonic.
  - q) Test site anechoic chamber refer to ANSI C63.4: 2009



## 7.5. Uncertainty

The measurement uncertainty is defined as 3.2 dB for Radiated Power Measurement.



## 7.6. Test Result

Product	GSM Mobile Phone		
Test Item	Conducted Spurious Emission		
Test Mode	Mode 1: CDMA 2000 1X BC0 Link Link		
Date of Test	2012/03/27	Test Site	TR-8



### Low Channel 1013(824.7MHz)



### Mid Channel 384(836.52MHz)







## High Channel 777(848.31MHz)





Product	GSM Mobile Phone		
Test Item	Conducted Spurious Emission		
Test Mode	Mode 2: CDMA 2000 1X BC1 Link		
Date of Test	2012/03/27	Test Site	TR-8

### Low Channel 25(1851.25MHz)







High Channel 1175(1908.75MHz)





Product	GSM Mobile Phone		
Test Item	Conducted Spurious Emission		
Test Mode	Mode 3: CDMA 2000 1X BC15 Link		
Date of Test	2012/03/27	Test Site	TR-8



### Low Channel 25(1711.25MHz)



Mid Channel 450(1732.50MHz)



## High Channel 875(1753.75MHz)



Product	CDMA 1X Mobile Phone		
Test Item	Radiated Spurious Emission		
Test Mode	Mode 1: CDMA 2000 1X BC0 Link Link		
Date of Test	2012/03/27	Test Site	AC-5

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 1013 (824.70MHz)								
1649.40	-55.35	V	-57.94	2.50	9.78	-50.66	-13.00	-37.66
2474.10	-61.68	V	-60.79	3.12	10.49	-53.42	-13.00	-40.42
1649.40	-49.04	H	-51.73	2.50	9.78	-44.45	-13.00	-31.45
2474.10	-59.12	H	-58.10	3.12	10.49	-50.73	-13.00	-37.73
Middle Channel 384 (836.52MHz)								
1672.64	-57.61	V	-60.28	2.51	9.94	-52.85	-13.00	-39.85
2508.96	-63.23	V	-62.60	3.18	10.61	-55.17	-13.00	-42.17
1672.64	-57.59	H	-60.01	2.51	9.94	-52.58	-13.00	-39.58
2508.96	-60.79	H	-59.71	3.18	10.61	-52.28	-13.00	-39.28
High Channel 777 (848.31MHz)								
1696.62	-56.28	V	-59.06	2.53	10.10	-51.49	-13.00	-38.49
2544.93	-62.88	V	-61.35	3.15	10.67	-53.83	-13.00	-40.83
1696.62	-57.08	H	-59.13	2.53	10.10	-51.56	-13.00	-38.56
2544.93	-59.86	H	-58.02	3.15	10.67	-50.50	-13.00	-37.50

Product	CDMA 1X Mobile Phone		
Test Item	Radiated Spurious Emission		
Test Mode	Mode 2: CDMA 2000 1X BC1 Link		
Date of Test	2012/03/27	Test Site	AC-5

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 25 (1851.25MHz)								
3702.50	-44.23	V	-40.79	3.83	12.69	-31.93	-13.00	-18.93
5553.75	-48.89	V	-40.37	4.82	13.14	-32.05	-13.00	-19.05
3702.50	-43.36	H	-39.99	3.83	12.69	-31.13	-13.00	-18.13
5553.75	-49.54	H	-41.65	4.82	13.14	-33.33	-13.00	-20.33
Middle Channel 600 (1880MHz)								
3760.00	-44.62	V	-41.4	3.73	12.72	-32.41	-13.00	-19.41
5640.00	-48.36	V	-40.43	4.92	13.13	-32.22	-13.00	-19.22
3760.00	-44.85	H	-41.55	3.73	12.72	-32.56	-13.00	-19.56
5640.00	-55.07	H	-47.46	4.92	13.13	-39.25	-13.00	-26.25
High Channel 1175 (1908.75MHz)								
3817.50	-45.99	V	-42.31	3.98	12.73	-33.56	-13.00	-20.56
5726.25	-46.72	V	-38.11	4.86	13.11	-29.86	-13.00	-16.86
3817.50	-44.57	H	-40.71	3.98	12.73	-31.96	-13.00	-18.96
5726.25	-51.42	H	-43.19	4.86	13.11	-34.94	-13.00	-21.94

Product	CDMA 1X Mobile Phone		
Test Item	Radiated Spurious Emission		
Test Mode	Mode 3: CDMA 2000 1X BC15 Link		
Date of Test	2012/03/27	Test Site	AC-5

Frequency (MHz)	SA Reading (dBm)	Ant.Pol. (H/V)	SG Reading (dBm)	Cable Loss (dB)	Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)
Low Channel 25 (1711.25MHz)								
3422.50	-55.23	V	-53.41	3.73	12.88	-44.26	-13.00	-31.26
5133.75	-57.91	V	-49.78	4.60	12.79	-41.59	-13.00	-28.59
3422.50	-54.10	H	-52.35	3.73	12.88	-43.20	-13.00	-30.20
5133.75	-57.79	H	-49.64	4.60	12.79	-41.45	-13.00	-28.45
Middle Channel 450 (1732.50MHz)								
3465.00	-60.59	V	-58.19	3.69	12.73	-49.15	-13.00	-36.15
5197.50	-58.78	V	-51.40	4.6	12.85	-43.15	-13.00	-30.15
3465.00	-59.11	H	-56.50	3.69	12.73	-47.46	-13.00	-34.46
5197.50	-57.90	H	-50.66	4.6	12.85	-42.41	-13.00	-29.41
High Channel 875 (1753.75MHz)								
3507.50	-57.36	V	-54.63	3.72	12.60	-45.75	-13.00	-32.75
5261.25	-61.41	V	-54.09	4.65	12.94	-45.80	-13.00	-32.80
3507.50	-59.36	H	-56.45	3.72	12.60	-47.57	-13.00	-34.57
5261.25	-62.42	H	-55.10	4.65	12.94	-46.81	-13.00	-33.81


## 8. Frequency Stability Under Temperature & Voltage Variations

### 8.1. Test Equipment

Frequency Stability Under Temperature & Voltage Variations / AC-6

Instrument	Manufacturer	Type No.	Serial No	Cali. Due Date
PSA Series Spectrum Analyzer	Agilent	E4440A	MY49420184	2012.04.10
Radio Communication Tester	R&S	CMU 200	117088	2012.04.29
Dual Directional Coupler	Agilent	778D	20160	2012.04.20
10dB Coaxial Coupler	Agilent	87300C	MY44300299	2012.04.20
DC Power Supply	IDRC	CD-035-020PR	977272	2012.09.22
Temperature & Humidity Chamber	Gaoyu	TH-1P-B	WIT-05121302	2013.01.13
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC6-TH	2013.01.10

### 8.2. Test Setup



**8.3. Limit**

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Limit	$< \pm 2.5 \text{ ppm}$
-------	-------------------------

**8.4. Test Procedure**

**Frequency Stability Under Temperature Variations:**

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

**Frequency Stability Under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

**8.5. Uncertainty**

The measurement uncertainty is defined as  $\pm 10 \text{ Hz}$ .

8.6. Test Result

Product	CDMA 1X Mobile Phone		
Test Item	Frequency Stability Under Temperature & Voltage Variations		
Test Mode	Mode 1: CDMA 2000 1X BC0 Link		
Date of Test	2012/03/27	Test Site	AC6

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	836.52	56	± 2091.3
-20	836.52	-49	± 2091.3
-10	836.52	-36	± 2091.3
0	836.52	28	± 2091.3
10	836.52	25	± 2091.3
20	836.52	-19	± 2091.3
30	836.52	35	± 2091.3
40	836.52	37	± 2091.3
50	836.52	42	± 2091.3

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
4.200	836.52	-28	± 2091.3
3.700	836.52	-19	± 2091.3
3.500	836.52	-41	± 2091.3

Product	CDMA 1X Mobile Phone		
Test Item	Frequency Stability Under Temperature & Voltage Variations		
Test Mode	Mode 2: CDMA 2000 1X BC1 Link		
Date of Test	2012/03/27	Test Site	AC6

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	1880	58	± 4700
-20	1880	-42	± 4700
-10	1880	-39	± 4700
0	1880	-45	± 4700
10	1880	22	± 4700
20	1880	-21	± 4700
30	1880	40	± 4700
40	1880	23	± 4700
50	1880	31	± 4700

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
4.200	1880	-28	± 4700
3.700	1880	-21	± 4700
3.500	1880	-30	± 4700

Product	CDMA 1X Mobile Phone		
Test Item	Frequency Stability Under Temperature & Voltage Variations		
Test Mode	Mode 3: CDMA 2000 1X BC15 Link		
Date of Test	2012/03/27	Test Site	AC6

Frequency Stability under Temperature

Temperature Interval (°C)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
-30	1732.50	62	± 4331.25
-20	1732.50	-54	± 4331.25
-10	1732.50	38	± 4331.25
0	1732.50	40	± 4331.25
10	1732.50	31	± 4331.25
20	1732.50	-27	± 4331.25
30	1732.50	-31	± 4331.25
40	1732.50	34	± 4331.25
50	1732.50	46	± 4331.25

Frequency Stability under Voltage

DC Voltage (V)	Test Frequency (MHz)	Deviation (Hz)	Limit (Hz)
4.200	1732.50	-36	± 4331.25
3.700	1732.50	-27	± 4331.25
3.500	1732.50	-39	± 4331.25