



## FCC SAR Exemption Evaluation Report

**Product Name:** Wearable Device

**Model:** TalkBand N1

**Report No.:** SYBH(Z-SAR)008062015-2

**FCC ID:** QISN1

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>Luo Ziliang</i>
DATE	2015-06-17	2015-06-17

The test results of this test report relate exclusively to the item(s) tested. The HUAWEI does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of HUAWEI.

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

**※ ※ Modified History ※ ※**

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2015-06-17	Luo Ziliang

## Table of Contents

1	EUT Description .....	4
1.1	General Description .....	4
2	Test specification(s).....	5
3	Testing laboratory .....	5
4	Applicant and Manufacturer.....	5
5	Application details .....	5
6	Ambient Condition.....	5
7	RF exposure limits .....	6
8	SAR Exemption Evaluation .....	7

## 1 EUT Description

Device Information:			
Product Name:	Wearable Device		
Model:	TalkBand N1		
FCC ID :	QISN1		
Device Type :	Portable device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment / general population		
Hardware Version :	R04		
Software Version :	21.01.09.01.00		
Antenna Type :	Internal Antenna		
Antenna Gain :	-0.36dBi		
Device Operating Configurations:			
Supporting Mode(s)	BT		
Test Modulation	GFSK		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	BT	2400-2483.5	2400-2483.5

Table 1: Device information and operating configuration

### 1.1 General Description

TalkBand N1 is a intelligent sports Necklace type earphone, which can be communicated with mobile phone via Bluetooth. N1 Supports voice recognition calls and MP3 player independently. It supports Bluetooth with 1TX and 1RX.

## 2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.( IEEE Std C95.1-1991)
KDB447498 D01	General RF Exposure Guidance v05r02

## 3 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Zone G1,Huawei Industrial Base, Bantian Industry Area, Longgang District, Shenzhen, Guangdong, China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01

## 4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

## 5 Application details

Start Date of test	2015-06-17
End Date of test	2015-06-17

## 6 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

## 7 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
<b>Spatial Peak SAR*</b> (Brain/Body/Arms/Legs)	<b>1.60 mW/g</b>	8.00 mW/g
<b>Spatial Average SAR**</b> (Whole Body)	0.08 mW/g	0.40 mW/g
<b>Spatial Peak SAR***</b> (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 2: RF exposure limits

The limit applied in this test report is shown in **bold** letters

### Notes:

\* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

\*\* The Spatial Average value of the SAR averaged over the whole body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation)

## 8 SAR Exemption Evaluation

Per FCC KDB 447498D01v05r02, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Band	$P_{\text{max}}$ (dBm)*	$P_{\text{max}}$ (mW)	Distance (mm)	f (GHz)	Calculation Result	Exclusion threshold	SAR evaluation
BT	4.0	2.51	$\leq 5$	2.450	0.79	3.0	Not required

Table 3: Standalone SAR test exclusion for BT

Note:

- 1)\* - Maximum possible output power(including tune-up tolerance) declared by manufacturer
- 2) The test separation distance for this device is  $\leq 5$  mm, so a distance of 5 mm is applied to determine SAR test exclusion per FCC KDB 447498D01.

According to the table above, the device can meet the SAR test exclusion thresholds requirement of FCC KDB 447498 D01 and SAR evaluation is not required.

**End**