



EMC Test Report

Product Name: Smart Phone

Model Number: HWV31

Report No: SYBH(Z-EMC)028112017-2

FCC ID: QISPIC-LX9

Reliability Laboratory of Huawei Technologies Co., Ltd.

Global Compliance and Testing Center of Huawei Technologies
Co., Ltd

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01
3. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 6369A-1.
4. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
5. The laboratory has been recognized by the US Federal Communications Commission (FCC) to perform compliance testing subject to the Commission's Certification rules. The Designation Number is CN1173, and the Test Firm Registration Number is 294140.
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Date of Receipt Test Item: Nov.10,2017
Start Date of Test: Nov.11,2017
End Date of Test: Nov.20,2017

Test Result: Pass

**Approved By
(Lab Manager)**

2017-11-23
Date

Roger Zhang
Name

Roger Zhang

Signature

**Prepared by
(Test Engineer)**

2017-11-22
Date

Huamei
Name

Hua Mei

Signature



Modification Record

No.	Last Report No.	Modification Description
1	NA	First Report.

TABLE OF CONTENT

1	General Information.....	6
1.1	EUT Description	6
1.2	Test Site Information.....	8
1.3	Applied Standards.....	8
2	Summary of Results	9
3	System Configuration during EMC Test	10
3.1	Test Mode	10
3.2	Test System Configuration	11
3.3	Cables Used during Test.....	12
3.4	Associated Equipment Used during Test	12
4	Electromagnetic Interference (EMI)	13
4.1	Radiated Disturbance 30MHz to 18GHz.....	13
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	15
5	Main Test Instruments	16
6	System Measurement Uncertainty	16
7	Test Data and Graph.....	17
7.1	Radiated Disturbance.....	17
7.2	Conducted Disturbance.....	19

1 General Information

1.1 EUT Description

EUT Description	
Product Name	Smart Phone
Model Number	HWV31
Input voltage	3.8V DC
TX Frequency	GSM 850:824MHz to 849MHz PCS 1900:1850MHz to 1910MHz WCDMA Band V:824MHz to 849MHz LTE BAND 5: 824MHz to 849MHz LTE BAND 7: 2500MHz to 2570MHz LTE BAND 26: 814MHz to 849MHz LTE BAND 38: 2570MHz to 2620MHz LTE BAND 41: 2545MHz to 2655MHz Bluetooth/WIFI: 2400MHz to 2483.5MHz
RX Frequency	GSM 850: 869MHz to 894MHz PCS 1900: 1930MHz to 1990MHz WCDMA Band V:869MHz to 894MHz LTE BAND 5:869MHz to 894MHz LTE BAND 7:2620MHz to 2690MHz LTE BAND 26:859MHz to 894MHz LTE BAND 38:2570MHz to 2620MHz LTE BAND 41:2545MHz to 2655MHz Bluetooth/WIFI:2400MHz to 2483.5MHz GPS: 1575.42MHz
S/N	NJSDU17930001576
HW Version	HL1PICL01M
SW Version	HWV31C791B100
EUT Accessory	
Data cable	Data Cable USB A Male to Type C,Shielded Manufacturer: HONGLIN TECHNOLOGY CO.,LTD; FOXCONN INTERCONNECT TECHNOLOGY LIMITED. LUXSHAREICT; Foxlink;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-059200UHQ Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V === 2A OR 9V === 2A Rated Power: 10W OR 18W SN: B76595GC521408; K76596GC324251;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-059200JHQ Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V === 2A OR 9V === 2A Rated Power: 10W OR 18W SN: B73098H9S21161; K73045H9J02473;

Rechargeable Li-ion	Manufacturer:Huawei Technologies Co.,Ltd. Battery Model: HB366179ECW Rated capacity: 2850mAh Nominal Voltage:  +3.82V Charging Voltage:  +4.40V SN:2563SIGC06X00001
Earphone	Manufacturer: Jiangxi Lianchuang Hongsheng Electronic Co.,LTD Goertek; Merry Electronics Co., Ltd BOLUO COUNTY QUANCHENG ELECTRONIC CO.,LTD

Remark: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed information.



1.2 Test Site Information

Test Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15 2016, Subpart B
ICES-003 Issue 5

2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode2~ Mode4	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the uncertainty of test system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

3 System Configuration during EMC Test

3.1 Test Mode

The EUT was configured, installed, arranged and operated in a manner consistent with typical application. The following mode(s) were applied during the compliance test.

Test Mode	
Mode 1:	Charging +traffic +WIFI +BT +GPS On +Earphone
Mode 2:	Charging +Camera On+ Earphone +idle
Mode 3:	Charging +Video Playing+ Earphone +idle
Mode 4:	USB Copy(EUT with PC) + Earphone + idle

Remark:

- 1) If there is one kind of accessories with different models, each one should be applied throughout the compliance test respectively, however, only the worst case will be recorded in this report.
- 2) If EUT has more than one typical operation, only the worst test mode will be recorded in this report.

Traffic Mode:

When the EUT state is switched on and with Radio Resource Control (RRC) connection established.

Idle Mode:


When the EUT state is switched on but without Radio Resource Control (RRC) connection.

Worst Case:


- 1) Radiated Emission
Mode 3: Adapter(Model: HW-059200UHQ, SN: K76523FCF06857)+Video Playing+Earphone+idle
the result is the worst.(30M-1G)
Mode 3: Adapter(Model: HW-059200UHQ, SN: B76595GC521408)+Video Playing+Earphone+idle
the result is the worst.(1G-18G)
- 2) Conducted Emission
Mode 3:Adapter(Model: HW-059200UHQ, SN: B76595GC521408)+Camera On+ Earphone+idle
the result is the worst.

3.2 Test System Configuration

Connection Diagram (Mode 1~Mode 3)



Connection Diagram (Mode 4)



3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	Shielded
Earphone	1	<3m	Unshielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline	Cal interval
Radio Communication Tester	CMU200	R&S	3608082535	2018-03-01	12
Radio Communication Tester	MT8820C	Anritsu	A110518805	2018-05-15	12
Notebook	S3	ThinkPad	A140714638	/	/
Mouse	MOHQUO	HP	G1K28AA	/	/

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz

4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANCI C63.4: 2014. The test distance was 3m. The set-up and test methods were according to ANCI C63.4: 2014.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; The emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m. The azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 kHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT was configured in idle mode and the test performed at worst emission state.

4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)

4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
Refer to the section 7.1.1 of this report for test data.

Test Limits (Class B)				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

4.2 Conducted Disturbance 0.15 MHz to 30MHz

4.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANCI C63.4: 2014 Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150 kHz to 30 MHz: 9 kHz;

The EUT was set in the shielded chamber and operated under nominal conditions.

4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines.

Refer to the section 7.2.1 of this report for test data.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dB μ V)	AV (dB μ V)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50

5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline	Cal interval
RE	EMI Test receiver	ESU26	100150	R&S	Jun. 20, 2018	12
	Broadband Antenna	VULB 9163	9163-491	SCHWARZBECK	Mar. 28, 2019	24
	Horn Antenna	HF906	100683	R&S	Mar. 28, 2019	24
CE	EMI Test receiver	ESU26	100150	R&S	May. 15, 2018	12
	Artificial Mains Network	ENV4200	100134	R&S	May. 15, 2018	12
	Artificial Mains Network	ENV216	100382	R&S	May. 15, 2018	12
Software Information						
Test Item	Software Name	Manufacturer		Version		
RE	EMC32	R&S		V9.25.0		
CE	EMC32	R&S		V9.25.0		

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dB μ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=5.1dB; k=2
CE	Disturbance Voltage (dB μ V)	U=2.5dB; k=2

7 Test Data and Graph

Only the worst test results were shown

7.1 Radiated Disturbance

7.1.1 30MHz~1GHz

Test Mode 3: Charging+Video Playing+ Earphone +idle



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
40.205429	28.2	17.2	40	11.8	101	68	V
45.244286	27.22	16.5	40	12.78	102	179	V
135.131143	24.78	13.6	43.5	18.72	101	297	V
194.340572	26.41	12.4	43.5	17.09	100	181	V
326.525429	29.69	16.7	46	16.31	101	296	H
455.414	31.65	19.4	46	14.35	102	287	H


Note:

Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

7.1.2 1GHz~18GHz

Test Mode 3: Charging+Video Playing+ Earphone +idle



MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
2441.968667	43.18	-7.6	74	30.82	100	234	V
16861.51533	59.72	20.9	74	14.28	191	248	H
17881.29733	59.64	21.6	74	14.36	125	218	V

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
2436.428	26.32	-7.6	54	27.68	178	290	V
16330.94667	43.41	18.5	54	10.59	100	210	V
16884.30733	46.4	21	54	7.6	100	328	V


Note:

Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)
The reading level is calculated by software which is not shown in the sheet.

7.2 Conducted Disturbance

7.2.1 AC Port Test Data

Test Mode 2: Charging+Camera On+Earphone+idle



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Line	Transd dB	Margin dB	Limit dBµV	PE
0.168264	52.6	L1	9.7	12.45	65.05	FLO
0.257861	48.01	L1	9.7	13.49	61.50	FLO
0.335883	43.71	N	9.7	15.59	59.30	FLO
0.555817	39.2	L1	9.7	16.8	56	FLO
0.743848	30.59	N	9.7	25.41	56	FLO
12.407144	37.83	N	10	22.17	60	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Line	Transd dB	Margin dB	Limit dBµV	PE
0.225988	28.18	N	9.7	24.42	52.6	FLO
0.572177	24.14	N	9.7	21.86	46	FLO
0.630286	22.25	N	9.7	23.75	46	FLO
2.251998	23.83	N	9.7	22.17	46	FLO
2.377189	26.36	N	9.7	19.64	46	FLO
13.250758	26.27	N	10.1	23.73	60	FLO

END
