

1 2 3 4

REV	ECA NQ	DESCRIPTION

A
B
C

A
B
C



Model: pRRU3901 PCS+2.6G
 电源额定值 POWER RATING:
 - 48 V; 1.15 A Supplied by PoE



CONFORMS TO
 UL STD. 60950-1
 CERTIFIED TO CSA STD.
 C22.2 NO. 60950-1

CAN ICES-3(B)/NMB-3(B)
 IC : 6369A-PRU01P2G6

FCC ID: QISPRU01P2G6

Intertek
 4001377
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

华为技术有限公司
 HUAWEI TECHNOLOGIES CO., LTD.
 中国制造
 MADE IN CHINA



D
E

D
E

NOTE :

1. Make the film according to the drawing.
2. The color of silk-screen characters is C:100 M:100 Y:100 K:100, The Text Outline width is 0.1 mm.
3. The silk-screen should be clear ,without burrs,and the dimension should be accurate.

RELEASE LEVEL: [] RELEASED []
 FILE NAME: 02310XGJM01_pRRU3901 PCS+2.6G DC

X.	± 0.5			HUAWEI TECHNOLOGIES Co.LTD			TITLE: product nameplate		
	± 0.2			DRAW: zhangxingwei			DATE: 12-Jun-2015	UNITS: mm	DWG NO: 02310XGJM01_pRRU3901 PCS+2.6G DC
.XX		ANG		CHKD: zhangxingwei	DATE: 12-Jun-2015	FINISH: A000	PART NO:		REV
THESE DRAWINGS AND SPECIFICATION ARE THE PROPERTY OF HUAWEI TECH Co.LTD AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HUAWEI TECH CO.LTD.				APPD: yangsiming	DATE: 12-Jun-2015	SCALE: 1:1	MAT'L: DKBA8.818.2466/29042966		C
				PRODUCT:					SHEET: 1 OF 1

F
A4

F

1 2 3 4

Label Location

