

Declaration of Compliance for RF Exposure Evaluation

To whom it may concern,

As to the product **RRU3261 2300M(LTE Band 30)** made by Huawei Technologies Co., Ltd. as the applicant and Huawei Technologies Co., Ltd. as the manufacturer, we declare that it complies with the following standards(s):

- 47CFR FCC Part 1 & OET Bulletin 65

The compliance is demonstrated based on the following calculation model assessment:

1. The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

- P = input power of the antenna.
- G = antenna gain relative to an isotropic antenna.
- θ, ϕ = elevation and azimuth angles.
- R = distance from the antenna to the point of investigation.

2. For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Where:

- S_i = the power density when the f is i .
- $S_{Limit,i}$ = the reference level requirement for power density when f is i .
- f = operating frequency.

3. The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation for Individual Source		
RF Source #1	f	=	2350 to 2360 MHz
	$S_{Limit,i}$	=	= 10 W/m ²

	$P, G_{(\theta,\phi)}$	☒ $P \times G_{(\theta,\phi)}$: $P^{(*)} = 25.12 \text{ W} (=43+1=44.0 \text{ dBm, per port})$ $100.48 \text{ W} (\text{calculated, four ports})$ $G_{(\theta,\phi)} = 63.096 (=18 \text{ dBi})$ $(*)$: The value is from: ☐ measured max (See relevant RF report), ☒ rated + declared tolerance, ☐ max allowed by RF standard. And, the transmission duty cycle is: ☒ ignored, ☐ used, that is: _____ % (for mode: _____).
	θ, ϕ	= The worst condition is considered, i.e. the max G is used.
	S_i	= $\frac{P \times G_{(\theta,\phi)}}{4 \times \pi} / R^2 = 504.51 / R^2 \text{ W/m}^2$
	$\frac{S_i}{S_{Limit,i}}$	= $50.45 / R^2$
Whole Product	Calculation for Whole Product	
Whole Product	$\frac{S}{S_{Limit}}$	= $50.45 / R^2 \leq 1$
	R	$\geq 7.1 \text{ m} (\text{the minimum Safe Distance})$
	NOTE: The result is the worst case of each individual source and simultaneous transmission sources (if applicable).	

Person responsible for making this declaration:



Li Guo
RF Engineer, EMC Lab
Reliability Laboratory of Huawei Technologies Co., Ltd.
July 27, 2015