



Appendix G

Frequency Stability

According to FCC Part 2.1055& Part 24.235



Frequency Error vs. Temperature:

Test Mode	RF Ch.	Volt.	Temp.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	VN	-30 °C	-22	-0.01170	---	±2.5	Pass
			-20 °C	7	0.00372	---	±2.5	Pass
			-10 °C	-16	-0.00851	---	±2.5	Pass
			0 °C	-16	-0.00851	---	±2.5	Pass
			10 °C	-14	-0.00745	---	±2.5	Pass
			20 °C	-15	-0.00798	---	±2.5	Pass
			30 °C	-7	-0.00372	---	±2.5	Pass
			40 °C	14	0.00745	---	±2.5	Pass
			50 °C	15	0.00798	---	±2.5	Pass
TM 2	M	VN	-30 °C	-12	-0.00638	---	±2.5	Pass
			-20 °C	-19	-0.01011	---	±2.5	Pass
			-10 °C	11	0.00585	---	±2.5	Pass
			0 °C	26	0.01383	---	±2.5	Pass
			10 °C	9	0.00479	---	±2.5	Pass
			20 °C	-15	-0.00798	---	±2.5	Pass
			30 °C	28	0.01489	---	±2.5	Pass
			40 °C	12	0.00638	---	±2.5	Pass
			50 °C	-15	-0.00798	---	±2.5	Pass
TM 3	M	VN	-30 °C	-13	-0.00691	---	±2.5	Pass
			-20 °C	20	0.01064	---	±2.5	Pass
			-10 °C	16	0.00851	---	±2.5	Pass
			0 °C	17	0.00904	---	±2.5	Pass
			10 °C	-21	-0.01117	---	±2.5	Pass
			20 °C	18	0.00957	---	±2.5	Pass
			30 °C	14	0.00745	---	±2.5	Pass
			40 °C	-7	-0.00372	---	±2.5	Pass
			50 °C	12	0.00638	---	±2.5	Pass



Frequency Error vs. Voltage:

Test Mode	RF Ch.	Temp.	Volt.	Freq. Error [Hz]	Freq. vs. rated [ppm]	Freq. vs. 20 °C [ppm]	Limit [ppm]	Verdict
TM 1	M	20 °C	VL	11	0.00585	---	±2.5	Pass
			VN	13	0.00691	---	±2.5	Pass
			VH	-21	-0.01117	---	±2.5	Pass
TM 2	M	20 °C	VL	25	0.01330	---	±2.5	Pass
			VN	-6	-0.00319	---	±2.5	Pass
			VH	-16	-0.00851	---	±2.5	Pass
TM 3	M	20 °C	VL	-10	-0.00532	---	±2.5	Pass
			VN	16	0.00851	---	±2.5	Pass
			VH	-11	-0.00585	---	±2.5	Pass

-----The END-----