



EMC Test Report

Product Name: HUAWEI MediaPad

Model Number: S7-303u

Report No: SYBH(Z-EMC)153112011-2

FCC ID: QISS7-303U

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

TABLE OF CONTENT

1	General Information	5
1.1	EUT Description.....	5
1.2	Test Site Information.....	6
1.3	Applied Standard	6
2	Summary of Results	7
3	System Configuration during EMC Test	8
3.1	Test Mode	8
3.2	Configurations of Test System	8
3.3	Cables Used during Test.....	9
3.4	Associated Equipment Used during Test	9
4	Electromagnetic Interference (EMI)	10
4.1	Radiated Disturbance 30MHz to 18GHz	10
4.2	Conducted Disturbance 0.15 MHz to 30MHz	12
5	Main Test Instruments	13
6	System Measurement Uncertainty.....	13
7	Graph and Data of Emission Test.....	14
7.1	Radiated Disturbance	14
7.2	Conducted Disturbance.....	16

1 General Information

1.1 EUT Description

EUT Description	
Product Name	HUAWEI MediaPad
Model Number	S7-303u
Serials Number	E3T6RD1171400378
Working Voltage	 +3.7V
TX Frequency	GPRS/EDGE 850: 824MHz To 849MHz GPRS/EDGE 1900: 1850MHz To 1910MHz WCDMA/HSDPA/HSUPA AWS: 1710MHz To 1755MHz WCDMA/HSDPA/HSUPA Band II: 1850MHz To 1910MHz Bluetooth: 2400MHz To 2483.5MHz WIFI: 2400MHz To 2483.5MHz
RX Frequency	GPRS/EDGE 850: 869MHz To 894MHz GPRS/EDGE 1900: 1930MHz To 1990MHz WCDMA/HSDPA/HSUPA AWS: 2110MHz To 2155MHz WCDMA/HSDPA/HSUPA Band II: 1850MHz To 1910MHz Bluetooth: 2400MHz To 2483.5MHz WIFI: 2400MHz To 2483.5MHz GPS:1575.42
HW Version	HIDS7PMA
SW Version	S7-303uV100R001C201
EUT Accessory	
Data Cable	Manufacture: Liansheng Model: LSA00319
	Manufacture: PENGYI Model: H09-000159
	Manufacture: PENGYI Model: H09-000287
Adapter	Manufacture: SHENZHEN FRECOM Model:FM050020-US Input voltage: 100V-240VAC,50/60Hz,0.6A Output voltage: +5V  2A
	Manufacture: SHENZHEN FRECOM Model: FPS012USA-050200 Input voltage: 100V-240VAC,50/60Hz,0.3A Output voltage: +5V  2A
	Manufacture: Huawei Technologies Co., Ltd. Model: HW-050200U3W Input voltage: 100V-240VAC,50/60Hz,0.5A Output voltage: +5V  2A
Li-ion	Manufacture: Huawei Technologies Co., Ltd. Model: HB3G1H Rated capacity:4000 mAh Nominal Voltage  +3.7V Charging Voltage  +4.2V
Earphone	Manufacture: QUANCHENGDIANZI Model: 1235#+3260# 3.5mm

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.2 Test Site Information

Test Site:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Bantian Longgang District Shenzhen, P.R. China

1.3 Applied Standard

APPLIED STANDARD

FCC 47 CFR FCC Part 15 SubpartB

2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode1 Mode2	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input checked="" type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1 Mode2 Mode3 Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

3 System Configuration during EMC Test

3.1 Test Mode


Huawei has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was in this test report and defined as:


Mode 1:	Adapter + TF card + Earphone + HDMI (TV) + Camera + radio service in Idle model + Personal computer
Mode 2:	Adapter + TF card + Earphone + HDMI (TV) + radio service in Idle model + U-disk
Mode 3:	Adapter + TF card + Earphone + HDMI (TV) + Camera + radio service in traffic model + Personal computer
Mode 4:	Adapter + TF card + Earphone + HDMI (TV) + radio service in traffic model + U-disk

Remark: When the EUT have multiple adapters, need separate test with multiple adapters . All test modes are performed, only the worst cases are recorded in this report.

3.2 Configurations of Test System

The solid ferrite is used adapter line and HDMI line during the test, the solid ferrite model is DYR-70-A.





3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
AC Power	1	<3m	unshielded
HDMI	1	<3m	shielded
Earphone	1	<3m	unshielded
Data cable	3	<3m	shielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline
Radio Communication Tester	CMU200	R&S	3607033573	2012-3-16
Wireless Connectivity Test Set	N4010A	Agilent	A110103426	2011-12-14
Notebook	D630	DELL	0W7349	N/A
Television	KLV-20S400A	SONY	5017657	N/A
U-disk	USM4GL	SONY	6939543906972	N/A

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz

4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4. The test distance was 3m. The set-up and test methods were according to ANSI C63.4.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup.

Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)

4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
The test data see section 7.1 of this report.

Test Limits				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

Test environment condition:

Performed Item	Item	Required	Actual
Radiated Emission	Ambient temperature	15°C ~ 35°C	23°C
	Relative humidity	25% ~ 75%	51%
	Atmospheric pressure	86kPa ~ 106kPa	101kPa

4.2 Conducted Disturbance 0.15 MHz to 30MHz

4.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei Mobile Station was communicated with the base station simulator through Air interface, the BTS simulator controls the Mobile Station to transmitter the maximum power which defined in specification of product. The Mobile Station operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

The Mobile Station was setup in the screened chamber and operated under nominal conditions.

4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines.
The test data see section 7.2 of this report.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dBμV)	AV(dBμV)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50

Test environment condition:

Performed Item	Item	Required	Actual
Conducted Disturbance	Ambient temperature	15°C ~ 35°C	23°C
	Relative humidity	25% ~ 75%	51%
	Atmospheric pressure	86kPa ~ 106kPa	101kPa

5 Main Test Instruments

Main Test Equipments					
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline
RE/CE	EMI Test receiver	ESU26	100150	R&S	May.29, 2012
	Broadband Antenna	VULB 9163	9163-941	SCHWARZBECK	Jul.07, 2012
	Horn Antenna	HF906	100683	R&S	May.15, 2012
	Artificial Mains Network	ENV216	100382	R&S	May.29, 2012
Software Information					
Test Item	Software Name	Manufacturer		Version	
RE/CE	ES-K1	R&S		1.7.1	

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items	Extended Uncertainty	
RE(30MHz-1GHz,)	Field strength (dB μ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=4.1dB; k=2
CE	Disturbance Voltage (dB μ V)	U=3.4dB; k=2

7 Graph and Data of Emission Test

Here only the worst test result was shown.

7.1 Radiated Disturbance


7.1.1 30MHz~1GHz



MEASUREMENT RESULT: QP Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBµV/m	dB	dBµV/m	dB	cm	deg	
53.400000	30.80	12.7	40.0	9.2	100.0	281.00	VERTICAL
158.940000	33.30	9.5	43.5	10.2	100.0	291.00	VERTICAL
168.000000	36.60	9.9	43.5	6.9	134.0	197.00	HORIZONTAL
304.740000	36.10	15.6	46.0	9.9	107.0	359.00	HORIZONTAL
362.940000	37.80	17.4	46.0	8.2	100.0	113.00	HORIZONTAL
594.060000	43.10	22.4	46.0	2.9	100.0	320.00	VERTICAL

7.1.2 1GHz~6GHz



MEASUREMENT RESULT: PK Detector


Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBµV/m	dB	dBµV/m	dB	cm	deg	
1483.500000	48.10	-14.6	74.0	25.9	100.0	0.00	VERTICAL
1619.500000	52.80	-13.9	74.0	21.2	100.0	41.00	HORIZONTAL
2268.000000	54.20	-11.0	74.0	19.8	100.0	61.00	HORIZONTAL

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dBµV/m	dB	dBµV/m	dB	cm	deg	
1483.500000	31.60	-14.6	54.0	22.4	100.0	0.00	VERTICAL
1619.500000	45.60	-13.9	54.0	8.4	100.0	43.00	HORIZONTAL
2268.000000	48.10	-11.0	54.0	5.9	100.0	60.00	HORIZONTAL

7.2 Conducted Disturbance

7.2.1 AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency	Level	Transducer	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.364000	39.10	10.0	59	19.5	N	FLO
0.508000	44.80	10.1	56	11.2	N	FLO
0.512000	44.20	10.1	56	11.8	N	FLO
0.630000	43.60	10.1	56	12.4	N	FLO
1.190000	39.30	10.1	56	16.7	N	FLO
1.542000	40.40	10.1	56	15.6	N	FLO

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.404000	30.40	10.0	48	17.4	N	FLO
0.494000	36.10	10.1	46	10.0	N	FLO
0.632000	34.70	10.1	46	11.3	N	FLO
1.364000	32.20	10.1	46	13.8	N	FLO
2.432000	31.90	10.1	46	14.1	N	FLO
5.142000	33.60	10.2	50	16.4	L1	FLO

-----END-----