



EMC Test Report

Product Name: HUAWEI MediaPad 7 Lite

Model Number: S7-931w

Report No: SYBH(Z-EMC)171082012-2

FCC ID: QISS7-931W

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518



Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
5. The test report is invalid if not marked with "exclusive stamp for the test report".
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Date of Receipt Test Item: Aug,19, 2012
Start Date of Test: Aug.22, 2012
End Date of Test: Aug.28, 2012
Test Result: Pass

**Approved By
(Lab Manager)**

2012-08-30
Date

Liuchunlin
Name

Signature

Operator

2012-08-29
Date

Liulingbin
Name

Signature



Modification Record

No.	Last Report No.	Modification Description
1	NA	First report



TABLE OF CONTENT

1	General Information	6
1.1	EUT Description	6
1.2	Test Site Information	6
1.3	Applied Standards	6
2	Summary of Results.....	7
3	System Configuration during EMC Test.....	8
3.1	Test Mode.....	8
3.2	Configurations of Test System	8
3.3	Cables Used during Test	9
3.4	Associated Equipment Used during Test.....	9
4	Electromagnetic Interference (EMI).....	10
4.1	Radiated Disturbance 30MHz to 18GHz.....	10
4.2	Conducted Disturbance 0.15 MHz to 30MHz	12
5	Main Test Instruments.....	13
6	System Measurement Uncertainty	14
7	Test Data and Graph.....	15
7.1	Radiated Disturbance.....	15
7.2	Conducted Disturbance	17



1 General Information

1.1 EUT Description

EUT Description	
Product Name	HUAWEI MediaPad 7 Lite
Model Number	S7-931w
Serials Number	P9Q6RB9271465368
Working Voltage	5Vdc
TX Frequency	Bluetooth: 2402MHz To 2480MHz WIFI: 2412MHz To 2462MHz
RX Frequency	Bluetooth: 2402MHz To 2480MHz WIFI: 2412MHz To 2462MHz GPS: 1575.42MHz
HW Version	SH1931UM
SW Version	S7-931Wv100R001C001
EUT Accessory	
Data cable	Brand: Huawei Technologies Co., Ltd. Data Cable USB Male to Mini USB Male, Black,
Adapter 1	Brand: HUAWEI Model:HW-050200U3W Input voltage: 100V-240V~50/60Hz, 0.5A MAX Output voltage: 5V $\overline{\text{---}}$ 2A S/N:HWHKAAC41900013; HWXQAAC41700019
Li-ion	Brand: HUAWEI Battery Model: HB3G1 Rated capacity: 4000mAh Nominal Voltage: $\overline{\text{---}}$ +3.7V Charging Voltage: $\overline{\text{---}}$ +4.2V

Remark: The information of the EUT is declared by the manufacturer. Please refer to the specifications or user manual for details.

1.2 Test Site Information

Test Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2011, Subpart B



2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode2 Mode3	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input checked="" type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the uncertainty of test system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

3 System Configuration during EMC Test

3.1 **Test Mode**

The EUT was configured, installed, arranged and operated in a manner consistent with typical application. The following mode(s) were applied during the compliance test.

Test Mode	
Mode 1:	Adapter (charge) + earphone + Camera on + wireless service traffic mode
Mode 2:	PC (Power supply and USB xcopy) + TF card + earphone + wireless service IDLE mode
Mode 3:	Adapter (charge) + earphone + Camera on + wireless service IDLE mode

Remark: If there is more than one adapter, each one should be applied throughout the compliance test respectively, however, only the worst case will be recorded in this report.


Traffic Mode:


State of EUT when switched on and with Radio Resource Control (RRC) connection established

IDLE Mode:

State of EUT when switched on but with no Radio Resource Control (RRC) connection

3.2 **Configurations of Test System**





3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	shielded
Earphone	1	<3m	unshielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline	Cal interval (month)
Radio Communication Tester	CMU200	R&S	1117057	2012-9-2	12
Notebook	X200	Lenovo	3108052581	/	/
TF card	2GB	Kingdon	1040RE5672k	/	/

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz

4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4-2009. The test distance was 3m. The set-up and test methods were according to ANSI C63.4-2009.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; The emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m. The azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 kHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT was configured in idle mode and the test performed at worst emission state.

4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)

4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
Refer to the section 7.1 of this report for test data.

Test Limits (Class B)				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

4.2 Conducted Disturbance 0.15 MHz to 30MHz

4.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANSI C63.4-2009.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

The EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

The Mobile Station was setup in the shielded chamber and operated under nominal conditions.

4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines.

Refer to the section 7.2 of this report for test data.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dB μ V)	AV (dB μ V)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50



5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline	Cal interval (month)
RE	EMI Test receiver	ESU26	100387	R&S	Nov.23, 2012	12
	Broadband Antenna	VULB 9163	9163-520	SCHWAR ZBECK	Dec.08, 2013	24
	Horn Antenna	HF907	10365	R&S	Nov.09,2013	24
CE	EMI Test receiver	ESCI	101163	R&S	Mar.05, 2013	12
	Artificial Mains Network	ENV216	100382	R&S	Mar.21, 2013	12
Software Information						
Test Item	Software Name		Manufacturer		Version	
RE	EMC 32		R&S		V8.50.10	
CE	EMC 32		R&S		V8.52.0	



6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dB μ V/m)	U=4.2dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=5.3dB; k=2
CE	Disturbance Voltage (dB μ V)	U=2.6dB; k=2

7 Test Data and Graph

Only the worst test results were shown

7.1 Radiated Disturbance

7.1.1 30MHz~1GHz



MEASUREMENT RESULT: QP Detector


Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
32.737600	23.7	12.0	40.0	16.3	100.0	150.0	VERTICAL
115.179200	19.1	11.7	43.5	24.4	100.0	165.0	VERTICAL
172.805120	28.8	10.7	43.5	14.7	204.0	89.0	HORIZONTAL
230.411520	23.3	13.8	46.0	22.7	137.0	2.0	HORIZONTAL
299.976960	23.8	16.0	46.0	22.2	100.0	328.0	HORIZONTAL
403.196480	29.2	18.8	46.0	16.8	137.0	110.0	VERTICAL

Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is used to calculate by software which is not shown in the sheet.

7.1.2 1GHz~18GHz



MEASUREMENT RESULT: PK Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dB μ V/m	dB	dB μ V/m	dB	cm	deg	
1566.894666	30.1	-11.7	74.0	43.9	114.0	-32.0	VERTICAL
4279.052667	38.7	-0.8	74.0	35.3	113.0	186.0	HORIZONTAL
9074.248667	39.7	7.6	74.0	34.3	100.0	247.0	VERTICAL

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Height	Azimuth	Polarisation
MHz	dB μ V/m	dB	dB μ V/m	dB	cm	deg	
1481.462666	16.3	-12.6	54.0	37.7	100.0	61.0	HORIZONTAL
4273.163334	25.0	-0.8	54.0	29.0	200.0	274.0	HORIZONTAL
7613.735334	27.7	6.1	54.0	26.3	100.0	129.0	VERTICAL


Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is used to calculate by software which is not shown in the sheet.

7.2 Conducted Disturbance

7.2.1 AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency	Level	Transducer	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.161932	59.6	9.7	65.4	5.8	L1	FLO
0.162604	59.6	9.7	65.3	5.7	L1	FLO
0.162682	59.6	9.7	65.3	5.7	L1	FLO
3.355188	47.3	9.8	56.0	8.7	L1	FLO
4.333069	48.9	9.8	56.0	7.1	L1	FLO
4.804302	46.6	9.8	56.0	9.4	L1	FLO

MEASUREMENT RESULT: AV Detector

Frequency	Level	Transducer	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.400950	31.9	9.7	47.8	15.9	L1	FLO
0.476651	36.7	9.7	46.4	9.7	L1	FLO
1.282282	35.5	9.7	46.0	10.5	L1	FLO
1.909309	34.1	9.7	46.0	11.9	L1	FLO
3.297218	37.4	9.8	46.0	8.6	L1	FLO
4.268798	35.3	9.8	46.0	10.7	L1	FLO



Note:

Level= Reading level+ Transducer (cable loss + correction factor)

The reading level is used to calculate by software which is not shown in the sheet.

-----**END**-----