



HUAWEI

Report No:SYBH (Z-SAR) 032082011-2

FCC ID:QISU2801-34

IC : 6369A-U280134

Appendix B. SAR Measurement Plots

Table of contents
GSM 850 MHz head
GSM 850 MHz body
GSM 1900 MHz head
GSM 1900 MHz body
WCDMA 1700 MHz head
WCDMA 1700 MHz body

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 190CH Left hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.883$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.01, 6.01, 6.01); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.394 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = 0.037 dB

Peak SAR (extrapolated) = 0.533 W/kg

SAR(1 g) = 0.380 mW/g; SAR(10 g) = 0.274 mW/g

Maximum value of SAR (measured) = 0.403 mW/g



0 dB = 0.403mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 190CH Left hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.883$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.01, 6.01, 6.01); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.226 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.289 W/kg

SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.157 mW/g

Maximum value of SAR (measured) = 0.230 mW/g



0 dB = 0.230mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 190CH Right hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.883$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.01, 6.01, 6.01); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.371 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.494 W/kg

SAR(1 g) = 0.354 mW/g; SAR(10 g) = 0.255 mW/g

Maximum value of SAR (measured) = 0.375 mW/g



0 dB = 0.375mW/g

Date/Time: 8/28/2011 5:03:48, Date/Time: 8/28/2011 5:12:46

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 190CH Right hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.883$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.01, 6.01, 6.01); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.235 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.7 V/m; Power Drift = 0.065 dB

Peak SAR (extrapolated) = 0.404 W/kg

SAR(1 g) = 0.226 mW/g; SAR(10 g) = 0.148 mW/g

Maximum value of SAR (measured) = 0.248 mW/g



0 dB = 0.248mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 GPRS 190CH 1TS Towards Phantom 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.225 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.3 V/m; Power Drift = 0.041 dB

Peak SAR (extrapolated) = 0.295 W/kg

SAR(1 g) = 0.221 mW/g; SAR(10 g) = 0.160 mW/g

Maximum value of SAR (measured) = 0.232 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 GPRS 190CH 2TS Towards Phantom 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.278 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.9 V/m; Power Drift = 0.033 dB

Peak SAR (extrapolated) = 0.365 W/kg

SAR(1 g) = 0.273 mW/g; SAR(10 g) = 0.197 mW/g

Maximum value of SAR (measured) = 0.288 mW/g



0 dB = 0.288mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 GPRS 190CH 2TS Towards ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.616 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.6 V/m; Power Drift = 0.025 dB


Peak SAR (extrapolated) = 0.794 W/kg

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.428 mW/g

Maximum value of SAR (measured) = 0.624 mW/g



0 dB = 0.624mW/g



Date/Time: 8/27/2011 16:47:30, Date/Time: 8/27/2011 16:54:52

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 EGPRS 190CH 1TS Towards ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.497 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.1 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 0.653 W/kg

SAR(1 g) = 0.485 mW/g; SAR(10 g) = 0.347 mW/g

Maximum value of SAR (measured) = 0.515 mW/g



0 dB = 0.515mW/g

Date/Time: 8/27/2011 17:49:28, Date/Time: 8/27/2011 17:56:50

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 EGPRS 190CH 2TS Towards ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.593 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24 V/m; Power Drift = 0.035 dB

Peak SAR (extrapolated) = 0.779 W/kg

SAR(1 g) = 0.578 mW/g; SAR(10 g) = 0.410 mW/g

Maximum value of SAR (measured) = 0.613 mW/g



0 dB = 0.613mW/g

Date/Time: 8/27/2011 21:54:40, Date/Time: 8/27/2011 22:02:03

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM850 190CH Towards Ground 15mm with headset

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.996$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(6.03, 6.03, 6.03); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.418 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = -0.166 dB

Peak SAR (extrapolated) = 0.564 W/kg

SAR(1 g) = 0.392 mW/g; SAR(10 g) = 0.274 mW/g



0 dB = 0.418mW/g

Test Laboratory: HUAWEI SAR Lab

U2801 - 34 GSM1900 661CH Left hand touch cheek

DUT: U2801 - 34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.96, 4.96, 4.96); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.328 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13 V/m; Power Drift = 0.094 dB

Peak SAR (extrapolated) = 0.518 W/kg

SAR(1 g) = 0.332 mW/g; SAR(10 g) = 0.201 mW/g

Maximum value of SAR (measured) = 0.362 mW/g



0 dB = 0.362mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 661CH Left hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.96, 4.96, 4.96); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.512 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19 V/m; Power Drift = -0.031 dB

Peak SAR (extrapolated) = 0.972 W/kg

SAR(1 g) = 0.555 mW/g; SAR(10 g) = 0.311 mW/g

Maximum value of SAR (measured) = 0.614 mW/g



0 dB = 0.614mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 661CH Right hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.96, 4.96, 4.96); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.608 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.5 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 1.3 W/kg

SAR(1 g) = 0.687 mW/g; SAR(10 g) = 0.369 mW/g

Maximum value of SAR (measured) = 0.770 mW/g



0 dB = 0.770mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 661CH Right hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.96, 4.96, 4.96); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.626 mW/g



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.8 V/m; Power Drift = 0.031 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.701 mW/g; SAR(10 g) = 0.365 mW/g

Maximum value of SAR (measured) = 0.783 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 GPRS 661CH 1TS Towards Phantom 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.175 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.6 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.284 W/kg

SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.107 mW/g

Maximum value of SAR (measured) = 0.192 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.6 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.220 W/kg

SAR(1 g) = 0.142 mW/g; SAR(10 g) = 0.089 mW/g

Maximum value of SAR (measured) = 0.152 mW/g



0 dB = 0.152mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 GPRS 661CH 2TS Towards Phantom 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.213 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.19 V/m; Power Drift = 0.00955 dB

Peak SAR (extrapolated) = 0.347 W/kg

SAR(1 g) = 0.216 mW/g; SAR(10 g) = 0.130 mW/g

Maximum value of SAR (measured) = 0.234 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.19 V/m; Power Drift = 0.00955 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR(1 g) = 0.174 mW/g; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.186 mW/g



0 dB = 0.186mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 GPRS 661CH 2TS Towards Ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section


DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor -Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57


Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.465 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.04 V/m; Power Drift = -0.00262 dB
Peak SAR (extrapolated) = 0.701 W/kg
SAR(1 g) = 0.436 mW/g; SAR(10 g) = 0.278 mW/g

Maximum value of SAR (measured) = 0.466 mW/g



0 dB = 0.466mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 EGPRS 661CH 1TS Towards Ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 0.380 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.11 V/m; Power Drift = 0.077 dB

Peak SAR (extrapolated) = 0.575 W/kg

SAR(1 g) = 0.356 mW/g; SAR(10 g) = 0.226 mW/g



0 dB = 0.380mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 EGPRS 661CH 2TS Towards Ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.468 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.02 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 0.705 W/kg

SAR(1 g) = 0.435 mW/g; SAR(10 g) = 0.277 mW/g

Maximum value of SAR (measured) = 0.467 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 GSM1900 661CH Towards Ground 15mm wiht headset

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.73, 4.73, 4.73); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.319 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.89 V/m; Power Drift = 0.060 dB

Peak SAR (extrapolated) = 0.496 W/kg

SAR(1 g) = 0.301 mW/g; SAR(10 g) = 0.183 mW/g

Maximum value of SAR (measured) = 0.324 mW/g



0 dB = 0.324mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Left hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 1.11 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.6 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.601 mW/g



0 dB = 1.11mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Left hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.773 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.6 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.886 mW/g; SAR(10 g) = 0.488 mW/g

Maximum value of SAR (measured) = 0.982 mW/g



0 dB = 0.982mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Right hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.08 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.6 V/m; Power Drift = -0.086 dB

Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.590 mW/g

Maximum value of SAR (measured) = 1.18 mW/g



0 dB = 1.18mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Right hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 1.14 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.7 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 2.01 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.533 mW/g



0 dB = 1.14mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1513CH Left hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1752.6 MHz

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm


Maximum value of SAR (measured) = 1.07 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.4 V/m; Power Drift = -0.055 dB

Peak SAR (extrapolated) = 1.53 W/kg

SAR(1 g) = 0.979 mW/g; SAR(10 g) = 0.580 mW/g



0 dB = 1.07mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1312CH Left hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.41 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 28.7 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 2.02 W/kg

SAR(1 g) = 1.29 mW/g; SAR(10 g) = 0.764 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.4 mW/g



0 dB = 1.4mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1513CH Left hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1752.6 MHz

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.818 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.9 V/m; Power Drift = -0.147 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.902 mW/g; SAR(10 g) = 0.495 mW/g

Maximum value of SAR (measured) = 0.985 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1312CH Left hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.07 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 29.3 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 2.2 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.661 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.32 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1513CH Right hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1752.6 MHz

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.09 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.6 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 1.94 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.557 mW/g

Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.12mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1312CH Right hand touch cheek

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.36 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm



Reference Value = 28.8 V/m; Power Drift = -0.027 dB

Peak SAR (extrapolated) = 2.47 W/kg

SAR(1 g) = 1.35 mW/g; SAR(10 g) = 0.741 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.5 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1513CH Right hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1752.6 MHz

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.09 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.9 V/m; Power Drift = 0.016 dB

Peak SAR (extrapolated) = 2.02 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.532 mW/g

Maximum value of SAR (measured) = 1.13 mW/g



0 dB = 1.13mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1312CH Right hand tilt 15 degree

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(5.1, 5.1, 5.1); Calibrated: 2011-3-11
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 2010-10-22
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Head/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.37 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 29.7 V/m; Power Drift = 0.00652 dB

Peak SAR (extrapolated) = 2.54 W/kg

SAR(1 g) = 1.33 mW/g; SAR(10 g) = 0.684 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.49 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Towards Phantom 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.91, 4.91, 4.91); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.290 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.94 V/m; Power Drift = -0.072 dB

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.285 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.308 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.94 V/m; Power Drift = -0.072 dB

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.149 mW/g

Maximum value of SAR (measured) = 0.253 mW/g



0 dB = 0.253mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Towards Ground 15mm

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.91, 4.91, 4.91); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.652 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = 0.012 dB


Peak SAR (extrapolated) = 0.979 W/kg

SAR(1 g) = 0.605 mW/g; SAR(10 g) = 0.370 mW/g

Maximum value of SAR (measured) = 0.659 mW/g



0 dB = 0.659mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-34 WCDMA1700 1413CH Towards Ground 15mm with Headset

DUT: U2801-34; Type: Mobile phone; Serial: N6S2A11172500010

Communication System: HW -UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3254; ConvF(4.91, 4.91, 4.91); Calibrated: 3/11/2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1235; Calibrated: 10/22/2010
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

Configuration/Body/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.515 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = 0.050 dB

Peak SAR (extrapolated) = 0.814 W/kg

SAR(1 g) = 0.494 mW/g; SAR(10 g) = 0.303 mW/g

Maximum value of SAR (measured) = 0.539 mW/g



0 dB = 0.539mW/g