



Appendix B. SAR Measurement Plots

Table of contents
GSM 850 MHz Head
GSM 850 MHz Body
GSM 1900 MHz Head
GSM 1900 MHz Body
WCDMA 1900 MHz Head
WCDMA 1900 MHz Body

Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM850 190CH Left Hand Touched cheek with battery BAAB830XB1446108

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 41.803$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm


Maximum value of SAR (measured) = 1.10 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 25.987 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 1.309 mW/g

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.761 mW/g



0 dB = 1.10 mW/g = 0.79 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM850 190CH Left Hand Touched cheek with battery GAGBC08L75229770

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.922$ mho/m; $\epsilon_r = 41.803$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.06 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 25.250 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.290 mW/g

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.746 mW/g

Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.06 mW/g = 0.54 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM850 GPRS 2TS 128CH Towards Ground 15mm with battery BAAB830XB1446108

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.979$ mho/m; $\epsilon_r = 53.254$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.04 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 32.193 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.287 mW/g

SAR(1 g) = 1.000 mW/g; SAR(10 g) = 0.730 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.06 mW/g



0 dB = 1.04 mW/g = 0.36 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM850 GPRS 2TS 128CH Towards Ground 15mm with battery GAGBC08L75229770

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 824.2 MHz

Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.979$ mho/m; $\epsilon_r = 53.254$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.01 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 31.595 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.236 mW/g

SAR(1 g) = 0.959 mW/g; SAR(10 g) = 0.701 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.02 mW/g



0 dB = 1.01 mW/g = 0.10 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM1900 661CH Right Hand Touched cheek with battery BAAB830XB1446108

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.409$ mho/m; $\epsilon_r = 39.351$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.634 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.863 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.100 mW/g

SAR(1 g) = 0.601 mW/g; SAR(10 g) = 0.327 mW/g

Maximum value of SAR (measured) = 0.667 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM1900 661CH Right Hand Touched cheek with battery GAGBC08L75229770

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1


Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz
 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.409$ mho/m; $\epsilon_r = 39.351$; $\rho = 1000$ kg/m³
 Phantom section: Right Section

DASY Configuration:


- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
 Maximum value of SAR (measured) = 0.646 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
 Reference Value = 17.200 V/m; Power Drift = 0.14 dB
 Peak SAR (extrapolated) = 1.129 mW/g
SAR(1 g) = 0.623 mW/g; SAR(10 g) = 0.337 mW/g
 Maximum value of SAR (measured) = 0.687 mW/g



0 dB = 0.687 mW/g = -3.26 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM1900 GPRS 2TS 661CH Towards Ground 15mm with battery BAAB830XB1446108

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.546$ mho/m; $\epsilon_r = 53.069$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.553 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.151 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.864 mW/g

SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.582 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 GSM1900 GPRS 2TS 661CH Towards Ground 15mm with battery GAGBC08L75229770**DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1**

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.546$ mho/m; $\epsilon_r = 53.069$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.566 mW/g



Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.514 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.908 mW/g

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.606 mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 WCDMA1900 9538CH Right hand tilt 15 degree with battery BAAB830XB1446108

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1


Communication System: HW-UMTS-FDD; Frequency: 1907.6 MHz
 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.427$ mho/m; $\epsilon_r = 39.262$; $\rho = 1000$ kg/m³
 Phantom section: Right Section

DASY Configuration:


- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
 Maximum value of SAR (measured) = 1.15 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
 Reference Value = 27.769 V/m; Power Drift = 0.04 dB
 Peak SAR (extrapolated) = 2.409 mW/g
SAR(1 g) = 1.2 mW/g; SAR(10 g) = 0.620 mW/g
 Maximum value of SAR (measured) = 1.38 mW/g



0 dB = 1.38 mW/g = 2.80 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 WCDMA1900 9538CH Right hand tilt 15 degree with battery GAGBC08L75229770

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1907.6 MHz

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.427$ mho/m; $\epsilon_r = 39.262$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.16 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 28.024 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 2.410 mW/g

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.617 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



0 dB = 1.16 mW/g = 1.26 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U2801-53 WCDMA1900 9400CH Towards Ground 10mm with Battery SN- BAAB830XB1446108

DUT: U8667; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.546$ mho/m; $\epsilon_r = 53.069$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.856 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.502 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 1.294 mW/g

SAR(1 g) = 0.808 mW/g; SAR(10 g) = 0.495 mW/g

Maximum value of SAR (measured) = 0.862 mW/g



0 dB = 0.862 mW/g = -1.29 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U2801-53 WCDMA1900 9400CH Towards Ground 15mm with Battery SN- GAGBC08L75229770

DUT: U2801-53; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.546$ mho/m; $\epsilon_r = 53.069$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.738 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.003 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.148 mW/g

SAR(1 g) = 0.710 mW/g; SAR(10 g) = 0.433 mW/g

Maximum value of SAR (measured) = 0.761 mW/g

