

P1528_OET65_EN62209- RightHandSide touched –GSM850

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 824.2 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 825$ MHz; $\sigma = 0.889$ mho/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(6.06, 6.06, 6.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.406 mW/g


head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.9 V/m; Power Drift = 0.050 dB

Peak SAR (extrapolated) = 0.507 W/kg

SAR(1 g) = 0.406 mW/g; SAR(10 g) = 0.304 mW/g

Maximum value of SAR (measured) = 0.431 mW/g



0 dB = 0.431mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

Annex 2.4 GSM 850 MHz body

Date/Time: 2010-07-14 22:41:27

P1528_OET65_EN62209- GSM850 GPRS 2TS towards phantom

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.727 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 28.1 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 0.820 W/kg

SAR(1 g) = 0.652 mW/g; SAR(10 g) = 0.483 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.686 mW/g



0 dB = 0.686mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards phantom

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.451 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 20.1 V/m; Power Drift = -0.129 dB

Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.428 mW/g; SAR(10 g) = 0.312 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.454 mW/g



0 dB = 0.454mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.963 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 31.7 V/m; Power Drift = 0.037 dB

Peak SAR (extrapolated) = 1.2 W/kg

SAR(1 g) = 0.930 mW/g; SAR(10 g) = 0.676 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.990 mW/g



0 dB = 0.990mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground**DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200**

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125


body/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mmInfo: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.03 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.8 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 1.3 W/kg

SAR(1 g) = 0.956 mW/g; SAR(10 g) = 0.662 mW/gInfo: [Interpolated medium parameters used for SAR evaluation.](#)

0 dB = 1.03mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.905 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 26.8 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.832 mW/g; SAR(10 g) = 0.577 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.894 mW/g



0 dB = 0.894mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 824.2 MHz;Duty Cycle: 1:4.1

Medium parameters used: $f = 825$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.867 mW/g


body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.3 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.821 mW/g; SAR(10 g) = 0.568 mW/g

Maximum value of SAR (measured) = 0.882 mW/g



Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 1.02$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.997 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 32.2 V/m; Power Drift = 0.00357 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.968 mW/g; SAR(10 g) = 0.701 mW/g

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.03 mW/g



0 dB = 1.03mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 GPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 824.2 MHz;Duty Cycle: 1:4.1

Medium parameters used: $f = 825$ MHz; $\sigma = 0.991$ mho/m; $\epsilon_r = 53.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.828 mW/g


body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.3 V/m; Power Drift = 0.0053 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.792 mW/g; SAR(10 g) = 0.576 mW/g

Maximum value of SAR (measured) = 0.839 mW/g



0 dB = 0.839mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 EGPRS 2TS towards ground

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 848.8 MHz;Duty Cycle: 1:4.1

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 1.02$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.01 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 32.4 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.978 mW/g; SAR(10 g) = 0.709 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.03 mW/g



0 dB = 1.03mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 towards ground with Headset

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 1.02$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.677 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 25.8 V/m; Power Drift = 0.0055 dB

Peak SAR (extrapolated) = 0.852 W/kg

SAR(1 g) = 0.655 mW/g; SAR(10 g) = 0.469 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.694 mW/g



Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209- GSM850 towards ground with Bluetooth Headset

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 1.02$ mho/m; $\epsilon_r = 53.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

body/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.841 mW/g

body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 29.7 V/m; Power Drift = 0.00706 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.821 mW/g; SAR(10 g) = 0.595 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.868 mW/g



0 dB = 0.868mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.5°C

Annex 2.5 UMTS (WCDMA) FDD AWS1700MHz head

Date/Time: 2010-07-20 22:29:25

P1528_OET65_EN62209-LeftHandSide touched -WCDMA FDD AWS1700**DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200**

Communication System: W1700 ; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.492 mW/g


head/Zoom Scan (9x9x9)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 0.878 W/kg

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.325 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.569 mW/g



0 dB = 0.569mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

Date/Time: 2010-07-20 23:15:43

P1528_OET65_EN62209-LeftHandSide tilted 15°- WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.243 mW/g

head/Zoom Scan (9x9x9)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 11.8 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.359 W/kg

SAR(1 g) = 0.241 mW/g; SAR(10 g) = 0.147 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.263 mW/g



0 dB = 0.263mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209-LeftHandSide touched -WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.554 mW/g

head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.49 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.717 W/kg

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.322 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.556 mW/g



0 dB = 0.556mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

Date/Time: 2010-07-21 00:55:43

P1528_OET65_EN62209-LeftHandSide tilted 15°- WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.176 mW/g

head/Zoom Scan (9x9x9)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 10.7 V/m; Power Drift = 0.032 dB

Peak SAR (extrapolated) = 0.257 W/kg

SAR(1 g) = 0.170 mW/g; SAR(10 g) = 0.107 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.183 mW/g



0 dB = 0.183mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209-RightHandSide touched- WCDMA FDD AWS1700**DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200**

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mmInfo: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.534 mW/g


head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.4 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 0.885 W/kg

SAR(1 g) = 0.530 mW/g; SAR(10 g) = 0.311 mW/gInfo: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.604 mW/g



0 dB = 0.604mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209-RightHandSide tilted 15°- WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.221 mW/g

head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 13.3 V/m; Power Drift = -0.000732 dB

Peak SAR (extrapolated) = 0.311 W/kg

SAR(1 g) = 0.213 mW/g; SAR(10 g) = 0.131 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.234 mW/g



0 dB = 0.234mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209-RightHandSide touched- WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.625 mW/g

head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.34 V/m; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 0.904 W/kg

SAR(1 g) = 0.623 mW/g; SAR(10 g) = 0.384 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.680 mW/g



0 dB = 0.680mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C

P1528_OET65_EN62209-RightHandSide tilted 15°- WCDMA FDD AWS1700

DUT: HUAWEI U3200-9/U3200-9/HUAWEI U3200/U3200

Communication System: W1700 ; Frequency: 1732.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.3$ mho/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.06, 5.06, 5.06); Calibrated: 12/18/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 12/18/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

head/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.152 mW/g

head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 10.6 V/m; Power Drift = 0.00543 dB

Peak SAR (extrapolated) = 0.221 W/kg

SAR(1 g) = 0.152 mW/g; SAR(10 g) = 0.098 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.164 mW/g



0 dB = 0.164mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 22.0°C; liquid temperature: 21.5°C