



EMC Test Report

**Product Name: WCDMA/GPRS/GSM/EDGE Mobile Phone
With Bluetooth**

Model Number: U3311

Report No: SYBHZ(R)E075022009EB-1

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice 1

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Notice 2

Modification Information:

Table 1 Modification Information

Modification Information	1	
	2	
	3	<i>Not Applicable!</i>
	4	
	5	
	6	
	7	

REPORT ON	EMC TEST OF WCDMA/GPRS/GSM/EDGE Mobile Phone With Bluetooth
	M/N: U3311
REGULATION	FCC CFR47 Part 15: Subpart B; FCC CFR47 Part 22: Subpart H; FCC CFR47 Part 24: Subpart E;
START OF TEST	Mar.10, 2009
END OF TEST	Mar.24, 2009
Final Judgement:	Pass

Approver

2009-03-27

Date

张兴海

Name

Signature



Reviewer

2009-03-26

Date

余辉

Name

Signature



Operator

2009-03-25

Date

张飞

Name

Signature



REPORT BODY CONTENT

1	Status	6
1.1	Product Information.....	6
1.2	Applied Standard	6
1.3	Test Site	6
1.4	Test environment condition.....	6
2	Summary of Results.....	7
3	Equipment Specification	8
3.1	General Description	8
3.2	Sub-Assembly Identity	8
4	System Configuration during EMC Test	9
4.1	Cables Used during Test	9
4.2	Associated Equipment Used during Test	9
4.3	Test Configurations and Test Mode.....	9
4.4	Test conditions and test Connections.....	9
5	Electromagnetic Interference (EMI).....	12
5.1	Radiated Disturbance 30MHz to 1000MHz	12
5.2	Conducted Disturbance 0.15 MHz to 30MHz	13
5.3	Radiated Spurious Emissions.....	13
6	Main Test Instruments	16
7	System Measurement Uncertainty.....	17
8	Graph and Data of Emission Test.....	18
8.1	Radiated Disturbance	18
8.2	Conducted Disturbance	19
8.3	Radiated Spurious Emission.....	20

1 Status

1.1 Product Information

CLIENT: Huawei Technologies Co., Ltd.
ADDRESS: Bantian Longgang District Shenzhen, P.R. China
MANUFACTURING DESCRIPTION: WCDMA/GPRS/GSM/EDGE Mobile Phone With Bluetooth
MANUFACTURERS MODEL NUMBER: U3311

1.2 Applied Standard

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
-	15.107	Conducted Emission at Power Port	PASS
-	15.109	Radiated Emission of Enclosure in Idle Mode	PASS
2.1051	22.917&24.238	Radiated Spurious Emission	PASS

1.3 Test Site

Site 1:
EMC LABORATORY OF RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD

Site 2:
EMC LABORATORY OF AUDIX LABORATORY

Site 3:
EMC LABORATORY OF HUATONGWEI INTERNATIONAL INSPECTION CO, Ltd.

1.4 Test environment condition

Ambient temperature	20~25°C
Relative humidity	40%~52%
Atmospheric pressure	101kPa

2 Summary of Results

Table 2 below shows a brief summary of the results obtained.

Table 2 Summary of results

EUT Classification: Wireless Terminal				
Test Items	Test Configuration & Test Mode	Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	TC1(TM6-TM10) TC2(TM6-TM10)	N/A	Pass	Site1
<u>Conducted Emissions</u>	TC1(TM1~TM10) TC2(TM1~TM10)	N/A	Pass	Site1
<u>Radiated Spurious Emissions</u> Enclosure Port	TC1(TM1-TM5) TC2(TM1-TM5)	N/A	Pass	Site1

Note:
1, Measurement taken is within the measurement uncertainty of measurement system.
2, TC = Test configuration
3, NT=no test. Because of not containing devices susceptible to magnetic fields, the EUT has been exempt from immunity test of power frequency magnetic field.

3 Equipment Specification

3.1 General Description

WCDMA/GPRS/GSM/EDGE Mobile Phone with Bluetooth-U3311 is subscriber equipment in the WCDMA/GSM system. The WCDMA frequency band is Band I and Band VIII. The GPRS/GSM/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850MHz and PCS1900MHz band test data are included in this report. U3311 implements such functions as RF signal receiving/sending, WCDMA and GPRS/GSM/EDGE protocol processing, voice, video and data service etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface.

3.1.1 Main Equipment Technical Data

Description:	WCDMA/GPRS/GSM/EDGE Mobile Phone With Bluetooth
Model:	U3311
Input Rated Voltage:	--- 3.7V
Rated Power:	Normal 3W ,Max 8 W
Dimensions:	99mm (L) × 46.6mm (W) × 17.5mm (H)
Weight:	<120g (with battery)

Table 3 Sub-Assembly Identity

Mode		Work Frequency	
		Transmitt Frequency (MHz)	Receive Frequency (MHz)
GSM	GSM850	824-849	869-894
	PCS1900	1850-1910	1930-1990

3.2 Sub-Assembly Identity

Table 4 Sub-Assembly Identity

Board				
Model Name	Qt y.	Hardware Version	Serial	Description
HD3U330M	1	VER.B	Q72AC10921700069	Main board of Mobile Phone
Accessory				
Name	Qt y.	Manufacture	Serials number	Description
Adapter	1	Huawei Technologies Co., Ltd.	BYA8C082819	Adapter Model: HS-050040U2 Voltage nominal: ~120V Input voltage: ~100-240V ;50/60Hz Output voltage: --- +5.0V, 0.4A Rate power: 2W
Adapter	1	Huawei Technologies Co., Ltd.	HKA8B0117825	Adapter Model: HS-050040E1 Input Voltage : ~100-240V 50/60Hz 0.2A Output Voltage: --- +5.0V, 0.4A Rated Power: 2W
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	FMT851510495Y	Battery Model: HBU570 Rated capacity: 900mAh Nominal Voltage: --- +3.7V Charging Voltage: --- +4.2V

4 System Configuration during EMC Test

The Equipment under Test (EUT) was functioning correctly during all tests. The EUT was installed within the test site and was configured to simulate a typical user installation.

4.1 Cables Used during Test

Table 5 Cable Used during Test

Port	Length	Quantity	Type of Cable
AC Power Port	3m	1	Unshielded
USB	0.85m	1	shielded
Earphone	1.25m	1	Unshielded

4.2 Associated Equipment Used during Test

Table 6 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date
Radio Communication Tester	CMU200	R&S	108522	2008-10-10

4.3 Test Configurations and Test Mode

4.3.1 Test Configuration.

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

TC1: operate with HS-050040U2 Adapter

TC2: operate with HS-050040E1 Adapter

Table 7 Configuration table

TC1	TM1~TM10
TC2	TM1~TM10

4.3.2 Test Mode

There were ten test Modes. TM1 to TM10 were shown in the diagrams below:

TM1: operate in traffic mode GSM 850;

TM2: operate in traffic mode EGPRS 850;

TM3: operate in traffic mode GSM 1900;

TM4: operate in traffic mode EGPRS 1900;

TM5: operate in traffic mode Bluetooth;

TM6: operate in idle mode GSM 850;

TM7: operate in idle mode EGPRS 850;

TM8: operate in idle mode GSM 1900;

TM9: operate in idle mode EGPRS 1900;

TM10: operate in idle mode Bluetooth;

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

4.4 Test conditions and test Connections

4.4.1 Test Conditions

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

4.4.2 Test Connections

Traffic Mode:

The EUT is required to be in traffic mode, a call is set up according to the generic call set up procedure and enter the EUT into loop back test mode.(GSM see ETSI TS 151.010).

For Cellular and PCS, the following conditions shall also be met:

- The EUT shall be commanded to operate at maximum transmit power;
- The downlink RXQUAL shall be monitored.

Assign channel frequency to an appropriate channel number. Set the ARFCN channel number to 192 for GSM850, and to 661 for PCS1900.




Figure 1.: Test Configuration

Idle Mode:


The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

The EUT is required to be in idle mode.

For Cellular and PCS, the following conditions shall be met:

When the EUT is required to be in idle mode, the test system shall simulate a Base Station (BS) with Broadcast Control Channel/Common Control Channel (BCCH/CCCH) on one carrier. The EUT shall be synchronized to the BCCH, listening to the CCCH and able to respond to paging messages. Periodic Location Updating shall be disabled.

Please refer to following figure:



ANT: Antenna
BER: Bit Error Rate

Figure 2. Test Configuration

5 Electromagnetic Interference (EMI)

5.1 Radiated Disturbance 30MHz to 1000MHz

5.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The test distance was 3m. The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4. The Radiated Disturbance measurements were made using a Rohde and Schwarz ESMI Test Receiver and control software ES-K1.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 1GHz by using test script of software; the emissions were measured using a Quasi-Peak Detector. The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

Huawei Mobile Station was communicated with the BTS simulator through Air interface. The Mobile Station operated on the typical channel and the Mobile Station worked in idle mode, transmitter was not work in this test.

EUT was configured in idle mode and the test performed at worst emission state.

Measurement bandwidth: 30 MHz – 1000 MHz: 120 k Hz

Test set up figure:




Figure 3. Test set-up

5.1.2 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.

Table 8 Test Limits

Frequency of Emission (MHz)	Radiated Limit	
	Unit($\mu\text{V}/\text{m}$)	Unit($\text{dB}\mu\text{V}/\text{m}$)
30-88	100	40
88-216	150	43.5
216-960	200	46

960-1000	500	54
----------	-----	----

5.2 Conducted Disturbance 0.15 MHz to 30MHz

5.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4: 2003.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei Mobile Station was communicated with the BTS simulator through Air interface, the BTS simulator controls the Mobile Station to transmitter the maximum power which defined in specification of product. The Mobile Station operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

Test Set-up figure:

The Mobile Station was setup in the screened chamber and operated under nominal conditions.




Figure 4. Test Set-up

5.2.2 Test Results

The EUT has met requirements for Conducted disturbance of power lines.

Table 9 Test Limit of DC&AC Power Port

Frequency range	150kHz~ 30MHz	
Classification	Class B	
Limit(Class B)	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66~56 dB μ V	56~46 dB μ V
0.5MHz~5MHz	56 dB μ V	46 dB μ V
5MHz~30MHz	60 dB μ V	50 dB μ V

5.3 Radiated Spurious Emissions


5.3.1 Test Procedure

A test site fulfilling the requirements of ITU-R Recommendation SM329-10 was used. The EUT was placed on a non-conducting support in the anechoic chamber and was operated from a power source via an RF filter to avoid radiation from the power leads.

Step 1:


For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the BTS simulator via the air interface.

Test the Radiated maximum output power by the Rohde and Schwarz ESIB26 Test Receiver from test antenna.



Step 2:

Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step1 on ESIB26 Test Receiver, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.



According to part 22.917, the defined measurement bandwidth as following:

22.917(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 1 GHz: 100 kHz;
Measurement bandwidth (RBW) for 1GHz up to 18 GHz: 1MHz;

Frequency band	Minimum requirement (E.R.P) traffic mode
30MHz~18GHz	-13dBm

According to part 24.238, the defined measurement bandwidth as following:

24.238 (b) Measurement procedure: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30 MHz up to 26.5 GHz: 1 MHz;

Table 10 Radiated Spurious Emissions Limits

Frequency band	Minimum requirement (E.R.P) traffic mode
30MHz~26.5GHz	-13dBm

5.3.2 Test Results

The EUT has met the requirements of Part22 and Part24 requirement.

6 Main Test Instruments

Table 11 Main Test Equipments

Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE	EMI Test receiver	ESMI	R&S	Apr.23, 2008	12
	Broadband Antenna	CBL 6112B (2536)	SCHAFFNER	Jun.08, 2008	12
CE	EMI Test receiver	ESCS30	R&S	Apr.22, 2008	12
	Artificial Mains Network	ENV4200	R&S	May.12, 2008	12
RSE	EMI Test receiver	ESIB26	R&S	May.30, 2008	12
	Horn Antenna	3117	ETS-LINDGREN	Jul.16, 2008	12
	Broadband Antenna	CBL6112B (2747)	SCHAFFNER	Oct.17,2008	12
	Horn Antenna	3160	ETS-LINDGREN	Aug.03,2008	12
Software Information					
Test Item	Software Name	Manufacturer	Version		
RE/CE	ES-K1	R&S	1.7.1		
RSE	EMC32	R&S	V5.10.99		

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


Table 12 System Measurement Uncertainty

	Items	Extended Uncertainty
RE	Field strength (dB μ V/m)	U=4.6dB; k=2(30MHz-1GHz)
RSE	ERP (dBm)	U=2.2dB; k=2
CE	Disturbance Voltage (dB μ V)	U=3.3dB; k=2

8 Graph and Data of Emission Test

8.1 Radiated Disturbance

This test was carried out in all the test modes. Here only the worst test result was shown.




MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
33.420000	33.90	11.7	40.0	6.1	100.0	57.00	VERTICAL
54.000000	32.60	12.7	40.0	7.4	107.0	62.00	VERTICAL
180.000000	31.30	10.9	43.5	12.2	203.0	360.00	VERTICAL
248.000000	32.20	12.7	46.0	13.8	108.0	54.00	VERTICAL
372.000000	28.50	13.2	46.0	17.5	200.0	38.00	VERTICAL
812.000000	30.20	25.2	46.0	15.8	300.0	143.00	HORIZONTAL

8.2 Conducted Disturbance

This test was carried out in all the test modes. Here only the worst test result was shown.

8.2.1 AC Power Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.613500	48.10	10.1	56	7.9	N	GND
1.050000	47.20	10.1	56	8.8	N	GND
1.540500	37.50	10.1	56	18.5	N	GND
1.887000	50.10	10.1	56	5.9	N	GND
1.972500	51.20	10.1	56	4.8	N	GND
2.674500	39.80	10.2	56	16.2	N	GND

MEASUREMENT RESULT: AV Detector


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.613500	32.30	10.1	46	13.7	N	GND
1.491000	32.90	10.1	46	13.1	N	GND
1.882500	36.50	10.1	46	9.5	N	GND
1.932000	36.00	10.1	46	10.0	N	GND
2.017500	32.30	10.1	46	13.7	N	GND
2.674500	24.70	10.2	46	21.3	N	GND

8.3 Radiated Spurious Emission


This test results are the maximum level of radiated spurious emissions in vertical and horizontal polarity.

8.3.1 For GSM 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.2 For EDGE 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.3 For PCS1900


Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)



Traffic Mode (2GHz-18GHz)




Traffic Mode (18GHz-26.5GHz)




8.3.4 For EDGE1900


Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)



Traffic Mode (2GHz-18GHz)



Traffic Mode (18GHz-26.5GHz)



END