

**P1528\_OET65\_EN62209- LeftHandSide touched -WCDMA AWS**

**DUT: U7519**

Communication System: W1700 ; Frequency: 1752.6 MHz;Duty Cycle: 1:1  
 Medium parameters used (interpolated):  $f = 1752.6$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.74, 7.74, 7.74); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.1 mW/g

**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 8.68 V/m; Power Drift = 0.091 dB

Peak SAR (extrapolated) = 1.88 W/kg

**SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.602 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.19 mW/g



0 dB = 1.19mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- LeftHandSide touched -WCDMA AWS**

**DUT: U7519**

Communication System: W1700 ; Frequency: 1712.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.31$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.74, 7.74, 7.74); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.06 mW/g

**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 8.8 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.588 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.14 mW/g



0 dB = 1.14mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**Annex 2.2 UMTS (WCDMA) AWS 1700MHz body**

Date/Time: 2009-08-12 22:16:20

**P1528\_OET65\_EN62209- WCDMA AWS towards phantom****DUT: U7519**

Communication System: W1700 ; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1732.4$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.318 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.449 W/kg

**SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.202 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.332 mW/g


**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.476 W/kg

**SAR(1 g) = 0.300 mW/g; SAR(10 g) = 0.184 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.328 mW/g



0 dB = 0.328mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground****DUT: U7519**

Communication System: W1700 ; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1732.4$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.523 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.183 dB

Peak SAR (extrapolated) = 0.781 W/kg

**SAR(1 g) = 0.489 mW/g; SAR(10 g) = 0.294 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.537 mW/g


**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.183 dB

Peak SAR (extrapolated) = 0.499 W/kg

**SAR(1 g) = 0.342 mW/g; SAR(10 g) = 0.223 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.365 mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground****DUT: U7519**

Communication System: W1700 ; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1752.6$  MHz;  $\sigma = 1.49$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.525 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 0.781 W/kg

**SAR(1 g) = 0.488 mW/g; SAR(10 g) = 0.296 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.527 mW/g


**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 0.499 W/kg

**SAR(1 g) = 0.338 mW/g; SAR(10 g) = 0.219 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.366 mW/g



0 dB = 0.366mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground****DUT: U7519**

Communication System: W1700 ; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.558 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.120 dB

Peak SAR (extrapolated) = 0.833 W/kg

**SAR(1 g) = 0.521 mW/g; SAR(10 g) = 0.313 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.569 mW/g


**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.120 dB

Peak SAR (extrapolated) = 0.557 W/kg

**SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.254 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.408 mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground with HSDPA****DUT: U7519**

Communication System: W1700 ; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.489 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = 0.156 dB

Peak SAR (extrapolated) = 0.738 W/kg

**SAR(1 g) = 0.460 mW/g; SAR(10 g) = 0.274 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.501 mW/g


**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = 0.156 dB

Peak SAR (extrapolated) = 0.541 W/kg

**SAR(1 g) = 0.364 mW/g; SAR(10 g) = 0.235 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.391 mW/g



0 dB = 0.391mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground with Headset**

**DUT: U7519**

Communication System: W1700 ; Frequency: 1712.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.480 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 11.4 V/m; Power Drift = 0.132 dB

Peak SAR (extrapolated) = 0.788 W/kg

**SAR(1 g) = 0.495 mW/g; SAR(10 g) = 0.300 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.537 mW/g



0 dB = 0.537mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- WCDMA AWS towards ground with Bluetooth Headset**

**DUT: U7519**

Communication System: W1700 ; Frequency: 1712.4 MHz;Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 1712.4$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.62, 7.62, 7.62); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**body/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.566 mW/g

**body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.1 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 0.873 W/kg

**SAR(1 g) = 0.544 mW/g; SAR(10 g) = 0.324 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.591 mW/g

**body/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 11.1 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 0.543 W/kg

**SAR(1 g) = 0.366 mW/g; SAR(10 g) = 0.241 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.394 mW/g



**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**Annex 2.3 PCS 1900 MHz head**

Date/Time: 2009-08-13 22:45:12

**P1528\_OET65\_EN62209-LeftHandSide touched-GSM1900**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.878 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.68 V/m; Power Drift = 0.00885 dB

Peak SAR (extrapolated) = 1.58 W/kg

**SAR(1 g) = 0.880 mW/g; SAR(10 g) = 0.490 mW/g**

Maximum value of SAR (measured) = 0.972 mW/g



0 dB = 0.972mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209-LeftHandSide tilted 15° - GSM1900**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.253 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.382 W/kg

**SAR(1 g) = 0.258 mW/g; SAR(10 g) = 0.164 mW/g**

Maximum value of SAR (measured) = 0.278 mW/g



0 dB = 0.278mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209-RightHandSide touched-GSM1900**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.691 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.42 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 0.938 W/kg

**SAR(1 g) = 0.638 mW/g; SAR(10 g) = 0.410 mW/g**

Maximum value of SAR (measured) = 0.694 mW/g



0 dB = 0.694mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209-RightHandSide tilted 15°-GSM1900**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.35$  mho/m;  $\epsilon_r = 39.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.230 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.2 V/m; Power Drift = -0.112 dB

Peak SAR (extrapolated) = 0.365 W/kg

**SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.145 mW/g**

Maximum value of SAR (measured) = 0.259 mW/g



0 dB = 0.259mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- LeftHandSide touched –GSM1900**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1909.8 MHz;Duty Cycle: 1:8.3

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 39.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.820 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.43 V/m; Power Drift = 0.012 dB

Peak SAR (extrapolated) = 1.44 W/kg

**SAR(1 g) = 0.793 mW/g; SAR(10 g) = 0.441 mW/g**

Maximum value of SAR (measured) = 0.865 mW/g



0 dB = 0.865mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- LeftHandSide touched –GSM1900****DUT: U7519**

Communication System: PCS 1900; Frequency: 1850.2 MHz;Duty Cycle: 1:8.3

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.33$  mho/m;  $\epsilon_r = 39.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.66, 7.66, 7.66); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.04 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.05 V/m; Power Drift = 0.037 dB

Peak SAR (extrapolated) = 1.78 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.566 mW/g**[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.12mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) :

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**Annex 2.4 PCS 1900 MHz body**

Date/Time: 2009-08-14 22:56:40

**P1528\_OET65\_EN62209- GSM1900 GPRS 2TS towards phantom**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz;Duty Cycle: 1:4.1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 54$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.22, 7.22, 7.22); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.349 mW/g

**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.62 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.518 W/kg

**SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.199 mW/g**


**Head/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.62 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.338 W/kg

**SAR(1 g) = 0.229 mW/g; SAR(10 g) = 0.150 mW/g**

Maximum value of SAR (measured) = 0.246 mW/g



**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- GSM1900 GPRS 2TS towards ground**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1880 MHz;Duty Cycle: 1:4.1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 54$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.22, 7.22, 7.22); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.437 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.6 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.695 W/kg

**SAR(1 g) = 0.435 mW/g; SAR(10 g) = 0.268 mW/g**

Maximum value of SAR (measured) = 0.468 mW/g



0 dB = 0.468mW/g

**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- GSM1900 GPRS 2TS towards ground**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1909.8 MHz;Duty Cycle: 1:4.1  
Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.51$  mho/m;  $\epsilon_r = 54$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.22, 7.22, 7.22); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.386 mW/g


**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.31 V/m; Power Drift = 0.090 dB

Peak SAR (extrapolated) = 0.619 W/kg

**SAR(1 g) = 0.386 mW/g; SAR(10 g) = 0.237 mW/g**

Maximum value of SAR (measured) = 0.412 mW/g



**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm  
ambient temperature: 23.0°C; liquid temperature: 22.3°C

### P1528\_OET65\_EN62209- GSM1900 GPRS 2TS towards ground

DUT: U7519

Communication System: PCS 1900; Frequency: 1850.2 MHz;Duty Cycle: 1:4.1

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 54.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.22, 7.22, 7.22); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.519 mW/g

**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 10.1 V/m; Power Drift = -0.025 dB

Peak SAR (extrapolated) = 0.859 W/kg

**SAR(1 g) = 0.532 mW/g; SAR(10 g) = 0.327 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.577 mW/g



**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C

**P1528\_OET65\_EN62209- GSM1900 EGPRS 2TS towards ground**

**DUT: U7519**

Communication System: PCS 1900; Frequency: 1850.2 MHz;Duty Cycle: 1:4.1

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 54.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3641; ConvF(7.22, 7.22, 7.22); Calibrated: 5/14/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn851; Calibrated: 5/14/2009
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

**Head/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.217 mW/g

**Head/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.48 V/m; Power Drift = 0.150 dB

Peak SAR (extrapolated) = 0.378 W/kg

**SAR(1 g) = 0.229 mW/g; SAR(10 g) = 0.141 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.256 mW/g



**Additional information:**

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 23.0°C; liquid temperature: 22.3°C