

P1528_OET65_EN62209- towards ground- WCDMA850 Low

DUT: HUAWEI U7520-5/U7520-5

Communication System: WCDMA850; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 2009-12-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 2009-12-18
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.2 Build 87

Body/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.672 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 23.5 V/m; Power Drift = -0.182 dB

Peak SAR (extrapolated) = 0.836 W/kg

SAR(1 g) = 0.632 mW/g; SAR(10 g) = 0.450 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.667 mW/g



Additional information:

position or distance of DUT to SAM (if not standard head positions) :15 mm

ambient temperature: 22.0°C; liquid temperature: 21.6°C

**P1528_OET65_EN62209- towards ground with HSDPA - WCDMA850 Low
DUT: HUAWEI U7520-5/U7520-5**

Communication System: WCDMA850; Frequency: 826.4 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.4$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 2009-12-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 2009-12-18
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.2 Build 87

Body/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.632 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 23.7 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.825 W/kg

SAR(1 g) = 0.615 mW/g; SAR(10 g) = 0.438 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.657 mW/g



Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.6°C

**P1528_OET65_EN62209- towards ground with Headset - WCDMA850 Low
DUT: HUAWEI U7520-5/U7520-5**

Communication System: WCDMA850; Frequency: 826.4 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.4$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 2009-12-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 2009-12-18
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.2 Build 87

Body/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.425 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 19.1 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.584 W/kg

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.295 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.452 mW/g



0 dB = 0.452mW/g

Additional information:

position or distance of DUT to SAM (if not standard head positions) : 15 mm

ambient temperature: 22.0°C; liquid temperature: 21.6°C

P1528_OET65_EN62209- towards ground with Bluetooth Headset - WCDMA850 Low
DUT: HUAWEI U7520-5/U7520-5

Communication System: WCDMA850; Frequency: 826.4 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.4$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3168; ConvF(5.97, 5.97, 5.97); Calibrated: 2009-12-18
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn852; Calibrated: 2009-12-18
- Phantom: SAM2; Type: SAM; Serial: TP-1474
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.2 Build 87

Body/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.648 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 24.5 V/m; Power Drift = -0.189 dB

Peak SAR (extrapolated) = 0.833 W/kg

SAR(1 g) = 0.630 mW/g; SAR(10 g) = 0.450 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.671 mW/g



0 dB = 0.671mW/g

Additional information:


position or distance of DUT to SAM (if not standard head positions) : 15 mm
 ambient temperature: 22.0°C; liquid temperature: 21.6°C

Annex 2.9 Z-axis scans


GSM 1900 Head:

HUAWEI U7520-5/U7520-5


LeftHandSide touched -GSM1900 Channel 661




LeftHandSide tilted 15° -GSM1900 Channel 661




RightHandSide touched -GSM1900 Channel 661




RightHandSide tilted 15° -GSM1900 Channel 661




LeftHandSide touched -GSM1900 Channel 810




LeftHandSide touched -GSM1900 Channel 512




GSM1900 Body:
HUAWEI U7520-5/U7520-5
Towards phantom- GSM1900 GPRS 2TS Channel 661




Towards ground- GSM1900 GPRS 2TS Channel 661




Towards ground- GSM1900 GPRS 2TS Channel 810




Towards ground- GSM1900 GPRS 2TS Channel 512




Towards ground- GSM1900 EGPRS 2TS Channel 512




Towards ground- GSM1900 EGPRS 2TS Channel 661




Towards ground- GSM1900 EGPRS 2TS Channel 810




Towards ground- GSM1900 with Headset Channel 810




Towards ground- GSM1900 with Bluetooth Headset Channel 810




GSM850 Head:
HUAWEI U7520-5/U7520-5
LeftHandSide touched - GSM850 Channel 192




LeftHandSide tilted 15° - GSM850 Channel 192




RightHandSide touched - GSM850 Channel 192




RighttHandSide tilted 15° - GSM850 Channel 192




RightHandSide touched - GSM850 Channel 251




RightHandSide touched - GSM850 Channel 128




LeftHandSide touched - GSM850 Channel 251




LeftHandSide touched - GSM850 Channel 128




GSM850 Body:
HUAWEI U7520-5/U7520-5
Towards phantom- GSM850 GPRS 2TS Channel 192




Towards ground- GSM850 GPRS 2TS Channel 192




Towards ground- GSM850 GPRS 2TS Channel 251




Towards ground- GSM850 GPRS 2TS Channel 128




Towards ground- GSM850 EGPRS 2TS Channel 192




Towards ground- GSM850 EGPRS 2TS Channel 251




Towards ground- GSM850 EGPRS 2TS Channel 128




Towards ground with Headset- GSM850 Channel 251




Towards ground with Bluetooth Headset- GSM850 Channel 251




WCDMA1900 Head:
HUAWEI U7520-5/U7520-5
LeftHandSide touched – WCDMA1900 Channel 9400




LeftHandSide tilted 15°– WCDMA1900 Channel 9400




RightHandSide touched – WCDMA1900 Channel 9400




RightHandSide tilted 15° - WCDMA1900 Channel 9400




LeftHandSide touched – WCDMA1900 Channel 9538




LeftHandSide touched – WCDMA1900 Channel 9262




WCDMA1900 Body:
HUAWEI U7520-5/U7520-5
Towards phantom- WCDMA1900 Channel 9400




Towards ground- WCDMA1900 Channel 9400




Towards ground- WCDMA1900 Channel 9538




Towards ground- WCDMA1900 Channel 9262




Towards ground- WCDMA1900 Channel 9538 with HSDPA




Towards ground- WCDMA1900 Channel 9538 with Headset




Towards ground- WCDMA1900 Channel 9538 with Bluetooth Headset




WCDMA850 Head:
HUAWEI U7520-5/U7520-5
LeftHandSide touched - WCDMA850 Channel 4182




LeftHandSide tilted 15° - WCDMA850 Channel 4182




RightHandSide touched - WCDMA850 Channel 4182




RightHandSide tilted 15° - WCDMA850 Channel 4182




LeftHandSide touched - WCDMA850 Channel 4132




LeftHandSide touched - WCDMA850 Channel 4233




WCDMA850 Body
HUAWEI U7520-5/U7520-5
Towards phantom- WCDMA 850 Channel 4182




Towards ground- WCDMA 850 Channel 4182




Towards ground- WCDMA 850 Channel 4233




Towards ground- WCDMA 850 Channel 4132




Towards ground- WCDMA 850 Channel 4132 with HSDPA



Towards ground- WCDMA 850 Channel 4132 with Headset



Towards ground- WCDMA 850 Channel 4132 with Bluetooth Headset





Annex 3 Calibration parameters

Calibration parameters are described in the additional document:

Appendix to test report no. SYBH(Z-SAR) 014102010-2

Calibration data, Phantom certificate and detail information of the DASY5 System

Annex 4 Photo documentation

Annex 4.1 Test Facility

Photo 1: Measurement System DASY5



Photo 2: Measurement System DASY5

