



FCC&IC Test Report

**Product Name: HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone
with Bluetooth**

Model Number: HUAWEI U8100-9/U8100-9/IVY

Report No: SYBHZ(R)E028032010EB-4

FCC ID: QISU8100-9

IC:6369A-U81009

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



REPORT ON **FCC&IC Test of HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth**

M/N: HUAWEI U8100-9/U8100-9/IVY

Report No: SYBHZ(R)E028032010EB-4

FCC ID: QISU8100-9

IC:6369A-U81009

REGULATION **FCC CFR47 Part 2: Subpart J;**
FCC CFR47 Part 27: Subpart C&L;

RSS-Gen Issue 2

RSS-139 Issue 2

CONCLUSION **Pass**

General Manager

2010.3.25

Date

张兴海

Name

signature

Technical Responsibility
For Area of Testing

2010.3.25

Date

余 辉

Name

signature

Test Lab Engineer

2010.3.25

Date

胡 俊

Name

signature



Contents

1	<u>Summary</u>	5
2	<u>Product Description</u>	6
2.1	PRODUCTION INFORMATION	6
2.2	MODIFICATION INFORMATION	6
3	<u>Test Site Description</u>	7
3.1	TESTING PERIOD	7
3.2	GENERAL SET UP DESCRIPTION	7
4	<u>Product Description</u>	8
4.1	TECHNICAL CHARACTERISTICS	8
4.2	EUT IDENTIFICATION LIST	10
5	<u>Main Test Instruments</u>	11
6	<u>Transmitter Measurements</u>	12
7	<u>System Measurement Uncertainty</u>	29
8	<u>Appendices</u>	30



1 Summary

The table below summarizes the measurements and results for the EUT. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

FCC Measurement Specification	FCC Limits Part(s)	Section in RSS-139	Description	Result
2.1046	27.50(d)(2)	6.4	Effective Radiated Power of Transmitter	PASS
2.1046	27.50(d)(2)	6.4	Conducted Power of Transmitter	PASS
2.1047	/	/	Modulation Characteristics	PASS
2.1049	/	6.5	Occupied Bandwidth	PASS
2.1051	27.53(g)	6.5	Band Edges Compliance	PASS
2.1051	27.53(g)	6.5	Spurious Emission at Antenna Terminal	PASS
2.1055	27.54	6.3	Frequency Stability	PASS



2 Product Description

2.1 Production Information

2.1.1 General Description

HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth - HUAWEI U8100-9/U8100-9/IVY is subscriber equipment in the WCDMA/GSM system. The HSDPA/UMTS frequency band is Band I and AWS, but only AWS band test data included in this report. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850MHz and PCS1900MHz band test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSDPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video, MMS service, GPS, and WIFI etc. Externally it provides micro SD card interface, earphone port(to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

Note: Only tests for AWS (WCDMA Band IV) band was included in this report for the requirement of FCC part 2 & 27.

2.1.2 Support function and Service

The HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth support the function and service as follows:

Table 2 Service and Test mode List

Service Name	Characteristic	Corresponding Test Mode	Note
Data	Modulation: QPSK	TM1	WCDMA
Data	Modulation: QPSK	TM2	HSDPA

Note: * The WCDMA test condition & settings are defined in 3GPP TS 34.121 V7.5.0.

2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable				



3 Test Site Description

The test site of:

***Huawei Technologies Co. Ltd.
P.O. Box 518129
Huawei base, bantian,
Longgang District, Shenzhen, China***

3.1 Testing Period

The test have been performed during the period of

Mar. 22, 2010 – Mar. 22, 2010

3.2 General Set up Description

TM1: WCDMA Mode with QPSK Modulation

TM2: HSDPA Mode with QPSK Modulation



4 Product Description

4.1 Technical Characteristics

4.1.1 Frequency Range

Table 4 Frequency Range

1700M Band	
Uplink band:	1710 to 1755 MHz
Downlink band:	2110 to 2155 MHz

4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

	WCDMA/HSDPA
Channel Raster	200k Hz
Channel spacing:	5MHz

4.1.3 Type of Emission

Table 6 Type of Emission

	WCDMA/HSDPA
Emission Designation:	5M0F9W

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

4.1.4 Environmental Requirements

Table 7 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%-95%RH

4.1.5 Power Source

Power Source

AC voltage nominal:	~ 120 V
AC voltage range	~ 100 V to ~ 240 V
AC current maximal:	650mA

4.1.6 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

4.1.7 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 8 Applied RF Module DC Voltages and Currents

Voltage:	≡ +2.8V
Current:	100mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)



4.2 EUT Identification List

4.2.1 Board Information

Table 9 Board Information

HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth		
HUAWEI U8100-9/U8100-9/IVY		
Board and Module		
Equipment Designation / Description	Serial Number	Remarks
MAINBOARD	H82BA11020600079	HD3U811M Ver.A

4.2.2 Adapter Technical Data

AC/DCAdapter Model	:	HS-050040U5
Manufacturer	:	Huawei Technologies Co., Ltd.
Input Voltage	:	~100-240V 50/60Hz 0.2A
Output Voltage	:	=== +5.0V, 400mA
Rated Power	:	2W
S/N	:	HKA9B1519758

4.2.3 Battery Technical Data

Name	Qty.	Manufacture	Serials number	Description
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	YAC9608HI201020 3	Battery Model: HB5A2H Rated capacity: 1150mAh Nominal Voltage: === +3.7V Charging Voltage: === +4.2V

4.2.4 FCC Identification

Grantee Code: QIS
Product Code: U8100-9
FCC Identification: QISU8100-9

4.2.5 IC Identification

Grantee Code: 6369A
Product Code: U81009
IC Identification: 6369A-U81009

5 Main Test Instruments

Table 10 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until (MM.DD.YYYY)
Receiver	R&S	ESIB 26	100318	04.21.2010
BiLog Antenna	Schaffner	CBL 6112B	2747	11.16.2010
Horn Antenna	ETS-Lindgren	3117	00062553	08.15.2010
Horn Antenna	ETS-Lindgren	3160	00060006	08.03.2010
Dipole	Schwarzbeck	D69250- UHAP/D69250-VHAP	979/917	10.11.2010
Signal Generator	R&S	SMR 40	100325	05.11.2010
Signal Generator	R&S	SMU200A	101717	04.10.2010
Power Supply	Keithley	2306	1045337	05.11.2010
Climate Chamber	WEISS	WK11-180/170	5822604947001 0	10.23.2010
Universal Radio Communication Tester	R&S	CMU200	112347	03.30.2010
Wireless communication test set	Agilent	8960	GB43461081	05.10.2010
Spectrum Analyzer	R&S	FSU26	200245	08.27.2010



6 Transmitter Measurements

6.1 Effective Radiated Power of Transmitter (EIRP)

6.1.1 Test Conditions

Table 11 Test Conditions

Preconditioning:	0.5 hour
Measured at:	enclosure
Ambient temperature:	25°C
Relative humidity:	55%
Test Configurations:	TM1/TM2 at Channel Bottom, Middle, Top

6.1.2 Test Specifications and Limits

6.1.2.1 Specification

CFR 47 (FCC) part 2.1046 and Part 27.50(d)2

6.1.2.2 Supporting Standards

Table 12 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.1.2.3 Limits

Compliance with Part 27.232, mobile/portable stations are limited to 1 watts EIRP peak power.
 $W(\text{dBm}) = 10 \cdot \log(W_{\text{in mW}})$.

Table 13 Limits

Maximum Output Power (Watts)	< 1 Watts
Maximum Output Power (dBm)	< 30 dBm


6.1.3 Test Method and Setup

- For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the air interface. The band is set as AWS.
- Test the Radiated maximum output power by the CMU200 received from test antenna.

- (c) Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step (b) on CMU200, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.

Test setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum EIRP




Figure 1. Test Set-up

NOTE: Effective radiated power (ERP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

There is a constant difference of 2.15 dB between ERP and EIRP.

$EIRP (dBm) = ERP (dBm) + 2.15$ (ITU-R Recommendation SM.329-10).

EIRP was measured using 1 host.

6.1.4 Measurement Results

6.1.4.1 Pre-test Results

For HSDPA test mode, there are 4 sub-test for different configuration. For the sub-test 1, The channel is Middle range.

Sub-test	c	d	d (SF)	c/d	HS (Note1, Note 2)	CM(dB) (Note 3)	MPR (dB) (Note 3)	Test result
1	2/15	15/15	64	2/15	4/15	0	0	22.76
2	12/15	15/15	64	12/15	24/15	1	0	21.91
3	15/15	8/15	64	15/8	30/15	1.5	0.5	20.39
4	15/15	4/15	64	15/4	30/15	1.5	0.5	19.85

For the following test, the TM2 was used for HSDPA;

Table 14 Pre-test Measurement Results

		RF Output Power (EIRP)					
TEST CONDITIONS		Channel1312(B) 1712.4MHz		Channel1412(M) 1732.4MHz		Channel1513(T) 1752.6MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	T _{nom} (25 °C) V _{nom} (3.3V)	25.98	30	25.81	30	25.93	30
TM2	T _{nom} (25 °C) V _{nom} (3.3V)	25.47	30	25.36	30	25.22	30

6.1.4.2 Substitution Results

Table 15 Substitution Results

Test Mode	Freq. [MHz]	Meas. Level [dBm]	Substitution Antenna Type	SGP [dBm]	Substitution Gain [dBi]	Cable Loss [dB]	Substitution Level (EIRP) [dBm]	FCC limit [dBm]	Result
TM1	1712.4	25.98	Horn Ant.	22.24	4.5	1.0	25.74	30	Pass
TM1	1732.4	25.81	Horn Ant.	22.48	4.5	1.0	25.98	30	Pass
TM1	1752.6	25.93	Horn Ant.	22.06	4.8	1.0	25.86	30	Pass
TM2	1712.4	25.47	Horn Ant.	21.89	4.5	1.0	25.39	30	Pass
TM2	1732.4	25.36	Horn Ant.	21.97	4.5	1.0	25.47	30	Pass
TM2	1752.6	25.22	Horn Ant.	21.38	4.8	1.0	25.18	30	Pass

Note: a, For get the EIRP (Effective Isotropic Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{EIRP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBi]}$$



NOTE: SGP- Signal Generator Level

b, RBW=10kHz, VBW=300kHz, and integrated by the instrument to 5M for TM1 and TM2.

6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.



6.2 Conducted Power of Transmitter

6.2.1 Test Conditions

Table 16 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	52 %
Test Configurations:	TM1/TM2 at Channel Bottom, Middle, Top

6.2.2 Test Specifications and Limits

6.2.2.1 Specification

CFR 47 (FCC) part 2.1047 and Part 27.50(d)(2)

6.2.2.2 Supporting Standards

Table 17 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.2.2.3 Limits

Compliance with Part 27.232, in no any case may the peak power of a mobile station transmitter exceed 2 W. The calculated longitude EIRP by following formula:

$$\text{EIRP(dBm)} = 10 \cdot \log(\text{EIRP}_{\text{mW}}).$$

And for conducted power, we can use Antenna Gain to calculate the limit. So the conducted power:

$$\text{P}_{\text{cod}}(\text{dBm}) = \text{EIRP}(\text{dBm}) - \text{Gain}(\text{dBi}).$$

and $\text{Gain}(\text{dBi}) = \text{Gain}(\text{dBd}) + 2.15\text{dB}$

Table 18 Limits

Maximum Output Power (Watts)	< 1 Watts (30 dBm)
Antenna Gain(dBi):	2.6
Maximum Conducted Output Power (dBm)	< 27.4

6.2.3 Test Method and Setup

(a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, Conducted maximum power shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the wireless communication tester CMU200 via the antenna connector. The band class is set as AWS.

(b) Test the Conducted maximum output power by the CMU200.

Test setup




Figure 2. Test Set-up

6.2.4 Measurement Results

Table 19 Measurement Results

		RF Output Power(Conducted)					
TEST CONDITIONS		Channel1312(B) 1712.4MHz		Channel1412(M) 1732.4MHz		Channel1513(T) 1752.6MHz	
		dBm		dBm		dBm	
		Measured	Limit	Measured	Limit	Measured	Limit
TM1	T _{nom} (25 °C) V _{nom} (3.3V)	23.38	27.4	23.21	27.4	23.33	27.4
TM2	T _{nom} (25 °C) V _{nom} (3.3V)	22.87	27.4	22.76	27.4	22.62	27.4

6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.

6.3 Modulation Characteristics

6.3.1 Test Conditions

Table 20 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	52 %
Test Configurations:	TM1 at frequency Middle

6.3.2 Test Specifications and Limits

6.3.2.1 Specification

CFR 47 (FCC) part 2.1047 and Part 27 Subpart C&L

6.3.2.2 Supporting Standards

Table 21 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.3.2.3 Limits

No specific modulation characteristics requirement limits in part 2.1047 and part 24 subpart E.

Table 22 Limits

Limits	Not applicable
--------	----------------

6.3.3 Test Method and Setup

Connect the EUT to Universal Radio Communication Tester CMU200 via the antenna connector. The frequency band is set as AWS; the EUT's output is matched with 50 Ω load, test method was according to 3GPP TS 34.121. The waveform quality and constellation of the EUT Module was tested.

Test setup




Figure 3. Test Set-up



6.3.4 Measurement Results

Table 23 Measurement Results

		Modulation Characteristic
TEST CONDITIONS		Channel 1412(M) 1732.4MHz
		Measured
		TM1
T _{nom} (25 °C)	V _{nom} (3.3V)	Refer to Appendix A

6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix A.



6.4 Occupied Bandwidth

6.4.1 Test Conditions

Table 24 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	55 %
Test Configurations:	TM1 at frequency Bottom, Middle, Top

6.4.2 Test Specifications and Limits

6.4.2.1 Specification

CFR 47 (FCC) part 2.1049 and Part 27

6.4.2.2 Supporting Standards

Table 25 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.4.2.3 Limits

No specific occupied bandwidth requirement in Part 27 Subpart C&L, but the occupied bandwidth was defined in part 2.1049: the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Table 26 Limits

Upper /lower frequency limits	0.5% of the mean power
-------------------------------	------------------------

6.4.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSU26 via the one RF connector. The band class is set as AWS; The EUT was controlled to transmit maximum power. Measure and record the occupied bandwidth of the EUT HUAWEI U8100-9/U8100-9/IVY Module by the R&S FSU26.

The OBW, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

Refer to 47CFR part2.1049 section (g)&(h).

(g) Transmitter in which the modulating base band comprises not more than three independent channels - when modulated by the full complement of signals for which the transmitter is rated. The

level of modulation for each channel should be set to that prescribed in rule parts applicable to the services for which the transmitter is intended. If specific modulation levels are not set forth in the rules, the tests should provide the manufacturer's maximum rated condition.

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudorandom generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at discretion of the user.

For TM1 following RBW and VBW are employed:

Measurement bandwidth (RBW): 50 kHz (Resolution bandwidth)

Video bandwidth (VBW): 500 kHz

Test Set-up




Figure 4. Test Set-up

6.4.4 Measurement Results

Table 27 Measurement Results

TEST CONDITIONS		Occupied Bandwidth		
Center Frequency		Channel1312(B) 1712.4MHz	Channel1412(M) 1732.4MHz	Channel1513(T) 1752.6MHz
		Measured (MHz)	Measured (MHz)	Measured (MHz)
		TM1	TM1	TM1
Tnom (25 °C) Vnom (3.7V)	99%	4.18	4.18	4.18

6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.

For the measurement results refer to appendix B.



6.5 Band Edges Compliance

6.5.1 Test Conditions

Table 28 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	55 %
Test Configurations:	TM1 at frequency Bottom, Top

6.5.2 Test Specifications and Limits

6.5.2.1 Specification

CFR 47 (FCC) part 2.1051 and Part 27.53

6.5.2.2 Supporting Standards

Table 29 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.5.2.3 Limits

Compliance with Part 27.50(d) (2), all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$ (W). (Whereas P is the rated power of the EUT).

Table 30 Limits

	TM3
Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm - 37 dB
Absolute level	- 13 dBm

6.5.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSU26 via the one RF connector, the band class is set as AWS. The EUT controlled to transmit maximum power. Measure and record band edges compliance of the EUT by the R&S FSU26.

For TM1 following RBW and VBW are employed:

Measurement bandwidth (RBW): 50 kHz (Resolution bandwidth)

Video bandwidth (VBW): 200 kHz

Test Set-up




Figure 5. Test Set-up

6.5.4 Measurement Results

Table 31 Measurement Results outside Band Edges-- Single Carrier

Band	Frequency of Band edges [MHz]	Channel Number	Test Mode	Spurious Level measured [dBm]	FCC limit	Result
Cellular	T_{nom} (25 °C), V_{nom} (3.3V)					
	1712.4	1312	TM1	<-13(See appendix C)	- 13 dBm	Pass
	1752.6	1513	TM1	<-13(See appendix C)	- 13 dBm	Pass

6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix C.



6.6 Spurious Emission at Antenna Terminal

6.6.1 Test Conditions

Table 32 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	50 %
Test Configurations:	TM1 at frequency Bottom, Middle, Top

6.6.2 Test Specifications and Limits

6.6.2.1 Specification

CFR 47 (FCC) part 2.1051 and Part 27.53

6.6.2.2 Supporting Standards

Table 33 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.6.2.3 Limits

Compliance with Part 27.50(d)(2), all spurious emission must be attenuated below the transmitter power by at least $43 + 10 \log_{10} P$. (Whereas P is the rated power of the EUT).

Table 34 Limits

	TM1
Rated Power:	24 dBm
Required attenuation:	$43 + 10 \log(0.25) = 37$, 24 dBm - 37 dB
Absolute level	- 13 dBm

6.6.3 Test Method and Setup

The EUT was connected to the wireless signal analyzer R&S FSU26 via the one RF connector, the band class is set as AWS. The EUT was controlled to transmit maximum power. Measure and record the Conducted Spurious Emission of the EUT by the R&S FSU26.

According to Part 27.50(d) (2), the defined measurement bandwidth as following:

24.238 (b) Measurement procedure: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30MHz: 10 kHz;
Measurement bandwidth (RBW) for 30 MHz up to 20GHz: 1MHz;

Test Set-up




Figure 6. Test Set-up

6.6.4 Measurement Results

Table 35 Measurement Results

Channel Number	Test Mode	Test Range (Frequency)	Output Power [dBm]	Spurious Level measured [dBm]	FCC limit	Result
Channel 1312(B)	TM1	9 kHz~20GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 1412(M)	TM1	9 kHz~20GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass
Channel 1513(T)	TM1	9 kHz~20GHz	24	<- 13 dBm (See appendix D)	- 13 dBm	Pass

6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.
For the measurement results refer to appendix D.



6.7 Frequency Stability

6.7.1 Test Conditions

Table 36 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	See below
Relative humidity:	55 % at 25 °C
Test Configurations:	TM1 at frequency Middle

6.7.2 Test Specifications and Limits

6.7.2.1 Specification

CFR 47 (FCC) part 2.1055 and Part 27.54

6.7.2.2 Supporting Standards

Table 37 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
3GPP TS 34.121 V7.5.0	Technical Specification Group Radio Access Network; User Equipment (UE) conformance specification; Radio transmission and reception (FDD);

6.7.2.3 Limits

No specific frequency stability requirement in part 2.1055 and Part 27.50(d)(2).

6.7.3 Test Method and Setup

The frequency stability shall be measured with variation of ambient temperature as follows:

- (1) From -30 ° to +50 ° centigrade for all equipment except that specified in subparagraphs
- (2) and (3) of paragraph 2.1055

(a) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(b) The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 95 to 105 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment,

or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

(c) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment.)

The EUT can only work in such extreme voltage 3.6V and 4.2V, so here the EUT is tested in the 3.6V and 4.2V.

Test Set up

Connect the EUT to the Wireless Communication test set CMU200 via the connector. Then measure the frequency error by the Wireless Communication test set CMU200. The EUT's output is matched with a 50 Ω load.




Figure 7. Test Set up

6.7.4 Measurement Results

6.7.4.1 Measurement Results vs. Variation of Temperature

- **TM1, 3.6V DC Channel No.4182(836.4MHz)**

Table 38 Measurement Results vs. Variation of Temperature—TM1

Temperature	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
-30 °C	1732.4	3	Pass
-20 °C	1732.4	9	Pass
-10 °C	1732.4	-11	Pass
0 °C	1732.4	-4	Pass
+10 °C	1732.4	-12	Pass
+20 °C	1732.4	8	Pass
+30 °C	1732.4	14	Pass
+40 °C	1732.4	6	Pass
+50 °C	1732.4	-1	Pass



6.7.4.2 Measurement Results vs. Variation of Voltage

- **TM1, 25 °C ,Channel No. 4182(836.4MHz)**

Table 39 Measurement Results vs. Variation of Voltage—TM1

Voltage	Nominal Frequency (MHz)	Measured Frequency Error(Hz)	Result
4.2 V	1732.4	-2	Pass
3.7 V	1732.4	12	Pass
3.6 V	1732.4	-8	Pass

6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.



7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 40 System Measurement Uncertainty

Items		Extended Uncertainty
Effective Radiated Power of Transmitter	EIRP (dBm)	U=3dB; k=2
Band Width	Magnitude (%)	U=0.2%; k=2
Band Edge Compliance	Disturbance Power (dBm)	U=2.0dB; k=2
Conducted Spurious Emission at Antenna Terminal	Disturbance Power (dBm)	U=2.0dB; k=2
Frequency Stability	Frequency Accuracy(ppm)	U=0.21ppm; k=2



8 Appendices

Appendix A	Measurement Results Modulation Characteristics	2 Pages
Appendix B	Measurement Results Occupied Bandwidth	4 Pages
Appendix C	Measurement Results Band Edges	3 Pages
Appendix D	Measurement Results Spurious Emission at Antenna Terminal	10 Pages




Appendix A

Modulation Characteristics

According to FCC Part 2.1047 & Part 27 Subpart C&L



TM1: WCDMA Channel 1412






Appendix B

Occupied Bandwidth

According to FCC Part 2.1049 & Part 27 Subpart C&L
& RSS-139




TM1:WCDMA Channel 1312






Channel 1412





Channel 1513






Appendix C

Band Edges Compliance

According to FCC Part 2.1051 & Part 27 Subpart C&L
& RSS-139




TM1:WCDMA Left Edge Channel 1312





Right Edge Channel 1513






Appendix D


Spurious Emission at Antenna Terminal


According to FCC Part 2.1051 & Part 27 Subpart C&L
& RSS-139



TM1:WCDMA
Channel 1312












Channel 1412









Channel 1513

