



EMC Test Report

**Product Name: Vodafone 858
Smart ;HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with
Bluetooth;Vodafone 858;VF858**

Model Number: HUAWEI U8160 /U8160

Report No: SYBH(Z-EMC)035022011-2

FCC ID: QISU8160

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice 1

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Notice 2

Modification Information:

Modification Information

Modification Information	1	
	2	
	3	<i>Not Applicable!</i>
	4	
	5	
	6	
	7	

REPORT ON	Vodafone 858 Smart ;HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;Vodafone 858;VF858
	HUAWEI HUAWEI U8160 /U8160
REGULATION	FCC CFR47 Part 15: Subpart B;
	FCC CFR47 Part 22: Subpart H;
	FCC CFR47 Part 24: Subpart E;
START OF TEST	Mar.15,2011
END OF TEST	Mar.22,2011
Final Judgement:	Pass

Approved By

2011-03-27

Date

Liuchunlin

Name



Signature

Reviewed By

2011-03-27

Date

Dailinjun

Name



Signature

Operator

2011-03-27

Date

Wenjianfeng

Name



Signature

REPORT BODY CONTENT

1	Status	6
1.1	Product Information	6
1.2	Test Site	6
1.3	Test environment condition	6
2	Summary of Results	7
3	Equipment Specification	8
3.1	General Description	8
4	System Configuration during EMC Test	10
4.1	Cables Used during Test	10
4.2	Associated Equipment Used during Test	10
4.3	Test Configurations and Test Mode	10
4.4	Test conditions and test Connections	11
5	Electromagnetic Interference (EMI)	12
5.1	Radiated Disturbance 30MHz to 18GHz	12
5.2	Conducted Disturbance 0.15 MHz to 30MHz	13
5.3	Radiated Spurious Emissions	14
6	Main Test Instruments	16
7	System Measurement Uncertainty	17
8	Graph and Data of Emission Test	18
8.1	Radiated Disturbance	18
8.2	Conducted Disturbance	20
8.3	Radiated Spurious Emission	21

1 Status

1.1 Product Information

CLIENT:	Huawei Technologies Co., Ltd.
ADDRESS:	Bantian Longgang District Shenzhen, P.R. China
MANUFACTURING DESCRIPTION	Vodafone 858 Smart ;HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;Vodafone 858;VF858
MANUFACTURERS MODEL NUMBER	HUAWEI HUAWEI U8160 /U8160

1.2 Test Site

Site 1:

EMC LABORATORY OF RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD

1.3 Test environment condition

Ambient temperature	20~25°C
Relative humidity	40%~52%
Atmospheric pressure	101kPa

2 Summary of Results

Table below shows a brief summary of the results obtained.

Summary of results

EUT Classification: Wireless Terminal				
Test Items	Test Configuration & Test Mode	Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	TC1/TC2 (TM9-TM16)	N/A	Pass	Site1
<u>Conducted Emissions</u>	TC1 (TM1-TM16)	N/A	Pass	Site1
<u>Radiated Spurious Emissions</u> Enclosure Port	TC1 (TM1-TM6)	N/A	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, TC = Test configuration				

3 Equipment Specification

3.1 General Description

HUAWEI U8160 /U8160 are subscriber equipment in the WCDMA/GSM system. The HSDPA/UMTS frequency band is Band I. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only GSM850 and PCS1900MHz bands test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSDPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video, MMS service, GPS, AGPS and Wi-Fi etc. Externally it provides micro SD card interface, earphone port(to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

HUAWEI U8160-U/U8160-U is a HSDPA/UMTS/GPRS/GSM/EDGE mobile phone with Bluetooth, which supports GSM850/900/1800/1900 and WCDMA900 /2100.

HUAWEI U8160/U8160 is a HSDPA/UMTS/GPRS/GSM/EDGE mobile phone with Bluetooth, which supports GSM850/900/1800/1900 and WCDMA2100

The PCB of them is the same.

The difference between HUAWEI U8160-U/U8160-U and HUAWEI U8160/U8160 is showed in the following table.

	HUAWEI U8160-U/ U8160-U	HUAWEI U8160/ U8160
GSM four bands	support	support
WCDMA 2100M	support	support
WCDMA 900M	support	No
FLASH	Same	Same
PCB	the same	the same
Appearance	the same	the same
Bluetooth mode	the same	the same
WLAN mode	the same	the same
BT/ WLAN antenna	the same	the same
GSM/ WCDMA antenna	the same	the same
External camera	the same	the same
Internal camera	No	No
Adapter	the same	the same
Battery	the same	the same

3.1.1 Main Equipment Technical Data

Description:	Vodafone 858 Smart ;HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;Vodafone 858;VF858
Models:	HUAWEI U8160 /U8160
Input Rated Voltage	3.7V
Extreme Voltage	3.6V and 4.2V
Rated Power	Normal 3W ,Max 8 W
Dimensions	107mm (L)×57.5mm (W)×13mm (H)
Weight	<100g (with battery)

Sub-Assembly Identity

Mode		Work Frequency	
		Transmitt Frequency (MHz)	Receive Frequency (MHz)
GSM	GSM850	824 - 849	869 - 894
	PCS1900	1850-1910	1930-1990
Bluetooth		2400-2483.5	
WIFI		2400-2483.5	

Sub-Assembly Identity

Board				
Model Name	Qty.	Serial	Description	
HD1U813M	1	Z8D7NB1130200225	Main board of Mobile Phone	
Accessory				
Name	Qty.	Manufacture	Serials number	Description
Adapter	1	Huawei Technologies Co., Ltd.	XQH962600147	Adapter Model: HS-050040U6 Input Voltage : ~100-240V 50/60Hz 0.2A Output Voltage: === 5.0V 400mA Rated Power: 2W
Adapter	1	Huawei Technologies Co., Ltd.	BYAAB2106358	Adapter Model: HS-050040E7 Input Voltage : ~100-240V 50/60Hz 0.2A Output Voltage: === 5.0V 400mA Rated Power: 2W
Adapter	1	Huawei Technologies Co., Ltd.	HKAA71059634	Adapter Model: HS-050040B7 Input Voltage : ~100-240V 50/60Hz 0.2A Output Voltage: === 5.0V 400mA Rated Power: 2W
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	UNHA917XA3707152	Battery Model: HB4J1H Rated capacity: 1200mAh Nominal Voltage: === +3.7V Charging Voltage: === +4.2V

4 System Configuration during EMC Test

The Equipment under Test (EUT) was functioning correctly during all tests. The EUT was installed within the test site and was configured to simulate a typical user installation.

4.1 Cables Used during Test

Cable Used during Test

Cable	Quantity	Type of Cable
USB	1	shielded
Earphone	1	Unshielded

4.2 Associated Equipment Used during Test

Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date
Radio Communication Tester	CMU200	R&S	3607111817	2010-7-23
Notebook	T61	IBM	3108052508	N/A

4.3 Test Configurations and Test Mode

4.3.1 Test Configuration.

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

TC1:EUT powered with an adapter and connected to the test system (Base Station Simulator).

TC2:EUT connected to the notebook by USB port.

Configuration table

TC1/TC2	TM1~TM16
---------	----------

4.3.2 Test Mode

There were 16 test Modes. TM1 to TM16 were shown in the diagrams below:

TM1	operate in traffic mode GSM850;
TM2	operate in traffic mode GSM1900;
TM3	operate in traffic mode GPRS850;
TM4	operate in traffic mode GPRS 1900;
TM5	operate in traffic mode EDGE850;
TM6	operate in traffic mode EDGE1900;
TM7	operate in traffic mode Bluetooth;
TM8	operate in traffic mode WIFI;
TM9	operate in idle mode GSM850;
TM10	operate in idle mode GSM1900;
TM11	operate in idle mode GPRS850;
TM12	operate in idle mode GPRS 1900;
TM13	operate in idle mode EDGE850;
TM14	operate in idle mode EDGE1900;
TM15	operate in idle mode Bluetooth;
TM16	operate in idle mode WIFI;

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

4.4 Test conditions and test Connections

4.4.1 Test Conditions

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

4.4.2 Test connections

Traffic Mode:

The EUT is required to be in the traffic mode, a call is set up according to the generic call set up procedure and enter the EUT into loop back test mode. (GSM see ETSI TS 151.010).

For EGSM and PCS, the following conditions shall also be met:

The EUT shall be commanded to operate at maximum transmit power;

The downlink RXQUAL shall be monitored.

Assign channel frequency to an appropriate channel number.




Figure 1.: Test Configuration

Idle Mode:

The EUT is required to be in the idle mode.

For GSM850 and PCS1900, the following conditions shall be met::

When the EUT is required to be in the idle mode, the test system shall simulate a Base Station (BS) with Broadcast Control Channel/Common Control Channel (BCCH/CCCH) on one carrier. The EUT shall be synchronized to the BCCH, listening to the CCCH and able to respond to paging messages. Periodic Location Updating shall be disabled.

5 Electromagnetic Interference (EMI)

5.1 Radiated Disturbance 30MHz to 18GHz

5.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4. The test distance was 3m. The set-up and test methods were according to ANSI C63.4 .


A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

Measurement bandwidth: 30 MHz – 1000 MHz: 120 k Hz

Measurement bandwidth: 1GHz – 18GHz: 1MHz

Test set up figure:



5.1.2 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.

Test Limits

Frequency of Emission (MHz)	Radiated Limit	
	Unit($\mu\text{V}/\text{m}$)	Unit($\text{dB}\mu\text{V}/\text{m}$)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

5.2 Conducted Disturbance 0.15 MHz to 30MHz

5.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4.


Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei Mobile Station was communicated with the BTS simulator through Air interface, the BTS simulator controls the Mobile Station to transmitter the maximum power which defined in specification of product. The Mobile Station operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

Test Set-up figure:

The Mobile Station was setup in the screened chamber and operated under nominal conditions.



5.2.2 Test Results

The EUT has met requirements for Conducted disturbance of power lines.

Test Limit of DC&AC Power Port

Frequency range	150kHz~ 30MHz	
Classification	Class B	
Limit(Class B)	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66~56 dB μ V	56~46 dB μ V
0.5MHz~5MHz	56 dB μ V	46 dB μ V
5MHz~30MHz	60 dB μ V	50 dB μ V

5.3 Radiated Spurious Emissions


5.3.1 Test Procedure

A test site fulfilling the requirements of ITU-R Recommendation SM329-10 was used. The EUT was placed on a non-conducting support in the anechoic chamber and was operated from a power source via an RF filter to avoid radiation from the power leads.

Step 1:


For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the BTS simulator via the air interface.

Test the Radiated maximum output power by the Test Receiver from test antenna.



Step 2:

Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step1 on Test Receiver, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.



Test should be performed in normal voltage condition.

22.917(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30MHz up to 1 GHz: 100 kHz;
Measurement bandwidth (RBW) for 1GHz up to 18GHz: 1MHz;

Radiated Spurious Emissions Limits

Frequency band	Minimum requirement (E.R.P) traffic mode
9KHz~18GHz	-13dBm

24.238(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30MHz up to 26.5GHz: 1MHz;

Radiated Spurious Emissions Limits

Frequency band	Minimum requirement (E.R.P) traffic mode
9KHz~26.5GHz	-13dBm

No peak found in pre- test. All frequency points' margin is bigger than 20dB, so the substitution method isn't used.

Calculation Sample:

Substitution Results

Freq. [MHz]	Measure ment Value [dBm]	Substitution Antenna Type	Gain [dBd]	Cable Loss [dB]	Signal Generator Level [dBm]	Substitution Level [dBm]	FCC limit [dBm]	Result

Note: For get the E.R.P. (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$\text{E.R.P. [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

NOTE: SGP- Signal Generator Level

5.3.2 Test Results

The EUT has met the requirements of FCC Part22/24.

6 Main Test Instruments

Main Test Equipments

Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE&CE	EMI Test receiver	ESU26	R&S	Jun.25, 2010	12
	Broadband Antenna	VULB 9163	SCHWARZBECK	May.15, 2010	12
	Horn Antenna	HF906	R&S	May.15, 2010	12
	LISN	ENV216	R&S	Jun.25.2010	12
RSE	EMI Test receiver	ESIB26	R&S	May.05, 2010	12
	Horn Antenna	3117	EMCO	Dec.13.2010	12
	Broadband Antenna	CBL 6112B	SCHAFFNER	Dec.11.2010	12
	Horn Antenna	3160	ETS-Lindgren	Dec.23.2010	12
Software Information					
Test Item	Software Name	Manufacturer		Version	
RE/CE	ES-K1	R&S		1.7.1	
RSE	EMC32	R&S		V8.40.10	

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty


Items		Extended Uncertainty
RE	Field strength (dB μ V/m)	U=4.1dB; k=2(30MHz-1GHz)
RE	Field strength (dB μ V/m)	U=4.1dB; k=2(1GHz-18GHz)
RSE	ERP (dBm)	U=2.2dB; k=2
CE	Disturbance Voltage (dB μ V)	U=3.4dB; k=2

8 Graph and Data of Emission Test

8.1 Radiated Disturbance

This test was carried out in all the test modes, here only the worst test result was shown.


30MHz-1GHz



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
35.972000	26.30	12.0	40.0	13.7	107.0	254.00	VERTICAL
42.476000	25.00	13.1	40.0	15.0	100.0	0.00	VERTICAL
88.204000	17.80	11.2	43.5	25.7	108.0	201.00	VERTICAL
157.028000	19.10	9.4	43.5	24.4	113.0	276.00	VERTICAL
261.128000	22.80	14.2	46.0	23.2	100.0	85.00	HORIZONTAL
619.160000	30.40	22.7	46.0	15.6	135.0	359.00	HORIZONTAL

1GHz-18GHz




MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/ m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
1600.400000	16.60	-14.4	54.0	37.4	148.0	248.00	HORIZONTAL
2327.800000	19.70	-11.7	54.0	34.3	149.0	344.00	VERTICAL
4172.800000	24.50	-5.6	54.0	29.5	169.0	20.00	HORIZONTAL
6500.400000	26.90	-1.0	54.0	27.1	179.0	31.00	VERTICAL
11026.700000	30.20	6.8	54.0	23.8	125.0	106.00	VERTICAL
17979.900000	36.40	17.2	54.0	17.6	119.0	280.00	VERTICAL

8.2 Conducted Disturbance

This test was carried out in all the test modes, here only the worst test result was shown.



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.362000	40.30	10.0	59	18.7	N	FLO
0.796000	38.40	10.1	56	17.6	N	FLO
1.590000	37.40	10.1	56	18.6	N	FLO
2.988000	39.10	10.2	56	16.9	N	FLO
10.266000	38.90	10.3	60	21.1	N	FLO
16.010000	37.30	10.3	60	22.7	N	FLO

MEASUREMENT RESULT: AV Detector


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.362000	32.10	10.0	49	16.9	N	FLO
0.434000	31.40	10.1	47	15.6	N	FLO
1.888000	29.70	10.1	46	16.3	N	FLO
3.250000	31.00	10.2	46	15.0	N	FLO
7.904000	28.70	10.2	50	21.3	N	FLO
16.000000	25.70	10.3	50	24.3	N	FLO

8.3 Radiated Spurious Emission


This test results are the maximum level of radiated spurious emissions in vertical and horizontal polarity. The highest peak exceeds the limit line is carrier frequency

8.3.1 For GSM 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.2 For GPRS 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.3 For EDGE 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.4 For GSM 1900


Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




Traffic Mode (18GHz-26.5GHz)




8.3.5 For GPRS 1900 Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




Traffic Mode (18GHz-26.5GHz)




8.3.6 For EDGE 1900 Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)



Traffic Mode (2GHz-18GHz)



Traffic Mode (18GHz-26.5GHz)



-----END-----