



EMC Test Report

Product Name: HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; StarTrail II; webphones Android™ by sfr STARTRAIL II; HUAWEI Ascend Y 200; Ascend Y 200

Model Number: HUAWEI U8655-1,U8655-1

**Report No: SYBH(Z-EMC)012022012-2
FCC ID:QISU8655-1**

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Applicant: Huawei Technologies Co., Ltd.
Address: Huawei Base, Bantian, Longgang District, Shenzhen
518129, P.R. China

Date of Receipt Test Item: Feb.11, 2012
Start Date of Test: Feb.11, 2012
End Date of Test: Feb.21, 2012

Test Result: Pass

**Approved By
(Lab Manager)**

2012-02-22
Date

Liuchunlin
Name



Signature

Operator

2012-02-22
Date

Xuchang
Name



Signature

TABLE OF CONTENT

1	General Information	5
1.1	EUT Description	5
1.2	Test Site Information	7
1.3	Applied Standards	7
2	Summary of Results.....	8
3	System Configuration during EMC Test.....	9
3.1	Test Mode	9
3.2	Configurations of Test System.....	9
3.3	Cables Used during Test.....	12
3.4	Associated Equipment Used during Test.....	12
4	Electromagnetic Interference (EMI).....	13
4.1	Radiated Disturbance 30MHz to 18GHz	13
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	15
5	Main Test Instruments.....	16
6	System Measurement Uncertainty	16
7	Graph and Data of Test.....	17
7.1	Radiated Disturbance.....	17
7.2	Conducted Disturbance.....	19

1 General Information

1.1 EUT Description

EUT Description	
Product Name	HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; StarTrail II; webphones Android™ by sfr STARTRAIL II; HUAWEI Ascend Y 200; Ascend Y 200
Model Number	HUAWEI U8655-1,U8655-1
Serials Number	L3F01A11C2000106
Working Voltage	120V/60Hz
TX Frequency	GSM850:824MHz To 849MHz; PCS1900:1850MHz To 1910MHz Bluetooth: 2400MHz To 2483.5MHz WIFI: 2400MHz To 2483.5MHz
RX Frequency	GSM850:869MHz To 894MHz; PCS1900:1930MHz To 1990MHz Bluetooth: 2400MHz To 2483.5MHz WIFI: 2400MHz To 2483.5MHz GPS: 1575.42MHz
HW Version	HD1U8655M
SW Version	U8655-1V100R001C00B869
EUT Accessory	
Data cable	Data Cable USB A Male to Micro Usb, Black
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100U1W Input voltage: ~100-240V 50/60Hz 0.2A Output voltage: 5V  1A Rated Power: 5W S/N:TPABB2503568 S/N:HKABB2414149
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100A1W Input voltage: ~100-240V 50/60Hz 0.2A Output voltage: 5V  1A Rated Power: 5W S/N: HKBBA2399493
Rechargeable Li-ion	Manufacturer: Huawei Technologies Co., Ltd. Battery Model: HB5K1H Rated capacity: 1400mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V S/N:WHCBC02HI4763186
Rechargeable Li-ion	Manufacturer: Huawei Technologies Co., Ltd. Battery Model: HB5K1 Rated capacity: 1250mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V S/N:GAGBC29L97419334 S/N:BAAC214F97400318

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.2 Test Site Information

Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Bantian Longgang District Shenzhen, P.R. China

1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2010, Subpart B

2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode1~ Mode2 Mode5 Mode7~ Mode8	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

3 System Configuration during EMC Test


3.1 Test Mode

Huawei has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was in this test report and defined as:


Test Mode	
Mode 1:	adapter+earphone+Camera On +Idle
Mode 2:	adapter+earphone+MP3 +Idle
Mode 3:	adapter+earphone+Traffic
Mode 4:	adapter+Traffic
Mode 5:	USB Copy(EUT with PC)+earphone +Idle
Mode 6:	Traffic
Mode 7:	Camera On+earphone+Idle
Mode 8:	earphone+MP3+Idle

Remark: When the EUT have multiple adapters, need separate test with multiple adapters . All test modes are performed, only the worst cases are recorded in this report.


3.2 Configurations of Test System




Connection Diagram (Mode 4)




Connection Diagram (Mode 5)



Connection Diagram (Mode 6)



Connection Diagram (Mode 7-Mode 8)



3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	shielded
Earphone	1	<3m	Unshielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date
Radio Communication Tester	CMU200	R&S	3607033573	2011-03-17
Notebook	T61	IBM	3108052508	N/A

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz


Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4. The test distance was 3m. The set-up and test methods were according to ANSI C63.4.


A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

Test setup



Test set-up of radiated disturbance(30MHz-1GHz)



Test set-up of radiated disturbance(above 1GHz)

Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
The test data see section 7.1 of this report.

Test Limits				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

Test environment condition:


Performed Item	Item	Required	Actual
Radiated Emission	Ambient temperature	15°C~35°C	23.0°C
	Relative humidity	25%~75%	53.5%
	Atmospheric pressure	86 kPa~106kPa	101kPa

4.2 Conducted Disturbance 0.15 MHz to 30MHz

Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4. Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector. EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.
Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;
The EUT was setup in the screened chamber and operated under nominal conditions.

Test Setup



Test Set-up of conducted disturbance

Test Results

The EUT has met requirements for Conducted disturbance of power lines.
The test data see section 7.2 of this report.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66-56dBμV	56-46 dBμV
0.5MHz-5MHz	56dBμV	46 dBμV
5MHz~30MHz	60dBμV	50 dBμV

Test environment condition:

Performed Item	Item	Required	Actual
Conducted Disturbance	Ambient temperature	15°C~35°C	23.0°C
	Relative humidity	25%~75%	53.5%
	Atmospheric pressure	86 kPa~106kPa	101kPa

5 Main Test Instruments

Main Test Equipments					
Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE/CE	EMI Test receiver	ESU26	R&S	May.30, 2011	12
	Broadband Antenna	VULB 9163	SCHWARZBECK	May.16, 2011	12
	Horn Antenna	HF906	R&S	May.16, 2011	12
	Artificial Mains Network	ENV216	R&S	May.30, 2011	12
Software Information					
Test Item	Software Name	Manufacturer		Version	
RE/CE	ES-K1	R&S		1.7.1	

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dB μ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=4.1dB; k=2
CE	Disturbance Voltage (dB μ V)	U=3.4dB; k=2

7 Graph and Data of Test

Only the worst test result was shown in this report.

7.1 Radiated Disturbance


30MHz~1GHz



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
33.900000	25.40	14.8	40.0	14.6	100.0	251.00	VERTICAL
79.740000	21.00	10.5	40.0	19.0	200.0	126.00	VERTICAL
159.780000	15.80	10.1	43.5	27.7	100.0	0.00	VERTICAL
239.760000	15.40	13.8	46.0	30.6	100.0	128.00	VERTICAL
554.880000	19.40	19.9	46.0	26.6	100.0	180.00	HORIZONTAL
881.880000	25.30	24.7	46.0	20.7	200.0	359.00	VERTICAL

1GHz~18GHz



MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
6069.500000	39.60	0.3	74.0	34.4	101.0	144.00	HORIZONTAL
14462.000000	48.20	14.6	74.0	25.8	150.0	74.00	HORIZONTAL
17827.500000	50.20	18.8	74.0	23.8	118.0	124.00	VERTICAL

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
6243.000000	27.40	0.6	54.0	26.6	150.0	152.00	HORIZONTAL
14165.500000	34.70	13.7	54.0	19.3	149.0	318.00	HORIZONTAL
17830.000000	37.20	18.9	54.0	16.8	137.0	130.00	VERTICAL

7.2 Conducted Disturbance

AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transducer dB	Limit dBµV	Margin dB	Line	PE
0.158000	41.80	10.1	66	24.2	N	FLO
0.436000	35.60	10.1	57	21.4	N	FLO
1.512000	30.80	10.1	56	25.2	N	FLO
4.772000	28.70	10.2	56	27.3	N	FLO
7.400000	30.10	10.2	60	29.9	N	FLO
23.806000	25.50	10.4	60	34.5	L1	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Transducer dB	Limit dBµV	Margin dB	Line	PE
0.356000	28.00	10.0	49	21.0	N	FLO
0.436000	29.50	10.1	47	17.5	N	FLO
0.954000	24.80	10.1	46	21.2	N	FLO
2.714000	23.90	10.2	46	22.1	N	FLO
6.936000	23.80	10.2	50	26.2	N	FLO
22.096000	19.60	10.4	50	30.4	L1	FLO

-----END-----