



# FCC Test Report

**Product Name: HUAWEI IDEOS X5;  
HSPA+/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth;  
IDEOS X5**

**Product Name:HUAWEI IDEOS X5;  
HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with  
Bluetooth; IDEOS X5**

**Model Number: HUAWEI U8800H/U8800H  
Model Number:HUAWEI U8800/U8800**

**Report No: SYBHZ(R)E063082010EB-5  
FCC ID: QISU8800**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518



## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
3. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



**REPORT ON**

FCC 47CFR part 15 subpart C Test of  
HUAWEI IDEOS X5;HSPA+/UMTS/GPRS/GSM/EDGE Mobile  
Phone with Bluetooth; IDEOS X5

HUAWEI IDEOS X5;HSPA/UMTS/GPRS/GSM/EDGE Mobile  
Phone with Bluetooth; IDEOS X5

M/N: HUAWEI U8800H/U8800H  
HUAWEI U8800/U8800  
Report No: SYBHZ(R)E063082010EB-5  
FCC ID: QISU8800

**REGULATION**

**FCC CFR47 Part 2: Subpart J;**

**FCC CFR47 Part 15: Subpart C;**

**CONCLUSION**

**Pass**

Approved By

2010-10-11  
Date

Liuchunlin  
Name

  
Signature

Reviewed By

2010-10-11  
Date

Dailinjun  
Name

  
Signature

Operator

2010-10-10  
Date

Wenjianfeng  
Name

  
Signature

**Contents**



---

---

<b>1</b>	<b><u>Summary</u></b> .....	<b>5</b>
<b>2</b>	<b><u>Product Description</u></b> .....	<b>6</b>
2.1	PRODUCTION INFORMATION .....	6
2.2	MODIFICATION INFORMATION.....	6
<b>3</b>	<b><u>Test Site Description</u></b> .....	<b>7</b>
3.1	TESTING PERIOD .....	7
3.2	GENERAL SET UP DESCRIPTION .....	7
<b>4</b>	<b><u>Product Description</u></b> .....	<b>8</b>
4.1	TECHNICAL CHARACTERISTICS .....	8
4.2	EUT IDENTIFICATION LIST .....	10
<b>5</b>	<b><u>Main Test Instruments</u></b> .....	<b>11</b>
<b>6</b>	<b><u>Transmitter Measurements</u></b> .....	<b>12</b>
6.1	20DB BANDWIDTH MEASUREMENT .....	12
6.2	CARRIER FREQUENCY SEPARATION MEASUREMENT .....	14
6.3	NUMBER OF HOPPING CHANNEL.....	16
6.4	TIME OF OCCUPANCY .....	18
6.5	PEAK OUTPUT POWER .....	20
6.6	BAND EDGE SPURIOUS EMISSION .....	22
6.7	CONDUCTED RF SPURIOUS .....	24
6.8	RADIATED SPURIOUS EMISSION & SPURIOUS IN RESTRICTED BAND .....	26
6.9	CONDUCTED EMISSION AT POWER PORT .....	29
<b>7</b>	<b><u>System Measurement Uncertainty</u></b> .....	<b>31</b>
<b>8</b>	<b><u>Appendices List</u></b> .....	<b>32</b>



# 1 Summary

The table below summarizes the measurements and results for the HUAWEI U8800H/U8800H/  
HUAWEI U8800/U8800. Detailed results and descriptions are shown in the following pages.

Table 1 Summary of results

<b>FCC Measurement Specification</b>	<b>Description</b>	<b>Result</b>
15.247 (a) (1)	20dB bandwidth measurement	PASS
15.247 (a) (1)	Carrier frequency separation measurement	PASS
15.247 (a) (1) III	Number of hopping channel	PASS
15.247 (a) (1) III	Time of occupancy	PASS
15.247 (b) (1)	Peak output power	PASS
15.247 (d)	Band edge compliance measurement	PASS
15.247 (d)	Conducted RF spurious	PASS
15.247 (d) / 15.205 & 15.209	Radiated spurious emission & Radiated restricted band measurement	PASS
15.207	Conducted emission test for power port	PASS



## 2 Product Description

### 2.1 Production Information

#### 2.1.1 General Description

HUAWEI U8800H/U8800H/HUAWEI U8800/U8800 is subscriber equipment in the WCDMA/GSM system. The HSPA/HSPA+/UMTS frequency band is Band I and Band VIII. The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSPA/HSPA+/UMTS and GSM/GPRS/EDGE protocol processing, voice, video, MMS service, GPS and WIFI etc. Externally it provides micro SD card interface, earphone port(to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

#### 2.1.2 Support function and Service

The Mobile Phone HUAWEI U8800H/U8800H/HUAWEI U8800/U8800 support the Bluetooth's function and service as follows:

Table 2 Service and Test mode List

Service Name	Characteristic	Corresponding Test Mode	Note
Data and Voice	Modulation: GFSK	TM1	/

### 2.2 Modification Information

For original equipment, following table is not application.

Table 3 Modification Information

Model Number	Board/Module	Original Version	New Version	Modify Information
Not applicable!				



### **3 Test Site Description**

The test site of:

***Huawei Technologies Co. Ltd.  
P.O. Box 518129  
Huawei base, bantian,  
Longgang District, Shenzhen, China***

#### **3.1 Testing Period**

The test have been performed during the period of

Sep.25, 2010 to Sep.28, 2010

#### **3.2 General Set up Description**

The EUT can Support 2.4GHz Band. For compliance with FCC regulation 47CFR part15 subpart C, we set the EUT as following test mode to do all compliance tests.

**Bluetooth MODE:**

**TM1:** GFSK Modulation



## 4 Product Description

### 4.1 Technical Characteristics

#### 4.1.1 Frequency Range

Table 4 Frequency Range

Uplink band:	2400 to 2483.5 MHz	
Downlink band:	2400 to 2483.5 MHz	
Hop frequency support:	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO

#### 4.1.2 Channel Spacing / Separation

Table 5 Channel Spacing / Separation

Channel spacing:	1 MHz
Channel separation:	1 MHz

#### 4.1.3 Type of Emission

Table 6 Type of Emission

Emission Designation:	-
-----------------------	---

According to CFR 47 (FCC) part 2, subpart C, section 2.201 and 2.202

#### 4.1.4 Antenna Information

Table 7 Antenna Information

Type:	Integrated / Internal
Maximum Gain(dBi):	0 (from 2400MHz to 2500MHz)



#### 4.1.5 Environmental Requirements

Table 8 Environmental Requirements

Minimum temperature:	- 10 °C
Maximum temperature:	+ 55 °C
Relative Humidity:	5%-95%

#### 4.1.6 Power Source

Table 9 Power Source

AC voltage nominal:	~120V
AC voltage range	~100V-240V
AC current maximal:	650mA

#### 4.1.7 Tune-up Procedure

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (9).

Please reference the document Tune-up Procedure in TCF.

#### 4.1.8 Applied DC Voltages and Currents

According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8).

The voltage and current in the final RF stage is:

Table 10 Applied RF module DC Voltages and Currents

Voltage:	 3.7V
Current:	100mA According to CFR (FCC) part 2, subpart 2, section 2.1033(c) (8)



## 4.2 EUT Identification List

### 4.2.1 Board Information

Table 11 Board Information

HUAWEI IDEOS X5;HSPA+/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; IDEOS X5		
HUAWEI U8800H/U8800H		
HUAWEI IDEOS X5;HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; IDEOS X5		
HUAWEI U8800/U8800		
Board and Module		
Equipment Designation / Description	Serial Number	Remarks
Main board	6Q7NBB1082000649	HD1U880M

### 4.2.2 Battery Technical Data

Name	Qty.	Manufacture	Serials number	Description
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	SCCA605H123315 22	Battery Model: HB4F1 Rated capacity: 1500mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V

### 4.2.3 FCC Identification

**Grantee Code:** QIS  
**Product Code:** U8800  
**FCC Identification:** QISU8800



## 5 Main Test Instruments

Table 12 Main Test Equipments

Equipment Description	Manufacturer	Model	Serial Number	Calibrated until (MM.DD.YYYY)
Receiver	R&S	ESU26	100150	05.24.2011
Pre-Amplifier	R&S	SCA-SCU 18	10003	NA
Pre-Amplifier	R&S	SCA-SCU 26	3357-3358	NA
BiLog Antenna	SCHWARZBECK	VULB 9163	9163-356	05.14.2011
Horn Antenna	R&S	HF906	100683	05.14.2011
Horn Antenna	ETS-Lindgren	3160	00091989	09.20.2011
LISN	R&S	ENV216	100382	07.24.2011
Universal Radio Communication Tester	R&S	CBT	100548	02.21.2011
Signal Analyzer	Agilent	E4440A	3608083811	12.17.2010
Power Divider	Agilent	11667A	54723	NA



## 6 Transmitter Measurements

### 6.1 20dB bandwidth measurement

#### 6.1.1 Test Conditions

Table 13 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	76%
Test Configurations:	TM1 at channel No.0, 40, 78

#### 6.1.2 Test Specifications and Limits

##### 6.1.2.1 Specification

CFR 47 (FCC) part 15.247 (a) (1) and DA 00-705

##### 6.1.2.2 Supporting Standards

Table 14 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
---------------------	---

##### 6.1.2.3 Limits

Not Applicable.

#### 6.1.3 Test Method and Setup

- (a) Connect test port of mobile phone to universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function, then set the measured frequency number and test the 20dB bandwidth with universal communication tester.

## Test setup




Figure 1. Test Set-up

## 6.1.4 Measurement Results

Table 15 Measurement Results

Bandwidth Type	Channel Position	Channel Number	Frequency [GHz]	Measured Bandwidth [MHz]	Result
20dB	B	0	2.402	0.944M	Pass
20dB	M	40	2.442	0.952M	Pass
20dB	T	78	2.480	0.972M	Pass

## 6.1.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix A.



## 6.2 Carrier frequency separation measurement

### 6.2.1 Test Conditions

Table 16 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	76%
Test Configurations:	TM1 at channel No.39, 40, 41

### 6.2.2 Test Specifications and Limits

#### 6.2.2.1 Specification

CFR 47 (FCC) part 15.247 (a) (1) and DA 00-705

#### 6.2.2.2 Supporting Standards

Table 17 Supporting Standards:

ANSI/TIA-603-C:2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
---------------------	---

#### 6.2.2.3 Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Table 18 Limits

Regulation:	$\geq 0.025$ or $2/3$ of the 20 dB bandwidth
Limit:	$\geq 2/3 \times 0.952M = 0.635$ MHz

### 6.2.3 Test Method and Setup

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function, then set the measured frequency number to two adjacent channels separately and test the carrier frequency separation with spectrum analyzer.

## Test setup




Figure 2. Test Set-up

## 6.2.4 Measurement Results

Table 19 Measurement Results

Channel No.	Frequency [GHz]	Channel No.	Frequency [GHz]	Measured frequency separation [MHz]	Limit [MHz]	Result
40	2.442	39	2.441	1.0	$\geq 0.635$	Pass
40	2.442	41	2.443	1.0	$\geq 0.635$	Pass

## 6.2.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix B.



## 6.3 Number of hopping channel

### 6.3.1 Test Conditions

Table 20 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	76%
Test Configurations:	TM1 at hopping frequency state

### 6.3.2 Test Specifications and Limits

#### 6.3.2.1 Specification

CFR 47 (FCC) part 15.247 (a) (1) iii and DA 00-705

#### 6.3.2.2 Supporting Standards

Table 21 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.3.2.3 Limits

Number of hopping channel should be compliance with the requirements in part15.247 (a) (1) iii.

Table 22 Limits

Limits	≥ 15 hopping frequency channel
--------	--------------------------------

### 6.3.3 Test Method and Setup

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch on frequency hopping function, then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.
- (c) Count the quantity of peaks to get the number of hopping channels.

## Test setup




Figure 3. Test Set-up

## 6.3.4 Measurement Results

Table 23 Measurement Results

Measured frequency range [MHz]	Channel No. range	Measured Channel No.	Limit	Result
2400 to 2483.5	0-78	79	$\geq 15$	Pass

## 6.3.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix C.



## 6.4 Time of occupancy

### 6.4.1 Test Conditions

Table 24 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	76%
Test Configurations:	TM1 at hopping frequency state

### 6.4.2 Test Specifications and Limits

#### 6.4.2.1 Specification

CFR 47 (FCC) part 15.247 (a) (1) iii and DA 00-705

#### 6.4.2.2 Supporting Standards

Table 25 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.4.2.3 Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Table 26 Limits

Limits for time of occupancy	≤ 0.4s
------------------------------	--------

### 6.4.3 Test Method and Setup

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch on frequency hopping function.
- (c) Set the span of spectrum analyzer to 0 Hz, and set the resolution bandwidth to 1 MHz and the video bandwidth to 1 MHz, then get the time domain measured diagram. and set sweep time to 2 times of one burst occupancy time, and measure the time of occupancy of one burst.
- (d) Set the resolution bandwidth to 1 MHz and the video bandwidth to 3 MHz, and set the sweep time to a period (0.4 seconds multiplied by the number of hopping channels employed), and count the number of the bursts.
- (e) Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.

## Test setup




Figure 4. Test Set-up

### 6.4.4 Measurement Results

Table 27 Measurement Results

Time of Single Slot [ms]	Numbers of slots in a period	Time of occupied in a period [s]	Limit [s]	Result
1.8	106.7	0.19206	≤ 0.4	Pass

Note: The result is measured at DH5 mode in GFSK modulation, which has longest time in one transmission burst.

### 6.4.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix D.



## 6.5 Peak output power

### 6.5.1 Test Conditions

Table 28 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	76%
Test Configurations:	TM1 at channel No.0, 40, 78

### 6.5.2 Test Specifications and Limits

#### 6.5.2.1 Specification

CFR 47 (FCC) part 15.247 (b) (1) and DA 00-705

#### 6.5.2.2 Supporting Standards

Table 29 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.5.2.3 Limits

Compliance with part 15.247 (b) (1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watt.

Table 30 Limits

2.4GHz and 5.8GHz hopping frequency system	1 Watt (=30 dBm)
--	------------------

### 6.5.3 Test Method and Setup

- (a) Connect test port of mobile phone to universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function.
- (c) Then set the mobile phone to transmit at high, middle and low frequency and measure the conducted output power separately.

## Test setup




Figure 5. Test Set-up

## 6.5.4 Measurement Results

Table 31 Measurement Results

Channel	Channel No.	Center Freq.[MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
Bottom	0	2402	2.04	< 30	Pass
Middle	40	2442	1.92	< 30	Pass
Top	78	2480	1.77	< 30	Pass

## 6.5.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix E.

## 6.6 Band edge spurious emission

### 6.6.1 Test Conditions

Table 32 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25°C
Relative humidity:	76%
Test Configurations:	TM1 at channel No. 0, 78 and frequency hopping state

### 6.6.2 Test Specifications and Limits

#### 6.6.2.1 Specification

CFR 47 (FCC) part 15.247 (d) and DA 00-705

#### 6.6.2.2 Supporting Standards

Table 33 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.6.2.3 Limits

Compliance with part 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

Table 34 Limits

Band edge spurious:	20 dBc/100kHz
---------------------	---------------

### 6.6.3 Test Method and Setup

- Connect test port of mobile phone to spectrum analyzer and universal communication tester
- Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function.
- Then set the mobile phone to transmit at high, low frequency and measure the conducted band edge spurious separately.
- Switch on the frequency hopping function, and repeat above measurement.

## Test setup




Figure 6. Test Set-up

## 6.6.4 Measurement Results

Table 35 Measurement Results for Band Edge immediately outside the 2.4GHz Band

	Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max. Spurious Level [dBm]	Limit [dBm]	Result
Low Edge	0	2402	1.91	Off	-46.55	< -18.09	Pass
	-	-	1.93	On	-54.48	< -18.07	Pass
High Edge	78	2480	1.65	Off	-53.82	< -18.35	Pass
	-	-	1.59	On	-53.76	< -18.41	Pass

## 6.6.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix F.

## 6.7 Conducted RF spurious

### 6.7.1 Test Conditions

Table 36 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Antenna connector
Ambient temperature:	25 °C
Relative humidity:	76%
Test Configurations:	TM1 at channel No.0, 40, 78

### 6.7.2 Test Specifications and Limits

#### 6.7.2.1 Specification

CFR 47 (FCC) part 15.247 (d) and DA 00-705

#### 6.7.2.2 Supporting Standards

Table 37 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
----------------------	---

#### 6.7.2.3 Limits

Compliance with part 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

Table 38 Limits

Band edge spurious:	20 dBc/100kHz
---------------------	---------------

### 6.7.3 Test Method and Setup

- Connect test port of mobile phone to spectrum analyzer and universal communication tester
- Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function.
- Then set the mobile phone to transmit at high, middle and low frequency and measure the conducted band edge spurious separately.
- Switch on the frequency hopping function, and repeat above measurement.

## Test setup




Figure 7. Test Set-up

## 6.7.4 Measurement Results

Table 39 Measurement Results

Test Frequency Range	Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max. Spurious Level [dBm]	Limit [dBm]	Result
9kHz-25GHz	0	2402	1.42	Off	-46.33	< -18.58	Pass
9kHz-25GHz	40	2442	1.78	Off	-44.52	< -18.22	Pass
9kHz-25GHz	78	2480	1.5	Off	-43.22	< -18.5	Pass

## 6.7.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix G.



## 6.8 Radiated spurious emission & spurious in restricted band

### 6.8.1 Test Conditions

Table 40 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Enclosure
Ambient temperature:	25 °C
Relative humidity:	55 %
Test Configurations:	TM1 at channel No.0, 40, 78

### 6.8.2 Test Specifications and Limits

#### 6.8.2.1 Specification

CFR 47 (FCC) part 15.247 (d), 15.205 & 15.209 and DA 00-705

#### 6.8.2.2 Supporting Standards

Table 41 Supporting Standards:

ANSI/TIA-603-C: 2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI C63.4: 2003	Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

#### 6.8.2.3 Limits

According to part 15.247 (d) / 15.205 & 15.209, all spurious emission in the frequency range from 30MHz to 10<sup>th</sup> harmonics of carrier frequency should be meet the requirement of following table.

Table 42 Limits

Frequency (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance (meters)	Detector
30 - 88	100	40	3	QP
88 - 216	150	43.5	3	QP
216 - 960	200	46	3	QP
960 -1000	500	54	3	QP
Above 1000	500	54	3	PK

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a) (see above table).

### 6.8.3 Test Method and Setup

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4. The Radiated Disturbance measurements were made using a Rohde and Schwarz Test Receiver and control software.

A preliminary scan and a final scan of the emissions were made by using test script of software; the emissions were measured using a Quasi-Peak Detector below 1GHz, and AV detector above 1GHz. The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0°to 360°, The receive antenna has two polarizations V and H.

Huawei HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth HUAWEI U8800H/U8800H/HUAWEI U8800/U8800 was communicated with the BTS simulator through Air interface. The Mobile Phone transmits maximum output power at 2.4GHz and switch off frequency hopping function.

Measurement bandwidth: 30 MHz - 1000 MHz: 120 kHz  
 Measurement bandwidth: 1000 MHz - 10<sup>th</sup> Carrier Frequency: 1 MHz

**Test set up**




Figure 8. Test Set up

**6.8.4 Measurement Results**

Note: The following measurement results exceed the limit line is the carrier frequency.

**Measured Result of channel: 0 (2402MHz)**

Table 43 MEASUREMENT RESULT

Frequency (MHz)	Level (dBµV/m)	Transd (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
33.300000	22.60	11.7	40.0	17.4	147.0	96.00	VERTICAL
54.600000	19.10	12.7	40.0	20.9	276.0	36.00	VERTICAL
145.320000	15.40	8.9	43.5	28.1	275.0	223.00	VERTICAL
245.220000	20.90	14.1	46.0	25.1	224.0	292.00	HORIZONTAL
549.900000	28.70	21.4	46.0	17.3	236.0	100.00	VERTICAL
938.220000	38.80	26.5	46.0	7.2	149.0	8.00	HORIZONTAL
3046.000000	26.40	-9.0	54.0	27.6	100.0	50.00	HORIZONTAL
4800.500000	25.00	-4.1	54.0	29.0	141.0	319.00	VERTICAL
6230.500000	25.40	-1.4	54.0	28.6	114.0	178.00	VERTICAL
9608.500000	31.80	5.1	54.0	22.2	154.0	25.00	HORIZONTAL
14175.000000	34.00	11.4	54.0	20.0	125.0	315.00	VERTICAL
18000.000000	36.90	17.3	54.0	17.1	178.0	350.00	HORIZONTAL
2310.000000	38.00	33.3	54.0	16.0	200.0	9.00	VERTICAL



2390.000000	38.40	33.5	54.0	15.6	183.0	162.00	VERTICAL
2483.500000	38.30	33.7	54.0	15.7	122.0	144.00	HORIZONTAL
2500.000000	38.30	33.8	54.0	15.7	198.0	132.00	HORIZONTAL

**Measured Result of channel: 40 (2442MHz)**

Table 44 MEASUREMENT RESULT

Frequency (MHz)	Level (dBµV/m)	Transd (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
33.000000	22.20	11.7	40.0	17.8	113.0	129.00	VERTICAL
53.760000	20.50	12.7	40.0	19.5	100.0	61.00	VERTICAL
140.880000	16.90	8.7	43.5	26.6	124.0	346.00	VERTICAL
209.940000	24.20	12.5	43.5	19.3	107.0	2.00	VERTICAL
377.940000	25.00	17.6	46.0	21.0	246.0	98.00	HORIZONTAL
938.220000	36.30	26.5	46.0	9.7	140.0	115.00	HORIZONTAL
3046.000000	28.30	-9.0	54.0	25.7	100.0	52.00	HORIZONTAL
4415.500000	24.40	-5.7	54.0	29.6	102.0	38.00	VERTICAL
4960.000000	37.50	-3.8	54.0	16.5	101.0	346.00	VERTICAL
9920.000000	32.80	5.1	54.0	21.2	107.0	315.00	VERTICAL
14264.500000	34.20	11.7	54.0	19.8	133.0	147.00	VERTICAL
17999.500000	37.00	17.3	54.0	17.0	109.0	332.00	VERTICAL

**Measured Result of channel: 78 (2480MHz)**

Table 45 MEASUREMENT RESULT

Frequency (MHz)	Level (dBµV/m)	Transd (dB)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Polarisation
33.180000	24.30	11.7	40.0	15.7	100.0	83.00	VERTICAL
85.980000	22.40	10.5	40.0	17.6	139.0	85.00	VERTICAL
129.780000	22.50	9.3	43.5	21.0	100.0	331.00	VERTICAL
209.460000	24.60	12.5	43.5	18.9	100.0	356.00	VERTICAL
292.020000	30.30	15.3	46.0	15.7	100.0	107.00	HORIZONTAL
466.140000	31.50	19.2	46.0	14.5	109.0	317.00	VERTICAL
3046.500000	29.60	-9.0	54.0	24.4	100.0	50.00	HORIZONTAL
4884.000000	33.10	-3.9	54.0	20.9	125.0	347.00	VERTICAL
5146.000000	26.00	-3.3	54.0	28.0	174.0	359.00	VERTICAL
8594.000000	29.00	3.2	54.0	25.0	124.0	241.00	HORIZONTAL
11724.500000	30.30	7.0	54.0	23.7	100.0	351.00	HORIZONTAL
17988.500000	37.20	17.2	54.0	16.8	100.0	111.00	VERTICAL
2310.000000	38.00	33.3	54.0	16.0	141.0	296.00	HORIZONTAL
2390.500000	38.40	33.5	54.0	15.6	152.0	351.00	VERTICAL
2483.500000	38.90	33.7	54.0	15.1	100.0	316.00	VERTICAL
2500.000000	38.40	33.8	54.0	15.6	168.0	203.00	HORIZONTAL

**6.8.5 Conclusion**

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix H.

## 6.9 Conducted Emission at Power Port

### 6.9.1 Test Conditions

Table 46 Test Conditions

Preconditioning:	0.5 hour
Measured at:	Power port
Ambient temperature:	23.5°C
Relative humidity:	55 %
Test Configurations:	TM1 at channel No. 40

### 6.9.2 Test Specifications and Limits

#### 6.9.2.1 Specification

CFR 47 (FCC) part 15.207 and DA 00-705

#### 6.9.2.2 Supporting Standards

Table 47 Supporting Standards:

ANSI C63.4: 2003	Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
------------------	--

#### 6.9.2.3 Limits

Compliance with part15.207, conducted emission must meet the requirement of following table.

Table 48 Limits

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

Note: \* Decreases with the logarithm of the frequency.

### 6.9.3 Test Method and Setup

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4: 2003.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth HUAWEI U8800H/U8800H/HUAWEI U8800/U8800 was communicated with the BTS simulator through Air interface, the BTS simulator controls the Mobile Phone to transmitter the maximum power which defined in specification of product. The Mobile Phone operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

### Test Set-up

The Mobile Phone was setup in the screened chamber and operated under nominal conditions.




Figure 9. Test Set-up

### 6.9.4 Measurement Results

Table 49 MEASUREMENT RESULT:QP DECTER

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.180000	49.80	10.1	64	14.2	QP	N	FLO
0.466000	42.20	10.1	57	14.8	QP	N	FLO
2.086000	32.60	10.1	56	23.4	QP	N	FLO
2.560000	31.00	10.1	56	25.0	QP	N	FLO
5.818000	26.50	10.2	60	33.5	QP	N	FLO
21.060000	24.20	10.4	60	35.8	QP	L1	FLO

Table 50 MEASUREMENT RESULT:AV DECTER

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.228000	24.70	10.0	52	27.3	AV	N	FLO
0.392000	27.80	10.0	48	20.2	AV	N	FLO
1.456000	20.40	10.1	46	25.6	AV	N	FLO
3.938000	24.60	10.2	46	21.4	AV	N	FLO
5.632000	16.50	10.2	50	33.5	AV	N	FLO
21.004000	12.60	10.4	50	37.4	AV	L1	FLO

### 6.9.5 Conclusion

The equipment **PASSED** the requirement of this clause.  
 For the measurement results refer to appendix I.



## 7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Table 51 System Measurement Uncertainty

Items		Extended Uncertainty
20dB bandwidth measurement	Magnitude (%)	U=0.2%; k=2
Carrier frequency separation measurement	Magnitude (%)	U=0.2%; k=2
Time of occupancy	Magnitude (%)	U=0.2%; k=2
Peak output power	Power(dBm)	U=0.39dB; k=2
Band edge compliance measurement	Disturbance Power(dBm)	U=2.0dB; k=2
Conducted RF spurious	Disturbance Power(dBm)	U=2.0dB; k=2
Radiated spurious emission & Radiated restricted band measurement	Field strength (dB $\mu$ V/m)	U=4.1dB; k=2
Conducted emission test for power port	Disturbance Voltage(dB $\mu$ V)	U=3.4dB; k=2



## 8 Appendices List

Appendix A	Measurement Results 20dB bandwidth measurement	4 pages
Appendix B	Measurement Results Carrier frequency separation measurement	2 pages
Appendix C	Measurement Results Number of hopping channel	2 pages
Appendix D	Measurement Results Time of occupancy	3 pages
Appendix E	Measurement Results Peak output power	4 pages
Appendix F	Measurement Results Band edge compliance measurement	5 pages
Appendix G	Measurement Results Conducted RF spurious	10 pages
Appendix H	Measurement Results Radiated spurious emission	12 pages
Appendix I	Measurement Results Conducted emission test for power port	2 pages
Appendix J	Photos of Test Setup	3 pages

----- End of Report -----