



# EMC Test Report

**Product Name: HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; HUAWEI Ascend G 300; Ascend G 300**

**Model Number: HUAWEI U8815, U8815**

**Report No: SYBH(Z-EMC)031012012-2**

**FCC ID: QISU8815**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

---

## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



## TABLE OF CONTENT

1	General Information .....	5
1.1	EUT Description .....	5
1.2	Test Site Information .....	7
1.3	Applied Standards .....	7
2	Summary of Results.....	8
3	System Configuration during EMC Test.....	9
3.1	Test Mode .....	9
3.2	Configurations of Test System.....	9
3.3	Cables Used during Test.....	12
3.4	Associated Equipment Used during Test.....	12
4	Electromagnetic Interference (EMI).....	13
4.1	Radiated Disturbance 30MHz to 18GHz .....	13
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	15
5	Main Test Instruments.....	16
6	System Measurement Uncertainty .....	16
7	Graph and Data of Test.....	17
7.1	Radiated Disturbance.....	17
7.2	Conducted Disturbance.....	19

# 1 General Information

## 1.1 EUT Description

EUT Description	
Product Name	HSDPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; HUAWEI Ascend G 300; Ascend G 300
Model Number	HUAWEI U8815,U8815
Serials Number	F8L01A11C1900286
Working Voltage	120V/60Hz
TX Frequency	GSM850:824MHz to 849MHz; PCS1900:1850MHz to1910MHz WIFI/Bluetooth: 2400MHz to 2483.5MHz
RX Frequency	GSM850:869MHz to 894MHz; PCS1900:1930MHz to1990MHz WIFI/Bluetooth: 2400MHz to 2483.5MHz GPS: 1575.42MHz
HW Version	HD1U8815M
SW Version	U8815V100R001C00B867
EUT Accessory	
Data cable	Data Cable USB A Male to Micro Usb, Black
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100U1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\overline{=}$ 1.0A Rated Power: 5W SN: HKAB82691401 SN:TPABA2691429
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100A1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\overline{=}$ 1.0A Rated Power:5W SN: HKBBA2395738 SN: TPABB2651395
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100E1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\overline{=}$ 1.0A Rated Power: 5W SN: HKBBA1464916 SN: TPABB0564720
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Model: HW-050100B1W Input voltage: ~100-240V 50/60Hz, 0.2A Output voltage: 5.0V $\overline{=}$ 1.0A Rated Power:5W SN: HKBBA1861970 SN: TPABB1909584
Rechargeable Li-ion	Manufacturer: Huawei Technologies Co., Ltd.

	Battery Model: HB5N1 Rated capacity: 1350mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V S/N: GAGBB07XC4566848 S/N: BAABC12C98021583
Rechargeable Li-ion	Manufacturer: Huawei Technologies Co., Ltd. Battery Model: HB5N1H Rated capacity: 1500mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V S/N: WLCB916613600897 S/N: UPDBC14X97502821

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.2 Test Site Information

Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Bantian Longgang District Shenzhen, P.R. China

## 1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2010, Subpart B

## 2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode1~ Mode2 Mode5 Mode7~ Mode8	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

### 3 System Configuration during EMC Test


#### 3.1 Test Mode

Huawei has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was in this test report and defined as:


Test Mode	
Mode 1:	adapter+earphone+Camera On +Idle
Mode 2:	adapter+earphone+MP3 +Idle
Mode 3:	adapter+earphone+Traffic
Mode 4:	adapter+Traffic
Mode 5:	USB Copy(EUT with PC)+earphone +Idle
Mode 6:	Traffic
Mode 7:	Camera On+earphone+Idle
Mode 8:	earphone+MP3+Idle

Remark: When the EUT have multiple adapters, need separate test with multiple adapters . All test modes are performed, only the worst cases are recorded in this report.


#### 3.2 Configurations of Test System




Connection Diagram (Mode 4)




Connection Diagram (Mode 5)



Connection Diagram (Mode 6)



Connection Diagram (Mode 7-Mode 8)



### 3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	shielded
Earphone	1	<3m	Unshielded

### 3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date
Radio Communication Tester	CMU200	R&S	3607033573	2011.12.17
Notebook	T61	IBM	3108052508	N/A

## 4 Electromagnetic Interference (EMI)

### 4.1 Radiated Disturbance 30MHz to 18GHz

#### Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4. The test distance was 3m. The set-up and test methods were according to ANSI C63.4.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

#### Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)

## Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.  
The test data see section 7.1 of this report.

Test Limits				
Frequency of Emission (MHz)	Radiated Limit			
	Unit( $\mu$ V/m)		Unit(dB $\mu$ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

Test environment condition:

Performed Item	Item	Required	Actual
Radiated Emission	Ambient temperature	15°C~35°C	22.5°C
	Relative humidity	25%~75%	50.5%
	Atmospheric pressure	86 kPa~106kPa	101kPa

## 4.2 Conducted Disturbance 0.15 MHz to 30MHz

### Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4. Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector. EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.  
Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;  
The EUT was setup in the screened chamber and operated under nominal conditions.

### Test Setup




Figure 3. Test Set-up of conducted disturbance

### Test Results

The EUT has met requirements for Conducted disturbance of power lines.  
The test data see section 7.2 of this report.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66-56dB $\mu$ V	56-46 dB $\mu$ V
0.5MHz-5MHz	56dB $\mu$ V	46 dB $\mu$ V
5MHz~30MHz	60dB $\mu$ V	50 dB $\mu$ V

Test environment condition:

Performed Item	Item	Required	Actual
Conducted Disturbance	Ambient temperature	15°C~35°C	22.5°C
	Relative humidity	25%~75%	50.5%
	Atmospheric pressure	86 kPa~106kPa	101kPa

## 5 Main Test Instruments

Main Test Equipments					
Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE/CE	EMI Test receiver	ESU26	R&S	May.30, 2011	12
	Broadband Antenna	VULB 9163	SCHWARZBECK	May.16,2011	12
	Horn Antenna	HF906	R&S	May.16,2011	12
	Artificial Mains Network	ENV216	R&S	May.30, 2011	12
Software Information					
Test Item	Software Name	Manufacturer		Version	
RE/CE	ES-K1	R&S		1.7.1	

## 6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz,)	Field strength (dB $\mu$ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB $\mu$ V/m)	U=4.1dB; k=2
CE	Disturbance Voltage (dB $\mu$ V)	U=3.4dB; k=2

## 7 Graph and Data of Test

Only the worst test result was shown in this report.

### 7.1 Radiated Disturbance


#### 30MHz~1GHz



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
31.980000	21.00	14.7	40.0	19.0	100.0	89.00	VERTICAL
52.500000	13.70	14.8	40.0	26.3	103.0	175.00	VERTICAL
123.600000	9.10	11.0	43.5	34.4	131.0	153.00	VERTICAL
148.260000	9.90	9.8	43.5	33.6	100.0	233.00	VERTICAL
757.860000	24.00	23.4	46.0	22.0	200.0	321.00	HORIZONTAL
836.760000	24.60	24.0	46.0	21.4	200.0	316.00	HORIZONTAL

1GHz~18GHz



MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
3324.000000	35.70	-6.9	74.0	38.3	126.0	178.00	VERTICAL
9060.500000	41.90	7.1	74.0	32.1	106.0	315.00	HORIZONTAL
14537.500000	48.70	14.5	74.0	25.3	100.0	318.00	HORIZONTAL

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transducer dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
3455.000000	23.70	-6.2	54.0	30.3	100.0	84.00	VERTICAL
9937.000000	30.90	8.0	54.0	23.1	100.0	304.00	HORIZONTAL
14361.500000	35.50	14.7	54.0	18.5	119.0	221.00	HORIZONTAL

## 7.2 Conducted Disturbance

### AC Port Test Data



#### MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transducer dB	Limit dBµV	Margin dB	Line	PE
0.204000	44.50	10.1	63	18.5	L1	FLO
0.210000	46.20	10.0	63	16.8	N	FLO
0.282000	44.00	10.0	61	17.0	L1	FLO
0.422000	40.50	10.0	57	16.5	L1	FLO
0.634000	41.30	10.1	56	14.7	L1	FLO
2.046000	34.00	10.1	56	22.0	L1	FLO

#### MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Transducer dB	Limit dBµV	Margin dB	Line	PE
0.210000	31.80	10.0	53	21.2	L1	FLO
0.278000	30.00	10.0	51	21.0	L1	FLO
0.420000	28.80	10.0	47	18.2	L1	FLO
0.634000	29.20	10.1	46	16.8	L1	FLO
0.844000	28.00	10.1	46	18.0	L1	FLO
1.622000	26.70	10.1	46	19.3	L1	FLO

-----END-----