



Appendix B. SAR Measurement Plots

Table of contents
GSM850 MHz Head
GSM850 MHz Body
GSM1900 MHz Head
GSM1900 MHz Body
WCDMA850 MHz Head
WCDMA850 MHz Body
WCDMA1700 MHz Head
WCDMA1700MHz Body
WCDMA1900 MHz Head
WCDMA1900 MHz Body
WiFi 802.11b Head
WiFi 802.11b Body

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Left Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.926$ mho/m; $\epsilon_r = 41.499$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.234 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.750 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.285 mW/g

SAR(1 g) = 0.226 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.239 mW/g



0 dB = 0.234 mW/g = -12.62 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Left Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.926$ mho/m; $\epsilon_r = 41.499$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.204 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.821 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.238 mW/g

SAR(1 g) = 0.194 mW/g; SAR(10 g) = 0.152 mW/g

Maximum value of SAR (measured) = 0.203 mW/g



0 dB = 0.204 mW/g = -13.81 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Right Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.926$ mho/m; $\epsilon_r = 41.499$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.210 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.150 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.240 mW/g

SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.154 mW/g

Maximum value of SAR (measured) = 0.209 mW/g



0 dB = 0.210 mW/g = -13.56 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Right Hand Tilt 15 degree**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.926$ mho/m; $\epsilon_r = 41.499$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.175 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.439 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.212 mW/g

SAR(1 g) = 0.171 mW/g; SAR(10 g) = 0.134 mW/g

Maximum value of SAR (measured) = 0.180 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.439 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.180 mW/g

SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.092 mW/g

Maximum value of SAR (measured) = 0.154 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Left Hand Touch Check with battery-2#**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.926$ mho/m; $\epsilon_r = 41.499$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.243 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.339 V/m; Power Drift = -0.19 dB


Peak SAR (extrapolated) = 0.293 mW/g

SAR(1 g) = 0.235 mW/g; SAR(10 g) = 0.180 mW/g

Maximum value of SAR (measured) = 0.246 mW/g



0 dB = 0.246 mW/g = -12.18 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 1TS 190CH Towards phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.308 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 17.788 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.358 mW/g

SAR(1 g) = 0.293 mW/g; SAR(10 g) = 0.228 mW/g

Maximum value of SAR (measured) = 0.306 mW/g



0 dB = 0.308 mW/g = -10.24 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.325 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.489 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.380 mW/g

SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.238 mW/g

Maximum value of SAR (measured) = 0.323 mW/g



0 dB = 0.325 mW/g = -9.76 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.726 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.602 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.884 mW/g

SAR(1 g) = 0.705 mW/g; SAR(10 g) = 0.529 mW/g

Maximum value of SAR (measured) = 0.741 mW/g



0 dB = 0.726 mW/g = -2.78 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Left edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.546 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 24.463 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.731 mW/g

SAR(1 g) = 0.539 mW/g; SAR(10 g) = 0.378 mW/g

Maximum value of SAR (measured) = 0.576 mW/g



0 dB = 0.546 mW/g = -5.25 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Right edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.379 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 19.925 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.496 mW/g

SAR(1 g) = 0.365 mW/g; SAR(10 g) = 0.254 mW/g

Maximum value of SAR (measured) = 0.389 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0925 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.716 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.123 mW/g

SAR(1 g) = 0.083 mW/g; SAR(10 g) = 0.054 mW/g

Maximum value of SAR (measured) = 0.0901 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 EGPRS 1TS 190CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.677 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 26.050 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.811 mW/g

SAR(1 g) = 0.650 mW/g; SAR(10 g) = 0.492 mW/g

Maximum value of SAR (measured) = 0.682 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 EGPRS 2TS 190CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.755 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 27.766 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.890 mW/g

SAR(1 g) = 0.704 mW/g; SAR(10 g) = 0.527 mW/g

Maximum value of SAR (measured) = 0.739 mW/g



0 dB = 0.755 mW/g = -2.44 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards Ground 10mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1


Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz
 Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY Configuration:


- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
 Maximum value of SAR (measured) = 0.770 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
 Reference Value = 27.975 V/m; Power Drift = -0.19 dB
 Peak SAR (extrapolated) = 0.908 mW/g
SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.536 mW/g
 Maximum value of SAR (measured) = 0.756 mW/g



0 dB = 0.756 mW/g = -2.43 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 1TS 190CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.274 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 17.056 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.327 mW/g

SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.205 mW/g

Maximum value of SAR (measured) = 0.279 mW/g



0 dB = 0.274 mW/g = -11.24 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.309 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.254 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.370 mW/g

SAR(1 g) = 0.299 mW/g; SAR(10 g) = 0.229 mW/g

Maximum value of SAR (measured) = 0.313 mW/g



0 dB = 0.309 mW/g = -10.21 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.560 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.988 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.678 mW/g

SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.399 mW/g

Maximum value of SAR (measured) = 0.564 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 EGPRS 1TS 190CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.504 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 22.743 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.607 mW/g

SAR(1 g) = 0.484 mW/g; SAR(10 g) = 0.365 mW/g

Maximum value of SAR (measured) = 0.509 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 EGPRS 2TS 190CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.560 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 24.213 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.667 mW/g

SAR(1 g) = 0.527 mW/g; SAR(10 g) = 0.394 mW/g

Maximum value of SAR (measured) = 0.556 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 190CH Towards Ground 15mm with Headset

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.319 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.128 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.387 mW/g

SAR(1 g) = 0.304 mW/g; SAR(10 g) = 0.227 mW/g

Maximum value of SAR (measured) = 0.320 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM850 GPRS 2TS 190CH Towards Ground 15mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 836.6 MHz

Medium parameters used: $f = 837$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 52.904$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.583 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 24.609 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.681 mW/g

SAR(1 g) = 0.539 mW/g; SAR(10 g) = 0.404 mW/g

Maximum value of SAR (measured) = 0.567 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Left Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.108 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.705 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.165 mW/g

SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 0.112 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.705 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.163 mW/g

SAR(1 g) = 0.107 mW/g; SAR(10 g) = 0.069 mW/g

Maximum value of SAR (measured) = 0.116 mW/g



0 dB = 0.108 mW/g = -19.34 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Left Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0885 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.928 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.151 mW/g

SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.052 mW/g

Maximum value of SAR (measured) = 0.106 mW/g



0 dB = 0.0885 mW/g = -21.07 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Right Hand Touch Check y løj 'lçwgt {/4%**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.173 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.346 V/m; Power Drift = 0.16 dB


Peak SAR (extrapolated) = 0.291 mW/g

SAR(1 g) = 0.189 mW/g; SAR(10 g) = 0.116 mW/g

Maximum value of SAR (measured) = 0.206 mW/g



0 dB = 0.206 mW/g = -13.72 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Right Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0676 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.566 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.109 mW/g

SAR(1 g) = 0.064 mW/g; SAR(10 g) = 0.035 mW/g

Maximum value of SAR (measured) = 0.0713 mW/g



0 dB = 0.0676 mW/g = -23.40 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Right Hand Touch Check with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.160 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.763 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.254 mW/g

SAR(1 g) = 0.169 mW/g; SAR(10 g) = 0.105 mW/g

Maximum value of SAR (measured) = 0.181 mW/g



0 dB = 0.160 mW/g = -15.93 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Towards phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.218 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.185 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.329 mW/g

SAR(1 g) = 0.197 mW/g; SAR(10 g) = 0.112 mW/g

Maximum value of SAR (measured) = 0.216 mW/g



0 dB = 0.218 mW/g = -13.23 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 2TS 661CH Towards phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.185 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.786 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.289 mW/g

SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.095 mW/g

Maximum value of SAR (measured) = 0.184 mW/g



0 dB = 0.185 mW/g = -14.64 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.625 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.937 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.339 mW/g

SAR(1 g) = 0.745 mW/g; SAR(10 g) = 0.388 mW/g

Maximum value of SAR (measured) = 0.836 mW/g



0 dB = 0.625 mW/g = -4.08 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Left edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.106 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.479 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.176 mW/g

SAR(1 g) = 0.100 mW/g; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.109 mW/g



0 dB = 0.106 mW/g = -19.53 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Right edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.108 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.469 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.189 mW/g

SAR(1 g) = 0.114 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.124 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.658 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.841 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.103 mW/g

SAR(1 g) = 0.632 mW/g; SAR(10 g) = 0.331 mW/g

Maximum value of SAR (measured) = 0.713 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 EGPRS 1TS 661CH Towards Ground 10mm"**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.760 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.251 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.404 mW/g

SAR(1 g) = 0.802 mW/g; SAR(10 g) = 0.423 mW/g

Maximum value of SAR (measured) = 0.906 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 EGPRS 2TS 661CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.679 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.420 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.304 mW/g

SAR(1 g) = 0.725 mW/g; SAR(10 g) = 0.377 mW/g

Maximum value of SAR (measured) = 0.819 mW/g



0 dB = 0.679 mW/g = -3.36 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 EGPRS 1TS 661CH Towards Ground 10mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.648 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.058 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.353 mW/g

SAR(1 g) = 0.780 mW/g; SAR(10 g) = 0.414 mW/g

Maximum value of SAR (measured) = 0.876 mW/g



0 dB = 0.648 mW/g = -3.76 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.129 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.502 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.205 mW/g

SAR(1 g) = 0.129 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.139 mW/g



0 dB = 0.129 mW/g = -17.81 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 2TS 661CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.110 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.221 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.176 mW/g

SAR(1 g) = 0.109 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.118 mW/g



0 dB = 0.110 mW/g = -19.17 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 GPRS 1TS 661CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.375 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.998 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.682 mW/g

SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.223 mW/g

Maximum value of SAR (measured) = 0.443 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 EGPRS 1TS 661CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.439 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.628 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.724 mW/g

SAR(1 g) = 0.437 mW/g; SAR(10 g) = 0.246 mW/g

Maximum value of SAR (measured) = 0.480 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 EGPRS 2TS 661CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 2TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.394 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.969 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.659 mW/g

SAR(1 g) = 0.386 mW/g; SAR(10 g) = 0.215 mW/g

Maximum value of SAR (measured) = 0.430 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Towards Ground 15mm with Headset

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.449 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.087 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.740 mW/g

SAR(1 g) = 0.440 mW/g; SAR(10 g) = 0.247 mW/g

Maximum value of SAR (measured) = 0.486 mW/g



0 dB = 0.449 mW/g = -6.95 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z GSM1900 661CH Towards Ground 15mm with Headset with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-GSM/GPRS/EDGE 1TS; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.411 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.407 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.757 mW/g

SAR(1 g) = 0.457 mW/g; SAR(10 g) = 0.258 mW/g

Maximum value of SAR (measured) = 0.505 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Left Hand Touch Cheek**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.47$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.164 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 4.860 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.202 mW/g


SAR(1 g) = 0.160 mW/g; SAR(10 g) = 0.121 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.169 mW/g



0 dB = 0.169 mW/g = -15.44 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Left Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.47$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.136 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.436 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.161 mW/g

SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.101 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)



0 dB = 0.136 mW/g = -17.34 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Right Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.47$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.157 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 3.808 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.178 mW/g

SAR(1 g) = 0.146 mW/g; SAR(10 g) = 0.112 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.154 mW/g



0 dB = 0.157 mW/g = -16.10 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Right Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.47$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.120 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 8.094 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.147 mW/g

SAR(1 g) = 0.120 mW/g; SAR(10 g) = 0.094 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.125 mW/g



0 dB = 0.120 mW/g = -18.40 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Left Hand Touch Check with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.47$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.46, 9.46, 9.46); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.163 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 5.074 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.198 mW/g

SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.118 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.165 mW/g



0 dB = 0.163 mW/g = -15.76 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.249 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 16.185 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.296 mW/g

SAR(1 g) = 0.239 mW/g; SAR(10 g) = 0.183 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.250 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Ground 10mm**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.564 mW/g



Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 23.882 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.697 mW/g

SAR(1 g) = 0.546 mW/g; SAR(10 g) = 0.405 mW/g[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.576 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Left edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.455 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 20.726 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.596 mW/g

SAR(1 g) = 0.434 mW/g; SAR(10 g) = 0.301 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.463 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Right edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.299 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 16.881 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.390 mW/g

SAR(1 g) = 0.282 mW/g; SAR(10 g) = 0.195 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.300 mW/g



0 dB = 0.299 mW/g = -10.48 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0677 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 3.466 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.096 mW/g

SAR(1 g) = 0.066 mW/g; SAR(10 g) = 0.043 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.0706 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Ground 10mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.564 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 23.882 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.697 mW/g

SAR(1 g) = 0.542 mW/g; SAR(10 g) = 0.403 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.576 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.239 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 15.836 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.291 mW/g

SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.177 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.245 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.414 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 20.314 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.511 mW/g

SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.298 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.423 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Ground 15mm with Headset

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.306 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 18.254 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.388 mW/g

SAR(1 g) = 0.365 mW/g; SAR(10 g) = 0.216 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.372 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA850 4182CH Towards Ground 15mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 836.4 MHz

Medium parameters used (interpolated): $f = 836.4$ MHz; $\sigma = 0.977$ mho/m; $\epsilon_r = 52.758$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(9.64, 9.64, 9.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.416 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 20.607 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.511 mW/g

SAR(1 g) = 0.400 mW/g; SAR(10 g) = 0.297 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.422 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Left Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ mho/m; $\epsilon_r = 40.57$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.64, 8.64, 8.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.114 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.489 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.173 mW/g

SAR(1 g) = 0.106 mW/g; SAR(10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.115 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.489 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.184 mW/g

SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 0.111 mW/g



0 dB = 0.114 mW/g = -18.83 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Left Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ mho/m; $\epsilon_r = 40.57$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.64, 8.64, 8.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.130 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.881 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.211 mW/g

SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.143 mW/g



0 dB = 0.130 mW/g = -17.73 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Right Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ mho/m; $\epsilon_r = 40.57$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.64, 8.64, 8.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.259 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.897 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.437 mW/g

SAR(1 g) = 0.260 mW/g; SAR(10 g) = 0.157 mW/g

Maximum value of SAR (measured) = 0.285 mW/g



0 dB = 0.259 mW/g = -11.74 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Right Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ mho/m; $\epsilon_r = 40.57$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.64, 8.64, 8.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.210 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.653 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.328 mW/g

SAR(1 g) = 0.196 mW/g; SAR(10 g) = 0.112 mW/g

Maximum value of SAR (measured) = 0.216 mW/g



0 dB = 0.210 mW/g = -13.56 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Right Hand Touch Check'y kj 'dcwgt{/4%**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.386$ mho/m; $\epsilon_r = 40.57$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.64, 8.64, 8.64); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.295 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.427 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.496 mW/g

SAR(1 g) = 0.282 mW/g; SAR(10 g) = 0.167 mW/g

Maximum value of SAR (measured) = 0.306 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.232 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.684 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.351 mW/g

SAR(1 g) = 0.221 mW/g; SAR(10 g) = 0.128 mW/g

Maximum value of SAR (measured) = 0.247 mW/g



0 dB = 0.232 mW/g = -12.69 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1513CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1752.6 MHz

Medium parameters used: $f = 1753$ MHz; $\sigma = 1.498$ mho/m; $\epsilon_r = 52.898$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.969 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.746 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.458 mW/g

SAR(1 g) = 0.853 mW/g; SAR(10 g) = 0.454 mW/g

Maximum value of SAR (measured) = 0.975 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.939 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.607 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.421 mW/g

SAR(1 g) = 0.831 mW/g; SAR(10 g) = 0.442 mW/g

Maximum value of SAR (measured) = 0.950 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1312CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.459$ mho/m; $\epsilon_r = 53.039$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.04 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 11.962 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.522 mW/g

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.492 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.05 mW/g



0 dB = 1.04 mW/g = 0.33 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Left edge 10mm**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.165 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.715 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.257 mW/g

SAR(1 g) = 0.146 mW/g; SAR(10 g) = 0.080 mW/g

Maximum value of SAR (measured) = 0.162 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.715 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.148 mW/g

SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.056 mW/g

Maximum value of SAR (measured) = 0.103 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Right edge 10mm**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.103 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.723 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.157 mW/g

SAR(1 g) = 0.097 mW/g; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.106 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.723 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.132 mW/g

SAR(1 g) = 0.086 mW/g; SAR(10 g) = 0.055 mW/g

Maximum value of SAR (measured) = 0.0923 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.798 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.467 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.292 mW/g

SAR(1 g) = 0.772 mW/g; SAR(10 g) = 0.413 mW/g

Maximum value of SAR (measured) = 0.878 mW/g



0 dB = 0.798 mW/g = -1.96 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1312CH Towards Ground 10mm with battery/4%**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.459$ mho/m; $\epsilon_r = 53.039$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.01 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 10.953 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.625 mW/g


SAR(1 g) = 0.944 mW/g; SAR(10 g) = 0.501 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.06 mW/g



0 dB = 1.06 mW/g = 0.51 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1312CH Towards Ground 10mm with battery-2#-hotspot closed

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1712.4 MHz

Medium parameters used (interpolated): $f = 1712.4$ MHz; $\sigma = 1.459$ mho/m; $\epsilon_r = 53.039$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.31 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 12.532 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.163 mW/g

SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.678 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.43 mW/g



0 dB = 1.31 mW/g = 2.33 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm


Maximum value of SAR (measured) = 0.186 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.401 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.263 mW/g

SAR(1 g) = 0.171 mW/g; SAR(10 g) = 0.106 mW/g



0 dB = 0.186 mW/g = -14.60 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.658 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.250 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.991 mW/g

SAR(1 g) = 0.618 mW/g; SAR(10 g) = 0.357 mW/g

Maximum value of SAR (measured) = 0.690 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards Ground 15mm with Headset

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.703 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.189 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.045 mW/g

SAR(1 g) = 0.655 mW/g; SAR(10 g) = 0.378 mW/g

Maximum value of SAR (measured) = 0.718 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1700 1413CH Towards Ground 15mm with Headset with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1732.6 MHz

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.473$ mho/m; $\epsilon_r = 52.935$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.39, 8.39, 8.39); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.683 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.939 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.071 mW/g

SAR(1 g) = 0.669 mW/g; SAR(10 g) = 0.384 mW/g

Maximum value of SAR (measured) = 0.742 mW/g



0 dB = 0.683 mW/g = -3.32 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Left Hand Touch Check**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.202 mW/g

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.049 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.329 mW/g

SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.115 mW/g

Maximum value of SAR (measured) = 0.225 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.049 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.310 mW/g

SAR(1 g) = 0.205 mW/g; SAR(10 g) = 0.133 mW/g

Maximum value of SAR (measured) = 0.221 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Left Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.184 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.451 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.318 mW/g

SAR(1 g) = 0.197 mW/g; SAR(10 g) = 0.112 mW/g

Maximum value of SAR (measured) = 0.216 mW/g



0 dB = 0.184 mW/g = -14.69 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Right Hand Touch Check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.350 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.571 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.554 mW/g

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.222 mW/g

Maximum value of SAR (measured) = 0.397 mW/g



0 dB = 0.350 mW/g = -9.11 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Right Hand Tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.147 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.436 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.246 mW/g

SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.080 mW/g

Maximum value of SAR (measured) = 0.159 mW/g



0 dB = 0.147 mW/g = -16.67 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Right Hand Touch Check with battery/4%**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.392$ mho/m; $\epsilon_r = 39.303$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(8.33, 8.33, 8.33); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.328 mW/g



Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.147 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.566 mW/g

SAR(1 g) = 0.367 mW/g; SAR(10 g) = 0.224 mW/g

Maximum value of SAR (measured) = 0.398 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.245 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.333 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.416 mW/g

SAR(1 g) = 0.245 mW/g; SAR(10 g) = 0.138 mW/g

Maximum value of SAR (measured) = 0.270 mW/g



0 dB = 0.245 mW/g = -12.20 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9538CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1907.6 MHz

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.585$ mho/m; $\epsilon_r = 51.529$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm


Maximum value of SAR (measured) = 1.17 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.523 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.970 mW/g

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.547 mW/g



0 dB = 1.17 mW/g = 1.40 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm


Maximum value of SAR (measured) = 1.17 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.994 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.961 mW/g

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.553 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9262CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.524$ mho/m; $\epsilon_r = 51.625$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.14 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 13.237 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.857 mW/g

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.539 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.14 mW/g = 1.15 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Left edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.132 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.962 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.242 mW/g

SAR(1 g) = 0.137 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.152 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.962 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.169 mW/g

SAR(1 g) = 0.096 mW/g; SAR(10 g) = 0.054 mW/g

Maximum value of SAR (measured) = 0.106 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Right edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.129 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.242 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.217 mW/g

SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.075 mW/g

Maximum value of SAR (measured) = 0.139 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.242 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.159 mW/g

SAR(1 g) = 0.095 mW/g; SAR(10 g) = 0.054 mW/g

Maximum value of SAR (measured) = 0.104 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9538CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1907.6 MHz

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.585$ mho/m; $\epsilon_r = 51.529$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.914 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.212 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 1.653 mW/g

SAR(1 g) = 0.933 mW/g; SAR(10 g) = 0.487 mW/g

Maximum value of SAR (measured) = 1.05 mW/g



0 dB = 0.914 mW/g = -0.78 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.984 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.988 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.789 mW/g

SAR(1 g) = 1 mW/g; SAR(10 g) = 0.527 mW/g

Maximum value of SAR (measured) = 1.12 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9262CH Bottom edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.524$ mho/m; $\epsilon_r = 51.625$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.948 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 14.219 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.710 mW/g

SAR(1 g) = 0.973 mW/g; SAR(10 g) = 0.513 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.10 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 10mm'y kj 'lcwgt{/4%

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.982 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 15.873 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 2.064 mW/g

SAR(1 g) = 1.13 mW/g; SAR(10 g) = 0.583 mW/g

Maximum value of SAR (measured) = 1.25 mW/g



0 dB = 1.25 mW/g = 1.94 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 10mm with battery-2#-hotspot closed

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.67 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.625 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.718 mW/g

SAR(1 g) = 1.49 mW/g; SAR(10 g) = 0.774 mW/g

Maximum value of SAR (measured) = 1.66 mW/g



0 dB = 1.67 mW/g = 4.44 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.264 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.821 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.405 mW/g

SAR(1 g) = 0.252 mW/g; SAR(10 g) = 0.154 mW/g

Maximum value of SAR (measured) = 0.271 mW/g



0 dB = 0.264 mW/g = -11.56 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9538CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1907.6 MHz

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.585$ mho/m; $\epsilon_r = 51.529$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.871 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.859 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.385 mW/g

SAR(1 g) = 0.800 mW/g; SAR(10 g) = 0.442 mW/g

Maximum value of SAR (measured) = 0.887 mW/g



0 dB = 0.871 mW/g = -1.20 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.906 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.493 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.394 mW/g

SAR(1 g) = 0.813 mW/g; SAR(10 g) = 0.452 mW/g

Maximum value of SAR (measured) = 0.903 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9262CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1852.4 MHz

Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.524$ mho/m; $\epsilon_r = 51.625$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.892 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm


Reference Value = 12.856 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.367 mW/g

SAR(1 g) = 0.803 mW/g; SAR(10 g) = 0.449 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.898 mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 15mm with Headset

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.953 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 13.412 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.520 mW/g

SAR(1 g) = 0.861 mW/g; SAR(10 g) = 0.473 mW/g

Maximum value of SAR (measured) = 0.960 mW/g



0 dB = 0.953 mW/g = -0.42 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WCDMA1900 9400CH Towards Ground 15mm with Headset with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: HW-UMTS-FDD; Frequency: 1880 MHz

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r = 51.577$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.89, 7.89, 7.89); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.857 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.611 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.376 mW/g

SAR(1 g) = 0.802 mW/g; SAR(10 g) = 0.447 mW/g

Maximum value of SAR (measured) = 0.868 mW/g



0 dB = 0.857 mW/g = -1.34 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Left hand touch check

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.825$ mho/m; $\epsilon_r = 38.421$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.48, 7.48, 7.48); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0215 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.894 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.039 mW/g

SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.00791 mW/g

Maximum value of SAR (measured) = 0.0234 mW/g



0 dB = 0.0215 mW/g = -33.37 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Left hand tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.825$ mho/m; $\epsilon_r = 38.421$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.48, 7.48, 7.48); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0134 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.343 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.037 mW/g

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00561 mW/g

Maximum value of SAR (measured) = 0.0164 mW/g



0 dB = 0.0134 mW/g = -37.45 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Right hand touch cheek

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.825$ mho/m; $\epsilon_r = 38.421$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.48, 7.48, 7.48); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0253 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.958 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.057 mW/g

SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00625 mW/g

Maximum value of SAR (measured) = 0.0200 mW/g



0 dB = 0.0200 mW/g = -33.98 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Right hand tilt 15 degree

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.825$ mho/m; $\epsilon_r = 38.421$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.48, 7.48, 7.48); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.00977 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.456 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.039 mW/g

SAR(1 g) = 0.013 mW/g; SAR(10 g) = 0.00493 mW/g

Maximum value of SAR (measured) = 0.0148 mW/g



0 dB = 0.00977 mW/g = -40.20 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Left hand touch cheek with battery-2#**DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1**

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.825$ mho/m; $\epsilon_r = 38.421$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.48, 7.48, 7.48); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM 2; Type: SAM; Serial: TP-1474
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Head/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0226 mW/g


Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.491 V/m; Power Drift = -0.19 dB


Peak SAR (extrapolated) = 0.045 mW/g

SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.0085 mW/g

Maximum value of SAR (measured) = 0.0249 mW/g



0 dB = 0.0249 mW/g = -32.08 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Phantom 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0264 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.472 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.062 mW/g

SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.012 mW/g

Maximum value of SAR (measured) = 0.0341 mW/g



0 dB = 0.0264 mW/g = -31.56 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Ground 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1


Communication System: WiFi (802.11*); Frequency: 2437 MHz
 Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY Configuration:


- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
 Maximum value of SAR (measured) = 0.0424 mW/g

Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
 Reference Value = 3.349 V/m; Power Drift = -0.01 dB
 Peak SAR (extrapolated) = 0.082 mW/g
SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.021 mW/g
 Maximum value of SAR (measured) = 0.0481 mW/g



0 dB = 0.0481 mW/g = -26.36 dB mW/g



Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Left edge 10mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0378 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.941 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.081 mW/g

SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.017 mW/g

Maximum value of SAR (measured) = 0.0415 mW/g



0 dB = 0.0378 mW/g = -28.44 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Ground 10mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0338 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.860 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.062 mW/g

SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.015 mW/g

Maximum value of SAR (measured) = 0.0374 mW/g



0 dB = 0.0338 mW/g = -29.41 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Phantom 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0165 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.079 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.037 mW/g

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00573 mW/g

Maximum value of SAR (measured) = 0.0172 mW/g



0 dB = 0.0165 mW/g = -35.66 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Ground 15mm

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0223 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 1.749 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.040 mW/g

SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.010 mW/g

Maximum value of SAR (measured) = 0.0252 mW/g



0 dB = 0.0223 mW/g = -33.03 dB mW/g

Test Laboratory: HUAWEI SAR Lab

U8867Z WiFi 11b 6CH Towards Ground 15mm with battery-2#

DUT: U8867Z; Type: HSPA/UMTS/GPRS/GSM/EDGE Mobile Phone with Bluetooth; Serial: SAR1

Communication System: WiFi (802.11*); Frequency: 2437 MHz

Medium parameters used: $f = 2437$ MHz; $\sigma = 2.005$ mho/m; $\epsilon_r = 52.298$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3661; ConvF(7.5, 7.5, 7.5); Calibrated: 1/27/2012;
- Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn679; Calibrated: 12/23/2011
- Phantom: SAM1; Type: SAM; Serial: TP-1475
- DASY52 52.8.1(838); SEMCAD X 14.6.5(6469)

Configuration/Body/Area Scan (8x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.0172 mW/g


Configuration/Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 2.659 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.069 mW/g

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00671 mW/g

Maximum value of SAR (measured) = 0.0204 mW/g



0 dB = 0.0172 mW/g = -35.31 dB mW/g