



FCC&IC SAR Compliance Test Report

Project Name: LTE/HSPA+/HSUPA/HSDPA/MTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth

Model : HUAWEI U9202L-3, U9202L-3

FCC ID : QISU9202L-3

IC : 6369A-U9202L3

Report No. : SYBH(Z-SAR)024092012-2

	APPROVED	CHECKED	PREPARED
BY	<i>Liu Chunlin</i>	<i>Aluicway</i>	<i>Yang Kang</i>
DATE	2012-09-28	2012-09-28	2012-09-28

The test results of this test report relate exclusively to the item(s) tested , The HUAWEI does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of HUAWEI.

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian,
Longgang District, Shenzhen, 518129, P.R.C
Tel: +86 755 28780808 Fax: +86 755 89652518



Table of Contents

1	General Information	4
1.1	Statement of Compliance	4
1.2	RF exposure limits	5
1.3	EUT Description	6
1.3.1	General Description	7
1.3.2	LTE information Summary	8
1.4	Test specification(s)	9
1.5	Testing laboratory	9
1.6	Applicant and Manufacturer	9
1.7	Application details	9
1.8	Ambient Condition	10
2	SAR Measurement System	10
2.1	SAR Measurement Set-up	10
2.2	Test environment	11
2.3	Data Acquisition Electronics description	11
2.4	Probe description	12
2.5	Phantom description	13
2.6	Device holder description	13
2.7	Test Equipment List	14
3	SAR Measurement Procedure	15
3.1	Scanning procedure	15
3.2	Spatial Peak SAR Evaluation	16
3.3	Data Storage and Evaluation	17
4	System Verification Procedure	19
4.1	Tissue Verification	19
4.2	System Check	21
4.3	Validation Procedure	22
5	Measurement Uncertainty Evaluation	23
5.1	Measurement uncertainty evaluation for SAR test	23
5.2	Measurement uncertainty evaluation for system validation	24
6	SAR Test Configuration	25
6.1	GSM Test Configuration	25
6.2	UMTS Test Configuration	25
6.3	LTE Test Configuration	29
6.4	WiFi Test Configuration	31
7	SAR Measurement Results	32
7.1	Conducted power measurements	32
7.1.1	Conducted power measurements GSM850	32
7.1.2	Conducted power measurements GSM1900	33
7.1.1	Conducted power measurements UMTS Band V	33
7.1.2	Conducted power measurements UMTS Band II	34
7.1.3	Conducted power measurements UMTS Band IV	34
7.1.4	Conducted power measurements LTE Band IV	35
7.1.5	Conducted power measurements LTE Band XVII	38
7.2	SAR measurement Result	40
7.2.1	SAR measurement Result of GSM850	40
7.2.1	SAR measurement Result of GSM1900	41
7.2.2	SAR measurement Result of UMTS Band V	42
7.2.3	SAR measurement Result of UMTS Band IV	43
7.2.4	SAR measurement Result of UMTS Band II	44
7.2.5	SAR measurement Result of LTE Band IV	45
7.2.6	SAR measurement Result of LTE Band XVII	47
7.2.1	SAR measurement Result of WiFi	55
7.3	Multiple Transmitter Evaluation	56
7.3.1	Stand-alone SAR	56
7.3.2	Simultaneous Transmission Possibilities	58
7.3.3	SAR Summation Scenario	58
	Appendix A. System Check Plots	59
	Appendix B. SAR Measurement Plots	59
	Appendix C. Calibration Certificate	59
	Appendix D. Photo documentation	59



※ ※ **Modified History** ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Release	2012-09-28	Yang Hang

1 General Information

1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for HUAWEI U9202L-3, U9202L-3 are as below Table 1.

Band	Position	Measured MAX SAR _{1g} (W/kg)	Conducted Power (dBm)	Tune-up Power(dBm)	Extrapolated Result(W/kg)
GSM 850	Head	0.477	30.96	32.70	0.712
	Body Worn(10mm)	0.904	28.86	29.50	1.048
	Hotspot(10mm)	0.904	28.86	29.50	1.048
GSM 1900	Head	0.258	30.62	31.00	0.282
	Body Worn(10mm)	0.700	26.96	27.00	0.706
	Hotspot(10mm)	0.700	26.96	27.00	0.706
UMTS Band V	Head	0.416	23.59	24.00	0.457
	Body Worn(10mm)	0.757	23.59	24.00	0.832
	Hotspot(10mm)	0.757	23.59	24.00	0.832
UMTS Band IV	Head	0.915	22.39	23.50	1.181
	Body Worn(10mm)	0.799	22.45	23.50	1.018
	Hotspot(10mm)	0.799	22.45	23.50	1.018
UMTS Band II	Head	0.790	22.10	22.50	0.866
	Body Worn(10mm)	0.790	22.10	22.50	0.866
	Hotspot(10mm)	0.790	22.10	22.50	0.866
LTE Band IV	Head	0.963	22.73	24.00	1.290
	Body Worn(10mm)	0.969	22.64	24.00	1.325
	Hotspot(10mm)	0.969	22.64	24.00	1.325
LTE Band XVII	Head	0.468	22.11	24.00	0.723
	Body Worn(10mm)	0.666	22.48	24.00	0.945
	Hotspot(10mm)	0.666	22.48	24.00	0.945
WiFi	Head	0.243	17.18	/	/
	Body Worn(10mm)	0.140	17.18	/	/
	Hotspot(10mm)	0.140	17.18	/	/

The Highest Simultaneous SAR is **1.109W/kg**

Table 1: Summary of test result

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits of 1.6 W/Kg as averaged over any 1 g tissue according to the FCC rule §2.1093, the ANSI/IEEE C 95.1:1992, the NCRP Report Number 86 for uncontrolled environment, according to the Health Canada's Safety Code 6 and the Industry Canada Radio Standards Specification RSS-102 for General Population/Uncontrolled exposure, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2003 & IEEE Std 1528a-2005 and FCC OET Bulletin 65 Supplement C Edition 01-01.

1.2 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain/Body)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 2: RF exposure limits

The limit applied in this test report is shown in **bold** letters

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

1.3 EUT Description

Device Information:			
DUT Name:	LTE/HSPA+/HSUPA/HSDPA/UMTS/GSM/GPRS/EDGE Mobile Phone with Bluetooth		
Type Identification:	HUAWEI U9202L-3, U9202L-3		
FCC ID :	QISU9202L-3		
IC :	6369A-U9202L3		
S/N No.:	K6H01A9261100062		
Device Type :	portable device		
Exposure Category:	uncontrolled environment / general population		
Hardware Version :	Ver.B		
Software Version :	U9202L-3V100R001C00B116		
Antenna Type :	Internal		
Battery Options :	Huawei Technologies Co., Ltd. Rechargeable Li-ion Battery Model: HB5R1H; Rated capacity: 1930mAh; Nominal Voltage: \approx +3.7V; Charging Voltage: \approx +4.2V.		
Others Accessories	Headset		
Device Operating Configurations:			
Supporting Mode(s)	GSM850/1900,UMTS Band II/IV/V,LTE Band IV/XVII,WiFi (Tested) ; Bluetooth		
Test Modulation	GMSK, QPSK/16QAM		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 - 849	869 - 894
	GSM1900	1850-1910	1930-1990
	UMTS Band II	1850-1910	1930-1990
	UMTS Band IV	1710-1755	2110-2155
	UMTS Band V	824 - 849	869 - 894
	LTE Band IV	1710-1755	2110-2155
	LTE Band XVII	704- 716	734-746
	Bluetooth	2400-2483.5	2400-2483.5
WiFi	2400-2483.5	2400-2483.5	
GPRS Multislot Class (10)	Max Number of Timeslots in Uplink:	2	
	Max Number of Timeslots in Downlink:	4	
	Max Total Timeslot:	5	
EGPRS Multislot Class (10)	Max Number of Timeslots in Uplink:	2	
	Max Number of Timeslots in Downlink:	4	
	Max Total Timeslot:	5	
Power Class :	1, tested with power level 0 (GSM1900)		
	4, tested with power level 5 (GSM850)		
	3, tested with power control "all 1"(UMTS Band II)		
	3, tested with power control "all 1"(UMTS Band IV)		
	3, tested with power control "all 1"(UMTS Band V)		
	3, tested with power control all Max.(LTE Band IV)		
3, tested with power control all Max.(LTE Band XVII)			
Test Channels(low-mid-high):	128-190-251 (GSM850)		
	512-661-810 (GSM1900)		
	19957-20175-20393(LTE Band IV BW=1.4MHz)		
	19965-20175-20385(LTE Band IV BW=3MHz)		

	19975-20175-20375(LTE Band IV BW=5MHz)
	20000-20175-20350(LTE Band IV BW=10MHz)
	20025-20175-20325(LTE Band IV BW=15MHz)
	120050-20175-20300(LTE Band IV BW=20MHz)
	23755-23790-23825(LTE Band XVII BW=5MHz)
	23780-23790-23800(LTE Band XVII BW=10MHz)
	1-6-11(WiFi)

Table 3: Device information and operating configuration

1.3.1 General Description

HUAWEI U9202L-3, U9202L-3 is subscriber equipment in the LTE/UMTS/GSM system. The LTE frequency band is Band IV and Band XVII. The HSPA+/HSUPA/HSDPA/UMTS frequency band is Band I, Band II, Band IV and Band V. only Band II, Band IV and Band V can be used in this report. The GSM/GPRS/EDGE frequency band includes GSM850 and DCS1800 and PCS1900, but only GSM850MHz and PCS1900MHz bands test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/UMTS/GSM protocol processing, voice, video, MMS service, GPS, AGPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and USIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

1.3.2 LTE information Summary

Items	Device Operating Configurations for LTE	Remark
1	Frequency Range of each LTE transmission band	Band IV: 1710 MHz to 1755 MHz Band XVII:704 MHz to 716 MHz
2	Channel Bandwidths	Band IV: 1.4MHz, 3MHz , 5MHz, 10MHz, 15MHz, 20MHz Band XVII: 5MHz, 10MHz
4a	UE Category	3
4b	Modulations Supported in UL	QPSK, 16QAM
5	Description of LTE Tx and Ant. Implementation	Refer to page 58 Definition of Antennas
6	Identify the LTE voice/data requirements in each operating mode and exposure condition	Exposure conditions 1) Head&Body SAR is required; 2) Hotspot SAR is required.
7	LTE MPR Permanently implement per 3GPP TS36.101 section 6.2.3~6.2.5?(manufacturer attestation to be provided)	Yes, pls refer to page 29 MPR is permanently built-in by design; A-MPR was disabled.
8	Conducted power table provided for 1RB(Low and high offset),50%RB(centered),100%RB	Refer to the RF Output Power Table
9~10	Non-LTE operating Modes and Band	* Supported band & Exposure conditions 1) Bluetooth 2.4GHz - Exposure Conditions: BT SAR is not required due to its low power and antenna separation distance. 2) WiFi 2.4GHz - Exposure Conditions: Head/Body SAR required * WiFi Hotspot is supported. 3) Supported WWAN bands: GSM850/1900,UMTS Band V/IV/II,LTE Band IV/XVII -Exposure Conditions: Head and Body SAR required; Hotspot SAR required on select modes.
11	Simultaneous Tx Conditions	Refer to page 34, Simultaneous Tx Combination
12	Power Reduction used for SAR Compliance	NO
13	Supporting descriptions for power reduction	NO
14	When appropriate, include a SAR test plan proposal with respect to the above	Not Applicable
15	If applicable, include preliminary SAR test data and/or supporting information in laboratory testing inquiries to address specific issues and concerns or for requesting further test reduction considerations appropriate for the device; for example,simultaneous transmission configurations	Not Applicable

Table 4: LTE information Summary per FCC KDB 941225 D05

1.4 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
IEEE Std 1528-2003	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
IEEE Std 1528a-2005	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Amendment 1: CAD File for Human Head Model (SAM Phantom)
OET Bulletin No. 65, Supplement C Edition 01-01– 2001	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields---Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions
Canada's Safety Code 6	Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz (99-EHD-237)
RSS-102	Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands (Issue 4 of March 2010)
KDB941225 D01	SAR test for 3G devices v02
KDB941225 D03	SAR Test Reduction GSM GPRS EDGE vo1
KDB941225 D05	SAR for LTE Devices v01
KDB248227 D01	SAR Measurement Procedures for 802.11 a,b,g Transmitters
KDB941225 D06	Hot Spot SAR v01
KDB648474 D01	SAR Handsets Multi Xmitter and Ant v01r05
KDB450824 D01	SAR Probe Calibration and System Verification
KDB450824 D02	Dipole SAR Validation Verification v01

1.5 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Zone K3,Huawei Industrial Base, Bantian Industry Area, Longgang District, Shenzhen, Guangdong, China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA Registration number: 2174.01

1.6 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.7 Application details


Start Date of test	2012-09-08
End Date of test	2012-09-18

1.8 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2 SAR Measurement System

2.1 SAR Measurement Set-up



The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows XP.
- DASY5 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System validation dipoles allowing to validate the proper functioning of the system.

2.2 Test environment

The DASY4 measurement system is placed at the head end of a room with dimensions: 5 x 2.5 x 3 m³, the SAM phantom is placed in a distance of 75 cm from the side walls and 1.1m from the rear wall. Above the test system a 1.5 x 1.5 m² array of pyramid absorbers is installed to reduce reflections from the ceiling.

Picture 1 of the photo documentation shows a complete view of the test environment.

The system allows the measurement of SAR values larger than 0.005 mW/g.

2.3 Data Acquisition Electronics description

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.


DAE4

Input Impedance	200MOhm	
The Inputs	symmetrical and floating	
Common mode rejection	above 80 dB	

2.4 Probe description

These probes are specially designed and calibrated for use in liquids with high permittivities. They should not be used in air, since the spherical isotropy in air is poor (± 2 dB). The dosimetric probes have special calibrations in various liquids at different frequencies.

Isotropic E-Field Probe ES3DV3 for Dosimetric Measurements

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Calibration	ISO/IEC 17025 calibration service available.	
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones	

Isotropic E-Field Probe EX3DV4 for Dosimetric Measurements

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Calibration	ISO/IEC 17025 calibration service available.	
Frequency	10 MHz to >6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic range	10 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%	

2.5 Phantom description

SAM Twin Phantom

Shell Thickness	2mm +/- 0.2 mm; The ear region: 6mm	
Filling Volume	Approximately 30 liters	
Dimensions	Length:1000mm; Width:500mm; Height: adjustable feet	
Measurement Areas	Left hand Right hand Flat phantom	
<p>The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.</p>		

ELI4 Phantom

Shell Thickness	2mm +/- 0.2 mm	
Filling Volume	Approximately 30 liters	
Dimensions	Length:1000mm; Width:500mm; Height: adjustable feet	
Measurement Areas	Flat phantom	
<p>The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209-2 and all known tissue simulating liquids.</p>		

2.6 Device holder description

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used.



Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values.

Therefore those devices are normally only tested at the flat part of the SAM.

2.7 Test Equipment List

This table gives a complete overview of the SAR measurement equipment
 Devices used during the test described are marked

	Manufacturer	Device	Type	Serial number	Date of last calibration)*
<input checked="" type="checkbox"/>	SPEAG	Dosimetric E-Field Probe	EX3DV4	3744	2012-07-27
<input checked="" type="checkbox"/>	SPEAG	Dosimetric E-Field Probe	EX3DV4	3736	2012-04-26
<input checked="" type="checkbox"/>	SPEAG	750 MHz Validation Dipole	D750V3	1044	2011-09-16
<input checked="" type="checkbox"/>	SPEAG	835 MHz Validation Dipole	D835V2	4d126	2011-11-07
<input checked="" type="checkbox"/>	SPEAG	1800 MHz Validation Dipole	D1800V2	2d184	2011-03-08
<input checked="" type="checkbox"/>	SPEAG	1900 MHz Validation Dipole	D1900V2	5d143	2011-09-26
<input type="checkbox"/>	SPEAG	2450 MHz Validation Dipole	D2450V2	860	2011-03-08
<input type="checkbox"/>	SPEAG	2600 MHz Validation Dipole	D2600V2	1021	2011-11-22
<input checked="" type="checkbox"/>	SPEAG	Data acquisition electronics	DAE4	852	2011-11-16
<input checked="" type="checkbox"/>	SPEAG	Data acquisition electronics	DAE4	851	2012-03-28
<input checked="" type="checkbox"/>	SPEAG	Software	DASY 5	N/A	N/A
<input type="checkbox"/>	SPEAG	Twin Phantom	SAM1	TP-1475	N/A
<input type="checkbox"/>	SPEAG	Twin Phantom	SAM2	TP-1474	N/A
<input checked="" type="checkbox"/>	SPEAG	Twin Phantom	SAM3	TP-1597	N/A
<input checked="" type="checkbox"/>	SPEAG	Twin Phantom	SAM4	TP-1620	N/A
<input type="checkbox"/>	SPEAG	Flat Phantom	ELI 4.0	TP-1038	N/A
<input type="checkbox"/>	SPEAG	Flat Phantom	ELI 4.0	TP-1111	N/A
<input checked="" type="checkbox"/>	Anritsu	WideBand Radio Communication Tester	MT8820C	6200971028	2012-05-09
<input checked="" type="checkbox"/>	R & S	Universal Radio Communication Tester	CMU 200	111379	2012-06-07
<input checked="" type="checkbox"/>	Agilent)*	Network Analyser	E5071B	MY42404956	2012-02-14
<input checked="" type="checkbox"/>	Agilent	Dielectric Probe Kit	85070E	2484	N/A
<input checked="" type="checkbox"/>	Agilent	Signal Generator	N5181A	MY47420989	2012-02-14
<input checked="" type="checkbox"/>	MINI-CIRCUITS	Amplifier	ZHL-42W	QA0746001	N/A
<input checked="" type="checkbox"/>	Agilent	Power Meter	E4417A	MY45101339	2012-02-14
<input checked="" type="checkbox"/>	Agilent	Power Meter Sensor	E9321A	MY44420359	2012-02-14

Note: All the test equipments are calibrated once a year, except the dipoles, which are calibrated every three years. Moreover, we have self-calibration every year to the dipoles.

1) Per KDB 450824 D02 requirements for dipole calibration, Huawei SAR lab has adopted three years calibration interval. But each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System validation with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

3 SAR Measurement Procedure

3.1 Scanning procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

- The reference and drift measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. +/- 5 %.
- The surface check measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above $\pm 0.1\text{mm}$). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.)
- The area scan measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strength is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension. If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in Appendix B.
- A 7x7x7 zoom scan measures the field in a volume around the 2D peak SAR value acquired in the previous coarse scan. This is a fine 7x7 grid where the robot additionally moves the probe in 7 steps along the z-axis away from the bottom of the Phantom. Grid spacing for the cube measurement is 5 mm in x and y-direction and 5 mm in z-direction. DASY5 is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in Appendix B. Test results relevant for the specified standard (see chapter 1.4.) are shown in table form in chapter 7.2.
- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2mm steps. This measurement shows the continuity of the liquid and can - depending in the field strength – also show the liquid depth. A z-axis scan of the measurement with maximum SAR value is shown in Appendix B.

3.2 Spatial Peak SAR Evaluation

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 7 x 7 x 7 points. The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR - values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

Advanced Extrapolation

DASY5 uses the advanced extrapolation option which is able to compensate boundary effects on E-field probes.

3.3 Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a ₁₀ , a ₁₁ , a ₁₂
	- Conversion factor	ConvF _i
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf/dcp_i$$

with	V _i	= compensated signal of channel i	(i = x, y, z)
	U _i	= input signal of channel i	(i = x, y, z)
	cf	= crest factor of exciting field (DASY parameter)	
	dcp _i	= diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:
$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$

H-field probes:
$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2)/f$$

- with V_i = compensated signal of channel i (i = x, y, z)
 $Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
[mV/(V/m)²] for E-field Probes
 $ConvF$ = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strength of channel i in V/m
 H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\rho \cdot 1000)$$

- with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

- with P_{pwe} = equivalent power density of a plane wave in mW/cm²
 E_{tot} = total electric field strength in V/m
 H_{tot} = total magnetic field strength in A/m

4 System Verification Procedure

4.1 Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The following materials are used for producing the tissue-equivalent materials.

Ingredients (% of weight)	Head Tissue					
Frequency Band (MHz)	750	835	1800	1900	2450	2600
Water	39.2	41.45	52.64	54.9	62.7	55.242
Salt (NaCl)	2.7	1.45	0.36	0.18	0.5	0.306
Sugar	57.0	56.0	0.0	0.0	0.0	0.0
HEC	0.0	1.0	0.0	0.0	0.0	0.0
Bactericide	0.0	0.1	0.0	0.0	0.0	0.0
Cellulose	1.0	0.0	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	47.0	44.92	36.8	44.452
Preventol	0.1	0.0	0.0	0.0	0.0	0.0
Ingredients (% of weight)	Body Tissue					
Frequency Band (MHz)	750	835	1800	1900	2450	2600
Water	50.3	52.4	69.91	71.88	73.2	70.4
Salt (NaCl)	1.6	1.40	0.13	0.39	0.04	0.1
Sugar	47	45.0	0.0	0.0	0.0	0.0
HEC	0.0	1.0	0.0	0.0	0.0	0.0
Bactericide	0.0	0.1	0.0	0.0	0.0	0.0
Cellulose	1.0	0.0	0.0	0.0	0.0	0.0
DGBE	0.0	0.0	29.96	29.44	26.7	29.5
Preventol	0.1	0.0	0.0	0.0	0.0	0.0

Table 5: Tissue Dielectric Properties

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16M Ω + resistivity
 HEC: Hydroxyethyl Cellulose; DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
 Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

Tissue Type	Measure d Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r (+/-5%)	σ (S/m) (+/-5%)	ϵ_r	σ (S/m)		
750H	710	42.15 (40.04~44.26)	0.89 (0.8455~0.9345)	41.46	0.85	21.4°C	2012-09-14
	750	41.94 (39.84~44.03)	0.89 (0.85~0.93)	40.58	0.905		
750B	710	55.2 (52.44~57.96)	0.96 (0.92~1.02)	55.43	0.9476	21.4°C	2012-09-16
	750	55.2 (52.44~57.96)	0.97 (0.92~1.02)	54.99	0.995		
835H	825	41.6 (39.52~43.68)	0.90 (0.86~0.95)	42.06	0.88	21.4°C	2012-09-12
	835	41.5 (39.43~43.58)	0.90 (0.86~0.95)	41.9	0.889		
	850	41.5 (39.43~43.58)	0.92 (0.87~0.97)	41.66	0.892		
835B	825	55.2 (52.44~57.96)	0.97 (0.92~1.02)	52.9	0.9676	21.4°C	2012-09-08

	835	55.2 (52.44~57.96)	0.97 (0.92~1.02)	52.83	0.9714		
	850	55.2 (52.44~57.96)	0.99 (0.94~1.04)	52.73	0.9879		
1800H	1710	40.1 (38.10~42.11)	1.35 (1.28~1.42)	40.38	1.385	21.4°C	2012-09-11
	1730	40.1 (38.10~42.11)	1.36 (1.29~1.43)	40.32	1.407		
	1750	40.1 (38.10~42.11)	1.37 (1.30~1.44)	40.08	1.418		
	1800	40.0 (38.00~42.00)	1.40 (1.33~1.47)	39.81	1.448		
1800H	1710	40.1 (38.10~42.11)	1.35 (1.28~1.42)	40.88	1.362	21.4°C	2012-09-13
	1730	40.1 (38.10~42.11)	1.36 (1.29~1.43)	40.64	1.371		
	1750	40.1 (38.10~42.11)	1.37 (1.30~1.44)	40.62	1.388		
	1800	40.0 (38.00~42.00)	1.40 (1.33~1.47)	40.41	1.436		
1800B	1710	53.5 (50.83~56.18)	1.46 (1.39~1.53)	51.40	1.467	21.4°C	2012-09-12
	1730	53.5 (50.83~56.18)	1.48 (1.41~1.55)	51.35	1.478		
	1750	53.4 (50.73~56.07)	1.49 (1.42~1.56)	51.19	1.496		
	1800	53.3 (50.64~55.97)	1.52 (1.44~1.60)	51.31	1.530		
1800B	1710	53.5 (50.83~56.18)	1.46 (1.39~1.53)	51.93	1.458	21.4°C	2012-09-13
	1730	53.5 (50.83~56.18)	1.48 (1.41~1.55)	51.88	1.473		
	1750	53.4 (50.73~56.07)	1.49 (1.42~1.56)	51.72	1.491		
	1800	53.3 (50.64~55.97)	1.52 (1.44~1.60)	51.84	1.525		
1900H	1850	40.0 (38.00~42.00)	1.40 (1.33~1.47)	41.54	1.398	21.4°C	2012-09-18
	1880	40.0 (38.00~42.00)	1.40 (1.33~1.47)	41.42	1.43		
	1910	40.0 (38.00~42.00)	1.40 (1.33~1.47)	41.37	1.457		
	1900	40.0 (38.00~42.00)	1.40 (1.33~1.47)	41.46	1.454		
1900B	1850	53.3 (50.64~55.97)	1.52 (1.44~1.60)	53.38	1.471	21.4°C	2012-09-17
	1880	53.3 (50.64~55.97)	1.52 (1.44~1.60)	53.27	1.498		
	1910	53.3 (50.64~55.97)	1.52 (1.44~1.60)	53.29	1.535		
	1900	53.3 (50.64~55.97)	1.52 (1.44~1.60)	53.31	1.530		
ϵ_r = Relative permittivity, σ = Conductivity							

Table 6: Measured Tissue Parameter

Note:

- 1) The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.
- 2) KDB 450824 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.
- 3) The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.

4.2 System Check

The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system validation is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows validation results for all frequency bands and tissue liquids used during the tests (Graphic Plot(s) see Appendix A).


System Check	Target SAR (1W) (+/-10%)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (mW/g)	10-g (mW/g)	1-g (mW/g)	10-g (mW/g)		
D750V2 Head	8.40 (7.56~9.24)	5.50 (4.95~6.05)	8.36	5.52	21.4°C	2012-09-14
D835V2 Head	9.40 (8.46~10.34)	6.16 (5.54~6.78)	9.76	6.40	21.4°C	2012-09-12
D1800V2 Head	39.1 (35.19~43.01)	20.3 (18.27~22.33)	37.48	19.08	21.4°C	2012-09-11
D1800V2 Head	39.1 (35.19~43.01)	20.3 (18.27~22.33)	37.64	19.20	21.4°C	2012-09-13
D1900V2 Head	39.8 (35.82~43.78)	20.8 (18.72~22.88)	39.80	20.32	21.4°C	2012-09-18
D750V2 Body	8.80 (7.92~9.68)	5.84 (5.26~6.42)	8.64	5.80	21.4°C	2012-09-08
D835V2 Body	9.54 (8.59~10.49)	6.29 (5.66~6.92)	10.00	6.56	21.4°C	2012-09-18
D1800V2 Body	38.8 (34.92~42.68)	20.4 (18.36~22.44)	37.00	18.96	21.4°C	2012-09-12
D1800V2 Body	38.8 (34.92~42.68)	20.4 (18.36~22.44)	36.88	18.92	21.4°C	2012-09-13
D1900V2 Body	40.5 (36.45~44.55)	21.1 (18.99~23.21)	40.00	20.76	21.4°C	2012-09-17

Table 7: System Check Results

4.3 Validation Procedure

The validation is performed by using a validation dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 250 mW. To adjust this power a power meter is used. The power sensor is connected to the cable before the validation to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the validation to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

Validation results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.



5 Measurement Uncertainty Evaluation

5.1 Measurement uncertainty evaluation for SAR test

The overall combined measurement uncertainty of the measurement system is $\pm 10.9\%$ ($K=1$).

The expanded uncertainty ($k=2$) is assessed to be $\pm 21.9\%$

This measurement uncertainty budget is suggested by IEEE P1528 and determined by Schmid & Partner Engineering AG. The breakdown of the individual uncertainties is as follows:

Error Sources	Uncertainty Value	Probability Distribution	Divisor	c_i 1g	c_i 10g	Standard Uncertainty 1g	Standard Uncertainty 10g	v_i^2 or v_{eff}
Measurement System								
Probe calibration	$\pm 6.0\%$	Normal	1	1	1	$\pm 6.0\%$	$\pm 6.0\%$	∞
Axial isotropy	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 1.9\%$	$\pm 1.9\%$	∞
Hemispherical isotropy	$\pm 9.6\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 3.9\%$	$\pm 3.9\%$	∞
Spatial resolution	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
Boundary effects	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Probe linearity	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	∞
System detection limits	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Readout electronics	$\pm 0.3\%$	Normal	1	1	1	$\pm 0.3\%$	$\pm 0.3\%$	∞
Response time	$\pm 0.8\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.5\%$	$\pm 0.5\%$	∞
Integration time	$\pm 2.6\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.5\%$	$\pm 1.5\%$	∞
RF ambient conditions	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
Probe positioner	$\pm 0.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.2\%$	$\pm 0.2\%$	∞
Probe positioning	$\pm 2.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
Max. SAR evaluation	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Test Sample Related								
Device positioning	$\pm 2.9\%$	Normal	1	1	1	$\pm 2.9\%$	$\pm 2.9\%$	145
Device holder uncertainty	$\pm 3.6\%$	Normal	1	1	1	$\pm 3.6\%$	$\pm 3.6\%$	5
Power drift	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.9\%$	$\pm 2.9\%$	∞
Phantom and Set-up								
Phantom uncertainty	$\pm 4.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.3\%$	$\pm 2.3\%$	∞
Liquid conductivity (target)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.64	0.43	$\pm 1.8\%$	$\pm 1.2\%$	∞
Liquid conductivity (meas.)	$\pm 2.5\%$	Normal	1	0.64	0.43	$\pm 1.6\%$	$\pm 1.1\%$	∞
Liquid permittivity (target)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	∞
Liquid permittivity (meas.)	$\pm 2.5\%$	Normal	1	0.6	0.49	$\pm 1.5\%$	$\pm 1.2\%$	∞
Combined Uncertainty	$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					$\pm 10.9\%$	$\pm 10.7\%$	387
Expanded Std. Uncertainty	$u_e = 2u_c$	Normal	K=2			$\pm 21.9\%$	$\pm 21.4\%$	

Table 8: Measurement uncertainties

5.2 Measurement uncertainty evaluation for system validation

The overall combined measurement uncertainty of the measurement system is $\pm 9.5\%$ ($K=1$).

The expanded uncertainty ($k=2$) is assessed to be $\pm 18.9\%$

This measurement uncertainty budget is suggested by IEEE P1528 and determined by Schmid & Partner Engineering AG. The breakdown of the individual uncertainties is as follows:

Error Sources	Uncertainty Value	Probability Distribution	Divisor	c_i 1g	c_i 10g	Standard Uncertainty 1g	Standard Uncertainty 10g	v_i^2 or v_{eff}
Measurement System								
Probe calibration	$\pm 6.0\%$	Normal	1	1	1	$\pm 6.0\%$	$\pm 6.0\%$	∞
Axial isotropy	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	∞
Hemispherical isotropy	$\pm 9.6\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 0.0\%$	$\pm 0.0\%$	∞
Boundary effects	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Probe linearity	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	∞
System detection limits	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Readout electronics	$\pm 0.3\%$	Normal	1	1	1	$\pm 0.3\%$	$\pm 0.3\%$	∞
Response time	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
Integration time	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
RF ambient conditions	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Probe positioner	$\pm 0.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.2\%$	$\pm 0.2\%$	∞
Probe positioning	$\pm 2.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
Max. SAR evaluation	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
Dipole								
Deviation of experimental dipole	$\pm 5.5\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 3.2\%$	$\pm 3.2\%$	∞
Dipole axis to liquid distance	$\pm 2.0\%$	Rectangular	1	1	1	$\pm 1.2\%$	$\pm 1.2\%$	∞
Power drift	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	∞
Phantom and Set-up								
Phantom uncertainty	$\pm 4.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.3\%$	$\pm 2.3\%$	∞
Liquid conductivity (target)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.64	0.43	$\pm 1.8\%$	$\pm 1.2\%$	∞
Liquid conductivity (meas.)	$\pm 2.5\%$	Normal	1	0.64	0.43	$\pm 1.6\%$	$\pm 1.1\%$	∞
Liquid permittivity (target)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	∞
Liquid permittivity (meas.)	$\pm 2.5\%$	Normal	1	0.6	0.49	$\pm 1.5\%$	$\pm 1.2\%$	∞
Combined Uncertainty	$u_c = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$					$\pm 9.5\%$	$\pm 9.2\%$	
Expanded Std. Uncertainty	$u_e = 2u_c$	Normal	K=2			$\pm 18.9\%$	$\pm 18.4\%$	

Table 9: Measurement uncertainties

6 SAR Test Configuration

6.1 GSM Test Configuration

SAR tests for GSM1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to “0” in SAR of GSM1900. The tests in the band of GSM1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 10 for this EUT, it has at most 2 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5. The EGPRS class is 10 for this EUT, it has at most 2 timeslots in uplink, and at most 4 timeslots in downlink, the maximum total timeslot is 5.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot.

The allowed power reduction in the multi-slot configuration is as following:

Number of timeslots in uplink assignment		Reduction of maximum output power, (dB)		
Band	Time Slots	GPRS (GMSK)	EGPRS (GMSK)	EGPRS (8PSK)
GSM850	1 TX slot	0	0	0
	2 TX slots	3	3	1
GSM1900	1 TX slot	0	0	0
	2 TX slots	4	4	3

Table 10: The allowed power reduction in the multi-slot configuration of GSM

6.2 UMTS Test Configuration

1) RMC

As the SAR body tests for UMTS Band II/IV/V, we established the radio link through call processing. The maximum output power were verified on high, middle and low channels for each test band according to 3GPP TS 34.121 with the following configuration:

- 1) 12.2kbps RMC, 64,144,384 kbps RMC with TPC set to ‘all 1’.
- 2) Test loop Mode 1.

For the output power, the configurations for the DPCCH and DPDCH₁ are as followed (EUT do not support the DPDCH_{2-n})

	Channel Bit Rate (kbps)	Channel Symbol Rate (ksps)	Spreading Factor	Spreading Code Number	Bits/Slot
DPCCH	15	15	256	0	10
DPDCH ₁	15	15	256	64	10
	30	30	128	32	20
	60	60	64	16	40
	120	120	32	8	80
	240	240	16	4	160
	480	480	8	2	320
DPDCH _n	960	960	4	1	640
	960	960	4	1, 2, 3	640

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits configured to all “1s”. SAR for other spreading codes and multiple DPDCH_n, when supported by the

EUT, are not required when the maximum average outputs of each RF channel, for each spreading code and DPDCHn configuration, are less than ¼ dB higher than those measured in 12.2 kbps RMC.
2) HSDPA

SAR for body exposure configurations is measured according to the “Body SAR Measurements” procedures of 3G device. In addition, body SAR is also measured for HSDPA when the maximum average outputs of each RF channel with HSDPA active is at ¼ dB higher than that measured without HSDPA using 12.2kbps RMC or the maximum SAR 12.2kbps RMC is above 75% of the SAR limit. Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA.

HSDPA should be configured according to UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HAPRQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission condition, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. The β_c and β_d gain factors for DPCCH and DPDCH were set according to the values in the below table, β_{hs} for HS-DPCCH is set automatically to the correct value when $\Delta ACK, \Delta NACK, \Delta CQI = 8$. The variation of the β_c / β_d ratio causes a power reduction at sub-tests 2 - 4.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs} (1)	CM(dB)(2)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta ACK, \Delta NACK$ and $\Delta CQI = 8$. $A_{hs} = \beta_{hs} / \beta_c = 30/15$. $\beta_{hs} = 30/15 * \beta_c$

Note 2: CM=1 for $\beta_c/\beta_d= 12/15, \beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$

Table 11: Sub-tests for UMTS Release 5 HSDPA

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI's
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

Table 12: settings of required H-Set 1 QPSK acc. to 3GPP 34.121

HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	Maximum HS-DSCH Transport Block Bits/HS-DSCH TTI	Total Soft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

Table 13:HSDPA UE category

3) HSUPA

Body SAR is also measured for HSDPA when the maximum average outputs of each RF channel with HSDPA active is at ¼ dB higher than that measured without HSDPA using 12.2kbps RMC or the maximum SAR 12.2kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-set 1 and QPSK for FRC and 12.2kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.2 kbps RMC without HSPA.

Due to inner loop power control requirements in HSDPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSDPA should be configured according to the values indicated below as well as other applicable procedures described in the 'UMTS Handset' and 'Release 5 HSDPA Data Device' sections of 3G device.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs(1)}$	β_{ec}	β_{ed}	β_c (SF)	β_{ed} (code)	CM ⁽²⁾ (dB)	MP R _d (dB)	AG ⁽⁴⁾ Index	E-TFC I
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/25	1039/25	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: $\Delta ACK, \Delta NACK$ and $\Delta CQI = 8$. $A_{hs} = \beta_{hs}/\beta_c = 30/15$. $\beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table 14:Subtests for UMTS Release 6 HSUPA

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2S	11484	5.76
	4	4	2	F4	20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2S	22996	?
	4	4	10	F4	20000	?

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM. (TS25.306-7.3.0).

Table 15:HSUPA UE category

6.3 LTE Test Configuration

SAR for LTE band exposure configurations is measured according to the Procedures of KDB941225 D05. The MT8820C WideBand Radio Communication Tester was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing.

When MPR is implemented permanently within the UE, regardless of network requirements, only those RB configurations allowed (see 3GPP standards) for the channel bandwidth and modulation combinations may be tested with MPR. Configurations with RB allocations below the required RB thresholds must be tested without MPR. A-MPR must always be disabled.

LTE Band IV MPR as follows:

LTE Band IV						
Frequency (MHz)	BW(MHz)	Modulation	RB Size	Target power	MPR Target	MPR Allowed by 3Gpp
Uplink:1710~1785 Downlink:1805~1880	1.4	QPSK	≤5	22.5	0	0
		16-QAM	≤5	21.5	1	0-1
		QPSK	>5	21.5	1	0-1
		16-QAM	>5	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	3	QPSK	≤4	22.5	0	0
		16-QAM	≤4	21.5	1	0-1
		QPSK	>4	21.5	1	0-1
		16-QAM	>4	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	5	QPSK	≤8	22.5	0	0
		16-QAM	≤8	21.5	1	0-1
		QPSK	>8	21.5	1	0-1
		16-QAM	>8	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	10	QPSK	≤12	22.5	0	0
		16-QAM	≤12	21.5	1	0-1
		QPSK	>12	21.5	1	0-1
		16-QAM	>12	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	15	QPSK	≤16	22.5	0	0
		16-QAM	≤16	21.5	1	0-1
		QPSK	>16	21.5	1	0-1
		16-QAM	>16	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	20	QPSK	≤18	22.5	0	0
		16-QAM	≤18	21.5	1	0-1
		QPSK	>18	21.5	1	0-1
		16-QAM	>18	20.5	2	0-2

LTE Band XVII MPR as follows:

LTE Band XVII						
Frequency (MHz)	BW(MHz)	Modulation	RB Size	Target power	MPR Target	MPR Allowed by 3Gpp
Uplink:1710~1785 Downlink:1805~1880	5	QPSK	≤8	22.5	0	0
		16-QAM	≤8	21.5	1	0-1
		QPSK	>8	21.5	1	0-1
		16-QAM	>8	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	10	QPSK	≤12	22.5	0	0
		16-QAM	≤12	21.5	1	0-1
		QPSK	>12	22.5	1	0-1
		16-QAM	>12	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	15	QPSK	≤16	22.5	0	0
		16-QAM	≤16	21.5	1	0-1
		QPSK	>16	21.5	1	0-1
		16-QAM	>16	20.5	2	0-2
Uplink:1710~1785 Downlink:1805~1880	20	QPSK	≤18	22.5	0	0
		16-QAM	≤18	21.5	1	0-1
		QPSK	>18	21.5	1	0-1
		16-QAM	>18	20.5	2	0-2

For each LTE frequency band, detail reduce test information is referred to section 7.2.3 to 7.2.4 and final test summary is as follows:

- a. Per KDB941225 D05 page 4,3) A), QPSK with 50% RB is required for the highest bandwidth.
- b. Per KDB941225 D05 page 4,3) B), QPSK with 1 RB for both channel edges are required for the highest bandwidth.
- c. Per KDB941225 D05 page 4,4) A), 16QAM with 50% RB is required for the highest bandwidth.
- d. Per KDB941225 D05 page 4,4) B), 16QAM with 1 RB for both channel edges are required for the highest bandwidth.
- e. Per KDB941225 D05 page 4, 3) A) I and 4) A) I, 100% RB allocation is not required to be tested since SAR is not >1.45W/kg for the highest bandwidth.

6.4 WiFi Test Configuration

For the 802.11b/g SAR tests, a communication link is set up with the test mode software for WiFi mode test. The Absolute Radio Frequency Channel Number(ARFCN) is allocated to 1,6 and 11 respectively in the case of 2450 MHz. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate.

802.11b/g operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g modes are tested on channel 1,6,11; however, if output power reduction is necessary for channels 1 and/or 11 to meet restricted band requirements the highest output channel closest to each of these channels must be tested instead.

SAR is not required for 802.11g channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels.

Mode	Band	GHz	Channel	"Default Test Channels"	
				802.11b	802.11g
802.11b/g	2.4 GHz	2.412	1#	√	△
		2.437	6	√	△
		2.462	11#	√	△

Notes:

√ = "default test channels"

△ = possible 802.11g channels with maximum average output ¼ dB the "default test channels"

= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

802.11 Test Channels per FCC Requirements

7 SAR Measurement Results

7.1 Conducted power measurements

For the measurements a Rohde & Schwarz Radio Communication Tester CMU 200 and WideBand Radio Communication Tester MT8820C were used.

SAR drift measured at the same position in liquid before and after each SAR test as below 7.2 chapter.

Note:1)CMU200 measures GSM peak and average output power for active timeslots. For SAR the timebased average power is relevant. The difference in between depends on the duty cycle of the TDMA signal :

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.1	1:2.77	1:2.08
timebased avg. power compared to slotted avg. power	-9.19 dB	-6.13 dB	-4.42dB	-3.18dB

The signalling modes differ as follows:

mode	coding scheme	modulation
GPRS	CS1 to CS4	GMSK
EDGE	MCS1 to MCS4	GMSK
EDGE	MCS5 to MCS9	8PSK

Apart from modulation change (GMSK/8PSK) coding schemes differ in code rate without influence on the RF signal. Therefore one coding scheme per mode was selected for conducted power measurements.

7.1.1 Conducted power measurements GSM850

GSM850		Burst-Averaged output Power (dBm)			Division Factors	Frame-Averaged output Power (dBm)		
		128CH	190CH	251CH		128CH	190CH	251CH
GSM (CS)		32.08	31.96	31.83	-9.19	22.89	22.77	22.64
GPRS (GMSK)	1 Tx Slot	32.05	31.96	31.82	-9.19	22.86	22.77	22.63
	2 Tx Slots	29.03	28.88	29.08	-6.13	22.90	22.75	22.95
EDGE (GMSK)	1 Tx Slot	32.06	31.96	31.87	-9.19	22.87	22.77	22.68
	2 Tx Slots	29.02	28.86	29.06	-6.13	22.89	22.73	22.93
EDGE (8PSK)	1 Tx Slot	26.83	26.81	26.75	-9.19	17.64	17.62	17.56
	2 Tx Slots	26.53	26.47	26.52	-6.13	20.40	20.34	20.39

Table 16:Test results conducted power measurement GSM850

Note: 1. The conducted power of GSM850 is measured with RMS detector.

2. Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timesolts.

7.1.2 Conducted power measurements GSM1900

GSM1900		Burst-Averaged output Power (dBm)			Division Factors	Frame-Averaged output Power (dBm)		
		512CH	661CH	810CH		512CH	661CH	810CH
GSM (CS)		30.48	30.62	30.68	-9.19	21.29	21.43	21.49
GPRS (GMSK)	1 Tx Slot	30.48	30.56	30.67	-9.19	21.29	21.37	21.48
	2 Tx Slots	26.92	26.96	26.88	-6.13	20.79	20.83	20.75
EDGE (GMSK)	1 Tx Slot	30.48	30.54	30.63	-9.19	21.29	21.35	21.44
	2 Tx Slots	26.88	26.93	26.87	-6.13	20.75	20.80	20.74
EDGE (8PSK)	1 Tx Slot	27.08	26.97	26.96	-9.19	17.89	17.78	17.77
	2 Tx Slots	24.12	24.08	24.13	-6.13	17.99	17.95	18.00

Table 17: Test results conducted power measurement GSM1900

Note: 1. The conducted power of GSM1900 is measured with RMS detector.

2. Frame-averaged output power was calculated from the measured burst-averaged output power by converting the slot powers into linear units and calculating the energy over 8 timeslots.

7.1.1 Conducted power measurements UMTS Band V

UMTS Band V		Conducted Power (dBm)		
		4132CH	4182CH	4233CH
WCDMA	12.2kbps RMC	23.78	23.59	23.70
	64kbps RMC	23.79	23.59	23.71
	144kbps RMC	23.74	23.56	23.60
	384kbps RMC	23.74	23.58	23.65
HSDPA	Subtest 1	22.70	22.55	22.53
	Subtest 2	22.35	22.26	22.33
	Subtest 3	21.91	21.65	21.72
	Subtest 4	21.93	21.63	21.67
HSUPA	Subtest 1	21.91	21.85	22.12
	Subtest 2	19.54	19.28	19.47
	Subtest 3	21.08	20.44	21.26
	Subtest 4	21.68	21.54	21.87
	Subtest 5	21.72	21.74	22.11

Table 18: Test results conducted power measurement UMTS Band V

Note: The conducted power of UMTS Band V is measured with RMS detector.

7.1.2 Conducted power measurements UMTS Band II

UMTS Band II		Conducted Power (dBm)		
		9262CH	9400CH	9538CH
WCDMA	12.2kbps RMC	22.09	22.10	21.84
	64kbps RMC	22.12	22.07	21.78
	144kbps RMC	22.11	22.05	21.79
	384kbps RMC	22.08	22.05	21.79
HSDPA	Subtest 1	21.13	21.09	20.82
	Subtest 2	20.99	20.84	20.84
	Subtest 3	20.40	20.23	20.10
	Subtest 4	20.23	20.25	20.11
HSUPA	Subtest 1	20.38	20.24	19.90
	Subtest 2	17.70	17.82	17.38
	Subtest 3	19.76	19.43	19.44
	Subtest 4	19.88	19.68	19.54
	Subtest 5	20.92	20.05	20.35

Table 19: Test results conducted power measurement UMTS Band II

Note: The conducted power of UMTS Band II is measured with RMS detector.

7.1.3 Conducted power measurements UMTS Band IV

UMTS Band II		Conducted Power (dBm)		
		1312CH	1413CH	1513CH
WCDMA	12.2kbps RMC	22.39	22.45	22.43
	64kbps RMC	22.40	22.45	22.35
	144kbps RMC	22.34	22.41	22.36
	384kbps RMC	22.36	22.41	22.48
HSDPA	Subtest 1	21.62	21.70	21.72
	Subtest 2	21.44	21.49	21.53
	Subtest 3	20.80	20.99	21.04
	Subtest 4	20.84	20.96	20.87
HSUPA	Subtest 1	20.93	20.76	20.81
	Subtest 2	18.38	18.31	18.37
	Subtest 3	20.30	20.31	20.18
	Subtest 4	20.89	20.77	20.29
	Subtest 5	20.80	20.76	20.66

Table 20: Test results conducted power measurement UMTS Band IV

Note: The conducted power of UMTS Band IV is measured with RMS detector.

7.1.4 Conducted power measurements LTE Band IV

Low Channel

Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Target MPR(dB)	Average Power [dBm]
19957	1.4	1	0	QPSK	0	22.55
		1	5	QPSK	0	22.55
		3	2	QPSK	0	22.61
		6	0	QPSK	1	21.67
		1	0	16-QAM	1	21.62
		1	5	16-QAM	1	21.52
		3	2	16-QAM	1	21.57
		6	0	16-QAM	2	20.48
19965	3	1	0	QPSK	0	22.58
		1	14	QPSK	0	22.48
		8	4	QPSK	1	21.5
		15	0	QPSK	1	21.45
		1	0	16-QAM	1	21.74
		1	14	16-QAM	1	21.64
		8	4	16-QAM	2	20.65
		15	0	16-QAM	2	20.49
19975	5	1	0	QPSK	0	22.71
		1	24	QPSK	0	22.67
		12	6	QPSK	1	21.53
		25	0	QPSK	1	21.4
		1	0	16-QAM	1	21.87
		1	24	16-QAM	1	21.87
		12	6	16-QAM	2	20.58
		25	0	16-QAM	2	20.42
20000	10	1	0	QPSK	0	22.58
		1	49	QPSK	0	22.62
		25	13	QPSK	1	21.33
		50	0	QPSK	1	21.31
		1	0	16-QAM	1	21.48
		1	49	16-QAM	1	21.41
		25	13	16-QAM	2	20.4
		50	0	16-QAM	2	20.27
20025	15	1	0	QPSK	0	22.59
		1	74	QPSK	0	22.49
		36	18	QPSK	1	21.26
		75	0	QPSK	1	21.34
		1	0	16-QAM	1	21.45
		1	74	16-QAM	1	21.44
		36	18	16-QAM	2	20.37
		75	0	16-QAM	2	20.29
20050	20	1	0	QPSK	0	22.64
		1	99	QPSK	0	22.63



		50	25	QPSK	1	21.17
		100	0	QPSK	1	21.35
		1	0	16-QAM	1	21.45
		1	99	16-QAM	1	21.45
		50	25	16-QAM	2	20.19
		100	0	16-QAM	2	20.32

Mid Channel

20175	1.4	1	0	QPSK	0	22.57
		1	5	QPSK	0	22.61
		3	2	QPSK	0	22.63
		6	0	QPSK	1	21.59
		1	0	16-QAM	1	21.34
		1	5	16-QAM	1	21.26
		3	2	16-QAM	1	21.79
		6	0	16-QAM	2	20.5
	3	1	0	QPSK	0	22.61
		1	14	QPSK	0	22.68
		8	4	QPSK	1	21.61
		15	0	QPSK	1	21.62
		1	0	16-QAM	1	21.56
		1	14	16-QAM	1	21.51
		8	4	16-QAM	2	20.57
		15	0	16-QAM	2	20.57
	5	1	0	QPSK	0	22.69
		1	24	QPSK	0	22.62
		12	6	QPSK	1	21.55
		25	0	QPSK	1	21.48
		1	0	16-QAM	1	21.46
		1	24	16-QAM	1	21.97
		12	6	16-QAM	2	20.6
		25	0	16-QAM	2	20.46
	10	1	0	QPSK	0	22.59
		1	49	QPSK	0	22.63
		25	13	QPSK	1	21.47
		50	0	QPSK	1	21.38
		1	0	16-QAM	1	21.46
		1	49	16-QAM	1	21.5
		25	13	16-QAM	2	20.39
		50	0	16-QAM	2	20.38
	15	1	0	QPSK	0	22.54
		1	74	QPSK	0	22.6
		36	18	QPSK	1	21.3
		75	0	QPSK	1	21.25
		1	0	16-QAM	1	21.4
		1	74	16-QAM	1	21.52
		36	18	16-QAM	2	20.43
		75	0	16-QAM	2	20.27

	20	1	0	QPSK	0	22.55
		1	99	QPSK	0	22.56
		50	25	QPSK	1	21.38
		100	0	QPSK	1	21.44
		1	0	16-QAM	1	21.47
		1	99	16-QAM	1	21.41
		50	25	16-QAM	2	20.31
		100	0	16-QAM	2	20.33

High Channel

20393	1.4	1	0	QPSK	0	22.63
		1	5	QPSK	0	22.66
		3	2	QPSK	0	22.62
		6	0	QPSK	1	21.72
		1	0	16-QAM	1	21.51
		1	5	16-QAM	1	21.54
		3	2	16-QAM	1	21.57
		6	0	16-QAM	2	20.51
20385	3	1	0	QPSK	0	22.47
		1	14	QPSK	0	22.62
		8	4	QPSK	1	21.58
		15	0	QPSK	1	21.61
		1	0	16-QAM	1	21.33
		1	14	16-QAM	1	21.43
		8	4	16-QAM	2	20.62
		15	0	16-QAM	2	20.49
20375	5	1	0	QPSK	0	22.74
		1	24	QPSK	0	22.61
		12	6	QPSK	1	21.43
		25	0	QPSK	1	21.50
		1	0	16-QAM	1	21.75
		1	24	16-QAM	1	21.77
		12	6	16-QAM	2	20.5
		25	0	16-QAM	2	20.52
20350	10	1	0	QPSK	0	22.67
		1	49	QPSK	0	22.65
		25	13	QPSK	1	21.41
		50	0	QPSK	1	21.36
		1	0	16-QAM	1	21.78
		1	49	16-QAM	1	21.81
		25	13	16-QAM	2	20.48
		50	0	16-QAM	2	20.30
20325	15	1	0	QPSK	0	22.63
		1	74	QPSK	0	22.74
		36	18	QPSK	1	21.34
		75	0	QPSK	1	21.34
		1	0	16-QAM	1	21.72

20300	20	1	74	16-QAM	1	21.81
		36	18	16-QAM	2	20.32
		75	0	16-QAM	2	20.28
		1	0	QPSK	0	22.58
		1	99	QPSK	0	22.73
		50	25	QPSK	1	21.35
		100	0	QPSK	1	21.40
		1	0	16-QAM	1	21.77
		1	99	16-QAM	1	21.81
50	25	16-QAM	2	20.35		
100	0	16-QAM	2	20.33		

Table 21: Test results conducted power measurement LTE Band IV

Note: The conducted power of LTE Band IV is measured with RMS detector

7.1.5 Conducted power measurements LTE Band XVII

Low Channel

Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Target MPR(dB)	Average Power [dBm]
23755	5	1	0	QPSK	0	22.21
		1	24	QPSK	0	22.71
		12	6	QPSK	1	21.13
		25	0	QPSK	1	21.19
		1	0	16-QAM	1	21.24
		1	24	16-QAM	1	21.74
		12	6	16-QAM	2	20.17
		25	0	16-QAM	2	20.15
23780	10	1	0	QPSK	0	22.13
		1	49	QPSK	0	22.07
		25	13	QPSK	1	21.35
		50	0	QPSK	1	21.14
		1	0	16-QAM	1	21.56
		1	49	16-QAM	1	21.76
		25	13	16-QAM	2	20.39
		50	0	16-QAM	2	20.10

Mid Channel

23790	5	1	0	QPSK	0	22.52
		1	24	QPSK	0	22.49
		12	6	QPSK	1	21.50
		25	0	QPSK	1	21.35
		1	0	16-QAM	1	21.50
		1	24	16-QAM	1	21.58
		12	6	16-QAM	2	20.64
		25	0	16-QAM	2	20.43
	10	1	0	QPSK	0	22.15
		1	49	QPSK	0	22.11
		25	13	QPSK	1	21.33

		50	0	QPSK	1	21.19
		1	0	16-QAM	1	21.27
		1	49	16-QAM	1	21.11
		25	13	16-QAM	2	20.05
		50	0	16-QAM	2	20.07

High Channel

23825	5	1	0	QPSK	0	22.68
		1	24	QPSK	0	21.03
		12	6	QPSK	1	21.29
		25	0	QPSK	1	20.96
		1	0	16-QAM	1	21.81
		1	24	16-QAM	1	20.20
		12	6	16-QAM	2	20.40
		25	0	16-QAM	2	20.11
23800	10	1	0	QPSK	0	22.48
		1	49	QPSK	0	21.79
		25	13	QPSK	1	21.61
		50	0	QPSK	1	21.48
		1	0	16-QAM	1	21.60
		1	49	16-QAM	1	20.83
		25	13	16-QAM	2	20.70
		50	0	16-QAM	2	20.45

Table 22: Test results conducted power measurement LTE Band XVII

Note: The conducted power of LTE Band XVII is measured with RMS detector

7.2 SAR measurement Result

7.2.1 SAR measurement Result of GSM850

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	190/836.6	GSM	0.477	0.357	0.100	31.96	21.4°C
Left Hand Tilted 15°	190/836.6	GSM	0.292	0.225	-0.150		21.4°C
Right Hand Touched	190/836.6	GSM	0.447	0.341	0.190		21.4°C
Right Hand Tilted 15°	190/836.6	GSM	0.273	0.213	-0.100		21.4°C

Table 23: Test results head SAR GSM 850MHz

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	190/836.6	GPRS 1TS	0.590	0.457	-0.010	31.96	21.4°C
Towards Phantom	190/836.6	GPRS 2TS	0.588	0.455	-0.130	28.88	21.4°C
Towards Ground	128/824.2	GPRS 1TS	0.688	0.532	-0.040	32.05	21.4°C
Towards Ground	190/836.6	GPRS 1TS	0.805	0.622	-0.030	31.96	21.4°C
Towards Ground	251/848.8	GPRS 1TS	0.782	0.601	0.020	31.82	21.4°C
Left edge	190/836.6	GPRS 1TS	0.678	0.475	0.010	31.96	21.4°C
Right edge	190/836.6	GPRS 1TS	0.599	0.421	0.050		21.4°C
Bottom edge	190/836.6	GPRS 1TS	0.066	0.038	-0.120		21.4°C
Towards Ground	128/824.2	EDGE 1TS	0.670	0.517	-0.070	32.06	21.4°C
Towards Ground	190/836.6	EDGE 1TS	0.833	0.645	-0.090	31.96	21.4°C
Towards Ground	251/848.8	EDGE 1TS	0.797	0.614	0.010	31.87	21.4°C
Towards Ground	128/824.2	EDGE 2TS	0.559	0.428	-0.070	29.02	21.4°C
Towards Ground	190/836.6	EDGE 2TS	0.904	0.688	-0.190	28.86	21.4°C
Towards Ground	251/848.8	EDGE 2TS	0.902	0.673	0.010	29.06	21.4°C
Towards Ground with Headset	190/836.6	GSM	0.611	0.470	-0.060	31.96	21.4°C

Table 24: Test results Body SAR GSM850

7.2.1 SAR measurement Result of GSM1900

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	661/1880	GSM	0.137	0.091	-0.150	30.62	21.4°C
Left Hand Tilted 15°	661/1880	GSM	0.065	0.042	0.050		21.4°C
Right Hand Touched	661/1880	GSM	0.258	0.149	0.040		21.4°C
Right Hand Tilted 15°	661/1880	GSM	0.068	0.042	0.070		21.4°C

Table 25:Test results head SAR GSM 1900MHz

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	661/1880	GPRS 1TS	0.214	0.118	-0.130	30.56	21.4°C
Towards Phantom	661/1880	GPRS 2TS	0.263	0.144	0.010	26.96	21.4°C
Towards Ground	661/1880	GPRS 2TS	0.700	0.361	0.120		21.4°C
Left edge	661/1880	GPRS 2TS	0.052	0.029	0.130		21.4°C
Right edge	661/1880	GPRS 2TS	0.131	0.072	0.180		21.4°C
Bottom edge	661/1880	GPRS 2TS	0.535	0.284	-0.070		21.4°C
Towards Ground	661/1880	EDGE 1TS	0.554	0.284	-0.170	30.54	21.4°C
Towards Ground	661/1880	EDGE 2TS	0.632	0.327	0.170	26.93	21.4°C
Towards Ground with Headset	661/1880	GSM	0.626	0.328	0.000	30.62	21.4°C

Table 26:Test results body SAR GSM1900

Note: 1) The maximum SAR value of each test band is shown in **bold** letters.

2) Per KDB447498 D01,the SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8 W/kg), testing at the high and low channels is optional.

3) Per KDB941225 D06,for the antenna-to-edge distance is greater than 2.5 cm,so the top side does not need to be tested.

7.2.2 SAR measurement Result of UMTS Band V

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	4182/836.4	RMC	0.416	0.311	-0.150	23.59	21.4°C
Left Hand Tilted 15°	4182/836.4	RMC	0.217	0.166	-0.090		21.4°C
Right Hand Touched	4182/836.4	RMC	0.388	0.292	0.040		21.4°C
Right Hand Tilted 15°	4182/836.4	RMC	0.227	0.175	0.030		21.4°C

Table 27:Test results head SAR UMTS Band V

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducte d Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	4182/836.4	RMC	0.530	0.406	-0.030	23.59	21.4°C
Towards Ground	4182/836.4	RMC	0.757	0.570	0.080		21.4°C
Left edge	4182/836.4	RMC	0.598	0.410	0.090		21.4°C
Right edge	4182/836.4	RMC	0.543	0.374	0.130		21.4°C
Bottom edge	4182/836.4	RMC	0.056	0.033	-0.150		21.4°C
Towards Ground with Headset	4182/836.4	RMC	0.536	0.405	0.170		21.4°C

Table 28:Test results body SAR UMTS Band V

7.2.3 SAR measurement Result of UMTS Band IV

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	1513/1752.6	RMC	0.806	0.475	-0.030	22.43	21.4°C
	1413/1732.6	RMC	0.854	0.506	0.140	22.45	21.4°C
	1312/1712.4	RMC	0.915	0.546	0.170	22.39	21.4°C
Left Hand Tilted 15°	1413/1732.6	RMC	0.222	0.137	0.050	22.45	21.4°C
Right Hand Touched	1413/1732.6	RMC	0.484	0.300	0.120		21.4°C
Right Hand Tilted 15°	1413/1732.6	RMC	0.250	0.153	0.180		21.4°C

Table 29:Test results head SAR UMTS Band IV

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	1413/1732.6	RMC	0.777	0.453	0.060	22.45	21.4°C
Towards Ground	1413/1732.6	RMC	0.799	0.471	-0.030		21.4°C
Left edge	1413/1732.6	RMC	0.330	0.194	0.000		21.4°C
Right edge	1413/1732.6	RMC	0.064	0.037	0.090		21.4°C
Bottom edge	1413/1732.6	RMC	0.711	0.388	-0.070		21.4°C
Towards Ground with Headset	1413/1732.6	RMC	0.733	0.437	0.150		21.4°C

Table 30:Test results body SAR UMTS Band IV

7.2.4 SAR measurement Result of UMTS Band II

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	9400/1880	GSM	0.790	0.474	-0.190	22.10	21.4°C
Left Hand Tilted 15°	9400/1880	GSM	0.324	0.206	0.040		21.4°C
Right Hand Touched	9400/1880	GSM	0.477	0.295	0.170		21.4°C
Right Hand Tilted 15°	9400/1880	GSM	0.381	0.231	0.050		21.4°C

Table 31:Test results head SAR UMTS Band II

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	9400/1880	RMC	0.772	0.475	0.190	22.10	21.3°C
Towards Ground	9400/1880	RMC	0.676	0.409	-0.040		21.3°C
Left edge	9400/1880	RMC	0.501	0.292	-0.130		21.3°C
Right edge	9400/1880	RMC	0.138	0.080	0.050		21.3°C
Bottom edge	9400/1880	RMC	0.411	0.223	-0.070		21.3°C
Towards Phantom with Headset	9400/1880	RMC	0.790	0.481	-0.140		21.3°C

Table 32:Test results body SAR UMTS Band II

Note: 1) The maximum SAR value of each test band is shown in **bold** letters.

2) Per KDB447498 D01,the SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8 W/kg), testing at the high and low channels is optional.

3) Per KDB941225 D06,for the antenna-to-edge distance is greater than 2.5 cm,so the top side does not need to be tested.

4) Per KDB941225 D01,Body SAR is not required for handset with HSPA when the maximum average output power of HSPA active is less than 0.25dBm higher than that measured without HSPA using 12.2kbps RMC and maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit.

7.2.5 SAR measurement Result of LTE Band IV

Test Position	Test channel /Frequency	LTE Configuration	SAR Value (W/kg)		Power Drift (dB)	Conducte d Power (dBm)	Liquid Temp.
			1-g	10-g			
20M/QPSK							
Left Hand Touched	20175/1732.5	50%RB/#25	0.677	0.404	0.120	21.38	21.4°C
Left Hand Tilted 15°	20175/1732.5		0.176	0.110	0.010		21.4°C
Right Hand Touched	20175/1732.5		0.374	0.234	0.050		21.4°C
Right Hand Tilted15°	20175/1732.5		0.197	0.121	0.070		21.4°C
20M/QPSK							
Left Hand Touched	20050/1720	1RB/#0	0.909	0.551	-0.170	22.64	21.4°C
Left Hand Tilted 15°	20050/1720		0.244	0.151	0.020		21.4°C
Right Hand Touched	20050/1720		0.680	0.386	-0.080		21.4°C
Right Hand Tilted15°	20050/1720		0.252	0.156	0.070		21.4°C
20M/QPSK							
Left Hand Touched	20300/1745	1RB/#99	0.963	0.566	0.060	22.73	21.4°C
Left Hand Tilted 15°	20300/1745		0.238	0.148	0.030		21.4°C
Right Hand Touched	20300/1745		0.497	0.306	-0.080		21.4°C
Right Hand Tilted15°	20300/1745		0.257	0.157	0.060		21.4°C
20M/16QAM							
Left Hand Touched	20175/1732.5	50%RB/#25	0.573	0.337	-0.140	21.38	21.4°C
Left Hand Tilted 15°	20175/1732.5		0.131	0.081	0.080		21.4°C
Right Hand Touched	20175/1732.5		0.322	0.197	0.190		21.4°C
Right Hand Tilted15°	20175/1732.5		0.154	0.093	0.080		21.4°C
20M/16QAM							
Left Hand Touched	20300/1745	1RB/#0	0.764	0.448	0.120	21.77	21.4°C
Left Hand Tilted 15°	20300/1745		0.190	0.117	0.070		21.4°C
Right Hand Touched	20300/1745		0.437	0.267	0.110		21.4°C
Right Hand Tilted15°	20300/1745		0.209	0.126	0.020		21.4°C
20M/16QAM							
Left Hand Touched	20300/1745	1RB/#99	0.725	0.425	0.140	21.81	21.4°C
Left Hand Tilted 15°	20300/1745		0.187	0.115	0.070		21.4°C
Right Hand Touched	20300/1745		0.409	0.247	-0.170		21.4°C
Right Hand Tilted15°	20300/1745		0.213	0.127	0.060		21.4°C

Table 33:Test results head SAR LTE Band IV

Test Position	Test channel /Frequency	LTE Configuration	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
20M/QPSK							
Towards Phantom	20175/1732.5	50%RB/#25	0.581	0.349	0.030	21.38	21.4°C
Towards Ground	20175/1732.5		0.659	0.389	0.040		21.4°C
Left edge	20175/1732.5		0.244	0.145	-0.030		21.4°C
Right edge	20175/1732.5		0.055	0.033	0.050		21.4°C
Bottom edge	20175/1732.5		0.600	0.324	-0.010		21.4°C
20M/QPSK							
Towards Phantom	20050/1720	1RB/#0	0.825	0.476	-0.020	22.64	21.4°C
Towards Ground	20050/1720		0.969	0.565	-0.020		21.4°C
Left edge	20050/1720		0.331	0.196	-0.050		21.4°C
Right edge	20050/1720		0.073	0.043	-0.130		21.4°C
Bottom edge	20050/1720		0.902	0.487	-0.090		21.4°C
20M/QPSK							
Towards Phantom	20300/1745	1RB/#99	0.754	0.453	0.030	22.73	21.4°C
Towards Ground	20300/1745		0.757	0.453	-0.100		21.4°C
Left edge	20300/1745		0.350	0.205	-0.020		21.4°C
Right edge	20300/1745		0.068	0.040	-0.120		21.4°C
Bottom edge	20300/1745		0.764	0.414	-0.080		21.4°C
20M/16QAM							
Towards Phantom	20175/1732.5	50%RB/#25	0.508	0.299	0.090	21.38	21.4°C
Towards Ground	20175/1732.5		0.528	0.311	-0.100		21.4°C
Left edge	20175/1732.5		0.180	0.108	-0.160		21.4°C
Right edge	20175/1732.5		0.045	0.026	-0.010		21.4°C
Bottom edge	20175/1732.5		0.490	0.265	-0.130		21.4°C
20M/16QAM							
Towards Phantom	20300/1745	1RB/#0	0.617	0.370	0.020	21.77	21.4°C
Towards Ground	20300/1745		0.689	0.405	-0.100		21.4°C
Left edge	20300/1745		0.253	0.150	-0.150		21.4°C
Right edge	20300/1745		0.060	0.035	0.130		21.4°C
Bottom edge	20300/1745		0.652	0.351	0.000		21.4°C
20M/16QAM							
Towards Phantom	20300/1745	1RB/#99	0.589	0.355	0.120	21.81	21.4°C
Towards Ground	20300/1745		0.597	0.354	0.040		21.4°C
Left edge	20300/1745		0.257	0.151	-0.190		21.4°C
Right edge	20300/1745		0.058	0.034	0.030		21.4°C
Bottom edge	20300/1745		0.573	0.308	0.020		21.4°C

Table 34: Test results body SAR LTE Band IV

7.2.6 SAR measurement Result of LTE Band XVII

Test Position	Test channel /Frequency	LTE Configuration	SAR Value (W/kg)		Power Drift (dB)	Conducte d Power (dBm)	Liquid Temp.
			1-g	10-g			
10M/QPSK							
Left Hand Touched	23790/710	50%RB/#25	0.268	0.208	-0.17	21.33	21.4°C
Left Hand Tilted 15°	23790/710		0.152	0.121	0.070		21.4°C
Right Hand Touched	23790/710		0.263	0.205	0.170		21.4°C
Right Hand Tilted15°	23790/710		0.156	0.125	0.180		21.4°C
10M/QPSK							
Left Hand Touched	23800/711	1RB/#0	0.427	0.331	0.040	22.48	21.4°C
Left Hand Tilted 15°	23800/711		0.242	0.193	0.050		21.4°C
Right Hand Touched	23800/711		0.410	0.320	0.180		21.4°C
Right Hand Tilted15°	23800/711		0.238	0.191	0.170		21.4°C
10M/QPSK							
Left Hand Touched	23790/710	1RB/#49	0.468	0.362	0.140	22.11	21.4°C
Left Hand Tilted 15°	23790/710		0.262	0.209	0.090		21.4°C
Right Hand Touched	23790/710		0.445	0.344	0.120		21.4°C
Right Hand Tilted15°	23790/710		0.300	0.123	0.140		21.4°C
10M/16QAM							
Left Hand Touched	23790/710	50%RB/#25	0.215	0.166	0.040	20.05	21.4°C
Left Hand Tilted 15°	23790/710		0.133	0.106	0.040		21.4°C
Right Hand Touched	23790/710		0.208	0.162	-0.190		21.4°C
Right Hand Tilted15°	23790/710		0.145	0.115	0.190		21.4°C
10M/16QAM							
Left Hand Touched	23800/711	1RB/#0	0.309	0.239	0.160	21.60	21.4°C
Left Hand Tilted 15°	23800/711		0.189	0.150	0.050		21.4°C
Right Hand Touched	23800/711		0.324	0.252	0.120		21.4°C
Right Hand Tilted15°	23800/711		0.208	0.165	0.030		21.4°C
10M/16QAM							
Left Hand Touched	23780/709	1RB/#49	0.348	0.269	0.130	21.76	21.4°C
Left Hand Tilted 15°	23780/709		0.213	0.168	0.150		21.4°C
Right Hand Touched	23780/709		0.331	0.256	0.090		21.4°C
Right Hand Tilted15°	23780/709		0.216	0.171	0.160		21.4°C

Table 35:Test results head SAR LTE Band XVII

Test Position	Test channel /Frequency	LTE Configuration	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
10M/QPSK							
Towards Phantom	23790/710	50%RB/#25	0.326	0.252	-0.040	21.33	21.4°C
Towards Ground	23790/710		0.468	0.357	0.060		21.4°C
Left edge	23790/710		0.246	0.174	0.110		21.4°C
Right edge	23790/710		0.241	0.171	0.030		21.4°C
Bottom edge	23790/710		0.036	0.022	0.110		21.4°C
10M/QPSK							
Towards Phantom	23800/711	1RB/#0	0.496	0.382	-0.030	22.48	21.4°C
Towards Ground	23800/711		0.666	0.511	0.080		21.4°C
Left edge	23800/711		0.378	0.267	0.110		21.4°C
Right edge	23800/711		0.358	0.254	0.100		21.4°C
Bottom edge	23800/711		0.064	0.039	0.190		21.4°C
10M/QPSK							
Towards Phantom	23790/710	1RB/#49	0.537	0.414	0.010	22.11	21.4°C
Towards Ground	23790/710		0.633	0.485	0.070		21.4°C
Left edge	23790/710		0.408	0.288	0.170		21.4°C
Right edge	23790/710		0.421	0.298	0.070		21.4°C
Bottom edge	23790/710		0.065	0.040	0.120		21.4°C
10M/16QAM							
Towards Phantom	23790/710	50%RB/#25	0.252	0.195	0.000	20.05	21.4°C
Towards Ground	23790/710		0.373	0.287	0.040		21.4°C
Left edge	23790/710		0.198	0.140	0.130		21.4°C
Right edge	23790/710		0.191	0.136	0.050		21.4°C
Bottom edge	23790/710		0.033	0.020	0.070		21.4°C
10M/16QAM							
Towards Phantom	23800/711	1RB/#0	0.393	0.303	0.050	21.60	21.4°C
Towards Ground	23800/711		0.524	0.402	0.010		21.4°C
Left edge	23800/711		0.289	0.205	0.070		21.4°C
Right edge	23800/711		0.287	0.202	-0.080		21.4°C
Bottom edge	23800/711		0.049	0.030	0.030		21.4°C
10M/16QAM							
Towards Phantom	23780/709	1RB/#49	0.399	0.309	-0.030	21.76	21.4°C
Towards Ground	23780/709		0.513	0.392	0.000		21.4°C
Left edge	23780/709		0.296	0.209	-0.010		21.4°C
Right edge	23780/709		0.291	0.206	0.050		21.4°C
Bottom edge	23780/709		0.042	0.026	0.030		21.4°C

Table 36: Test results body SAR LTE Band XVII

Note:

- 1) The value with **bold** colour is the maximum SAR value of each test band.
- 2) A-MPR was disabled by Radio Communication Tester for all SAR tests.
- 3) LTE Head SAR was evaluated to cover third-party VoIP applications that may result in LTE being used near the head.
- 4) Per KDB941225 D06, for the antenna-to-edge distance is greater than 2.5 cm, so the top side does not need to be tested.
- 5) LTE Band IV/XVII test reduce is as below the following:

First step:

Refer to Item 3A): Begin by measuring SAR on the high, middle and low (H, M, L) channels² using the largest channel bandwidth, in QPSK with 50% RB allocation⁴ centered within the channel bandwidth.

And Foot note 2: When the maximum output power variation across H, M and L channels is $\leq \frac{1}{2}$ dB, start with the middle channel; otherwise, start with the highest output power channel. When the measured 1-g SAR for the middle or highest output power channel is ≤ 0.8 W/kg, testing of the remaining two channels in that device and exposure configuration is not necessary. Also see footnote 1.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Max Difference
Low Channel	20050	20	50	25	QPSK	21.17	0.21
Mid Channel	20175	20	50	25	QPSK	21.38	
High Channel	20300	20	50	25	QPSK	21.35	

➔Band IV, Mid channel, 20MHz BW, 50%RB#25, QPSK has been selected.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Max Difference
Low Channel	23780	10	25	13	QPSK	21.35	0.28
Mid Channel	23790	10	25	13	QPSK	21.33	
High Channel	23800	10	25	13	QPSK	21.61	

➔Band XVII, Mid channel, 10MHz BW, 50%RB#25, QPSK has been selected.

Second step:

Refer to Item 3B): Measure SAR in QPSK with 1 RB allocated at the high end of the channel edge using the highest SAR channel measured in A); and then repeat the measurement at the low end of the channel edge.⁶

And Foot note 6: If the maximum average conducted output power for a 1 RB allocation is $> \frac{1}{2}$ dB higher than the 50% RB allocation, instead of using the highest SAR channel measured for QPSK and 50% RB allocation, measure SAR on the highest output power channel for the 1 RB allocation. The maximum average conducted output power should be compared with 1RB/50% RB allocation of the same channel as below the following:

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	1	0	QPSK	22.64	1.47
		20	50	25	QPSK	21.17	
Mid Channel	20175	20	1	0	QPSK	22.55	1.17
		20	50	25	QPSK	21.38	
High Channel	20300	20	1	0	QPSK	22.58	1.23
		20	50	25	QPSK	21.35	

→ Band IV, Low channel, 20 MHz BW, 1RB/#0, has been selected.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	1	0	QPSK	22.13	0.78
		10	25	13	QPSK	21.35	
Mid Channel	23790	10	1	0	QPSK	22.15	0.82
		10	25	13	QPSK	21.33	
High Channel	23800	10	1	0	QPSK	22.48	0.87
		10	25	13	QPSK	21.61	

→ Band XVII, High channel, 10 MHz BW, 1RB/#0, has been selected.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	1	99	QPSK	22.63	1.46
		20	50	25	QPSK	21.17	
Mid Channel	20175	20	1	99	QPSK	22.56	1.18
		20	50	25	QPSK	21.38	
High Channel	20300	20	1	99	QPSK	22.73	1.38
		20	50	25	QPSK	21.35	

→ Band IV, High channel, 20 MHz BW, 1RB/#99, has been selected.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	1	49	QPSK	22.07	0.72
		10	25	13	QPSK	21.35	
Mid Channel	23790	10	1	49	QPSK	22.11	0.78
		10	25	13	QPSK	21.33	
High Channel	23800	10	1	49	QPSK	21.79	0.18
		10	25	13	QPSK	21.61	

→ Band XVII, Mid channel, 10 MHz BW, 1RB/#49, has been selected.

For measured SAR in QPSK with 1 RB is < 1.45 W/kg-> Test 1RB configuration on other channels is not required. (Refer to LTE SAR test result as bellows)

Third step:

Refer to Item 4A): For the largest channel bandwidth in each LTE frequency band⁷: Measure SAR in 16QAM with 50% RB allocation using the highest SAR channel measured in 3) A).⁸

And Foot note 7: If the maximum average conducted output power for 16QAM is more than ¼ dB higher than QPSK, apply the procedures for QPSK in 3) to test 16QAM.

And Foot note 8: If the maximum average conducted output power for 16QAM with 50% RB allocation is > ½ dB higher than QPSK with 50% RB allocation, instead of using the highest SAR channel measured in QPSK measure SAR on the highest output power channel for 16QAM with 50% RB allocation.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	1	0	16QAM	21.46	-1.18
		20	1	0	QPSK	22.64	
Mid Channel	20175	20	1	0	16-QAM	21.47	-1.09
		20	1	99	QPSK	22.56	
High Channel	20300	20	1	99	16-QAM	21.81	-0.92
		20	1	99	QPSK	22.73	

➔ Measuring SAR in 16QAM see footnote 8.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	50	25	16QAM	20.19	-0.98
		20	50	25	QPSK	21.17	
Mid Channel	20175	20	50	25	16-QAM	20.31	-1.07
		20	50	25	QPSK	21.38	
High Channel	20300	20	50	25	16-QAM	20.35	-1
		20	50	25	QPSK	21.35	

➔ Band IV, using the highest SAR channel measured in 3) A).

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	1	49	16-QAM	21.76	-0.37
		10	1	0	QPSK	22.13	
Mid Channel	23790	10	1	0	16-QAM	21.27	-0.88
		10	1	0	QPSK	22.15	
High Channel	23800	10	1	0	16-QAM	21.56	-0.92
		10	1	0	QPSK	22.48	

→ Measuring SAR in 16QAM see footnote 8.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	25	13	16QAM	20.31	-1.00
		10	25	13	QPSK	21.31	
Mid Channel	23790	10	25	13	16-QAM	20.01	-1.28
		10	25	13	QPSK	21.29	
High Channel	23800	10	25	13	16-QAM	20.65	-0.92
		10	25	13	QPSK	21.57	

→ Band XVII, using the highest SAR channel measured in 3) A).

Fourth step:

Refer to Item 4B): Measure SAR in 16QAM with 1 RB allocated at the high end of the channel edge using the SAR channel measured in A); and then repeat the measurement at the low end of the channel edge.⁹

And Foot note 9: If the maximum average conducted output power for a 1 RB allocation is > ½ dB higher than the 50% RB allocation, instead of using the highest SAR channel measured for 16QAM and 50% RB measure SAR on the highest output power channel for the 1 RB allocation.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	1	0	16QAM	21.46	1.27
		20	50	25	16QAM	20.19	
Mid Channel	20175	20	1	0	16QAM	21.47	1.16
		20	50	25	16QAM	20.31	
High Channel	20300	20	1	0	16QAM	21.77	1.42
		20	50	25	16QAM	20.35	

→ Band IV, High channel, 20 MHz BW, 1RB/#0, has been selected.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	1	0	16QAM	21.56	1.17
		10	25	13	16QAM	20.39	
Mid Channel	23790	10	1	0	16QAM	21.27	1.22
		10	25	13	16QAM	20.05	
High Channel	23800	10	1	0	16QAM	21.60	0.86
		10	25	13	16QAM	20.70	

➔ Band XVII, High channel, 10 MHz BW, 1RB/#0, has been selected.

LTE Band IV	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	20050	20	1	99	16QAM	21.45	1.26
		20	50	25	16QAM	20.19	
Mid Channel	20175	20	1	99	16QAM	21.41	1.10
		20	50	25	16QAM	20.31	
High Channel	20300	20	1	99	16QAM	21.81	1.46
		20	50	25	16QAM	20.35	

➔ Band IV, High channel, 20 MHz BW, 1RB/#99, has been selected.

LTE Band XVII	Uplink Channel Number	BW [MHz]	RB Size	RB Offset	Mod	Max Conducted Power (dBm)	Difference
Low Channel	23780	10	1	49	16QAM	21.76	1.37
		10	25	13	16QAM	20.39	
Mid Channel	23790	10	1	49	16QAM	21.11	1.06
		10	25	13	16QAM	20.05	
High Channel	23800	10	1	49	16QAM	20.83	0.13
		10	25	13	16QAM	20.70	

➔ Band XVII, Low channel, 10 MHz BW, 1RB/#49, has been selected.

For measured SAR in QPSK with 1 RB is < 1.45 W/kg-> Test 1RB configuration on other channels is not required. (Refer to LTE SAR test result as bellows)

Fifth step:

Refer to Item 5B): 1.4MHz/3MHz/5MHz/10MHz/15MHz BW is not required to be tested since the smaller channel bandwidth maximum average conducted power is within ½ dB, higher or lower, for 20MHz BW and SAR is < 1.45 W/kg.

LTE Band IV	20 MHz	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz
Max Power	22.73	22.66	22.68	22.74	22.67	22.74
Difference	---	-0.07	-0.05	0.01	-0.06	0.01

Refer to Item 5B): 5MHz BW is not required to be tested since the smaller channel bandwidth maximum average conducted power is within ½ dB, higher or lower, for 10MHz BW and SAR is < 1.45 W/kg.

LTE Band XVII	10 MHz	5 MHz
Max Power	22.48	22.71
Difference	---	0.23

Therefore: that smaller channel bandwidth does not need testing

7.2.1 SAR measurement Result of WiFi

Test Position of Head	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Left Hand Touched	1/2412	802.11 b	0.135	0.064	0.180	17.18	21.4°C
Left Hand Tilted 15°	1/2412	802.11 b	0.177	0.082	0.100		21.4°C
Right Hand Touched	1/2412	802.11 b	0.156	0.074	0.010		21.4°C
Right Hand Tilted 15°	1/2412	802.11 b	0.243	0.105	-0.030		21.4°C

Table 37: Test results head SAR WiFi 2450MHz

Test Position of Body with 10mm	Test channel /Frequency	Test Mode	SAR Value (W/kg)		Power Drift (dB)	Conducted Power (dBm)	Liquid Temp.
			1-g	10-g			
Towards Phantom	1/2412	802.11 b	0.048	0.024	0.160	17.18	21.4°C
Towards Ground	1/2412	802.11 b	0.140	0.067	0.180		21.4°C
Left edge	1/2412	802.11 b	0.011	0.005	0.140		21.4°C
Right edge	1/2412	802.11 b	0.016	0.007	-0.170		21.4°C
Top edge	1/2412	802.11 b	0.111	0.050	0.140		

Table 38: Test results body SAR WiFi 2450MHz

Note:

- 1) The value with **bold** colour is the maximum SAR value of each test band.
- 2) Per KDB248227, Tests high average RF output power channel for the lowest data rate, other modes including 802.11 g/n were not investigated since the average output powers were not greater than 0.25dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
- 3) Testing at higher data rates is not required, when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate.
- 4) The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8 W/kg), testing at the other two channels is optional.
- 5 Per KDB941225 D06,for the antenna-to-edge distance is greater than 2.5 cm,so the Bottom side does not need to be tested.

7.3 Multiple Transmitter Evaluation

7.3.1 Stand-alone SAR

These procedures were followed according to FCC "KDB648474 D01 SAR Handsets Multi Xmitter and Ant, v01r05", Sept 2008. The procedures are applicable to phones with built-in unlicensed transmitters, such as 802.11 a/b/g and Bluetooth devices.


	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P_{Ref}	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table.				

Table 39: Output Power Thresholds for Unlicensed Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: <u>Unlicensed only</u>
Unlicensed Transmitters	<p><u>When there is no simultaneous transmission –</u></p> <ul style="list-style-type: none"> ○ output $\leq 60/f$: SAR not required ○ output $> 60/f$: stand-alone SAR required <p><u>When there is simultaneous transmission –</u> <u>Stand-alone SAR not required when</u></p> <ul style="list-style-type: none"> ○ output $\leq 2 \cdot P_{Ref}$ and antenna is ≥ 5.0 cm from other antennas ○ output $\leq P_{Ref}$ and antenna is ≥ 2.5 cm from other antennas ○ output $\leq P_{Ref}$ and antenna is < 2.5 cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR < 1.2 W/kg <p><u>Otherwise stand-alone SAR is required</u></p> <p><u>When stand-alone SAR is required</u></p> <ul style="list-style-type: none"> ○ test SAR on highest output channel for each wireless mode and exposure condition ○ if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedures 	<ul style="list-style-type: none"> ○ when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas <p><u>Licensed & Unlicensed</u></p> <ul style="list-style-type: none"> ○ when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas ○ when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3 <p>SAR required: <u>Licensed & Unlicensed</u></p> <p>antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition</p> <p>Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply</p>

Table 40: Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

The closest distance between BT/WiFi antenna and main antenna is 11.02cm > 5cm, and the location of the antennas inside mobile phone is shown as below picture:



Rear Side View

The output power of BT antenna is as following:

BT 2450MHz	Average Conducted Power (dBm)		
	0CH	39CH	78CH
	5.54	6.66	4.26

Table 41: Test results conducted power measurement BT 2450 MHz

Note: The conducted power of BT is measured with RMS detector.

The output power of WiFi antenna is as following:

Wi-Fi 2450MHz	Channel	Average Power (dBm) for Data Rates (Mbps)							
		1	2	5.5	11	/	/	/	/
802.11b	1	17.02	17.05	17.18	16.83	/	/	/	/
	6	17.09	17.06	17.08	17.05	/	/	/	/
	11	16.90	16.96	17.04	16.92	/	/	/	/
802.11g	Channel	6	9	12	18	24	36	48	54
	1	14.03	14.08	13.88	13.96	13.98	14.06	14.04	14.04
	6	14.01	14.09	13.97	14.03	13.95	13.98	14.06	14.03
	11	13.88	14.03	13.93	13.96	13.91	14.01	14.02	14.08
802.11n HT20	Channel	6.5	13	19.5	26	39	52	58.5	65
	1	12.90	13.02	13.08	12.99	13.02	13.02	12.96	13.03
	6	12.93	13.08	13.02	13.06	13.04	13.09	13.06	13.18
	11	13.08	12.96	12.94	12.97	13.08	13.04	12.95	13.04

Table 42: Test results conducted power measurement WiFi 2450 MHz

Note: The conducted power of WiFi is measured with RMS detector.

According to the output power measurement results and the distance between WiFi/BT antenna and GSM&UMTS<E antenna we can draw the conclusion that:

- stand-alone SAR evaluation is not required for BT, because the output power of BT unlicensed is 6.66 dBm ≤ 2PRef (13.8dBm) and antenna is >5cm from other antennas.

- 2) Stand-alone SAR evaluation is required for WiFi, because the output power of WiFi unlicensed transmitter is $17.18\text{dBm} \geq 24\text{mW}$ (13.8dBm).

7.3.2 Simultaneous Transmission Possibilities

The following table shows exposure conditions for all transmitters:

Table 43: Simultaneous Transmission Possibilities

No.	Capable Tx Configuration	LTE	GSM Voice	GPRS/EDGE	UMTS	WiFi 2.4GHz
1	LTE	---	NO	NO	NO	Yes
2	GSM Voice	NO	---	NO	NO	Yes
3	GPRS/EDGE	NO	NO	---	NO	Yes
4	UMTS	NO	NO	NO	---	Yes
4	WiFi 2.4GHz	Yes	Yes	Yes	Yes	---
5	BT 2.4GHz	No SAR test				

Note: This mode doesn't support simultaneous BT and WiFi, because they share the same antenna and can't transmit simultaneously by design.

7.3.3 SAR Summation Scenario

Test Position	GSM&UMTS<E SAR _{Max}							WiFi Max SAR	Σ1-g Max SAR
	GSM 850	GSM 1900	UMTS Band V	UMTS Band IV	UMTS Band II	LTE Band IV	LTE Band XVII		
Head SAR (W/kg)									
Left Hand Touched	0.477	0.137	0.416	0.915	0.790	0.963	0.468	0.135	1.098
Left Hand Tilted 15°	0.292	0.065	0.217	0.222	0.324	0.244	0.262	0.177	0.501
Right Hand Touched	0.447	0.258	0.388	0.484	0.477	0.680	0.445	0.156	0.836
Right Hand Tilted 15°	0.273	0.068	0.227	0.250	0.381	0.257	0.300	0.243	0.624
Body-Worn SAR (W/kg)									
Towards Phantom	0.590	0.263	0.530	0.777	0.772	0.825	0.537	0.048	0.873
Towards Ground	0.904	0.700	0.757	0.799	0.790	0.969	0.666	0.140	1.109
Hotspot SAR (W/kg)									
Towards Phantom	0.590	0.263	0.530	0.777	0.772	0.825	0.537	0.048	0.873
Towards Ground	0.904	0.700	0.757	0.799	0.790	0.969	0.666	0.140	1.109
Left edge	0.678	0.053	0.598	0.330	0.501	0.350	0.408	0.011	0.689
Right edge	0.599	0.131	0.543	0.064	0.138	0.073	0.421	0.016	0.615
Top edge	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.111	0.111
Bottom edge	0.066	0.535	0.056	0.711	0.411	0.902	0.065	0.000	0.902

Table 44: Simultaneous Tx Combination (GSM/ UMTS/LTE+WLAN)

According to the output power measurement results and the distance between WiFi/BT antenna and GSM/ UMTS/LTE antenna we can draw the conclusion that:

- 1) Simultaneous Transmission SAR evaluation is not required for GSM/ UMTS/LTE & BT, because stand-alone SAR are not required for BT and the sum of 1-g SAR_{max} is $0.969\text{W/kg} < 1.6\text{W/kg}$ for all simultaneous transmitting antennas.
- 2) Simultaneous Transmission SAR evaluation is not required for GSM/ UMTS/LTE & WiFi, because the sum of the 1g SAR_{max} is $1.109\text{W/kg} < 1.6\text{W/kg}$ for all simultaneous transmitting antennas.



Appendix A. System Check Plots

(Pls See Appendix A.)

Appendix B. SAR Measurement Plots

(Pls See Appendix B.)

Appendix C. Calibration Certificate

(Pls See Appendix C.)

Appendix D. Photo documentation

(Pls See Appendix D.)

End