



# Appendix A: 6dB Emission Bandwidth (EBW)



## 1 Result Table

EUT Conf.	EBW [KHz]	Verdict
TM1_DH5_Ch0	692.52	Pass
TM1_DH5_Ch19	699.30	Pass
TM1_DH5_Ch39	697.57	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0






2.2 TM1\_DH5\_Ch19



Copyright 2000-2008 Agilent Technologies



2.3 TM1\_DH5\_Ch39





# Appendix B: Maximum Peak Conducted Output Power




## 1 Result Table

EUT Conf.	Max. Peak Power [dBm]	Verdict
TM1_DH5_Ch0	0.96	Pass
TM1_DH5_Ch19	1.17	Pass
TM1_DH5_Ch39	0.84	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0






### 2.2 TM1\_DH5\_Ch19





### 2.3 TM1\_DH5\_Ch39





## Appendix C: Average Power

EUT Conf.	Average Power [dBm]	Verdict
TM1_DH5_Ch0	-1.86	Pass
TM1_DH5_Ch19	-1.77	Pass
TM1_DH5_Ch39	-2.05	Pass



# Appendix D: Maximum Power Spectral Density Level




## 1 Result Table

EUT Conf.	Max. Power Spectral Density Level [dBm]	Verdict
TM1_DH5_Ch0	-9.13	Pass
TM1_DH5_Ch19	-8.93	Pass
TM1_DH5_Ch39	-9.26	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0






### 2.2 TM1\_DH5\_Ch19



2.3 TM1\_DH5\_Ch39





# Appendix E: Band edge spurious emission




### 3 Result Table

EUT Conf.	Channel No.	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max. Spurious Level [dBm]	Limit [dBm]	Result
TM1_DH5_Ch0	0	2402	0.13	Off	-59.73	-19.87	Pass
TM1_DH5_Ch39	39	2480	0.09	Off	-57.63	-19.91	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0





2.2 TM1\_DH5\_Ch39





# Appendix F: Conducted RF Spurious Emission



## 1 Result Table

In this Appendix, the “Pref” refers to the peak power level in any 100 kHz bandwidth within the fundamental emission which is used as the reference level, the “Puw” refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \times \lg(100 [kHz]/\text{narrower RBW [kHz]})$ . As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

In the result table, the “< Limit” denotes that “The Puw [dBm] is less than Pref [dBm] - 20 [dB], see test plots for detailed”.


EUT Conf.	Pref [dBm/100 kHz]	Puw [dBm/100 kHz]	Verdict
TM1_DH5_Ch0	-0.02	< Limit	Pass
TM1_DH5_Ch39	0.02	< Limit	Pass
TM1_DH5_Ch78	-0.15	< Limit	Pass



## 2 Test Plot


### 2.1 TM1\_DH5\_Ch0


#### 2.1.1 Pref








2.1.2 Puw



















## 2.2 TM1\_DH5\_Ch19


### 2.2.1 Pref





2.2.2 Puw


















### 2.3 TM1\_DH5\_Ch39


#### 2.3.1 Pref








2.3.2 Puw

















# Appendix G: Radiated Emissions in the Restricted Bands

**Part 1: Testing Range of “30 MHz to 1 GHz”**


Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Plarization
32.700000	31.50	11.8	40.0	8.5	100.0	355.00	VERTICAL
95.580000	24.90	12.8	43.5	18.6	100.0	113.00	VERTICAL
181.980000	26.80	11.1	43.5	16.7	100.0	296.00	HORIZONTAL
286.020000	27.10	15.2	46.0	18.9	100.0	318.00	HORIZONTAL
471.240000	30.20	19.5	46.0	15.8	100.0	315.00	HORIZONTAL
858.000000	35.40	25.8	46.0	10.6	100.0	272.00	HORIZONTAL

### Part 2: Testing Range of "18 GHz to 26.5 GHz"



Note: No peak found in pre- test.




### Part 3: Testing Range of “2.3GHz to 2.5GHz”

- Note 1: The testing range of “2.3 GHz to 2.5 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.
- Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).
- Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.

### 3 Test Mode:

#### 3.1 Channel 0



**Note: The peak exceeds the limit line is carrier frequency.**

#### MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	56.10	34.7	74.0	17.9	100.0	67.00	VERTICAL
2483.500000	56.70	35.0	74.0	17.3	100.0	68.00	HORIZONTAL

#### MEASUREMENT RESULT: AVDetector

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	43.70	34.7	54.0	10.3	100.0	32.00	VERTICAL
2483.500000	43.60	35.0	54.0	10.4	100.0	255.00	HORIZONTAL



### 3.2 Channel 39



**Note: The peak exceeds the limit line is carrier frequency.**

MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	56.50	34.7	74.0	17.5	100.0	225.00	HORIZONTAL
2483.500000	56.60	35.0	74.0	17.4	100.0	78.00	VERTICAL

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	44.60	34.7	54.0	9.4	100.0	151.00	HORIZONTAL
2483.500000	44.70	35.0	54.0	9.3	100.0	129.00	HORIZONTAL

#### Part 4: Testing Range of “1 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “1 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “1 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).






# Appendix H: AC Power Line Conducted Emissions

# Channel 19

## MEASUREMENT RESULT: QP Detector



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.184914	49.4	9.7	64.3	14.9	L1	FLO
0.476239	47.6	9.7	56.4	8.8	N	FLO
0.844786	44.8	9.7	56.0	11.2	N	FLO
1.174642	45.2	9.7	56.0	10.8	N	FLO
2.535784	45.1	9.7	56.0	10.9	N	FLO
4.614844	40.1	9.8	56.0	15.9	N	FLO



## MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dB $\mu$ V	Transd dB	Limit dB $\mu$ V	Margin dB	Line	PE
0.183038	42.4	9.7	54.3	11.9	N	FLO
0.477859	41.2	9.7	46.4	5.2	N	FLO
0.842580	42.0	9.7	46.0	4.0	N	FLO
1.173566	39.5	9.7	46.0	6.5	N	FLO
1.505550	38.4	9.7	46.0	7.6	N	FLO
3.076826	35.8	9.7	46.0	10.2	N	FLO

Note: Level= Reading level+ Transd (cable loss + correction factor).The reading level is used to calculate by software which is not shown in the sheet.

---

END