

FCC TEST REPORT

For

UMTS Mobile Phone

Model Number: HUAWEI Y560-U03, Y560-U03

FCC ID: QISY560-U03

Report Number : WT 158002633

Test Laboratory : Shenzhen Academy of Metrology and Quality
Inspection
National Digital Electronic Product Testing Center
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan,
Shenzhen, China
Tel : 0086-755-86928965
Fax : 0086-755-86009898-31396
Web : www.smq.com.cn
E-mail : emcrf@smq.com.cn

Test report declaration

Applicant : Huawei Technologies Co.,Ltd
Address : Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen,518129, P.R.C
Manufacturer : Huawei Technologies Co.,Ltd
Address : Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen,518129, P.R.C
EUT Description : UMTS Mobile Phone
Model No : HUAWEI Y560-U03, Y560-U03
Trade mark : HUAWEI
Serial Number : /
FCC ID : QISY560-U03

Test Standards:

FCC Part 15 15.207, 15.209, 15.247(2014)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 15.207, 15.209 and 15.247.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.



Project Engineer:	 _____ (Chen Silin 陈司林)	Date:	<u>Jun.11.2015</u>
Checked by:	 _____ (Yang Dongping 杨东平)	Date:	<u>Jun.11.2015</u>
Approved by:	 _____ (Lin Bin 林斌)	Date:	<u>Jun.11.2015</u>

TABLE OF CONTENTS

TEST REPORT DECLARATION	2
1. TEST RESULTS SUMMARY	5
2. GENERAL INFORMATION	6
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer.....	6
2.3. Measurement Uncertainty.....	7
3. PRODUCT DESCRIPTION	8
3.1. EUT Description.....	8
3.2. Related Submittal(s) / Grant (s).....	8
3.3. Block Diagram of EUT Configuration.....	8
3.4. Operating Condition of EUT.....	9
3.5. Directional Antenna Gain.....	9
3.6. Support Equipment List.....	10
3.7. Test Conditions.....	11
3.8. Special Accessories.....	11
3.9. Equipment Modifications.....	11
4. TEST EQUIPMENT USED	12
5. 6DB BANDWIDTH MEASUREMENT	13
5.1. LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	13
5.2. TEST PROCEDURE.....	13
5.3. TEST SETUP.....	13
5.4. Test Data.....	14
6. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT	15
6.1. LIMITS OF Maximum Peak Conducted Output Power Measurement.....	15
6.2. TEST PROCEDURE.....	15
6.3. TEST DATA.....	15
7. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT	17
7.1. LIMITS OF Maximum Power Spectral Density Level Measurement.....	17
7.2. TEST PROCEDURE.....	17
7.3. TEST DATA.....	17

8.	CONDUCTED BANDEDGE AND SPURIOUS MEASUREMENT.....	19
8.1.	LIMITS OF Conducted Bandedge and Spurious Measurement.....	19
8.2.	TEST PROCEDURE.....	19
9.	RADIATED BANDEDGE AND SPURIOUS MEASUREMENT	23
9.1.	LIMITS OF Radiated Bandedge and Spurious Measurement.....	23
9.2.	TEST PROCEDURE.....	23
9.3.	TEST DATA.....	23
10.	CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT	47
10.1.	Test Standard and Limit.....	47
10.2.	Test Procedure	47
10.3.	Test Arrangement	47
10.4.	Test Data	47
11.	ANTENNA REQUIREMENTS.....	51
11.1.	Applicable requirements.....	51
11.2.	Antenna Connector	51
11.3.	Antenna Gain	51

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
6dB DTS bandwidth measurement	15.247 (a) (2)	Pass
Maximum Peak Conducted Power	15.247 (b) (3)	Pass
Maximum Power Spectral Density Level	15.247 (3)	Pass
Conducted Bandedge and Spurious	15.247 (d)	Pass
Radiated Bandedge and Spurious	15.247 (d) 15.209 15.205	Pass
Conducted emission test for AC power port	15.207	Pass
Antenna Requirement	15.203	Pass

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report information

- 2.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 2.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 2.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number are 446246 806614 994606(semi anechoic chamber).

The Laboratory is listed in Voluntary Control Council for Interference by Information Technology Equipment (VCCI), and the registration number are R-1974(open area test site) , R-1966(semi anechoic chamber),C-2117(mains ports conducted interference measurement) and T-180(telecommunication ports conducted interference measurement).

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is 11177A-1 11177A-2.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is E2024086Z02.

2.3.Measurement Uncertainty

Conducted Emission

9kHz~30MHz 3.5dB

Radiated Emission

30MHz~1000MHz 4.5dB

1GHz~26.5GHz 4.6dB

3. PRODUCT DESCRIPTION

3.1.EUT Description

Description	:	UMTS Mobile Phone
Manufacturer	:	HUAWEI Technology Limited
Model Number	:	HUAWEI Y560-U03, Y560-U03
Operate Frequency	:	2.402GHz~2.480GHz
Antenna Designation	:	GSM/WCDMA: LOOP Antenna -4dBi Wi-Fi/BT: IFA Antenna -1.5dBi

Remark: Remark 1:HUAWEI Y560-U03 compared with Y560-U03, only have different model number. All of the models' circuit theory, electrical design and the key pieces are the same. The differences do not affect the EMC and safety performance. Unless otherwise specified, the model HUAWEI Y560-U03 was chosen as representative model to perform all the tests.

Remark 2:This is a derivative report based on original report WT158002032(FCC ID: QISY560-U23). HUAWEI Y560-U03 , Y560-U03 and HUAWEI Y560-U23,Y560-U23 are identical in frequency, PCB, Antenna, Dimensions and the others. The differences between two products are software version and number of SIM slot. All the test data of HUAWEI Y560-U03 , Y560-U03 comes from the original test data of HUAWEI Y560-U23,Y560-U23.

Bluetooth Low Energy :

Table 2 Working Frequency List

Regulatory Range	RF Channels
2.400-2.4835 GHz	$f=2402+k*2$ MHz, $k=0, \dots, 39$

3.2.Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **QISY560-U03**, filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

3.3.Block Diagram of EUT Configuration



Figure 1 EUT setup

3.4. Operating Condition of EUT

Worst-case mode and channel used for 30-1000 MHz radiated and power line conducted emissions was the mode and channel with the highest output power.

Worst-case data rates as provided by the client were:

Bluetooth low energy

Test mode is configured to be with duty cycle >98%

3.5. Directional Antenna Gain

The EUT does NOT support a MIMO function.

Directional gain need NOT to be considered.

3.6.Support Equipment List

Table 3 Support Equipment List

Name	Model No	S/N	Manufacturer
Adaptor for EUT	HW-050100U01	H666LGF4G0626 2	Shen Zhen Huntkey Electronic Co., Ltd. (HK for short)
		Y66601F3L00042	Dongguan City Yingju Electronics Co.,Ltd. (YJ for short)
		P66606F4905716	Dongguan Phitek Electronics Co., Ltd. (Phitek for short)
		B66660F3G00256	Huizhou BYD Electronic Co., Ltd. (BYD for short)
Adaptor for EUT	HW-050100E01	H667LGF4723178	Shen Zhen Huntkey Electronic Co., Ltd.
		Y66801F3J00049	Dongguan City Yingju Electronics Co.,Ltd.
		P66707F3200350	Dongguan Phitek Electronics Co., Ltd.
		B66799F4200069	Huizhou BYD Electronic Co., Ltd.
Adaptor for EUT	HW-050100B01	--	Shen Zhen Huntkey Electronic Co., Ltd.
		--	Dongguan City Yingju Electronics Co.,Ltd.
		--	Dongguan Phitek Electronics Co., Ltd.
		--	Huizhou BYD Electronic Co., Ltd.
Adaptor for EUT	HW-050100A01	--	Shen Zhen Huntkey Electronic Co., Ltd.
		--	Dongguan City Yingju Electronics Co.,Ltd.
		--	Dongguan Phitek Electronics Co., Ltd.
		--	Huizhou BYD Electronic Co., Ltd.
Rechargeable Li-ion for EUT	HB494590EBC	--	BYD Lithium Battery Company Limited
Rechargeable Li-ion for EUT	HB494590EBC	--	SCUD (FUJIAN) Electronics Co., Ltd.
Data cable	130-41040	--	CHANGSHU HONGLIN TECHNOLOGY CO.,LTD.
Data cable	H09-000473	--	SHEN ZHEN PANG NGAI INDUSTRIAL CO., LTD.
Earphone	HA1-3	--	GoerTek Inc.
	HG-04A	--	
Earphone	1293#+3283# 3.5MM-150	--	BOLUO COUNTY QUANCHENG ELECTRONIC CO., LTD.
Earphone	MEMD1532B52800 0	--	Jiangxi Lianchuang Hongsheng Electronic Co., LTD.
Earphone	EMC323-011-01	--	MERRY ELECTRONICS CO., LTD.

3.7. Test Conditions

Date of test: May 15,2015-May 28, 2015

Date of EUT Receive: May 15,2015

Temperature: 21-24 °C

Relative Humidity: 48-54%

3.8. Special Accessories

Not available for this EUT intended for grant.

3.9. Equipment Modifications

Not available for this EUT intended for grant.

4. TEST EQUIPMENT USED

Table 4 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	Rohde & Schwarz	ESCS30	Dec.19, 2014	1 Year
SB3321	AMN	Rohde & Schwarz	ESH2-Z5	Jan.18, 2015	1 Year
SB2604	AMN	Rohde & Schwarz	ESH3-Z5	Nov.18, 2015	1 Year
----	Radiated Emissions Cable set	HUBER+SUHNER	---	Jan.19, 2015	1 Year
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	Mar.19, 2015	1 Year
SB8501/04	Bilog Antenna	Schwarzbeck	VULB9163	Mar.19, 2015	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.19, 2015	1 Year
SB5392/02	Horn Antenna	Amplifier Research	AT4560	May.15, 2016	1 Year
SB3450/01	3m Semi-anechoic chamber	Albatross Projects	9X6X6	Oct.09, 2014	2 Years
SB3345	Loop Antenna	Schwarzbeck	FMZB1516	Jan.20, 2015	2 Years
SB3437	Power meter	Rohde & Schwarz	NRVD	Jul.03,2015	1 Year
SB3437/01	Power sensor	Rohde & Schwarz	URV5-Z2	Jul.03,2015	1 Year
SB9721/02	Signal Analyzer	Agilent	N9020A	Jan.05, 2015	1 Year
----	Radiated Emissions Cable set	HUBER+SUHNER	---	Jan.19, 2015	1 Year
---	Radiated Emissions Cable set	HUBER+SUHNER	---	Jan.19, 2015	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Mar.27, 2015	1 Year
SB8501/16	Preamplifier	Rohde & Schwarz	SCU-26	Mar.27, 2015	1 Year
SB9059	Preamplifier	Rohde & Schwarz	SCU-40	May.12, 2015	1 Yea

5. 6DB BANDWIDTH MEASUREMENT

5.1.LIMITS OF 6dB BANDWIDTH MEASUREMENT

CFR 47 (FCC) part 15.247 (a) (2) and 558074 D01 DTS Meas Guidance v03r02

5.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

a) Set RBW = 100 kHz.

b) Set the video bandwidth (VBW) \geq 3 RBW.

c)Detector = Peak.

d)Trace mode = max hold.

e)Sweep = auto couple.

f)Allow the trace to stabilize.

g)Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.TEST SETUP



5.4. Test Data

Table 5 6dB Bandwidth Test Data BLE

CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	results
2402	0.6899	Pass
2442	0.6894	Pass
2480	0.6924	Pass



6. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT

6.1.LIMITS OF Maximum Peak Conducted Output Power Measurement

CFR 47 (FCC) part 15.247 (b) (3) and 558074 D01 DTS Meas Guidance v03r02

6.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

- a)Set the RBW \geq DTS bandwidth.
- b)Set VBW \geq 3 x RBW.
- c)Set span \geq 3 x RBW
- d)Sweep time = auto couple.
- e)Detector = peak.
- f)Trace mode = max hold.
- g)Allow trace to fully stabilize.
- h)Use peak marker function to determine the peak amplitude level.

6.3.TEST DATA

Table 6 Maximum Peak Conducted Output Power Test Data BLE

Center Freq.[MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
2402	0.506	< 30	Pass
2442	0.625	< 30	Pass
2480	0.609	< 30	Pass



7. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT

7.1.LIMITS OF Maximum Power Spectral Density Level Measurement

CFR 47 (FCC) part 15.247 (e) and 558074 D01 DTS Meas Guidance v03r02

7.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

a)Set analyzer center frequency to DTS channel center frequency.

b)Set the span to 1.5 times the DTS bandwidth.

c)Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

d)Set the VBW $\geq 3 \text{ RBW}$.

e)Detector = peak.

f)Sweep time = auto couple.

g)Trace mode = max hold.

h)Allow trace to fully stabilize.

i)Use the peak marker function to determine the maximum amplitude level within the RBW.

j)If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.3.TEST DATA

Table 7 Maximum Power Spectral Density Level Test Data BLE

Center Freq.[MHz]	PSD [dBm]	Limit [dBm]	Result
2402	0.007	8	Pass
2442	0.089	8	Pass
2480	0.040	8	Pass



8. CONDUCTED BANDEGE AND SPURIOUS MEASUREMENT

8.1.LIMITS OF Conducted Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v03r02

8.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.


Establish a reference level by using the following procedure:

- a)Set instrument center frequency to DTS channel center frequency.
- b)Set the span to ≥ 1.5 times the DTS bandwidth.
- c)Set the RBW = 100 kHz.
- d)Set the VBW $\geq 3 \times$ RBW.
- e)Detector = peak.
- f)Sweep time = auto couple.
- g)Trace mode = max hold.
- h)Allow trace to fully stabilize.
- i)Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a)Set the center frequency and span to encompass frequency range to be measured.
- b)Set the RBW = 100 kHz.
- c)Set the VBW $\geq 3 \times$ RBW.
- d)Detector = peak.
- e)Ensure that the number of measurement points \geq span/RBW
- f)Sweep time = auto couple.
- g)Trace mode = max hold.
- h)Allow trace to fully stabilize.
- i)Use the peak marker function to determine the maximum amplitude level.

TEST DATA
BLE CH0



BLE CH20


Pref



30MHz-3GHz



3GHz-25GHz



BLE CH39



9. RADIATED BANDEDGE AND SPURIOUS MEASUREMENT

9.1.LIMITS OF Radiated Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v03r02

9.2.TEST PROCEDURE

1. The testing follows the guidelines in ANSI C63.10-2009.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. Set RBW = 1 MHz, VBW= 10Hz for $f > 1$ GHz for AV measurement.

9.3.TEST DATA

9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: Changing and Transmitting
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

Field strength 30M-1GHz 1F 3m chamber



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: Changing and Transmitting
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

Field strength 30M-1GHz 1F 3m chamber



1GHz-18GHz

BLE CH0

Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



18GHz-26.5GHz

Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 18-26.5GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 18-26.5GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH0
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



BLE CH20

Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH20
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH20
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH20
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 18-26.5GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH20
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 18-26.5GHz



BLE CH39

Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 18-26.5GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:

FCC Electric Field Strength 18-26.5GHz



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Horizontal
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



Radiated Emission


EUT Information

EUT Model Name: HUAWEI Y560-U03
Operation mode: BLE CH39
Test Voltage:
Comment:

Common Information

Test Site: SMQ EMC Lab.
Environment
Antenna Polarization: Vertical
Operator Name:
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



10. CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT

10.1. Test Standard and Limit

10.1.1. Test Standard

FCC Part 15 15.207

10.1.2. Test Limit

Table 8 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

* Decreasing linearly with logarithm of the frequency

* The lower limit shall apply at the transition frequency.

10.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions from both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9kHz.

10.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

10.4. Test Data


The emissions don't show in below are too low against the limits. Refer to the test curves.

Table 9 Conducted Disturbance Test Data


Model No.: HUAWEI Y560-U03								
Test mode: Charging and transmitter								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB μ V)	Emission Level (dB μ V)	Limits (dB μ V)	Reading (dB μ V)	Emission Level (dB μ V)	Limits (dB μ V)
Line	0.150	9.7	40.9	50.6	66	26.4	36.1	56
	0.182	9.7	29.0	38.7	64.4	13.1	22.8	54.4
	0.230	9.7	28.7	38.4	62.4	13.9	23.6	52.4
	0.514	9.8	28.1	37.9	56	23.2	33	46
	0.598	9.8	29.6	39.4	56	22.8	32.6	46
	0.890	9.8	14.5	24.3	56	5.8	15.6	46
Neutral	0.154	9.7	39.1	48.8	65.8	17.0	26.7	55.8
	0.222	9.7	37.4	47.1	62.7	22.3	32	52.7
	0.270	9.7	25.5	35.2	61.1	11.2	20.9	51.1
	0.518	9.8	25.9	35.7	56	9.4	19.2	46
	0.582	9.8	25.7	35.5	56	6.0	15.8	46
	20.796	10.2	27.3	37.5	60	16.6	26.8	50

- REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)
 3. The other emission levels were very low against the limit.

EUT: HUAWEI Y560-U03
Manufacturer:
Operating Condition: Charging and transmitter
Test Site:
Operator:
Test Specification: L
Comment: AC 120V/60Hz



EUT: HUAWEI Y560-U03
Manufacturer:
Operating Condition: Charging and transmitter
Test Site:
Operator:
Test Specification: N
Comment: AC 120V/60Hz



11.ANTENNA REQUIREMENTS

11.1.Applicable requirements

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

11.2.Antenna Connector

Antenna Connector is on the PCB within enclosure and not accessible to user.

11.3.Antenna Gain

The antenna gain of EUT is less than 6 dBi.