

TABLE OF CONTENTS LIST

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

TEST REPORT:

PAGE 1.....GENERAL INFORMATION & TECHNICAL DESCRIPTION
PAGE 2-3....TECHNICAL DESCRIPTION & RF POWER OUTPUT
PAGE 4.....MODULATION CHARACTERISTICS
 AUDIO FREQUENCY RESPONSE PLOT
PAGE 5.....MODULATION LIMITING PLOT - 300 Hz
 MODULATION LIMITING PLOT - 1000 Hz
PAGE 6.....MODULATION LIMITING PLOT - 2500 Hz
 AUDIO LOW PASS FILTER PLOT
PAGE 7.....OCCUPIED BANDWIDTH
PAGE 8.....OCCUPIED BANDWIDTH PLOT
PAGE 9.....FIELD STRENGTH OF SPURIOUS EMISSIONS
PAGE 10.....METHOD OF MEASURING RADIATED SPURIOUS EMISSIONS
PAGE 11.....FREQUENCY STABILITY
PAGE 12-15..LIST OF TEST EQUIPMENT

EXHIBITS CONTAINING:

EXHIBIT 1.....LABEL SAMPLE & LOCATION
EXHIBIT 2.....EXTERNAL PHOTOGRAPHS
EXHIBIT 3.....INTERNAL PHOTOGRAPHS
EXHIBIT 4.....BLOCK DIAGRAM
EXHIBIT 5.....SCHEMATIC
EXHIBIT 6.....USER'S MANUAL
EXHIBIT 7.....CIRCUIT DESCRIPTION
EXHIBIT 8.....TUNING PROCEDURE
EXHIBIT 9.....PARTS LIST
EXHIBIT 10.....TEST SET UP PROCEDURE

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc
TABLE OF CONTENTS LIST

GENERAL INFORMATION REQUIRED
FOR TYPE ACCEPTANCE

2.1033(c)(1)(2) GLOBAL LINK CORPORATION LIMITED will manufacture the FCCID: QL2FRSKP3X FAMILY TRANSCEIVER in quantity, for use under FCC RULES PART 95. The UUT is a PTT Radio with a maximum duty cycle of 50%.

GLOBAL LINK CORPORATION LIMITED
ROOM 13B, CHINA MINMETALS TOWER
79 CHATHAM ROAD SOUTH
TSIM SHA TSUI, KOWLOON HONG KONG

2.1033 (c) TECHNICAL DESCRIPTION

2.1033(c)(3) Instruction book. A draft copy of the instruction manual is included as EXHIBIT #6.

2.1033(c) (4) Type of Emission: 11K0F3E
95.631

Bn = 2M + 2DK
M = 3000
D = 2500
Bn = 2(3000)+2(2500) = 11.0K

Authorized Bandwidth 12.5 kHz


2.1033(c)(5) Frequency Range: 1. 462.5625 8. 467.5625
95.627 2. 462.5875 9. 467.5875
3. 462.6125 10. 467.6125
4. 462.6375 11. 467.6375
5. 462.6625 12. 467.6625
6. 462.6875 13. 467.6875
7. 462.7125 14. 467.7125 MHz

2.1033(c)(6)(7) RF power output.

2.1046(a)

RF power is measured by the substitution method as outlined in TIA/EIA - 603. With a nominal battery voltage of 3.7V, and the transmitter properly adjusted, the RF output measures:

0.15 Watts ERP



Equipment placed 80 cm above ground on a rotatable platform.

95.647 The antenna is an integral part to the unit, it cannot be removed without rendering the unit inoperative. In order to remove the antenna the case must be unscrewed, then the PCB assemblies must be removed then the antenna can be removed.

2.1033(c)(8) DC Voltages and Current into Final Amplifier:
FINAL AMPLIFIER ONLY

FOR INPUT POWER: $(3.7V)(.204A) = 0.76$ Watts

2.1033(c)(9) Tune-up procedure. The tune-up procedure is included in EXHIBIT #8.

2.1033(c)(10) Complete Circuit Diagrams: The circuit diagram is included as EXHIBIT 5 of this report. The block diagram is included as EXHIBIT 4 of this report.


- 2.1033(c)(11) A photograph or a drawing of the equipment label is included as EXHIBIT 1.
- 2.1033(c)(12) Photographs(8"X10") of the equipment of sufficient clarity to reveal equipment construction and layout, including meters, labels for controls, including any view under shields - See EXHIBITS 2-3.
- 2.1033(c)(13) Digital modulation is not allowed.
- 2.1033(c)(14) The data required by 2.1046 through 2.1057 is submitted below.

2.1047(a)(b) Modulation characteristics:

AUDIO FREQUENCY RESPONSE

The audio frequency response was measured in accordance with TIA/EIA Specification 603. The audio frequency response curve is shown below. The audio signal was fed into a dummy microphone circuit and into the microphone connector. The input required to produce 30 percent modulation level was measured.

AUDIO FREQUENCY RESPONSE GRAPH




2.1047(b)


Audio input versus modulation

The audio input level needed for a particular percentage of modulation was measured in accordance with TIA/EIA Specification 603. The audio input curves versus modulation are shown below. Curves are provided for audio input frequencies of 300, 1000, and 2500 Hz.


MODULATION LIMITING GRAPH - 300 Hz



MODULATION LIMITING GRAPH - 1000 Hz



MODULATION LIMITING PLOT - 2500 Hz



95.637(b)


Post Limiter Filter The filter must be between the modulation limiter and the modulated stage. At any frequency between 3 & 20 kHz the filter must have an attenuation of $60\log(f/3)$ greater than the attenuation at 1KHz. See the plot below.

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc

Frequency Response of the Audio Low Pass Filter



2.1049(c)
95.633(c)


EMISSION BANDWIDTH:

Data in the plots shows that the sidebands from greater than 50% to 100% of the authorized bandwidth must be attenuated by at least 25 dB and from 100 to 250% the sidebands must be attenuated by at least 35 dB. Beyond 250% the sidebands must be attenuated by at least $43 + \log_{10}(TP)$. The transmitter was modulated with 2500 Hz, adjusted for 50% modulation plus 16 dB. The spectrum analyzer was set with the unmodulated carrier at the top of the screen. The test procedure diagram follows. See the following plot.


Radiotelephone transmitter with modulation limiter.

Test procedure diagram

OCCUPIED BANDWIDTH MEASUREMENT



OCCUPIED BANDWIDTH PLOT



APPLICANT: GLOBAL LINK CORPORATION LIMITED
FCC ID: QL2FRSKP3X
REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc
Page 8 of 15

2.1051 Not applicable, no antenna terminal allowed.

2.1053
95.635(b)(4) UNWANTED RADIATION:

REQUIREMENTS: Emissions must be attenuated by at least the following below the output of the transmitter.

$$43 + 10\log(\text{TP}) = 43 + 10\log(0.15) = 34.8 \text{ dB}$$

TEST DATA:

Emission Frequency	dBm	ATTN dBc	Margin dB
467.63	14.5	0.00	0.00
935.26	-43	56	23
1402.89	-48	62	27
1870.52	-47	61	26
2338.15	-49	63	28
2805.78	-50	64	29
3273.41	-54	68	33
3741.04	-41	55	21
4208.67	-42	56	22
4676.30	-46	60	25

MARGIN = (Field strength of Fund - xxxx db) - FS OF EMISSION


METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength of emissions test. The spectrum was scanned from 30 to at least the tenth harmonic of the fundamental. This test was conducted per TIA/EIA STANDARD 603 using the substitution method. Measurements were made at the open field test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

APPLICANT: GLOBAL LINK CORPORATION LIMITED
FCC ID: QL2FRSKP3X
REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc
Page 9 of 15

2.1053
95.635

UNWANTED RADIATION:

Method of Measuring Radiated Spurious Emissions



Equipment placed 80 cm above ground
on a rotatable platform.

2.1055 Frequency_stability:

Temperature and voltage tests were performed to verify that the frequency remains within the 0.00025%, 2.5 ppm specification limit. The test was conducted as follows: The transmitter was placed in the temperature chamber at 25 degrees C and allowed to stabilize for one hour. The transmitter was keyed ON for one minute during which four frequency readings were recorded at 15 second intervals. The worse case number was taken for temperature plotting. The assigned channel frequency was considered to be the reference frequency. The temperature was then reduced to -20 degrees C after which the transmitter was again allowed to stabilize for one hour. The transmitter was keyed ON for one minute, and again frequency readings were noted at 15 second intervals. The worst case number was recorded for temperature plotting. This procedure was repeated in 10 degree increments up to + 50 degrees C.

Readings were also taken at the battery end point.

MEASUREMENT DATA:

Assigned Frequency (Ref. Frequency): 467.637 5

TEMPERATURE °C	FREQUENCY MHz	PPM
REFERENCE_____	467.637 5	00.00
-20_____	467.638 47	2.07
-10_____	467.638 56	2.27
0_____	467.638 36	1.84
+10_____	467.638 01	1.09
+20_____	467.637 33	-0.36
+30_____	467.636 97	-1.13
+40_____	467.636 85	-1.39
+50_____	467.638 02	1.11

BATT. End-Point 3.15V/dc 467.637 84 0.73

EMC Equipment List

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
X	3-Meter OATS	TEI	N/A	N/A	Listed 1/13/03	1/13/06
	3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
	Receiver, Beige Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 8/31/01	8/31/03
	RF Preselector	HP	85685A	3221A01400	CAL 8/31/01	8/31/03
	Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 8/31/01	8/31/03
X	Receiver, Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/15/03	4/15/05
X	RF Preselector	HP	85685A	2926A00983	CAL 4/15/03	4/15/05
X	Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/15/03	4/15/05
	Receiver, Silver/Grey Tower Spectrum Analyzer	HP	8566B Opt 462	3552A22064 3638A08608	CAL 10/14/02	10/14/04
	RF Preselector	HP	85685A	2620A00294	CAL 10/14/02	10/14/04
	Quasi-Peak Adapter	HP	85650A	3303A01844	CAL 10/14/02	10/14/04
	Preamplifier	HP	8449B	3008A01075	CHAR 1/28/02	1/28/04
X	Biconnical Antenna	Electro-Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
	Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
	Biconnical Antenna	Eaton	94455-1	1057	CAL 3/18/03	3/18/05
	BiconiLog Antenna	EMCO	3143	9409-1043		
X	Log-Periodic Antenna	Electro-Metrics	LPA-25	1122	CAL 10/2/01	10/2/03
	Log-Periodic Antenna	Electro-Metrics	EM-6950	632	CHAR 10/15/01	10/15/03
	Log-Periodic Antenna	Electro-Metrics	LPA-30	409	CAL 3/4/03	3/4/05
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	152	CAL 3/21/01	3/21/04

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc

Page 12 of 15

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
	Dipole Antenna Kit	Electro-Metrics	TDA-30/1-4	153	CAL 9/26/02	9/26/05
	Double-Ridged Horn Antenna	Electro-Metrics	RGA -180	2319	CAL 2/17/03	2/17/05
	Horn Antenna	Electro-Metrics	EM-6961	6246	CAL 3/31/03	3/31/05
	Horn Antenna	ATM	19-443-6R	None	No Cal Required	
	Passive Loop Antenna	EMC Test Systems	EMCO 6512	9706-1211	CHAR 7/10/01	7/10/03
	Line Impedance Stabilization . . .	Electro-Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03
	Line Impedance Stabilization . . .	Electro-Metrics	EM-7820	2682	CAL 3/12/03	3/12/05
	Termaline Wattmeter	Bird Electronic Corporation	611	16405	CAL 5/25/99	5/25/01
	Termaline Wattmeter	Bird Electronic Corporation	6104	1926	CHAR 12/12/01	12/12/03
	Oscilloscope	Tektronix	2230	300572	CHAR 2/1/01	2/1/03
	System One	Audio Precision	System One	SYS1-45868	CHAR 4/25/02	4/25/04
	Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 1/22/02	1/22/04
	AC Voltmeter	HP	400FL	2213A14499	CAL 10/9/01	10/9/03
	AC Voltmeter	HP	400FL	2213A14261	CHAR 10/15/01	10/15/03
	AC Voltmeter	HP	400FL	2213A14728	CHAR 10/15/01	10/15/03
X	Digital Multimeter	Fluke	77	35053830	CHAR 1/8/02	1/8/04
	Digital Multimeter	Fluke	77	43850817	CHAR 1/8/02	1/8/04
	Digital Multimeter	HP	E2377A	2927J05849	CHAR 1/8/02	1/8/04
	Multimeter	Fluke	FLUKE-77-3	79510405	CHAR 9/26/01	9/26/03
	Peak Power Meter	HP	8900C	2131A00545	CHAR 1/26/01	1/26/03
	Power Meter	HP	432A	1141A07655	CAL 4/15/03	4/15/05
	Power Meter And Sensor	Bird	4421-107 4022	0166 0218	CAL 4/16/03	4/16/05
	Power Sensor	HP	478A	72129	CAL 4/15/03	4/15/05
	Digital Thermometer	Fluke	2166A	42032	CAL 1/16/02	1/16/04

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc

Page 13 of 15

	DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
	Thermometer	Traulsen	SK-128		CHAR 1/22/02	1/22/04
	Thermometer	Extech	4028	14871-2	CAL 3/7/03	3/7/05
X	Hygro-Thermometer	Extech	445703	0602	CAL 10/4/02	10/4/04
	Frequency Counter	HP	5352B	2632A00165	CAL 11/28/01	11/28/03
	Frequency Counter	HP	5385A	2730A03025	CAL 3/7/03	3/7/05
	Power Sensor	Agilent Technologies	84811A	2551A02705	CHAR 1/26/01	1/26/03
	Service Monitor	IFR	FM/AM 500A	5182	CAL 11/22/00	11/22/02
	Comm. Serv. Monitor	IFR	FM/AM 1200S	6593	CAL 5/12/02	5/12/04
	Signal Generator	HP	8640B	2308A21464	CAL 2/15/02	2/15/04
	Sweep Generator	Wiltron	6648	101009	CAL 4/15/03	4/15/05
	Sweep Generator	Wiltron	6669M	007005	CAL 3/3/03	3/3/05
	Modulation Analyzer	HP	8901A	3435A06868	CAL 9/5/01	9/5/03
	Modulation Meter	Boonton	8220	10901AB	CAL 4/15/03	4/15/05
	Near Field Probe	HP	HP11940A	2650A02748	CHAR 2/1/01	2/1/03
	BandReject Filter	Lorch Microwave	5BR4-2400/ 60-N	Z1	CHAR 3/2/01	3/2/03
	BandReject Filter	Lorch Microwave	6BR6-2442/ 300-N	Z1	CHAR 3/2/01	3/2/03
	BandReject Filter	Lorch Microwave	5BR4-10525/ 900-S	Z1	CHAR 3/2/01	3/2/03
	High Pass Filter	Microlab	HA-10N		CHAR 10/4/01	10/4/03
	High Pass Filter	Microlab	HA-20N		CHAR 2/7/03	2/7/05
	Audio Oscillator	HP	653A	832-00260	CHAR 3/1/01	3/1/03
	Frequency Counter	HP	5382A	1620A03535	CHAR 3/2/01	3/2/03
	Frequency Counter	HP	5385A	3242A07460	CAL 3/7/03	3/7/05
	Preamplifier	HP	8449B-H02	3008A00372	CHAR 3/4/01	3/4/03
	Amplifier	HP	11975A	2738A01969	CHAR 3/1/01	3/1/03

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc

Page 14 of 15

DEVICE	MFGR	MODEL	SERNO	CAL/CHAR DATE	DUE DATE or STATUS
Egg Timer	Unk			CHAR 8/31/01	8/31/03
Measuring Tape, 20M	Kraftixx	0631-20		CHAR 2/1/02	2/1/04
Measuring Tape, 7.5M	Kraftixx	7.5M PROFI		2/1/02	2/1/04
Coaxial Cable #51	Insulated Wire Inc.	NPS 2251-2880	Timco #51	CHAR 1/23/02	1/23/04
Coaxial Cable #64	Semflex Inc.	60637	Timco #64	CHAR 1/24/02	1/24/04
Coaxial Cable #65	General Cable Co.	E9917 RG233/U	Timco #65	CHAR 1/23/02	1/23/04
Coaxial Cable #106	Unknown	Unknown	Timco #106	CHAR 1/23/02	1/23/04

APPLICANT: GLOBAL LINK CORPORATION LIMITED

FCC ID: QL2FRSKP3X

REPORT #: G/GlobalLink_QL2\753AKT3\753AKT3TestReport.doc

Page 15 of 15